

CONSTRUCTION STAGE SOUND QUALITY EVALUATION

Wisconsin Department of Transportation

Factor Sheet D-2

Alternative	Total Length of Center Line of Existing Roadway Length of This Alternative
Preferred <input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> None Identified	

- 1. Identify and describe residences, schools, libraries, or other noise sensitive areas near the proposed action and which will be in use during construction of the proposed action. Include the number of persons potentially affected:**
- 2. Describe the types of construction equipment to be used on the project. Discuss the expected severity of noise levels including the frequency and duration of any anticipated high noise levels:**

The noise generated by construction equipment will vary greatly, depending on equipment type/model/make, duration of operation and specific type of work effort. However, typical noise levels may occur in the 67 to 107 dBA range at a distance of 50 feet.

- 3. Describe the construction stage noise abatement measures to minimize identified adverse noise effects.**

Check all that apply:

- WisDOT Standard Specifications 107.8(6) and 108.7.1 will apply.
- WisDOT Standard Specifications 107.8(6) and 108.7.1 will apply with the exception that the hours of operation requiring the engineer's written approval for operations will be changed to _____ P.M. until _____ A.M.
- WisDOT Standard Specifications 107.8(6) and 108.7.1 will apply with the exception that the hours of operation requiring the engineer's written approval for operations will be changed to _____ P.M. until _____ A.M.
- Special construction stage noise abatement measures will be required. Describe:

If special construction noise mitigation measures are required, contact the WisDOT Regional Environmental Coordinator for the appropriate verbiage.

All environmental commitments must be listed on Basic Sheet 8, Environmental Commitments.