

Removing Longitudinal Pavement Markings Water Blasting, Item SPV.0090.XXXX, Removing Special Pavement Markings Water Blasting, Item SPV.0090.XXXX

A. Description

This special provision describes removing pavement markings using high pressurized water spray from locations shown on the plans or as the engineer directs. Conform to standard spec 646 and 647 as modified in this special provision.

B. (Materials)

Provide necessary materials to remove the marking completely.

C. Construction

Remove pavement marking using a high pressurized water spray with a vacuum recovery system to provide a clean, dry surface, without the use of a secondary cleanup process when pavement or ambient air temperature is 36 degrees F and rising. Remove all markings in their entirety. Provide equipment with a storage system that contains wastewater and debris. Control blast head at all times.

Obtain approval from engineer to perform alternative removal process when either restricted from using water blasting or water blasting alone was unsuccessful. Grind markings off only if water blasting does not achieve full removal. Obtain engineer approval of the removal.

D. Measurement

The department will measure Removing Pavement Markings Water Blasting by the linear foot for longitudinal pavement markings or as each individual arrow, symbol or word for special markings acceptably completed. The department will count removing an RXR symbol as 3 individual symbols.

E. Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0090.XXXX	Removing Longitudinal Pavement Markings Water Blasting	LF
SPV.0090.XXXX	Removing Special Pavement Markings Water Blasting	Each