

1. Temporary Raised Pavement Markers, Type II, Item SPV.0060.01.

A Description

This special provision describes providing temporary raised pavement markers (reflective tabs) for temporary pavement markings in accordance with the pertinent sections of section 649 of the standard specifications.

B Materials

Provide single or multi-cover tabs in color shown in plans. Markers shall be of polyurethane material and have a minimum size reflective surface on each marker of 4” width x 0.25” height.

C Construction

Place Temporary Raised Pavement Markers, Type II in accordance with manufacturer recommendations. Bonding surface must be free of dust, dirt, oil and moisture. Place within 3 inches of the centerline longitudinal joint; do not place over the joint.

Replace reflective tabs that fail to adhere, are damaged or missing within 24 hours, at the contractor’s expense.

Remove protective covers from the reflective tabs prior to opening the closed lane(s) to traffic as required by the Traffic section of the special provisions.

Remove reflective tabs without damaging the asphalt pavement, seal coat, or fog seal. Repair areas of the pavement surface that are damaged at the contractor’s expense.

D Measurement

The department will measure Temporary Raised Pavement Markers, Type II by each acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0060.01	Temporary Raised Pavement Markers, Type II	EACH

Payment for Temporary Raised Pavement Markers, Type II is full compensation for preparing the surface; providing and installing temporary pavement marking reflective tabs; replacing tabs that fail to adhere, are damaged or missing; removing protective covers; and for the removal of the temporary raised pavement markers.