

Concrete Adhesive Anchors

Date last edited: 3/8/2019

This list applies for bid items 502.5000-6199 (2016 spec. & earlier) AND bid items 502.4100-4299 (2017 spec. and later)

READ STORAGE NOTES BELOW EACH PRODUCT

Product Name	Date Listed	Manufacturer	Supplied by:
AT-XP	Prior to 2015	Simpson Strong- Tie Company, Inc. 2600 International Street Columbus , OH 43228 800-999-5099, ext. 4130 www.simpsonanchors.com/	Simpson Strong- Tie Company, Inc. Contact; Bill Paar 800-999-5099 bpaar@strongtie.com
The shelf life of AT-XP in unopened cartridges is twelve months from the date of manufacture when stored at temperatures between 32°F and 80°F in accordance with the manufacturer's printed installation instructions.			
AC200+ AC100-+Gold	8/18/2017 Removed 7/27/2017	DEWALT 701 East Joppa Road Towson, Maryland 21286 800-524-3244 <u>SAME PRODUCT ACCEPTABLE FROM:</u> Powers Fasteners, Inc. 2 Powers Lane Brewster, NY 10509 914-235-6300	DEWALT Engineered by Powers 1650 Miller Park Way West Milwaukee, WI 53214
Dural ICC Gel	6/8/2018	Euclid Chemical Co. 19218 Redwood Rd Cleveland, OH 44110 216-531-9222	Euclid Chemical Co. 19219 Redwood Rd Cleveland, OH 44111 Contact: Brian Lewis 216-692-8305
12-month shelf life when stored in an unopened container in dry conditions. Store between 40°F and 77°F			
HIT HY-100 HIT HY-200-A HIT HY-200-R HIT-RE 500V3 HY-150-MAX-	11/7/2017 11/7/2017 11/7/2017 7/24/2018 Removed 7/8/2015	Hilti Inc 5400 S 122nd Avenue Tulsa, OK 74121 800-879-8000 http://www.us.hilti.com/	Hilti North America Contact: Arif Khatri 847-224-1667 arif.khatri@hilti.com
The manifold attached to each foil pack is stamped with the adhesive expiration date. The shelf life, as indicated by the expiration date, applies to unopened foil packs that are stored in accordance with the manufacturer's printed installation instructions.			
Liquid Roc 200	6/8/2018	MKT Fastening, LLC 1 Gunnebo Drive Lonoke, AR 72086 800-336-1640	Roy Bach & Associates 111 Union Ave. Batavia, IL 60510 Contact: Andy Bach 630-879-1596
Store in a cold and dark place, storage temperature: from 41°F up to 77°F. Shelf life: 18 months.			
Red-Head-EPCON-S7 Red Head EPCON A7+	Removed 7/2/2018 12/15/2016	ITW Commercial Construction North America 700 High Grove Boulevard Glendale Heights, IL 60139 630-825-7900 630-893-1291(fax) www.itwredhead.com	Bay Verte Machinery 975 Parkview Rd Green Bay, WI 920-336-7440
The original, unopened cartridge has a shelf life of fifteen months, as indicated by the "best used by" date stamped onto the cartridge, when stored in a cool, dry, ventilated area and in accordance with the manufacturer's printed installation instructions.			
ULTRABOND 365CC	12/15/2016	Adhesives Technology Corp. 450 E. Copans Rd. Pompano Beach, FL 33064 800-892-1880 www.atcepoxy.com Contact: Renee Thomas rthomas@atcepoxy.com	Ambrosius Concrete Supplies 219 Orlando Drive De Pere, WI 54115 920-336-8355 ambrosiusconcretesupplies@yahoo.com
The shelf life, as indicated by the "Use By" date stamped on the cartridge, corresponds to an unopened cartridge stored in a dry, dark environment. Storage temperature of the adhesive is 41°F to 77°F.			

Contact:Danielle De Tennis
608-266-8689

Bureau of Structures

email:

danielle.detennis@dot.wi.gov