



SECTION THRU DECK
ONE-PIECE THREADED COUPLER SHOWN



DOWEL BAR COUPLER
STAGE 2 DOWEL SCREWS INTO
COUPLER PLACED IN STAGE 1



ONE-PIECE THREADED COUPLER

BAR COUPLER ALTERNATIVES

NOTES


FOR DOWEL BAR COUPLERS, ALL DOWEL BARS SHALL BE LAPPED AND TIED TO THE REINFORCEMENT BARS.

DESIGNER NOTES

ON THE PLANS PROVIDE LOCATION, STAGING, SIZE AND QUANTITY REQ'D. DO NOT GIVE SPECIFIC INFORMATION REGARDING THE COUPLER AS THIS IS COVERED BY THE BID ITEM "BAR COUPLERS (SIZE)".

ON THE PLANS SHOW DETAILS SIMILAR TO "SECTION THRU DECK" AND "BAR COUPLER ALTERNATIVES".

AT THE PLAN BILL OF BARS, INDICATE WHICH BARS REQUIRE BAR COUPLERS BY USE OF A SYMBOL. USING THE SAME SYMBOL, ADD A NOTE STATING THAT A BAR COUPLER IS REQUIRED. BAR LENGTHS ARE COMPUTED TO THE $\frac{1}{2}$ OF THE CONSTRUCTION JOINT AND SHALL BE MODIFIED BY THE BAR COUPLER MANUFACTURERS RECOMMENDATIONS. DOWEL BARS ARE NOT TO BE DETAILED, AS THOSE BARS ARE INCLUDED IN THE BAR COUPLER BID ITEM SHOULD THE DOWEL OPTION BE CHOSEN.

BAR SPLICER (COUPLER) DETAILS AT STAGE CONSTRUCTION	
	BUREAU OF STRUCTURES
APPROVED: <u>Bill Oliva</u>	DATE: 7-19