



SECTION THRU ABUTMENT FOR GIRDERS



SECTION THRU ABUTMENT FOR PRESTRESSED BOX GIRDERS



SECTIONS A-A AND B-B ARE DETAILED ON STANDARD 7.01

NOTES

- FRONT FACE OF 'ALIGNMENT KEYBLOCK' LOCATION TO BE HELD REGARDLESS OF ACTUAL MODULAR BLOCK SIZE OR GRS ABUTMENT BATTER.
- 4'-0" WRAP (TYP.)
- INDICATES GEOSYNTHETIC REINFORCEMENT LAYER NUMBER, FOR LENGTHS, SEE 'GRS ABUTMENT INFORMATION' TABLE. SPACING OF GEOSYNTHETIC REINFORCEMENT LAYERS TO BE DESIGNED.
- FULL HEIGHT BLOCK IS TYPICAL IN FRONT OF BEARING SEAT BUT A HALF HEIGHT BLOCK AND A SPECIAL EXPANDED POLYSTYRENE THICKNESS MAY BE REQUIRED IN SOME APPLICATIONS.
- LIMITS OF GRS BACKFILL TO BE PAID FOR UNDER THE BID ITEM 'GEOSYNTHETIC REINFORCED SOIL ABUTMENT'

DESIGNER NOTES

- THE TOP OF THE CONTRAST-COLORED BLOCKS SHALL BE 2-3 BLOCK COURSES BELOW THE TOP OF RIPRAP ELEVATION.
- DIMENSION TO BE DESIGNED
- THE MINIMUM REQUIRED TENSILE STRENGTH OF THE GEOSYNTHETIC REINFORCEMENT SHALL BE SHOWN WITHIN THE SPECIAL PROVISION, 'GEOSYNTHETIC REINFORCED SOIL ABUTMENT'.
- MINIMUM CLEAR SPACE SHALL BE 3" OR 2% OF GRS ABUTMENT HEIGHT, WHICHEVER IS GREATER. MINIMUM CLEAR SPACE SHALL BE SHOWN ON THE PLANS.
- ** CONCRETE SPREAD FOOTING TO BE DETERMINED PER DESIGN.

GRS ABUTMENT INFORMATION

LAYER NUMBER	MINIMUM LENGTH* OF GEOTEXTILE (FT.)	EL. ±

*LENGTH MEASURED FROM FRONT FACE OF MODULAR BLOCK TO END OF GEOTEXTILE. (DOES NOT INCLUDE WRAPPED GEOTEXTILE WHERE APPLICABLE).

GRS ABUTMENT DETAILS



APPROVED: *Laura Shadewald* DATE: 7-18