HIGHWAY WORK PROPOSAL

2140-14-70

Wisconsin Department of Transportation DT1502 01/2020 s.66.0901(7) Wis. Stats

WISC 2025601

Proposal Number: 030

STATE ID FEDERAL ID PROJECT DESCRIPTION HIGHWAY COUNTY

Florist Ave to CTH Q

C Milwaukee 76th Street,

STH 181 Milwaukee

This proposal, submitted by the undersigned bidder to the Wisconsin Department of Transportation, is in accordance with the advertised request for proposals. The bidder is to furnish and deliver all materials, and to perform all work for the improvement of the designated project in the time specified, in accordance with the appended Proposal Requirements and Conditions.

Proposal Guaranty Required: \$360,000.00
Payable to: Wisconsin Department of Transportation

Bid Submittal
Date: October 14, 2025
Time (Local Time): 11:00 am

Contract Completion Time
December 01, 2026

Assigned Disadvantaged Business Enterprise Goal 9%

Attach Proposal Guaranty on back of this PAGE.

Firm Name, Address, City, State, Zip Code

SAMPLE NOT FOR BIDDING PURPOSES

This contract is exempt from federal oversight.

This certifies that the undersigned bidder, duly sworn, is an authorized representative of the firm named above; that the bidder has examined and carefully prepared the bid from the plans, Highway Work Proposal, and all addenda, and has checked the same in detail before submitting this proposal or bid; and that the bidder or agents, officer, or employees have not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free competitive bidding in connection with this proposal bid.

Do not sign, notarize, or submit this Highway Work Proposal when submitting an electronic bid on the Internet.

Subscribed and sworn to before me this date	
(Signature, Notary Public, State of Wisconsin)	(Bidder Signature)
(Print or Type Name, Notary Public, State Wisconsin)	(Print or Type Bidder Name)
(Date Commission Expires)	(Bidder Title)
Notary Seal	

Type of Work: For Department Use Only

Removals, Milling, Grading, Aggregate, Concrete Pavement, Asphalt Pavement, Curb and Gutter, Concrete Sidewalk, Erosion Control, Permanent Signing, Traffic Control, Pavement Marking, Lighting, Traffic Signals, Restoration.

Notice of Award Dated Date Guaranty Returned

PLEASE ATTACH PROPOSAL GUARANTY HERE

PROPOSAL REQUIREMENTS AND CONDITIONS

The bidder, signing and submitting this proposal, agrees and declares as a condition thereof, to be bound by the following conditions and requirements.

If the bidder has a corporate relationship with the proposal design engineering company, the bidder declares that it did not obtain any facts, data, or other information related to this proposal from the design engineering company that was not available to all bidders.

The bidder declares that they have carefully examined the site of, and the proposal, plans, specifications and contract forms for the work contemplated, and it is assumed that the bidder has investigated and is satisfied as to the conditions to be encountered, as to the character, quality, and quantities of work to be performed and materials to be furnished, and as to the requirements of the specifications, special provisions and contract. It is mutually agreed that submission of a proposal shall be considered conclusive evidence that the bidder has made such examination.

The bidder submits herewith a proposal guaranty in proper form and amount payable to the party as designated in the advertisement inviting proposals, to be retained by and become the property of the owner of the work in the event the undersigned shall fail to execute the contract and contract bond and return the same to the office of the engineer within fourteen (14) days after having been notified in writing to do so; otherwise to be returned.

The bidder declares that they understand that the estimate of quantities in the attached schedule is approximate only and that the attached quantities may be greater or less in accordance with the specifications.

The bidder agrees to perform the said work, for and in consideration of the payment of the amount becoming due on account of work performed, according to the unit prices bid in the following schedule, and to accept such amounts in full payment of said work.

The bidder declares that all of the said work will be performed at their own proper cost and expense, that they will furnish all necessary materials, labor, tools, machinery, apparatus, and other means of construction in the manner provided in the applicable specifications and the approved plans for the work together with all standard and special designs that may be designed on such plans, and the special provisions in the contract of which this proposal will become a part, if and when accepted. The bidder further agrees that the applicable specifications and all plans and working drawings are made a part hereof, as fully and completely as if attached hereto.

The bidder, if awarded the contract, agrees to begin the work not later than ten (10) days after the date of written notification from the engineer to do so, unless otherwise stipulated in the special provisions.

The bidder declares that if they are awarded the contract, they will execute the contract agreement and begin and complete the work within the time named herein, and they will file a good and sufficient surety bond for the amount of the contract for performance and also for the full amount of the contract for payment.

The bidder, if awarded the contract, shall pay all claims as required by Section 779.14, Statutes of Wisconsin, and shall be subject to and discharge all liabilities for injuries pursuant to Chapter 102 of the Statutes of Wisconsin, and all acts amendatory thereto. They shall further be responsible for any damages to property or injury to persons occurring through their own negligence or that of their employees or agents, incident to the performance of work under this contract, pursuant to the Standard Specifications for Road and Bridge Construction applicable to this contract.

In connection with the performance of work under this contract, the contractor agrees to comply with all applicable state and federal statutes relating to non-discrimination in employment. No otherwise qualified person shall be excluded from employment or otherwise be subject to discrimination in employment in any manner on the basis of age, race, religion, color, gender, national origin or ancestry, disability, arrest or conviction record (in keeping with s.111.32), sexual orientation, marital status, membership in the military reserve, honesty testing, genetic testing, and outside use of lawful products. This provision shall include, but not be limited to the following: employment, upgrading, demotion or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation, and selection for training, including apprenticeship. The contractor further agrees to ensure equal opportunity in employment to all applicants and employees and to take affirmative action to attain a representative workforce.

The contractor agrees to post notices and posters setting forth the provisions of the nondiscrimination clause, in a conspicuous and easily accessible place, available for employees and applicants for employment.

If a state public official (section 19.42, Stats.) or an organization in which a state public official holds at least a 10% interest is a party to this agreement, this contract is voidable by the state unless appropriate disclosure is made to the State of Wisconsin Ethics Board.

BID PREPARATION

Preparing the Proposal Schedule of Items

A. General

- (1) Obtain bidding proposals as specified in section 102 of the standard specifications prior to 11:45 AM of the last business day preceding the letting. Submit bidding proposals using one of the following methods:
 - 1. Electronic bid on the internet.
 - 2. Electronic bid on a printout with accompanying diskette or CD ROM.
 - 3. Paper bid under a waiver of the electronic submittal requirements.
- (2) Bids submitted on a printout with accompanying diskette or CD ROM or paper bids submitted under a waiver of the electronic submittal requirements govern over bids submitted on the internet.
- (3) The department will provide bidding information through the department's web site at:

https://wisconsindot.gov/Pages/doing-bus/contractors/hcci/bid-let.aspx

The contractor is responsible for reviewing this web site for general notices as well as information regarding proposals in each letting. The department will also post special notices of all addenda to each proposal through this web site no later than 4:00 PM local time on the Thursday before the letting. Check the department's web site after 5:00 PM local time on the Thursday before the letting to ensure all addenda have been accounted for before preparing the bid. When bidding using methods 1 and 2 above, check the Bid ExpressTM on-line bidding exchange at http://www.bidx.com/ after 5:00 PM local time on the Thursday before the letting to ensure that the latest schedule of items Expedite file (*.ebs or *.00x) is used to submit the final bid.

(4) Interested parties can subscribe to the Bid ExpressTM on-line bidding exchange by following the instructions provided at the www.bidx.com web site or by contacting:

Info Tech Inc. 5700 SW 34th Street, Suite 1235 Gainesville, FL 32608-5371 email: mailto:customer.support@bidx.com

- (5) The department will address equipment and process failures, if the bidder can demonstrate that those failures were beyond their control.
- (6) Contractors are responsible for checking on the issuance of addenda and for obtaining the addenda. Notice of issuance of addenda is posted on the department's web site at:

https://wisconsindot.gov/Pages/doing-bus/contractors/hcci/bid-let.aspx

- or by calling the department at (608) 266-1631. Addenda can ONLY be obtained from the department's web site listed above or by picking up the addenda at the Bureau of Highway Construction, 4th floor, 4822 Madison Yards Way, Madison, WI, during regular business hours.
- (7) Addenda posted after 5:00 PM on the Thursday before the letting will be emailed to the eligible bidders for that proposal. All eligible bidders shall acknowledge receipt of the addenda whether they are bidding on the proposal or not. Not acknowledging receipt may jeopardize the awarding of the project.

B. Submitting Electronic Bids

B.1 On the Internet

- (1) Do the following before submitting the bid:
 - 4. Have a properly executed annual bid bond on file with the department.
 - 5. Have a digital ID on file with and enabled by Info Tech Inc. Using this digital ID will constitute the bidder's signature for proper execution of the bidding proposal.
- (2) In lieu of preparing, delivering, and submitting the proposal as specified in 102.6 and 102.9 of the standard specifications, submit the proposal on the internet as follows:
 - 1. Download the latest schedule of items reflecting all addenda from the Bid Express TM web site.
 - 2. Use ExpediteTM software to enter a unit price for every item in the schedule of items.
 - 3. Submit the bid according to the requirements of ExpediteTM software and the Bid ExpressTM web site. Do not submit a bid on a printout with accompanying diskette or CD ROM or a paper bid. If the bidder does submit a bid on a printout with accompanying diskette or a paper bid in addition to the internet submittal, the department will disregard the internet bid
 - 4. Submit the bid before the hour and date the Notice to Contractors designates
 - 5. Do not sign, notarize, and return the bidding proposal described in 102.2 of the standard specifications.
- (3) The department will not consider the bid accepted until the hour and date the Notice to Contractors designates.

B.2 On a Printout with Accompanying Diskette or CD ROM

other files on the diskette or CD ROM.

- (1) Download the latest schedule of items from the Wisconsin pages of the Bid Express web site reflecting the latest addenda posted on the department's web site at:
 - https://wisconsindot.gov/Pages/doing-bus/contractors/hcci/bid-let.aspx
 - Use ExpediteTM software to prepare and print the schedule of items. Provide a valid amount for all price fields. Follow instructions and review the help screens provided on the Bid ExpressTM web site to assure that the schedule of items is prepared properly.
- (2) Staple an 8 1/2 by 11 inch printout of the Expedite □ □ generated schedule of items to the other proposal documents submitted to the department as a part of the bidder's sealed bid. As a separate submittal, not in the sealed bid envelop but due at the same time and place as the sealed bid, also provide the Expedite TM generated schedule of items on a 3 1/2 inch computer diskette or CD ROM. Label each diskette or CD ROM with the bidder's name, the 4 character department-assigned bidder identification code from the top of the bidding proposal, and a list of the proposal numbers included on that diskette or CD ROM as indicated in the following example:

Bidder Name BN00

Proposals: 1, 12, 14, & 22

- (3) If bidding on more than one proposal in the letting, the bidder may include all proposals for that letting on one diskette or CD ROM. Include only submitted proposals with no incomplete or
- (4) The bidder-submitted printout of the Expedite □ □ generated schedule of items is the governing contract document and must conform to the requirements of section 102 of the standard specifications. If a printout needs to be altered, cross out the printed information with ink or typewriter and enter the new information and initial it in ink. If there is a discrepancy between the printout and the diskette or CD ROM, the department will analyze the bid using the printout information.

- (5) In addition to the reasons specified in section 102 of the standard specifications, proposals are irregular and the department may reject them for one or more of the following:
 - 1. The check code printed on the bottom of the printout of the Expedite TM generated schedule of items is not the same on each page.
 - 2. The check code printed on the printout of the Expedite TM generated schedule of items is not the same as the check code for that proposal provided on the diskette or CD ROM.
 - 3. The diskette or CD ROM is not submitted at the time and place the department designates.

B Waiver of Electronic Submittal

- (1) The bidder may request a waiver of the electronic submittal requirements. Submit a written request for a waiver in lieu of bids submitted on the internet or on a printout with accompanying diskette or CD ROM. Use the waiver that was included with the paper bid document sent to the bidder or type up a waiver on the bidder's letterhead. The department will waive the electronic submittal requirements for a bidding entity (individual, partnership, joint venture, corporation, or limited liability company) for up to 4 individual proposals in a calendar year. The department may allow additional waivers for equipment malfunctions.
- (2) Submit a schedule of items on paper conforming to section 102 of the standard specifications. The department charges the bidder a \$75 administrative fee per proposal, payable at the time and place the department designates for receiving bids, to cover the costs of data entry. The department will accept a check or money order payable to: "Wisconsin, Dept. of Transportation."
- (3) In addition to the reasons specified in section 102 of the standard specifications, proposals are irregular and the department may reject them for one or more of the following:
 - 1. The bidder fails to provide the written request for waiver of the electronic submittal requirements.
 - 2. The bidder fails to pay the \$75 administrative fee before the time the department designates for the opening of bids unless the bidder requests on the waiver that they be billed for the \$75.
 - 3. The bidder exceeds 4 waivers of electronic submittal requirements within a calendar year.
- (4) In addition to the reasons specified in section 102 of the standard specifications, the department may refuse to issue bidding proposals for future contracts to a bidding entity that owes the department administrative fees for a waiver of electronic submittal requirements.

DT1303 1/2006

Proposal Number	Project Number		Letting Date
Name of Principal			
Name of Surety		State in Which Surety is	Organized

We, the above-named Principal and the above-named Surety, are held and firmly bound unto the State of Wisconsin in the sum equal to the Proposal Guaranty for the total bid submitted for the payment to be made; we jointly and severally bind ourselves, our heirs, executors, administrators, successors and assigns. The condition of this obligation is that the Principal has submitted a bid proposal to the State of Wisconsin acting through the Department of Transportation for the improvement designated by the Proposal Number and Letting Date indicated above.

If the Principal is awarded the contract and, within the time and manner required by law after the prescribed forms are presented for signature, enters into a written contract in accordance with the bid, and files the bond with the Department of Transportation to guarantee faithful performance and payment for labor and materials, as required by law, or if the Department of Transportation shall reject all bids for the work described, then this obligation shall be null and void; otherwise, it shall be and remain in full force and effect. In the event of failure of the Principal to enter into the contract or give the specified bond, the Principal shall pay to the Department of Transportation within 10 business days of demand a total equal to the Proposal Guaranty as liquidated damages; the liability of the Surety continues for the full amount of the obligation as stated until the obligation is paid in full.

The Surety, for value received, agrees that the obligations of it and its bond shall not be impaired or affected by any extension of time within which the Department of Transportation may accept the bid; and the Surety does waive notice of any such extension.

IN WITNESS, the Principal and Surety have agreed and have signed by their proper officers and have caused their corporate seals to be affixed this date: **(DATE MUST BE ENTERED)**

PRINCIPAL

(Company Name) (Affix Corporate Seal)			
(Signature and Title)			
(Company Name)			
(Signature and Title)			
(Company Name)			
(Signature and Title)		(Name of Surety) (Affix Seal)	
(Company Name)		(Signature of Attorney-in-Fact)	
(Signature and Title)			
NOTARY FOR PRINCIPAL		NOTARY FO	R SURETY
(Date)		(Dat	e)
State of Wisconsin)		State of Wisconsin)
County) s	SS.) ss. _County)
On the above date, this instrument was acknowledged before me by the named person(s).		On the above date, this instrument w named person(s).	as acknowledged before me by the
(Signature, Notary Public, State of Wiscon	sin)	(Signature, Notary Publi	ic, State of Wisconsin)
(Print or Type Name, Notary Public, State of Wi	isconsin)	(Print or Type Name, Notary	Public, State of Wisconsin)
(Date Commission Expires)		(Date Commis	sion Expires)

Notary Seal Notary Seal

IMPORTANT: A certified copy of Power of Attorney of the signatory agent must be attached to the bid bond.

CERTIFICATE OF ANNUAL BID BOND

DT1305 8/2003

Wisconsin Department of Transportation

(Date)

Time Period Valid (I	From/To)
Name of Surety	
Name of Contractor	
Certificate Holder	Wisconsin Department of Transportation
•	that an annual bid bond issued by the above-named Surety is currently on file with the artment of Transportation.
	is issued as a matter of information and conveys no rights upon the certificate holder mend, extend or alter the coverage of the annual bid bond.
Cancellation:	Should the above policy be cancelled before the expiration date, the issuing surety will give thirty (30) days written notice to the certificate holder indicated above.

(Signature of Authorized Contractor Representative)

LIST OF SUBCONTRACTORS

Section 66.0901(7), Wisconsin Statutes, provides that as a part of the proposal, the bidder also shall submit a list of the subcontractors the bidder proposes to contract with and the class of work to be performed by each. In order to qualify for inclusion in the bidder's list a subcontractor shall first submit a bid in writing, to the general contractor at least 48 hours prior to the time of the bid closing. The list may not be added to or altered without the written consent of the municipality. A proposal of a bidder is not invalid if any subcontractor and the class of work to be performed by the subcontractor has been omitted from a proposal; the omission shall be considered inadvertent or the bidder will perform the work personally.

No subcontract, whether listed herein or later proposed, may be entered into without the written consent of the Engineer as provided in Subsection 108.1 of the Standard Specifications.

Name of Subcontractor	Class of Work	Estimated Value

CERTIFICATION REGARDING DEBARMENT, SUSPENSION, AND OTHER RESPONSIBILITY MATTERS - PRIMARY COVERED TRANSACTIONS

Instructions for Certification

- By signing and submitting this proposal, the prospective contractor is providing the certification set out below.
- 2. The inability of a person to provide the certification required below will not necessarily result in denial of participation in this covered transaction. The prospective contractor shall submit an explanation of why it cannot provide the certification set out below. The certification or explanation will be considered in connection with the department or agency's determination whether to enter into this transaction. However, failure of the prospective contractor to furnish a certification or an explanation shall disqualify such person from participation in this transaction.
- 3. The certification in this clause is a material representation of fact upon which reliance was placed when the department determined to enter into this transaction. If it is later determined that the contractor knowingly rendered an erroneous certification in addition to other remedies available to the Federal Government the department may terminate this transaction for cause or default.
- 4. The prospective contractor shall provide immediate written notice to the department to whom this proposal is submitted if at any time the prospective contractor learns that its certification was erroneous when submitted or has become erroneous by reason of changed circumstances.
- 5. The terms "covered transaction," "debarred," "suspended," "ineligible," "lower tier covered transaction," "participant," "person," "primary covered transaction," "principal," "proposal," and "voluntarily excluded," as used in this clause, have the meanings set out in the Definitions and Coverage sections of the rules implementing Executive Order 12549. You may contact the department to which this proposal is being submitted for assistance in obtaining a copy of those regulations.
- 6. The prospective contractor agrees by submitting this proposal that, should this contract be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department entering into this transaction.
- 7. The prospective contractor further agrees by submitting this proposal that it will include the clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transaction," which is included as an addendum to PR- 1273 "Required Contract Provisions Federal Aid Construction Contracts," without modification, in all lower tier covered transactions and in all solicitations for lower tier covered transactions.
- 8. The contractor may rely upon a certification of a prospective subcontractor/materials supplier that it is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A contractor may decide the method and frequency by which it determines the eligibility of its principals. Each contractor may, but is not required to, check the Disapproval List (telephone # 608/266/1631).

- 9. Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of a contractor is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.
- 10. Except for transactions authorized under paragraph 6 of these instructions, if a contractor in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department may terminate this transaction for cause or default.

<u>Certification Regarding Debarment, Suspension, and Other Responsibility Matters - Primary Covered Transactions</u>

- 1. The prospective contractor certifies to the best of its knowledge and belief, that it and its principals:
 - (a) Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from covered transactions by any Federal department or agency;
 - (b) Have not within a three-year period preceding this proposal been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (Federal, State or local) transaction or contract under a public transaction; violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements or receiving stolen property;
 - (c) Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State or local) with commission of any of the offense enumerated in paragraph (1)(b) of this certification; and
 - (d) Have not within a three-year period preceding this proposal had one or more public transactions (Federal, State or local) terminated for cause or default.
- 2. Where the prospective contractor is unable to certify to any of the statements in this certification, such prospective contractor shall attach an explanation to this proposal.

Special Provisions

Table of Contents

	Article	Description	Page #
1.	General		4
2.	Scope of Work		4
3.	Prosecution and Progress		4
4.	Lane Rental Fee Assesment		6
5.	Traffic		7
6.	Holiday and Special Event Work Restri	ctions	11
7.	Utilities		11
8.	Referenced Construction Specifications	S	17
9.	Timely Decision Making Manual		18
10.	Other Contracts		18
11.	Work by Others		18
12.	Work by Others – City of Milwaukee –	Street Lighting	18
13.	Work by Others – WisDOT – Communi	cation Line	18
14.	Work by Others - WisDOT - ATR Pull	Boxes	18
15.	Railroad Insurance and Coordination –	Union Pacific Railroad Company	19
16.		Wisconsin and Southern Railroad Company	
17.		portation Construction General Permit (TCGP) for Storm	21
18.	Notice to Contractor – Milwaukee Cour	nty Transit System	21
19.	Notice to Contractor – Timmerman Airp	oort	22
20.	Notice to Contractor – Saw Cut Slurry.		23
21.	Notice to Contractor – Concrete Wash	out Containment	23
22.	Notice to Contractor – Minimum Vertica	al Clearances	23
23.	Notice to Contractor – Traffic Signal Ed	quipment Lead Time	23
24.	Notice to Contractor – Electronic Load	Tickets	23
25.	Erosion Control		24
26.	Coordination with Businesses and Res	idents	24
27.	Adjusting and Reconstructing Storm Se	ewer Structures	25
28.	Traffic Signals, General		25
29.	General Requirements for Electrical We	ork	25
30.	Electrical Conduit		26
31.	Traffic Signal Faces		26
32.	Signal Mounting Hardware		26
33.	STH 181 & Mill Rd, Item 204.9060.S.02 204.9060.S.03; Removing Traffic Signa Removing Traffic Signals STH 181 & G Signals STH 181 & Calumet Rd, Item 2 Bradley Rd, Item 204.9060.S.07; Remo	lorist Ave, Item 204.9060.S.01; Removing Traffic Signals 2; Removing Traffic Signals STH 181 & Acacia St, Item als STH 181 \$ Green Tree Rd, Item 204.9060S.04; Good Hope Rd, Item 204.9060.S.05; Removing Traffic 204.9060.S.06 Removing Traffic Signals STH 181 & Doving Traffic Signals STH 181 & Tower Ave, Item als STH 181 & Servite/Dean Rd, Item 204.9060.09;	;

	Signals STH 181 & Northridge Lakes Blvd, Item 204.9060.S.11	26
34.	Removing Loop Detector Wire and Lead-in Cable STH 181 & Florist Ave, Item 204.9060.S.12; Removing Loop Detector Wire and Lead-in Cable STH 181 & Mill Rd, Item 204.9060.S.13; Removing Loop Detector Wire and Lead-in Cable STH 181 & Acacia St, Item 204.9060.S.14; Removing Loop Detector Wire and Lead-in Cable STH 181 \$ Green Tree Rd, Item 204.9060.S.15; Removing Loop Detector Wire and Lead-in Cable STH 181 & Good Hope Rd, Item 204.9060.S.16; Removing Loop Detector Wire and Lead-in Cable STH 181 & Calumet Rd, Item 204.9060.S.17; Removing Loop Detector Wire and Lead-in Cable STH 181 & Bradley Rd, Item 204.9060.S.18; Removing Loop Detector Wire and Lead-in Cable STH 181 & Tower Ave, Item 204.9060.S.19; Removing Loop Detector Wire and Lead-in Cable STH 181 & Servite/Dean Rd, Item 204.9060.20; Removing Loop Detector Wire and Lead-in Cable STH 181 & Northridge Dr, Item 204.9060.S.21; Removing Loop Detector Wire and Lead-in Cable STH 181 & Northridge Lakes Blvd, Item 204.9060.S.22; Removing Loop Detector Wire and Lead-in Cable STH 181 & STH	28
35.	HMA Percent Within Limits (PWL) Test Strip Volumetrics, Item 460.0105.S; HMA Percent Within Limits (PWL) Test Strip Density, Item 460.0110.S	29
36.	HMA Pavement Percent Within Limits (PWL) QMP.	33
37.	Appendix A	41
38.	HMA Pavement Longitudinal Density	46
39.	Adjusting Manhole Covers, Item 611.8110.	
40.	Cover Plates Temporary, Item 611.8120.S	
41.	Fence Safety, Item 616.0700.S.	
42.	Connected Arrow Board, Item 643.0810.S.	51
43.	Connected Work Zone Start and End Location Markers, Item 643.1220.	
44.	Temporary Audible Message Devices, Item 644.1900.S	53
45.	Electrical Service Meter Breaker Pedestal STH 181 & Florist Ave, Item 656.0201.01; Electrical Service Meter Breaker Pedestal STH 181 & Mill Rd, Item 656.0201.02; Electrical Service Meter Breaker Pedestal STH 181 & Acacia St, Item 656.0201.03; Electrical Service Meter Breaker Pedestal STH 181 & Green Tree Rd, Item 656.0201.04; Electrical Service Meter Breaker Pedestal STH 181 & Good Hope Rd, Item 656.0201.05; Electrical Service Meter Breaker Pedestal STH 181 & Calumet Rd, Item 656.0201.06; Electrical Service Meter Breaker Pedestal STH 181 & Bradley Rd, Item 656.0201.07; Electrical Service Meter Breaker Pedestal STH 181 & Tower Ave, Item 656.0201.08; Electrical Service Meter Breaker Pedestal STH 181 & Servite/Dean Rd, Item 656.0201.09; Electrical Service Meter Breaker Pedestal STH 181 & Northridge Dr, Item 656.0201.10; Electrical Service Meter Breaker Pedestal STH 181 &	
40	Northridge Lakes Blvd, Item 656.0201.11	
46.	Lamp, Ballast, LED, Switch Disposal by Contractor, Item 659.5000.S.	
47.	Utility Line Opening (ULO), Item SPV.0060.01	
48.	Tuck Point Storm Sewer Structure, Item SPV.0060.02.	
49.	Strapping C-40-53, Item SPV.0060.03	56
50.	Install Type 9 Pole, Item SPV.0060.04; Install Type 9 Special Pole, Item SPV.0060.05 Install Type 10 Pole, Item SPV.0060.06; Install Type 10 Special Pole, Item SPV.0060.07; Install Monotube Arms 15-FT, Item SPV.0060.08; Install Monotube Arms 20-FT, Item SPV.0060.09; Install Monotube Arms 25-FT, Item SPV.0060.10; Install Monotube Arms 30-FT, Item SPV.0060.11; Install Monotube Arms 35-FT Special, Item SPV.0060.12; Install Monotube Arms 40-FT Special, Item SPV.0060.13; Install Monotube Arms 45-FT Special, Item SPV.0060.14; Install Luminaire Arms Steel 15-FT, Item SPV.0060.15.	57
51.	Transport and Install State Furnished Traffic Signal Cabinet Florist Ave, Item SPV.0060.16; Transport and Install State Furnished Traffic Signal Cabinet Mill Rd, Item SPV.0060.17; Transport and Install State Furnished Traffic Signal Cabinet Acacia St, Item SPV.0060.18; Transport and Install State Furnished Traffic Signal Cabinet Green Tree Rd, Item SPV.0060.19; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.0060.20; Transport and Install State Furnished Traffic Signal Cabinet Green Ed. Item SPV.	

2140-14-70 2 of 85

	Install State Furnished Traffic Signal Cabinet Calumet Rd, Item SPV.0060.21; Transport and Install State Furnished Traffic Signal Cabinet Bradley Rd, Item SPV.0060.22; Transport and Install State Furnished Traffic Signal Cabinet Tower Ave, Item SPV.0060.23; Transport and Install State Furnished Traffic Signal Cabinet Servite/Dean Rd, Item SPV.0060.24; Transport and Install State Furnished Traffic Signal Cabinet Northridge Dr, Item SPV.0060.25; Transport and Install State Furnished Traffic Signal Cabinet Northridge Lakes Blvd, Item SPV.0060.26.	58
52.	Transport Traffic Signal and Lighting Materials Florist Ave, Item SPV.0060.27; Transport Traffic Signal and Lighting Materials Mill Rd, Item SPV.0060.28; Transport Traffic Signal and Lighting Materials Acacia St, Item SPV.0060.29; Transport Traffic Signal and Lighting Materials Good Hope Rd, Item SPV.0060.30; Transport Traffic Signal and Lighting Materials Calumet Rd, Item SPV.0060.32; Transport Traffic Signal and Lighting Materials Bradley Rd, Item SPV.0060.33; Transport Traffic Signal and Lighting Materials Bradley Rd, Item SPV.0060.33; Transport Traffic Signal and Lighting Materials Servite/Dean Rd, Item SPV.0060.35; Transport Traffic Signal and Lighting Materials Northridge Dr, Item SPV.0060.36; Transport Traffic Signal and Lighting Materials Northridge Lakes Blvd, Item SPV.0060.37.	60
53.	Modify Traffic Signal STH 181 & STH 100, Item SPV.0060.38.	61
54.	Inlet Covers Type H-D, Item SPV.0060.39	61
55.	Cleaning Storm Sewer, Item SPV.0060.40	61
56.	Adjusting Water Valve Boxes, Item SPV.0060.41; Adjusting Water Manholes, Item SPV.0060.42	
57.	Adjusting Sanitary Manholes, Item SPV.0060.43.	63
58.	Internal Manhole Seals, Item SPV.0060.44.	64
59.	Manhole Covers Type MS-58A, Item SPV.0060.45.	65
60.	Adjusting CUC Manhole Cover, Item SPV.0060.46	65
61.	4' Diameter "Doghouse" Manhole Type CUC, Item SPV.0060.47	66
62.	5' Diameter "Doghouse" Manhole Type CUC, Item SPV.0060.48	
63.	Removing CUC Manhole, Item SPV.0060.49.	71
64.	Section Corner Monuments, Item SPV.0060.50.	73
65.	Removing Fence, R-40-76, Item SPV.0060.51.	
66.	Field Facilities Office Space, Item SPV.0060.52.	74
67.	Street Sweeping, Item SPV.0075.01.	75
68.	Concrete Curb and Gutter 6-Inch Sloped 18-Inch Type J, SPV.0090.01.	76
69.	Marking Crosswalk Epoxy Block Style 12-Inch White, SPV.0090.02.	76
70.	Excavation, Hauling, and Disposal of Lead Contaminated Soil, Item SPV.0195.01	77
71.	Excavation, Hauling, and Disposal of PAH Contaminated Soil, Item SPV.0195.02	79
72.	Excavation, Hauling, and Disposal of Petroleum Contaminated Soil, Item SPV.0195.03	82
73.	Asphaltic Repair, Item SPV.0195.04	84

2140-14-70 3 of 85

STSP'S Revised January 8, 2025 SPECIAL PROVISIONS

1. General.

Perform the work under this construction contract for Project C Milwaukee 76th Street, Florist Ave to CTH Q, STH 181, Milwaukee County, Wisconsin as the plans show and execute the work as specified in the State of Wisconsin, Department of Transportation, Standard Specifications for Highway and Structure Construction, 2025 Edition, as published by the department, and these special provisions.

If all or a portion of the plans and special provisions are developed in the SI metric system and the schedule of prices is developed in the US standard measure system, the department will pay for the work as bid in the US standard system.

100-005 (20240703)

2. Scope of Work.

The work under this contract shall consist of HMA milling and resurfacing, concrete pavement, concrete curb and gutter, ADA curb ramps, concrete sidewalk, traffic signals, signs, pavement markings, guardrail, storm sewer, erosion control, fence repair for R-40-76, surface repair for C-40-53 and all incidental items necessary to complete the work as shown on the plans and included in the proposal and contract.

104-005 (20090901)

3. Prosecution and Progress.

A General

Begin work within 10 calendar days after the engineer issues a written notice to do so.

Provide the start date to the engineer in writing within a month after executing the contract but at least 14 calendar days before the preconstruction conference. Upon approval, the engineer will issue the notice to proceed within ten calendar days before the approved start date.

To revise the start date, submit a written request to the engineer at least two weeks before the intended start date. The engineer will approve or deny that request based on the conditions cited in the request and its effect on the department's scheduled resources.

The contract time for completion is based on an expedited work schedule and may require extraordinary forces and equipment.

B Contractor Coordination

Coordinate the work in accordance with standard spec 105.5.2.

Do not commence work under this contract until the required traffic control devices and markings are in place and the engineer approves the installations.

Arrange and conduct weekly progress meetings. The contractor's superintendent or representative, designated materials representative, subcontractor's representatives for ongoing subcontract work or subcontract work expected to begin within the next three weeks shall attend. Provide and discuss the schedule and updates at the weekly progress meetings. Agenda items at the meeting shall include, but not be limited to, the following:

- Review of the contractor's and subcontractors' schedule. Indicate if the project is on, ahead or behind schedule. If behind indicate why, how much behind and how the project will get back on schedule.
- Utility conflicts and relocation schedule.
- · Evaluation of progress to date.
- Outstanding Requests for Information (RFI's) or issues that may cause contract modifications.
- Shop drawing submittal status.
- Materials submittal status.
- Materials sampling and testing activities and results.
- Lane, road, and ramp closure schedules.

2140-14-70 4 of 85

- · Impacts to businesses and private properties.
- · Impacts to bus routes, emergency services, postal services.
- Equipment status of orders and deliveries.

C Work Restrictions

C.1 General

Comply with all local ordinances which apply to work operations, including those pertaining to work during night-time hours. Furnish any and all ordinance variances issued by the municipality or required permits to the engineer in writing three working days before performing such work. Night-time and weekend work will not be allowed without written approval from the engineer and the City of Milwaukee at least three days in advance of the planned work during night-time and weekend hours.

Do not store equipment, vehicles, or materials on adjacent streets beyond the project limits without specific approval from the engineer. Park and store equipment and material only at work sites approved by the engineer.

Where the engineer in conjunction with the contractor's work schedule has permitted lane closure(s), make a continuous effort to complete the work within said lane closure(s) in a timely manner. If, in the engineer's judgment, the contractor's operations fail to meet the approved schedule, permission for a full time lane closure will be rescinded.

Do not begin or continue any work that closes traffic lanes outside the allowed time periods specified in the Traffic article in these special provisions.

Maintain or provide pedestrian access to adjacent properties, businesses, and bus stops where necessary, as directed by the engineer. When closing or relocating crosswalks or sidewalks, provide detectable temporary facilities and include accessibility features consistent with existing pedestrian facilities. Construction of the new curb ramps at each intersection shall be performed in a manner to minimize pedestrian disruption to the extent practical. Provide temporary curb ramps and/or bridging between the curb and right-of-way line over new pavement and other obstructions on the sidewalk area at the entrances to buildings or as directed by the engineer. The cost to maintain pedestrian access shall be incidental to the following bid items: Concrete Sidewalk 5-Inch.

Maintain emergency access to the project area at all times.

Upon completion of the normal workday and when work is not in progress, provide a minimum 3:1 slope off the edge of existing pavements. Sloping shall consist of materials suitable for carrying a vehicle.

Add the following to standard spec 107.18 Environmental Protection:

When performing the roadway cleaning operation, use equipment having vacuum or water spray mechanisms to eliminate the dispersion of dust. If vacuum equipment is employed, it shall have suitable, self-contained particulate collectors to prevent discharge from collection bin into the atmosphere. Store drums, buckets and other containers related to construction operations in a secure area to prevent vandalism, spills, and unwanted dumping. If an abandoned container is discovered on the project site, notify the WDNR at (800) 943-0003.

Add the following to standard spec 108.9.4 Contract Time for Completion Date Contracts:

Work on Saturday, Sunday, or nationally recognized legal holidays will not be allowed without approval from the engineer and the City of Milwaukee at least three days in advance. If scheduling changes after approval has been obtained, notify the engineer as soon as possible, but not later than 3:00 PM of the prior day.

D Schedule of Operations

The schedule of operations shall conform to the construction staging as shown in the construction staging plans, unless the engineer approves modifications to the schedule in writing.

Stage 1

 Construction of the outside lanes on 76th Street and minor streets for curb ramps, concrete curb and gutter, concrete sidewalk, storm sewer modifications, remove and replace guardrail, site restoration, street lighting and signal equipment as shown in plans. Contractor to minimize pedestrian disruption to extent possible.

2140-14-70 5 of 85

Stage 2

 Construction of the median areas on 76th Street for curb ramps, concrete curb and gutter, concrete sidewalk, storm sewer modifications, site restoration, and street lighting and signal equipment as shown in plans. Contractor to minimize pedestrian disruption to extent possible.

Stage 3A

 Construction of the parking, shoulder, and outside lanes of 76th Street, site restoration, northbound and southbound Brown Deer Rd entrance and exit ramps for HMA milling and resurfacing. Contractor to minimize pedestrian disruption to extent possible.

Stage 3B

 Construction of the inside lanes of 76th Street, northbound and southbound Brown Deer Rd entrance and exit ramps for HMA milling and resurfacing and pavement markings. Contractor to minimize pedestrian disruption to extent possible.

Stage 4A

 Construction of the parking, shoulder, and outside lanes on 76th Street and minor streets for pavement marking and permanent signing. Contractor to minimize pedestrian disruption to extent possible.

Stage 4B

 Construction of the inside lanes of 76th Street and minor streets for pavement marking and permanent signing. Contractor to minimize pedestrian disruption to extent possible.

Protection of Endangered Bats (Tree Clearing)

Northern long-eared bats (*Myotis septentrionalis*, or NLEB) have the potential to inhabit the project limits because they roost in trees, bridges and culverts. Roosts may not have been observed on this project, but conditions to support the species exist. The species and all active roosts are protected by the federal Endangered Species Act. If an individual bat or active roost is encountered during construction operations, stop work, and notify the engineer and the WisDOT Regional Environmental Coordinator (REC).

Ensure all operators, employees, and subcontractors working in areas of known or presumed bat habitat are aware of environmental commitments and avoidance and minimization measures (AMMs) to protect both bats and their habitat.

Direct temporary lighting, if used, away from wooded areas during the bat active season April 1 to October 31, both dates inclusive.

Contractor means and methods to remove trees will not be allowed. If it is determined that trees with a 3-inch or greater diameter at breast height (dbh) need to be removed beyond contractor means and methods, notify the engineer to coordinate with the WisDOT REC to determine if consultation with United States Fish and Wildlife Service (USFWS) is required. The contractor must be aware that the WisDOT REC and/or USFWS may not permit modifications.

4. Lane Rental Fee Assesment

A General

The contract designates some lane closures to perform the work. The contractor will not incur a Lane Rental Fee Assessment for closing lanes during the allowable lane closure times. The contractor will incur a Lane Rental Fee Assessment for each lane closure outside of the allowable lane closure times. If a lane is obstructed at any time due to contractor operations, it is considered a closure. The purpose of lane rental is to enforce compliance of lane restrictions and discourage unnecessary closures.

The allowable lane closure times are shown in the Traffic article.

Submit the dates of the proposed lane, ramp, and roadway restrictions to the engineer as part of the progress schedule.

Coordinate lane, ramp, and roadway closures with any concurrent operations on adjacent roadways within 3 miles of the project. If other projects are in the vicinity of this project, coordinate lane closures to run concurrent with lane closures on adjacent projects when possible. When lane closures on adjacent

2140-14-70 6 of 85

projects extend into the limits of this project, Lane Rental Fee Assessments will only occur if the closure facilitates work under this contract.

B Lane Rental Fee Assessment

The Lane Rental Fee Assessment incurred for each lane closure, each ramp closure, and each full closure of a roadway, per direction of travel, is as follows:

- Off Peak- \$500 per lane, per direction of travel, per hour broken into 15-minute increments
- On Peak- \$2,000 per lane, per direction of travel, per hour broken into 15-minute increments

The Lane Rental Fee Assessment represents a portion of the cost of the interference and inconvenience to the road users for each closure. All lane, roadway, or ramp closure event increments 15 minutes and less will be assessed as a 15-minute increment.

The engineer, or designated representative, will be the sole authority in determining time period length for the Lane Rental Fee Assessment.

Lane Rental Fee Assessments will not be assessed for closures due to crashes, accidents or emergencies not initiated by the contractor.

The department will assess Lane Rental Fee Assessment by the dollar under the administrative item Failing to Open Road to Traffic. The total dollar amount of Lane Rental Fee Assessment will be computed by multiplying the Lane Rental Assessment Rate by the number of 15-minute increments of each lane closure event as described above.

Lane Rental Fee Assessment will be in effect from the time of the Notice to Proceed until the department issues final acceptance. If interim completion time or contract time expires before the completion of specified work in the contract, additional liquidated damages will be assessed as specified in standard spec 108.11 or as specified within this contract.

stp-108-070 (20161130)

5. Traffic.

Supplement standard spec 643.3.1 with the following:

STH C Milwaukee 76th Street, Florist Ave to CTH Q, is not a designated OSOW route. However, if required all fixed message and width restricted signs must be in place prior to the beginning of the width restricted stage to inform multi trip permit holders to utilize alternate routes. See Wisconsin Lane Closure System Advance Notification article to address lane restrictions in LCS.

Provide the Milwaukee Police Department and the project engineer a current telephone number with which the contractor or his representative can be contacted during non-working hours in the event a safety hazard develops

Yield to all through traffic at all locations. Equip all vehicles or equipment operating in the live traffic lanes with a hazard identification beam (flashing yellow signal light) that is visible from 360 degrees. Operate the flashing yellow beam only when merging or exiting live traffic lanes or when parked or operating on shoulders, except when parked behind barrier wall. Do not cross live traffic lanes of N/S 76th Street with equipments or vehicles.

Provide minimum 24-hour advance notification to the engineer for any LCS cancellations (not related to weather).

Do not disturb, remove, or obliterate any traffic control signs, advisory signs, sand barrel array, shoulder delineators or beam guard in place along the traveled roadways without the approval of the engineer.

SER-643-001 (20230214)

Wisconsin Lane Closure System Advance Notification

Provide the following advance notification to the engineer for incorporation into the Wisconsin Lane Closure System (LCS).

2140-14-70 7 of 85

TABLE 108-1 CLOSURE TYPE AND REQUIRED MINIMUM ADVANCE NOTIFICATION

Closure type with height, weight, or width restrictions (available width, all lanes in one direction < 16 feet)	MINIMUM NOTIFICATION
Lane and shoulder closures	7 calendar days
Full roadway closures	7 calendar days
Ramp closures	7 calendar days
Detours	7 calendar days
Closure type without height, weight, or width restrictions (available width, all lanes in one direction ≥ 16 feet)	MINIMUM NOTIFICATION
	MINIMUM NOTIFICATION 3 calendar days
(available width, all lanes in one direction ≥ 16 feet)	
(available width, all lanes in one direction ≥ 16 feet) Shoulder Closures	3 calendar days

Discuss LCS completion dates and provide changes in the schedule to the engineer at weekly project meetings in order to manage closures nearing their completion date.

A General

Perform this work according to standard spec 643, the Manual on Uniform Traffic Control Devices (MUTCD), and as shown on the plans or as approved by the engineer.

Accomplish the construction sequence, including the associated traffic control as detailed in the Construction Staging section of the plans, and as described in the Prosecution and Progress article, and in this Traffic article.

Employ flaggers, signs, barricades, and drums as necessary to safeguard and direct traffic at all locations where construction operations may interfere with or restrict the smooth flow of traffic.

Use drums and barricades to direct vehicular and pedestrian traffic in the work zone and to protect and delineate hazards such as open excavations and abrupt drop-offs.

Coordinate traffic requirements under this project with other adjacent department or local municipality projects. Contractor is responsible for implementing and coordinating with other contractors all traffic control shown in the plans. Modifications to the traffic control plan may be required by the engineer to be safe and consistent with adjacent work by others.

Submit to the engineer for approval a detailed traffic control plan if different than the traffic control plan provided in the plan set. Submit this plan ten days prior to the pre-construction conference. No operation may proceed until all traffic control devices for such work are in the proper location. Have available at all times sufficient experienced personnel to promptly install, remove, and reinstall the required traffic control devices to reroute traffic during the construction operations. During all construction operations, maintain adequate turning provisions for vehicles, including buses and

B Definitions

The following definitions shall apply to this contract:

trucks, at the intersections that are to remain open.

Night-Time Periods

- 10:00 PM to 6:00 AM Monday, Tuesday, Wednesday, Thursday, and Friday
 Weekend Periods
- · 10:00 PM Friday to 6:00 AM Monday

C Traffic Control Description

Pedestrian Work Zone Traffic Control - 76th Street - Florist Ave to CTH Q

With the number of residences and businesses located within the project limits, maintaining pedestrian access during construction is vital and required at all times. The construction work will require limiting the curb ramp construction at each intersection to one ramp at a time. This allows for pedestrian traffic to be maintained at the other locations within the intersections. Refer to the Traffic Control Curb Ramp Construction Sequence Detail for additional information.

2140-14-70 8 of 85

The curb ramp numbering sequences are as follows:

Sequence #1 – north median curb ramp cut through Sequence #2 – east median curb ramp cut through Sequence #3 – south median curb ramp cut through Sequence #4 – west median curb ramp cut through Sequence #5 – northwest quadrant curb ramps Sequence #6 – northeast quadrant curb ramps Sequence #7 – southeast quadrant curb ramps Sequence #8 – southwest quadrant curb ramps

Stage 1:

- Construction of the outside lanes on 76th Street and minor streets for curb ramps, concrete curb and gutter, concrete sidewalk, storm sewer modifications, site restoration, remove and replace guardrail, and street lighting and signal equipment as shown in plans.
- Southbound and northbound parking, shoulder, and outside lane closures for 76th Street.
- Maintain two-way traffic southbound along 76th Street from the southern project limits to Station 214+75.
- Maintain one-way traffic southbound along 76th Street from Station 214+75 to the northern project limits.
- Maintain two-way traffic northbound along 76th Street from the southern project limits to Station 192+00.
- Maintain one-way traffic northbound along 76th Street from Station 192+00 to the northern project limits.
- Maintain southbound to eastbound left turn lanes per the plans.
- Maintain northbound to westbound left turn lanes per the plans.
- Curb ramp construction of one quadrant at a time by the following sequence #2, 4, 5, 6, 7, and 8
 at all intersections. Maintain pedestrian access at all other locations.

Stage 2:

- Construction of the median areas on 76th Street for curb ramps, concrete curb and gutter, concrete sidewalk, storm sewer modifications, site restoration, and street lighting and signal equipment as shown in plans.
- Southbound and northbound inside side lane closures for 76th Street.
- Maintain two-way traffic southbound along 76th Street from the southern project limits to Station 220+00.
- Maintain one-way traffic southbound along 76th Street from Station 220+00 to the northern project limits.
- Maintain two-way traffic northbound along 76th Street from the southern project limits to Station 222+00.
- Maintain one-way traffic northbound along 76th Street from Station 222+00 to the northern project limits.
- Maintain a southbound to eastbound left turn lane per the plans.
- · Maintain a northbound to westbound left turn lane per the plans.
- Curb ramp construction of one quadrant at a time by the following sequence #1, and 3 at all intersections. Maintain pedestrian access at all other locations.

Stage 3A:

- Construction of the parking, shoulder, and outside lanes of 76th Street, northbound and southbound Brown Deer Rd entrance and exit ramps for HMA milling and resurfacing.
- Southbound and northbound parking, shoulder, and outside lane closures for 76th Street.
- · Full lane closures for northbound and southbound Brown Deer Rd entrance and exit ramps.

2140-14-70 9 of 85

- Maintain one-way traffic southbound and northbound along 76th Street from the southern project limits to the northern project limits.
- Maintain southbound to eastbound left turn lanes per the plans.
- · Maintain northbound to westbound left turn lanes per the plans.

Stage 3B:

- Construction of the inside lanes of 76th Street, northbound and southbound Brown Deer Rd entrance and exit ramps for HMA milling and resurfacing and pavement markings.
- Southbound and northbound inside side lane closures for 76th Street.
- Maintain one-way traffic southbound and northbound along 76th Street from the southern project limits to the northern project limits.
- · Maintain a southbound to eastbound left turn lane per the plans.
- Maintain a northbound to westbound left turn lane per the plans.

Stage 4A:

- Construction of the parking, shoulder, and outside lanes on 76th Street and minor streets for pavement marking and permanent signing.
- Southbound and northbound parking, shoulder, and outside lane closures for 76th Street.
- Maintain two-way traffic southbound along 76th Street from the southern project limits to Station 214+75.
- Maintain one-way traffic southbound along 76th Street from Station 214+75 to the northern project limits.
- Maintain two-way traffic northbound along 76th Street from the southern project limits to Station 192+00.
- Maintain one-way traffic northbound along 76th Street from Station 192+00 to the northern project limits.
- · Maintain southbound to eastbound left turn lanes per the plans.
- Maintain northbound to westbound left turn lanes per the plans.

Stage 4B:

- Construction of the inside lanes of 76th Street and minor streets for pavement marking and permanent signing.
- Southbound and northbound inside side lane closures for 76th Street.
- Maintain two-way traffic southbound along 76th Street from the southern project limits to Station 220+00.
- Maintain one-way traffic southbound along 76th Street from Station 220+00 to the northern project limits.
- Maintain two-way traffic northbound along 76th Street from the southern project limits to Station 222+00.
- Maintain one-way traffic northbound along 76th Street from Station 222+00 to the northern project limits.
- · Maintain a southbound to eastbound left turn lane per the plans.
- Maintain a northbound to westbound left turn lane per the plans.

D Work Restrictions

Nighttime work is expected for this project for the milling and paving operations of the on and off ramps to/from Brown Deer Road (STH 100). The contractor is responsible for obtaining a nighttime working permit from the local municipalities. The night closures of these ramps must occur between 10PM and 6AM.

2140-14-70 10 of 85

Work for Stages 3A and 3B during the PM peak traffic hours (2PM to 6PM) along the STH 181 project limits will only be allowed if the traffic volumes allow. Two through lanes in each direction must be open during this time. Contractor to coordinate with the engineer. The engineer will determine if there are portions of the corridor that may be worked on.

Peak Hours

- 2:00 PM – 6:00 PM (Monday, Tuesday, Wednesday, Thursday, and Friday)

Off-Peak Hours

- 6:00 PM - 2:00 PM (Monday, Tuesday, Wednesday, Thursday, and Friday)

6. Holiday and Special Event Work Restrictions.

Do not perform work on, nor haul materials of any kind along or across any portion of the highway carrying STH 181 traffic, and entirely clear the traveled way and shoulders of such portions of the highway of equipment, barricades, signs, lights, and any other material that might impede the free flow of traffic during the following holiday and special event periods:

- From noon Wednesday, November 26, 2025, to 6:00 AM Monday, December 1, 2025, Thanksgiving Day;
- From noon Tuesday, December 23, 2025, to 6:00 AM Friday, December 26, 2025, Christmas;
- From noon Thursday, December 30, 2025, to 6:00 AM Monday, January 4, 2025, New Years;
- From noon Friday, May 22, 2026, to 6:00 AM Tuesday, May 26, 2026, Memorial Day;
- From noon Thursday, July 2, 2026, to 6:00 AM Monday, July 6, 2026, Independence Day;
- From noon Friday, September 4, 2026, to 6:00 AM Tuesday, September 8, 2026, Labor Day;
- From noon Wednesday, November 25, 2026, to 6:00 AM Monday, November 30, 2026, Thanksgiving Day;
- From noon Wednesday, December 23, 2026, to 6:00 AM Monday, December 28, 2026, Christmas;
- From noon Wednesday, December 30, 2026, to 6:00 AM Monday, January 4, 2027, New Years;

stp-107-005 (20210113)

7. Utilities.

A General

This contract comes under the provision of Administrative Rule Trans 220.

The utility work plan includes additional detailed information regarding the location of known discontinued, relocated, or removed utility facilities. These can be requested from the department during the bid preparation process or from the project engineer after the contract has been awarded and executed. Some of the utility work described below is dependent on prior work being performed by the contractor at a specific site. In such situations, provide the engineer and the affected utility a good faith notice of when the utility is to start work at the site. Provide this notice 14 to 16 calendar days in advance of when the prior work will be completed, and the site will be available to the utility. Follow-up with a confirmation notice to the engineer and the utility not less than 3 working days before the site will be ready for the utility to begin its work.

Stp-107-065 (20240703)

Any utility facility locations (stations, offsets, elevations, depths) listed in this article are approximate.

The following utility companies have facilities within the project area that need adjustments:

AT&T WI - Communication Line

To be completed by utility company during construction.

AT&T WI will require multiple conduit duct and cable relocations during road construction. Anticipated to be completed in 1 working day per each location at the following locations below:

• Station 73+64, 10' RT: AT&T to expose and adjust conduit duct 2 feet east to avoid temporary signal pole and avoid signal pole base.

2140-14-70 11 of 85

- Station 72+56, 75' LT: AT&T to expose and adjust conduit duct 2 feet north to avoid signal pole base.
- Station 127+41, 10' RT: AT&T to expose and adjust conduit duct 1 feet east to avoid signal pole base.
- Station 46+09, 60' LT: AT&T to expose and adjust fiber optic line 2' north to avoid signal pole base.
- Station 46+15, 72' LT: AT&T to expose and adjust fiber optic line 2' north to avoid signal pole base.
- Station 46+10, 10' RT: AT&T to relocate cables and ducts 2' east to avoid signal pole base.
- Station 47+38, 10' RT: AT&T to expose and adjust conduit ducts 1' east and 1' west to avoid signal pole base.
- Station 257+86, 44' RT: AT&T to expose and adjust conduit duct 1' west to avoid signal pole base.
- Station 86+07, 8' RT: AT&T to expose and adjust conduit duct 2' east to avoid signal pole base.
- Station 87+03, 9' RT: AT&T to expose and adjust conduit duct 2' east to avoid signal pole base.
- Station 205+53, 60' RT: AT&T to move existing pipe 2' north to avoid temporary signal pole.
- Station 206+68, 62' RT: AT&T to move existing 600 pair cable 2' northwest to avoid signal pole base.
- Station 99+30, 10' RT: AT&T to move conduit duct 2' east to avoid signal pole base.
- Station 100+35, 9' RT: AT&T to move duct 2' east to avoid signal pole base.
- · Station 152+95, 69' LT: AT&T to move conduit duct 2' north to avoid signal pole base
- Station 65+10, 41' RT: AT&T to pothole fiber optic and cable facility location and provide depth for guardrail post installation.

City of Milwaukee - Conduit

Manhole cover adjustment

<u>SPV.0060.46 – Adjusting City Underground Conduit (CUC) Manhole Covers for the following locations:</u>

Station 46+30, 36' LT

Station 46+86, 25' LT

Station 53+03, 25' LT

Station 58+20, 24' LT

Station 64+57, 23' LT

Station 72+97, 71' LT

Station 83+68, 26' LT

Station 86+69, 17' LT

Station 137+62, 17' LT

Station 147+72, 17' LT

Station 152+77, 18' LT

Station 157+77, 18' LT

Station 162+56, 18' LT

Station 167+65, 18' LT

Station 179+16, 72' LT

Station 179+22, 74' RT

2140-14-70 12 of 85

Station 179+24, 18' LT

Station 185+99, 17' LT

Station 191+77, 18' LT

Station 198+73, 18' LT;

Station 205+73, 16' LT

Station 212+40, 17' LT

Station 218+03, 40' LT

Station 223+55, 9' RT

Station 228+30, 9' RT

SPV.0060.47 – 4' Diameter Doghouse Manhole Type CUC for the following locations:

4' Doghouse Manhole structure replacement

Station 69+32, 20' LT

Station 78+68, 25' LT

Station 93+48, 17' LT

Station 105+96, 18' LT

Station 112+40, 18' LT

Station 116+16, 18' LT

Station 119+36, 18' LT

Station 131+86, 18' LT

Station 142+68, 17' LT

Station 173+88, 17' LT

SPV.0060.48 – 5' Diameter Doghouse Manhole Type CUC for the following locations:

5' Doghouse Manhole structure replacement

Station 72+92, 14' LT

Station 100+08, 18' LT

<u>SPV.0060.49 – Removing CUC Manhole for the following locations:</u>

Station 69+32, 20' LT

Station 72+92, 14' LT

Station 78+68, 25' LT

Station 93+48, 17' LT

Station 100+08, 18' LT

Station 105+96, 18' LT

Station 112+40, 18' LT

Station 116+16, 18' LT

Station 119+36, 18' LT

Station 131+86, 18' LT

Station 142+68, 17' LT

Station 173+88, 17' LT

2140-14-70 13 of 85

City of Milwaukee – Water

Water gate valve boxes and water manholes to be adjusted during construction prior to final HMA paving.

MWW requested (178) valve boxes and (5) water manhole adjustments be included in the paving contract as nonparticipating items and performed by the departments contractor. Adjust valves boxes and water manholes to match the new finished pavement elevations. Perform this work in accordance with the requirements of Adjusting Water Valve Boxes, Item SPV.0060.41 and Adjusting Water Manholes, Item SPV.0060.42

To be completed by utility company prior to construction.

Water Main alteration is required at Station 256+78, 44' LT (Northridge Lake Blvd.) due to direct conflict with proposed monotube. Anticipated to be completed in 3 working days and in the Fall of 2025.

Midwest Fiber Networks - Communication Line

To be completed by utility company prior to construction.

Acacia St - MWFN will be relocating our ducts entering/exiting our handhole (in easement) at Station 10+66.5 33.3' RT. The 4 new 1.25" ducts will leave the north side of the handhole and sweep to Station 10+61 28' RT east to Station 10+90 28' RT, where two ducts will then sweep to the south to intercept our existing duct at Station 85+98 59' LT and the other two ducts will turn north to intercept our existing line at Station 86+82.5 56' LT, discontinuing conflicting ducts in place.

Green Tree St - MWFN will redrill (2) 1.25" ducts beginning at Station 98+96 53.4' LT to Station 99+05 55.2' LT, continuing north to Station 100+00 56.2' LT and back to our existing ducts at Station 100+81.5 52.5' LT, discontinuing conflicting ducts in place.

Denver St - MWFN will redrill (2) 1.25" ducts beginning at Station 105+34 52.4' LT, sweeping to Station 106+16 62.4' LT and back to our existing handhole at Station 106+63.4 59.4' LT, discontinuing existing ducts in place.

Good Hope Rd - MWFN will redrill (2) 1.25" ducts beginning at Station 125+09 52' LT, sweeping into the sidewalk to Station 125+20 and continuing north to intercept our existing ducts at Station 125+49.6 55' LT, discontinuing existing ducts in place.

To be completed by utility company during construction

Denver St - MWFN will adjust existing handhole for sidewalk installation at Station 106+63.4 59.4' LT Provide advance notice after existing sidewalk is removed and subgrade is exposed, and the site is available to the utility owner. Utility owner shall adjust handhole to match proposed sidewalk. Anticipated to be completed in 1 working day.

Verizon Business - Communication Line

To be completed by utility company prior to construction.

Station 69+83, 68' RT - Vault to be relocated 10 feet East to STA:69+83 78'RT to avoid new concrete ADA ramp.

To be completed by utility company during construction

Station 153+50, 53'RT - Conduit in conflict with monopole SB13. Provide advance notice after existing sidewalk is removed and subgrade is exposed, and the site is available to the utility owner. Utility owner shall expose the conduit for 20 feet and move further into sidewalk. Anticipated to be completed in 1 working day.

We Energies - Electricity

To be completed by utility company during construction.

We Energies will require multiple manhole frame, chimney, and cover replacements during road construction. Anticipated to be completed in 1 working day per each location at the following locations below:

Station 274+91, 48.7' RT: MH74-415 Replace manhole frame, chimney, and cover

2140-14-70 14 of 85

Station 270+39, 49.7' RT: MH74-414 Replace manhole frame, chimney, and cover Station 264+44, 75.6' RT: MH71-423 Replace manhole frame, chimney, and cover Station 257+77, 53.5' RT: MH69-821 Replace manhole frame, chimney, and cover Station 207+01, 60.5' RT: MH70-443 Replace manhole frame, chimney, and cover Station 184+18, 4.5' RT: MH70-436 Replace manhole frame, chimney, and cover Station 178+94, 13.5' RT: MH9308 Replace manhole frame, chimney, and cover Station 173+64, 12.5' LT: MH70-409 Replace manhole frame, chimney, and cover Station 168+56, 16.3' LT: MH70-408 Replace manhole frame, chimney, and cover Station 139+62, 20.5' LT: MH70-403 Replace manhole frame, chimney, and cover Station 134+64, 21.7' LT: MH70-402 Replace manhole frame, chimney, and cover Station 129+70, 21' LT: MH70-401 Replace manhole frame, chimney, and cover Station 125+48, 14.7' LT: MH9270 Replace manhole frame, chimney, and cover Station 119+99, 34.7' LT: MH9269 Replace manhole frame, chimney, and cover Station 114+49, 25.1' LT: MH9268 Replace manhole frame, chimney, and cover Station 109+63, 25.8' LT: MH9267 Replace manhole frame, chimney, and cover Station 104+89, 33.7' LT: MH9266 Replace manhole frame, chimney, and cover Station 100+5, 36.4' LT: MH9265 Replace manhole frame, chimney, and cover Station 95+61, 27.3' LT: MH9264 Replace manhole frame, chimney, and cover Station 91+27, 30.5' LT: MH9263 Replace manhole frame, chimney, and cover Station 86+58, 42' LT: MH9262 Replace manhole frame, chimney, and cover Station 80+83, 30.6' LT: MH9261 Replace manhole frame, chimney, and cover Station 77+44, 30.6' LT: MH9260 Replace manhole frame, chimney, and cover Station 73+35, 10' LT: MH75-444 Replace manhole frame, chimney, and cover Station 72+59, 30.6' LT: MH9259 Replace manhole frame, chimney, and cover Station 69+58, 32.9' LT: MH9248 Replace manhole frame, chimney, and cover Station 64+42, 33.2' LT: MH9247 Replace manhole frame, chimney, and cover Station 46+19, 2.1' RT: MH7696 Replace manhole frame, chimney, and cover Notify:

ivoury.

We Energies

Tara Blecha

Electric Operations Supervisor

Office: (414) 540-5784 Mobile: (414) 737-4051

It is imperative that the highway contractor contact We Energies before removing any electrical underground cables, to verify that they have been discontinued and carry no electrical current. Do not assume that unmarked facilities have been discontinued. At no time is it acceptable to push, pull, cut, or drill an unmarked facility without explicit consent from We Energies. Call the We Energies 24-hour Dispatch line to arrange for this verification.

We Energies Electric Dispatch #1-800-662-4797

WE Energies - Gas

To be completed by utility company prior to construction.

We Energies is planning to replace HP gas facilities related to the N 76th St (County Line Rd – Florist) paving project starting in June 2025 at the following locations.

2140-14-70 15 of 85

- 1. N 76th St (W Brown Deer Rd W Glenbrook Rd)
- 2. N 76th St (W Florist Ave Union Pacific RR)
- 3. N 76th St (UPRR W Mill Rd)*

*This phase includes additional high pressure main replacement work on Mill Rd from N 77th St to N 80th St and continuing on N 80th St from Mill Rd to Casper.

20" High Pressure Transmission Main: We Energies will be replacing a total of approximately 1.5 miles of 20" high pressure transmission main in two areas within the project limits. The transmission main is not in conflict with proposed roadway features. The transmission main will be relocated adjacent to its current location offset 5' RT to 15' LT.

4" PE Distribution Main:

We Energies will be replacing approximately 675' of 3" PE. A portion of this is in conflict with Proposed Mono tube at North Ridge Lakes Blvd. The relocation of the gas main is approximately 41' RT of current location and in the southbound outside lane of N 76th Street.

2" PE Distribution Main:

N 76TH & W Dean Rd Intersection: We Energies will be relocating approximately 25' of 3" ST main and valve in conflict with the proposed signal base located at the SW intersection of N 76th & W Dean Road with 2" PE approximately 3'-4' west of current location and will be underneath the sidewalk.

N 76TH & Tower Ave Tee Intersection: There is a potential conflict with proposed signal base at the east side of N 76th St at Tower Ave. Existing gas main will be abandoned in place. A new gas service will be constructed from the west side of N 76th Street to the building on the east side.

To be completed by utility company during construction.

We Energies anticipates (10) working days to complete final tie-ins at N 76th Street/W Mill Road and (10) working days to complete all valve box adjustments. We Energies requires notice before the work site is anticipated to be available for each location of utility relocation and/or adjustment work.

Gas Valve Box and Gas Box Adjustments:

Location 1: Valve box V10430 & V10429 located at N 76th St & Glenbrook Rd entrance

Location 2: Valve box V15768 located at NW corner of N 76th & W Tower Ave

Location 3: Valve box V19266 located at NW corner of N 76th & W Lolita Ave

Location 4: Valve box V16174 & V16175 at NW & NE corners of N 76th St & W Calumet Rd

Location 5: Valve box V18944 located at the NW corner of N 76th St & W Clinton Ave

Location 6: Gas box located in road along N 76th St at Station 19+58 15' RT

Location 7: Gas box located in sidewalk at SW corner of N 76th St & Green Tree Rd

Location 8: Valve box V18935 & V02461 located at NW corner and in road at Station 73 +29 53' LT of N 76th St & W Mill Rd

Location 9: Valve box V19859 located at SE corner of N 76th St & W Florist Ave

It is imperative that the highway contractor contact We Energies before removing any gas facilities, to verify that they have been discontinued and carry no natural gas. Do not assume that unmarked facilities have been discontinued. At no time is it acceptable to push, pull, cut, or drill an unmarked facility without explicit consent from We Energies. Call the We Energies 24-hour Dispatch line to arrange for this verification.

We Energies Gas Dispatch #1-800-261-5325

The following utility companies have facilities within the project area; however, no adjustments are anticipated:

2140-14-70 16 of 85

ATC Management, Inc - Electricity-transmission

ATC has overhead and underground Communication facilities crossing 76th Street.

ATC has overhead and underground 138 kV transmission facilities crossing 76th Street

ATC has overhead 345 kV transmission facilities crossing 76th Street.

There are no anticipated conflicts.

<u>City of Milwaukee – Communication Line</u>

City of Milwaukee - Sewer

Everstream – Communication Line

Level 3 Communications – Communication Line

Mequon Water Utility - Water

<u>Milwaukee Metro Sewerage District – Sewer</u>

MMSD has manhole structures and sewers located within the project limits. Based on the project scope these structures will not require elevation adjustments.

MMSD Manhole 19911, Station 99+46.4, 21.6' LT

MMSD Manhole 19918, Station 103+3, 12' LT

MMSD Manhole 19919, Station 108+62, 23' LT

MMSD Manhole 19920, Station 113+98, 22' LT

MMSD Manhole 19921, Station 120+51, 23' LT

MMSD Manhole 19922, Station 126+58, 23' LT

PaeTec Communications – Communication Line

<u>Spectrum – Communication Line</u>

Sprint Communications – Communication Line

8. Referenced Construction Specifications.

Construct the work enumerated below conforming to the City of Milwaukee Standard Specifications and the Standard Specification for Sewer and Water Construction in Wisconsin. If there is a discrepancy or conflict between the referenced specification and the standard specifications regarding contract administration, part 1 of the standard specifications governs.

Conform to the referenced construction specifications for the following:

Adjusting Water Valve Boxes, Item SPV.0060.41

Adjusting Water Manholes, Item SPV.0060.42

Adjusting Sanitary Manholes, Item SPV.0060.43

Internal Manhole Seals, Item SPV.0060.44

Manhole Covers Type MS 58-A, SPV.0060.45

Adjusting CUC Manhole Cover, Item SPV.0060.46

4' Diameter "Doghouse" Manhole Type CUC, Item SPV.0060.47

5' Diameter "Doghouse" Manhole Type CUC, Item SPV.0060.48

Removing CUC Manhole, Item SPV.0060.49

stp-105-002 (20130615)

2140-14-70 17 of 85

9. Timely Decision Making Manual.

Use the Timely Decision Making Manual (TDM) on this contract. Coordinate with the department to modify the various published tools as necessary to meet the particular project needs and determine how to implement those tools under the contract. Ensure the full participation of the contractor and its principal subcontractors throughout the term of the contract.

Forms and associated guidance are published in the TDM available at the department's Highway Construction Contract Information (HCCI) web site at:

https://wisconsindot.gov/rdwy/admin/tdm.docx

stp-105-005 (20151210)

10. Other Contracts

For all projects, coordinate activities, detours, work zone traffic control, roadway, erosion control and lane closures, and other work items as required with other contracts.

The following contract is anticipated to be under construction within the time period of this contract, and includes necessary work found in Stage 4 under Prosecution and Progress in this contract unless otherwise indicated:

2729-07-70

Notify the engineer two weeks in advance of completion of each stage so the engineer can coordinate with project 2729-07-70.

11. Work by Others

Modifications to the traffic control plan may be required by the engineer to be safe and consistent with adjacent work by others.

It is expected that routine maintenance by city and county personnel may be required at certain times that is concurrent with the work being done under this contract.

SER-107-012 (20250501)

12. Work by Others – City of Milwaukee – Street Lighting

Street lighting conduit/circuitry located approximately 6" behind existing curb profiles. Circuitry is to be hot-lined and carefully excavated, field identified and relayed prior to backfill. Circuitry to be placed 24" below finished grades. Conduit that is damaged must be inspected by B.E.S. prior to encasement in appropriately sized split duct system. Damaged conduit/cable not allowed to be repositioned without inspection and approval by B.E.S. forces

13. Work by Others – WisDOT – Communication Line

WisDOT communications has fiber optic cable running East West in the median at Good Hope Road. The fiber line will not be relocated. Contractor will need to do a utility line opening (Approx STA 126+16, 93' right) in the East median of the intersection of North 76th Street and Good Hope Road to expose the fiber duct package (2–4-inch grey multi-cell PVC conduit) before work can commence on drilling for the base of the proposed monotube pole in the median at this location. The fiber conduit package is approx. 2-3 feet deep at this location.

14. Work by Others – WisDOT – ATR Pull Boxes

Existing loops in roadway to be abandoned and can be milled thru. Utility requires **5 days** prior notification for removal of existing ATR Cabinet. *Contact Russell Lewis*.

2140-14-70 18 of 85

Russell Lewis WISDOT ATR Pull Boxes - Electricity 3625 Pierstorff St Madison, WI 53702 (608) 516-5754 russell.lewis@dot.wi.gov

15. Railroad Insurance and Coordination – Union Pacific Railroad Company

A Description

Comply with standard spec 107.17 for all work affecting Union Pacific Railroad Company property and any existing tracks.

A.1 Railroad Insurance Requirements

In addition to standard spec 107.26, provide railroad protective liability insurance coverage as specified in standard spec 107.17.3 Insurance is filed in the name of Union Pacific Railroad Company.

Notify evidence of the required coverage, and duration to David C. LaPlante, Director -Real Estate-Special and Public Projects, 1400 Douglas St. STOP 1690, Omaha, NE 68179; Telephone: (402) 544-8563; E-mail: dclaplante@up.com.

Also send a copy to the following: Jason Kazmierski, SE Region Railroad Coordinator, 141 N. Barstow Street, Waukesha, WI 53188; Telephone (262)548-6700; E-mail jason.kazmierski@dot.wi.gov

Include the following information on the insurance document:

- Project ID: 2140-14-70
- Work Performed on or within 50' of RR ROW: Traffic control

#	Route Name	City/County	Crossing ID	RR Subdivision	RR Milepost
1	STH 181 / 76th Street	Milwaukee/Milwaukee	178876L	Shoreline Sub	MP 99.37
2	STH 181 / 76th Street	Milwaukee/Milwaukee	178899T	Granville Ind Ld	MP 95.946

A.2 Train Operation

#	Passenger Train Volume	Passenger Train Speed	Freight Train Volume	Freight Train Speed	Frequency	Switch Train Comment*
1	N/A	N/A	2	25	Daily	No switch trains
2	N/A	N/A	2	10	Daily	No switch trains

Switch trains are in addition to freight and passenger trains.

A.3 Names and Addresses of Railroad Representatives for Consultation and Coordination Construction Contact

Chris T. Keckeisen, Manager Special Projects - Industry & Public Projects Engineering Department; 1400 Douglas, MS 0910, Omaha, NE, 68179; Telephone (402) 5445131; E-mail ctkeckei@up.com for consultation on railroad requirements during construction.

Amend standard spec 108.4 to include the railroad in the distribution of the initial bar chart, and monthly schedule updates. The bar chart shall specifically show work involving coordination with the railroad.

Flagging Contact

See Construction Contact. If more than 30 days of flagging is required contact UP 40 days prior to needing a flagger on site. Reference the Wisconsin Milepost and Subdivision located in A.1.

Cable Locate Contact

In addition to contacting Diggers Hotline, contact the UP Call Before You Dig line at (800) 336-9193 at least five working days before the locate is needed. Normal business hours are 6:30 AM to 6:30 PM, Central Time, Monday through Friday, except holidays and are subject to change. Calls will be routed at all times in case of an emergency. Reference the Wisconsin Milepost and Subdivision located in A.1.

2140-14-70 19 of 85

UP will only locate railroad owned cable buried in the railroad right-of-way. The railroad does not locate any other utilities.

A.4 Work By Railroad

The railroad will perform the work described in this section, except for work described in other special provisions, and will be accomplished without cost to the contractor. None.

A.5 Temporary Grade Crossing

If a temporary grade crossing is desired, submit a written request to the railroad representative named in A.3 at least 40 days prior to the time needed. Approval is subject to the discretion of the railroad. The department has made no arrangements for a temporary grade crossing.

stp-107-026 (20250108)

16. Railroad Insurance and Coordination – Wisconsin and Southern Railroad Company

A Description

Comply with standard spec 107.17 for all work affecting Wisconsin and Southern Railroad Company property and any existing tracks.

A.1 Railroad Insurance Requirements

In addition to standard spec 107.26, provide railroad protective liability insurance coverage as specified in standard spec 107.17.3 Insurance is filed in the name of Watco Companies, L.L.C., and its affiliates, subsidiaries, and assigns.

Notify evidence of the required coverage, and duration to Justin Mahr, Senior Manger Real Estate - Contracts; 315 W. 3rd Street, Pittsburg, KS 66762; Telephone (402) 651-8238; E-mail: justin.mahr@watco.com

Also send a copy to the following: Jason Kazmierski, SE Region Railroad Coordinator, 141 N. Barstow Street, Waukesha, WI 53188; Telephone (262)548-6700; E-mail jason.kazmierski@dot.wi.gov

Include the following information on the insurance document:

- Project ID: 2140-14-70
- Work Performed on or within 50' of RR ROW:
 - 1) Mill & overlay, inlet protection, traffic control.
 - 2) Traffic control.

#	Route Name	City/County	Crossing ID	RR Subdivision	RR Milepost
1	STH 181 / 76th Street	Milwaukee/Milwaukee	386971E	Milwaukee Sub	MP 97.00
2	CTH PP / Good Hope Road	Milwaukee/Milwaukee	386972L	Milwaukee Sub	MP 97.20

A.2 Train Operation

#	Passenger Train Volume	Passenger Train Speed	Freight Train Volume	Freight Train Speed	Frequency	Switch Train Comment*
1	N/A	N/A	4	40	Daily	No switch trains
2	N/A	N/A	4	40	Daily	No switch trains

^{*} Switch trains are in addition to freight and passenger trains.

A.3 Names and Addresses of Railroad Representatives for Consultation and Coordination Construction Contact

Chris Jacobson, Superintendent of Engineering, Wisconsin and Southern Railroad Co.; 1890 East Johnson Street, Madison, WI 53704; Telephone (608) 750-6427; E-mail cjacobson@watco.com for consultation on railroad requirements during construction.

Amend standard spec 108.4 to include the railroad in the distribution of the initial bar chart, and monthly schedule updates. The bar chart shall specifically show work involving coordination with the railroad.

2140-14-70 20 of 85

Flagging Contact

See Construction Contact. Reference the Crossing ID, Wisconsin Milepost and Subdivision found in A.1. Contractor must officially request a railroad flagger a minimum of 15 day prior to scheduled work. If the contractor fails to do so and is required to pay an Expedited Fee, the project will not reimburse the contractor for said fee.

Cable Locate Contact

In addition to contacting Diggers Hotline, contact the Construction Contact at least five working days before the locate is needed. Reference the Crossing ID, Wisconsin Milepost and Subdivision found in A.1.

WSOR will only locate railroad owned facilities located in the railroad right-of-way. The railroad does not locate any other utilities.

A.4 Work by Railroad

The railroad will perform the work described in this section, except for work described in other special provisions, and will be accomplished without cost to the contractor. None.

A.5 Temporary Grade Crossing

If a temporary grade crossing is desired, submit a written request to the railroad representative named in A.3 at least 40 days prior to the time needed. Approval is subject to the discretion of the railroad. The department has made no arrangements for a temporary grade crossing.

stp-107-026 (20250108)

17. Information to Bidders, WPDES Transportation Construction General Permit (TCGP) for Storm Water Discharges.

The calculated land disturbance for the project site is 1.07 acres.

The department has obtained permit coverage through the Wisconsin Department of Natural Resources to discharge storm water associated with land disturbing construction activities under this contract. Conform to all permit requirements for the project.

This permit is the Wisconsin Pollutant Discharge Elimination System, Transportation Construction General Permit, (WPDES Permit No. WI-S066796-2). The permit can be found at:

https://widnr.widen.net/s/s5mwp2gd7s/finalsignedwisdotcsgp

A "Certificate of Permit Coverage" is available from the regional office by contacting Kurt Flierl, P.E., WisDOT Construction Project Manager at (262)-548-8724 or (414)-750-3085. Post the "Certificate of Permit Coverage" in a conspicuous place at the construction site.

Permit coverage for additional land disturbing construction activities related to contractor means and methods will be considered as part of the ECIP review and approval process. Coverage under the TCGP for additional land disturbance areas will be considered if the areas meet all of the following:

- Must meet the permit's applicability criteria.
- Must be for the exclusive use of a WisDOT project.
- Land disturbance first commences after the ECIP approval, and the areas are fully restored to meet the final stabilization criteria of the permit upon completion of the work.

The contractor is responsible for obtaining any permits for areas that are not approved by the department for coverage under the TCGP.

18. Notice to Contractor – Milwaukee County Transit System.

The Milwaukee County Transit System (MCTS) operates the following bus routes within and/or directly adjacent to the construction limits: route 76 (76th Street), route 88 (Brown Deer Road), and the BlueLine.

Impacts to MCTS Routing

Invite MCTS to all coordination meetings between the contractor, the department, local officials and business stakeholders to discuss the project schedule of operations including vehicular and pedestrian

2140-14-70 21 of 85

access during construction operations. Notify MCTS at least ten (10) business days prior to beginning project work to provide advance notice of potential service impacts.

Impacts to MCTS Signs and Posts

Notify MCTS of work impacting MCTS signs and posts in advance five (5) or more business days. MCTS signs include "Bus Stop" and turn disc signs. MCTS signs are mounted on MCTS posts; and on assets owned by others including streetlights, traffic regulators, crosswalk and street signposts. MCTS shall be responsible for MCTS sign and post removal and installation, with the contractor granting access to MCTS personnel to perform such work. Signs stating "No Parking Bus Stop" are the under the ownership and responsibility of City of Milwaukee.

Impacts to Bus Shelters

Contractor work may require bus shelter(s) to be temporarily removed. MCTS will be responsible for the removal and reinstallation of bus shelters, with the contractor granting access to MCTS personnel for the purposes of reinstallation before new pavement opens to vehicular traffic. Notify MCTS in advance ten (10) business days for each site-specific bus shelter location.

Non-detour Service Suspension at MCTS Bus Stops and Temporary Bus Stops

Occasions may arise when work requires neither a detour nor the physical alteration of MCTS bus stop assets, but (for passenger safety) those occasions involved require MCTS to temporarily suspend service at a bus stop location. Notify MCTS in advance five (5) business days of the site-specific occasion, and MCTS will sign appropriately to instruct passengers to board at a temporary bus stop. Notify MCTS upon completion of work. MCTS will resume service to any suspended bus stop locations when it is safe to do so.

Temporary Bus Stops

MCTS will designate temporary bus stop boarding locations using MCTS temporary signs. Temporary bus stops will be in existing right-of-way at ADA-accessible locations outside the project's construction zone. MCTS is not requesting this project to provide temporary boarding pads.

MCTS contacts:

Dan Adams (primarily construction planning & design)
Milwaukee County Transit System
1942 N. 17th St.
(414) 937-3273
dadams@mcts.org

Armond Sensabaugh (primarily staging & detours)
Milwaukee County Transit System
1942 N. 17th St.
Milwaukee, WI 53205
Phone: (414) 343-1728

Phone: (414) 343-1728 asensabaugh@mcts.org

dlocher@mcts.org

David Locher Milwaukee County Transit System 1942 N. 17th St. Milwaukee, WI 53205 Phone: (414) 343-1727

19. Notice to Contractor – Timmerman Airport

Timmerman Airport is located 1.52 miles southwest of the project point of beginning. Fill out the FAA Notice Criteria tool for all permanent structure (bridge, light pole, etc.) or equipment (crane, etc.) used during construction.

https://oeaaa.faa.gov/oeaaa/external/portal.jsp

2140-14-70 22 of 85

If required by the Notice Criteria tool, and for all crane or construction equipment higher than 200 feet above the ground, submit completed form 7460-1 (Notice of Proposed Construction or Alteration) to The Federal Aviation Administration (FAA) at least 45 days before starting construction.

Contact Josh Cothren (608-266-3351) or highstructures@dot.wi.gov, WisBOA airspace/tall structure manager for assistance submitting forms

20. Notice to Contractor – Saw Cut Slurry.

Saw cut slurry that may be generated as part of this contract shall be collected and actively managed. Take appropriate measures to prevent saw cut slurry from entering inlets, wetlands, waterways, and other natural areas.

21. Notice to Contractor – Concrete Washout Containment.

All concrete trucks shall washout into a containment system located sufficiently away from the work area to prevent runoff into wetlands, waterways, inlets, and drainage courses. The contractor shall provide a construction detail and location of the containment system with the ECIP and reviewed by the engineer prior to use.

22. Notice to Contractor – Minimum Vertical Clearances.

At a minimum, provide the following vertical clearances on N. 76th Street (STH 181) at the following bridge locations:

- N. 76th Street (STH 181) northbound lanes under the Wisconsin Southern Railroad Company (B-40-379): 14.82 ft minimum vertical clearance.
- N. 76th Street (STH 181) southbound lanes under the Wisconsin Southern Railroad Company (B-40-379): 14.84 ft minimum vertical clearance.

No reduction in the vertical clearance is acceptable under this contract. After staking and prior to paving HMA pavement under the railroad bridge B-40-379, measure the minimum vertical clearance in each direction (northbound and southbound) of N. 76th Street (STH 181) and coordinate with the engineer to verify the minimum vertical clearances will be met.

The railroad will perform the final clearance check. Contact the railroad upon completion of roadway.

23. Notice to Contractor – Traffic Signal Equipment Lead Time.

Order traffic signal equipment as soon as possible to assure the equipment is procured in a timely fashion and, therefore, installed, inspected, and ready for turn-on at the required date.

24. Notice to Contractor – Electronic Load Tickets.

Replace standard spec 109.1.4.3 (1) with the following:

(1) Submit an electronic ticket for each load of material for the following bid items:

- HMA Pavement 3 MT 58-28S;
- HMA Pavement 4 MT 58-28S

Include the information as specified in 109.1.4.2 on each electronic ticket. If there is a failure in the electronic ticket system, provide a printed ticket for each load of material as a substitute for electronic tickets.

stp-107-230 (20250108)

2140-14-70 23 of 85

25. Erosion Control

Perform this work according to the requirements of standard spec 107.20 and as hereinafter supplemented.

Take adequate precautions to install and maintain necessary erosion and sediment control during the excavation for the construction of concrete footings, and at other locations determined by the engineer. Protect storm drain inlets and manholes, as determined by the engineer, with a filter fabric meeting accepted design criteria, standards, and specifications. Maintain all erosion control measures until such time that the engineer determines the measures are no longer necessary.

Provide the ECIP 14 calendar days prior to the pre-construction conference. Provide 1 copy of the ECIP to WisDOT and 1 copy of the ECIP to the WDNR Liaison (Mr. Ryan Papas;

Ryan.Pappas@wisconsin.gov). Pursue operations in a timely and diligent manner, continuing all construction operations methodically from the initial removals and topsoil stripping operations through the subsequent grading, paving, and re-top soiling to minimize the period of exposure to possible erosion. Do not implement the ECIP until it has been approved by the department.

When performing roadway cleaning operations, the contractor shall use equipment having vacuum or water spray mechanism to eliminate the dispersion of dust. If vacuum equipment is employed, it shall have suitable self-contained particulate collectors to prevent discharge from the collection bin into the atmosphere.

Stockpile excess materials or spoils on upland areas away from wetlands, floodplains, and waterways. Immediately install perimeter silt fence protection around stockpiles. If stockpiled materials will be left for more than 14 days, install temporary seed or other temporary erosion control measures the engineer orders.

Re-apply topsoil on graded areas, as the engineer directs, immediately after the grading is completed within those areas. Place sod, as the engineer directs, within 5 days after placement of topsoil. If graded areas are left not completed and exposed for more than 14 days, seed those areas with temporary seed and mulch.

Dewatering (Mechanical Pumping) for Bypass Water (sediment-free) Operations If dewatering bypass operations are required from one pipe structure to another downstream pipe structure or from the upstream to downstream end of a culvert and the bypass flow is not transporting sediments (sand, silt, and clay particles) from a tributary work site area, bypass pumping operations will be allowed provided that the department has been made aware of and approves operation. When pumping bypass flows, the discharge location will need to be stable and not produce any erosion from the discharge velocity that would cause release of sediment downstream. Dewatering is considered incidental to the contract.

Dewatering (Mechanical Pumping) for Treatment Water (sediment-laden) Operations If dewatering operations require pumping of water containing sediments (sand, silt, and clay particles), the discharge will not be allowed to leave the work site or discharge to a storm water conveyance system without sediment removal treatment. Do not allow any excavation for; structures, utilities, grading, maintaining drainage that requires dewatering (mechanical pumping) of water containing sediments (sand, silt, and clay particles) to leave the work site or discharge to a storm water conveyance system without sediment removal treatment.

Prior to each dewatering operation, submit to the department a separate ECIP amendment for sediment removal. Guidance on dewatering can be found on the Wisconsin DNR website located in the Storm Water Construction Technical Standards, Dewatering Code #1061, http://dnr.wi.gov/topic/stormwater/standards/const_standards.html.

Include reasoning, location, and schedule duration proposed for each operation. Per Code 1061, include all selection criteria: site assessment, dewatering practice selection, calculations, plans, specifications, operations, maintenance, and location of proposed treated water discharge. Provide a stabilized discharge area. If directing discharge towards or into an inlet structure, provide additional inlet protection for back-up protection. Dewatering is considered incidental to the contract.

26. Coordination with Businesses and Residents.

The contractor shall arrange and conduct a meeting between the contractor, the department, affected residents, local officials and business people to discuss the project schedule of operations including vehicular and pedestrian access during construction operations. Hold the first meeting at least one week before the start of work under this contract and hold one meeting per month thereafter. The contractor

2140-14-70 24 of 85

shall arrange for a suitable location for meetings that provides reasonable accommodation for public involvement. The department will prepare and coordinate publication of the meeting notices and mailings for meetings. The contractor shall schedule meetings with at least 2 weeks' prior notice to the engineer to allow for these notifications.

stp-108-060 (20141107)

27. Adjusting and Reconstructing Storm Sewer Structures.

Add the following text to 611.3.1 of the standard specs:

Remove covers and frames prior to milling. Cover openings with a Cover Plates Temporary of sufficient thickness to carry traffic and at a depth to accommodate the milling operations. Backfill excavated areas with an asphalt surface mix to an elevation that will match the adjacent pavement. Cover Plates Temporary will paid as separate contract bid item. Storage of the frames and castings is incidental in the adjusting and reconstructing storm sewer structures bid items.

Add the following text to 611.3.7 of the standard specs:

The replacement of Grade A concrete when adjusting manhole covers in areas of bituminous resurfacing shall be to the top of the existing concrete base as shown on the detail for adjusting manhole covers. Use construction methods that conform to the requirements set forth in 611.3.3 of the standard specs.

Add the following text to 611.5 of the standard specs:

Pavement removal, asphalt patch removal, excavating, preparing the foundation, and shimming are incidental to the adjusting storm sewer structure bid items. The department will pay separately for sawing asphalt, cover plates temporary, asphaltic surface patching, and base patching concrete SHES. Monolithic shim concrete, concrete placement, and finishing is incidental to the base patching concrete SHES bid item. Removal and replacement of concrete curb and gutter will be paid for under items Removing Curb and Gutter and Concrete Curb and Gutter, Concrete Curb and Gutter 30-Inch Type A, Concrete Curb and Gutter 18-Inch Type D Concrete Curb and Gutter 6-Inch Sloped 30-Inch Type J, and Concrete Curb and Gutter 6-Inch Slope 18-Inch Type J.

SER-611-001 (20161216)

28. Traffic Signals, General.

All traffic signal work shall be in accordance with the State of Wisconsin Department of Transportation Standard Specifications for Highway and Structure Construction, 2025 edition, the plans, and these special provisions.

Note that the failure to comply with the state standards and specifications may result in the cost of corrections to be made at the Contractor's expense. Also, any additional disruption of State-owned facilities shall be repaired or relocated as needed at the Contractor's expense.

Notify the department's Electrical Field Unit at (414) 266-1170 at least three weeks prior to the beginning of the traffic signal work.

29. General Requirements for Electrical Work.

Replace 651.3.3(3) of the standard specifications with the following:

Request a signal inspection of the completed signal installation to the engineer at least five (5) working days prior to the time of the requested inspection. Notify the department's Electrical Field Unit at (414) 266-1170 to coordinate the inspection. The department's Region Electrical personnel will perform the inspection. In the event of deficiencies, request a re-inspection when the work is corrected. The engineer will not authorize turn-on until the contractor corrects all deficiencies.

2140-14-70 25 of 85

30. Electrical Conduit.

Replace 652.5(2) of the standard specifications with the following:

(2) Payment for Conduit Rigid Metallic, Conduit Rigid Nonmetallic, Conduit Reinforced Thermosetting Resin, and Conduit Special bid items is full compensation for providing the conduit, conduit bodies, and fittings; for providing all conduit hangers, clips, attachments, and fittings used to support conduit on structures; for pull wires or ropes; for expansion fittings and caps; for making necessary connections into an existing pull box, manhole, junction box or communication vault; for excavating, bedding, and backfilling, including any sand, concrete, or other required materials; for disposing of surplus materials; and for making inspections.

31. Traffic Signal Faces.

Append 658.3 of the standard specifications with the following:

(5) Connect all ungrounded conductors with wire nuts in the appropriate sections of the signal heads, when directed by WisDOT personnel. Connect the neutral conductors to the terminal strip. Be certain to twist wires prior to installing the wire nuts. All wire nuts must be installed facing up to prevent the entrance of water.

32. Signal Mounting Hardware.

Add the following to 658.2(7) of the standard specifications:

Use an approved type of pole or standard vertical mounting brackets/clamps for signal faces from an approved manufacturer. Pedestrian traffic signal heads mounted in the median shall use federal yellow aluminum side of pole 2-way upper and lower arm assemblies providing 16 $\frac{1}{2}$ -inch center to center spacing.

33. Removing Traffic Signals STH 181 & Florist Ave, Item 204.9060.S.01;

Removing Traffic Signals STH 181 & Mill Rd, Item 204.9060.S.02;

Removing Traffic Signals STH 181 & Acacia St, Item 204.9060.S.03;

Removing Traffic Signals STH 181 \$ Green Tree Rd, Item 204.9060S.04;

Removing Traffic Signals STH 181 & Good Hope Rd, Item 204.9060.S.05;

Removing Traffic Signals STH 181 & Calumet Rd, Item 204.9060.S.06

Removing Traffic Signals STH 181 & Bradley Rd, Item 204.9060.S.07;

Removing Traffic Signals STH 181 & Tower Ave, Item 204.9060.S.08;

Removing Traffic Signals STH 181 & Servite/Dean Rd, Item 204.9060.09;

Removing Traffic Signals STH 181 & Northridge Dr, Item 204.9060.S.10;

Removing Traffic Signals STH 181 & Northridge Lakes Blvd, Item 204.9060.S.11.

A Description

This special provision describes removing the existing traffic signals at 11 STH 181 intersections, conforming to standard spec 204 and as follows. Specific removal items are noted in the plans.

B (Vacant)

C Construction

Arrange for the de-energizing of the traffic signals with the local electrical utility after receiving approval from the engineer that the existing traffic signals can be removed.

Each traffic signal cabinet is connected to a fiber optic network. This item includes disconnecting the fiber gator patch cables in the signal cabinet and pulling the cable back to the nearest undisturbed pull box or communications vault.

Notify the department's Electrical Field Unit at (414) 266-1170 at least five (5) working days prior to the removal of the traffic signals. Complete the removal work as soon as possible following shut down of this equipment.

2140-14-70 26 of 85

All existing equipment shall remain in operation until the temporary traffic signal is energized and fully operational. The existing signal equipment shall only be de-energized when the temporary equipment is energized and fully operational. The de-energizing and removal of the existing equipment may only take place after receiving the approval from the engineer. The existing equipment shall be removed the same day as to not obstruct the newly operating equipment. Any remaining existing signal heads shall be bagged while the temporary signal is in operation.

Remove all standards and poles per plan from their concrete footings and disassemble out of traffic. Remove the transformer or pedestal bases from each pole. Remove the signal heads, emergency vehicle preemption heads (EVP), mast arms, luminaires, wiring/cabling, and traffic signal mounting devices from each signal standard, arm or pole. Ensure that all access hand hole doors and all associated hardware remain intact. Dispose of the underground signal cable, internal wires, and street lighting cable off the state right of way. Deliver the remaining materials, except for traffic signal LED and luminaire lamp, switch, and ballasts to the West Allis Electrical Service Facility at 935 South 60th Street, West Allis, Milwaukee County. Contact the department's Electrical Field Unit at (414) 266-1170 at least five working days prior to delivery to make arrangements. Traffic signal LED and luminaire lamp, switch, and ballast disposal shall be paid as a separate item.

DOT forces shall remove the signal cabinet from the footing. The signal cabinet and associated signal cabinet equipment will be removed from the site by DOT forces and will remain the property of the department.

D Measurement

Removing Traffic Signals will be measured as a single unit of work for each intersection acceptably completed.

E Payment

Removing Traffic Signals will be paid for the measured quantity at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
204.9060.S.01	Removing Traffic Signals STH 181 & Florist Ave	EACH
204.9060.S.02	Removing Traffic Signals STH 181 & Mill Rd	EACH
204.9060.S.03	Removing Traffic Signals STH 181 & Acacia St	EACH
204.9060.S.04	Removing Traffic Signals STH 181 & Green Tree Rd/Industrial Rd	EACH
204.9060.S.05	Removing Traffic Signals STH 181 & Good Hope Rd	EACH
204.9060.S.06	Removing Traffic Signals STH 181 & Calumet Rd	EACH
204.9060.S.07	Removing Traffic Signals STH 181 & Bradley Rd	EACH
204.9060.S.08	Removing Traffic Signals STH 181 & Tower Rd	EACH
204.9060.S.09	Removing Traffic Signals STH 181 & Servite/Dean Rd	EACH
204.9060.S.10	Removing Traffic Signals STH 181 & Northridge Dr	EACH
204.9060.S.11	Removing Traffic Signals STH 181 & Northridge Lakes Blvd	EACH

Payment is full compensation for removing specified traffic signal components, disassembly, and delivery of parts to the department.

2140-14-70 27 of 85

34. Removing Loop Detector Wire and Lead-in Cable STH 181 & Florist Ave, Item 204.9060.S.12:

Removing Loop Detector Wire and Lead-in Cable STH 181 & Mill Rd, Item 204.9060.S.13;

Removing Loop Detector Wire and Lead-in Cable STH 181 & Acacia St, Item 204.9060.S.14;

Removing Loop Detector Wire and Lead-in Cable STH 181 \$ Green Tree Rd, Item 204.9060S.15:

Removing Loop Detector Wire and Lead-in Cable STH 181 & Good Hope Rd, Item 204.9060.S.16;

Removing Loop Detector Wire and Lead-in Cable STH 181 & Calumet Rd, Item 204.9060.S.17

Removing Loop Detector Wire and Lead-in Cable STH 181 & Bradley Rd, Item 204.9060.S.18;

Removing Loop Detector Wire and Lead-in Cable STH 181 & Tower Ave, Item 204.9060.S.19;

Removing Loop Detector Wire and Lead-in Cable STH 181 & Servite/Dean Rd, Item 204.9060.20;

Removing Loop Detector Wire and Lead-in Cable STH 181 & Northridge Dr, Item 204.9060.S.21;

Removing Loop Detector Wire and Lead-in Cable STH 181 & Northridge Lakes Blvd, Item 204.9060.S.22;

Removing Loop Detector Wire and Lead-in Cable STH 181 & STH 100, Item 204.9060.S.23.

A Description

This special provision describes removing loop detector wire and lead-in cable at 11 STH 181 intersections as the plans show, conforming to standard spec 204, and as follows.

B (Vacant)

C Construction

Remove and dispose of detector lead-in cable including loop wire for abandoned loops off the project site.

D Measurement

Removing Loop Detector Wire and Lead-in Cable will be measured as a single unit of work for each intersection acceptably completed.

E Payment

Removing Loop Detector Wire and Lead-in Cable will be paid for the measured quantity at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
204.9060.S.12	Removing Loop Detector Wire and Lead-in Cable STH 181 & Florist Ave	EACH
204.9060.S.13	Removing Loop Detector Wire and Lead-in Cable STH 181 & Mill Rd	EACH
204.9060.S.14	Removing Loop Detector Wire and Lead-in Cable STH 181 & Acacia St	EACH
204.9060.S.15	Removing Loop Detector Wire and Lead-in Cable STH 181 & Green Tree Rd/Industrial Rd	EACH
204.9060.S.16	Removing Loop Detector Wire and Lead-in Cable STH 181 & Good Hope Rd	EACH
204.9060.S.17	Removing Loop Detector Wire and Lead-in Cable STH 181 & Calumet Rd	EACH
204.9060.S.18	Removing Loop Detector Wire and Lead-in Cable STH 181 & Bradley Rd	EACH
204.9060.S.19	Removing Loop Detector Wire and Lead-in Cable STH 181 & Tower Ave	EACH
204.9060.S.20	Removing Loop Detector Wire and Lead-in Cable STH 181 & Servite/Dean Rd	EACH
204.9060.S.21	Removing Loop Detector Wire and Lead-in Cable STH 181 & Northridge Dr	EACH
204.9060.S.22	Removing Loop Detector Wire and Lead-in Cable STH 181 & Northridge Lakes Blvd	EACH
204.9060.S.23	Removing Loop Detector Wire and Lead-in Cable STH 181 & STH 100	EACH

Payment is full compensation for removing and properly disposing of loop detector wire and lead-in cable.

2140-14-70 28 of 85

35. HMA Percent Within Limits (PWL) Test Strip Volumetrics, Item 460.0105.S; HMA Percent Within Limits (PWL) Test Strip Density, Item 460.0110.S.

A Description

This special provision describes the Hot Mix Asphalt (HMA) density and volumetric testing tolerances required for an HMA test strip. An HMA test strip is required for contracts constructed under HMA Percent Within Limits (PWL) QMP. A density test strip is required for each pavement layer placed over a specific, uniform underlying material, unless specified otherwise in the plans. Each contract is restricted to a single mix design per mix type per layer (e.g., upper layer and lower layer may have different mix type specified or may have the same mix type with different mix designs). Each mix design requires a separate test strip. Density and volumetrics testing will be conducted on the same test strip whenever possible.

Perform work according to standard spec 460 and as follows.

B Materials

Use materials conforming to HMA Pavement Percent Within Limits (PWL) QMP special provision.

C Construction

C.1 Test Strip

Submit the test strip start time and date to the department in writing at least 5 calendar days in advance of construction of the test strip. If the contractor fails to begin paving within 2 hours of the submitted start time, the test strip is delayed, and the department will assess the contractor \$2,000 for each instance according to Section E of this document. Alterations to the start time and date must be submitted to the department in writing a minimum of 24 hours prior to the start time. The contractor will not be liable for changes in start time related to adverse weather days as defined by standard spec 101.3 or equipment breakdown verified by the department.

On the first day of production for a test strip, produce approximately 750 tons of HMA. (Note: adjust tonnage to accommodate natural break points in the project.) Locate test strips in a section of the roadway to allow a representative rolling pattern (i.e. not a ramp or shoulder, etc.).

C.1.1 Sampling and Testing Intervals

C.1.1.1 Volumetrics

Laboratory testing will be conducted from a split sample yielding three components, with portions designated for QC (quality control), QV (quality verification), and retained.

During production for the test strip, obtain sufficient HMA mixture for three-part split samples from trucks prior to departure from the plant. Collect three split samples during the production of test strip material. Perform sampling from the truck box and three-part splitting of HMA according to WTM R47. These three samples will be randomly selected by the engineer from each *third* of the test strip tonnage (T), excluding the first 50 tons:

Sample Number	Production Interval (tons)
1	50 to 1/3 T
2	1/3 T to 2/3 T
3	2/3 T to T

C.1.1.2 Density

Required field tests include contractor QC and department QV nuclear density gauge tests and pavement coring at ten individual locations (five in each half of the test strip length) according to Appendix A: *Test Methods and Sampling for HMA PWL QMP Projects*. Both QV and QC teams shall have two nuclear density gauges present for correlation at the time the test strip is constructed. QC and QV teams may wish to scan with additional gauges at the locations detailed in Appendix A, as only gauges used during the test strip correlation phase will be allowed.

C.1.2 Field Tests

C.1.2.1 Density

For contracts that include STSP 460-020 QMP Density in addition to PWL, a gauge comparison according to WTM T355 shall be completed prior to the day of test strip construction. Daily standardization of gauges on reference blocks and a project reference site shall be performed according

2140-14-70 29 of 85

to WTM T355. A standard count shall be performed for each gauge on the material placed for the test strip, prior to any additional data collection. Nuclear gauge readings and pavement cores shall be used to determine nuclear gauge correlation according to Appendix A. The two to three readings for the five locations across the mat for each of two zones shall be provided to the engineer. The engineer will analyze the readings of each gauge relative to the densities of the cores taken at each location. The engineer will determine the average difference between the nuclear gauge density readings and the measured core densities to be used as a constant offset value. This offset will be used to adjust raw density readings of the specific gauge and shall appear on the density data sheet along with gauge and project identification. An offset is specific to the mix and layer; therefore, a separate value shall be determined for each layer of each mix placed over a differing underlying material for the contract. This constitutes correlation of that individual gauge for the given layer. Two gauges per team are not required to be onsite daily after completion of the test strip. Any data collected without a correlated gauge will not be accepted.

The contractor is responsible for coring the pavement from the footprint of the density tests and filling core holes according to Appendix A. Coring and filling of pavement core holes must be approved by the engineer. The QV team is responsible for the labeling and safe transport of the cores from the field to the QC laboratory. Testing of cores shall be conducted by the contractor and witnessed by department personnel. The contractor is responsible for drying the cores following testing. The department will take possession of cores following laboratory testing and will be responsible for any verification testing at the discretion of the engineer.

The target maximum density to be used in determining core density is the average of the three volumetric/mix Gmm values from the test strip multiplied by 62.24 lb/ft³. In the event mix and density portions of the test strip procedure are separated, or if an additional density test strip is required, the mix portion must be conducted prior to density determination. The target maximum density to determine core densities shall then be the Gmm four-test running average (or three-test average from a PWL volumetric-only test strip) from the end of the previous day's production multiplied by 62.24 lb/ft³. If no PWL production QV volumetric test is to be taken in a density-only test strip, a non-random QV test will be taken according to 460.2.8.3.1.4 as modified in HMA Pavement Percent Within Limits (PWL) QMP and if non-conforming to C.2.1 herein, follow corrective action outlined in 460.2.8.2.1.7(4) as modified in HMA Pavement Percent Within Limits (PWL) QMP.

Exclusions such as shoulders and appurtenances shall be tested and reported according to CMM 815. However, all acceptance testing of shoulders and appurtenances will be conducted by the department, and average lot (daily) densities must conform to standard spec Table 460-3. No density incentive or disincentive will be applied to shoulders or appurtenances. However, unacceptable shoulder material will be handled according to standard spec 460.3.3.1 and CMM 815.11.

C.1.3 Laboratory Tests

C.1.3.1 Volumetrics

Obtain random samples according to C.1.1.1 and Appendix A. Perform tests the same day as taking the sample.

Theoretical maximum specific gravities of each mixture sample will be obtained. Bulk specific gravities of both gyratory compacted samples and field cores shall be determined. The bulk specific gravity values determined from field cores shall be used to calculate a correction factor (i.e., offset) for each QC and QV nuclear density gauge. The correction factor will be used throughout the remainder of the layer.

C.2 Acceptance

C.2.1 Volumetrics

Produce mix conforming to the following limits based on individual QC and QV test results (tolerances based on most recent JMF):

ITEM	ACCEPTANCE LIMITS
Percent passing given sieve:	
37.5-mm	+/- 8.0
25.0-mm	+/- 8.0
19.0-mm	+/- 7.5
12.5-mm	+/- 7.5
9.5-mm	+/- 7.5

2140-14-70 30 of 85

2.36-mm	+/- 7.0
75-µm	+/- 3.0
Asphaltic content in percent ^[1]	- 0.5
Air Voids	-1.5 & +2.0
VMA in percent ^[2]	- 1.0
Maximum specific gravity	+/- 0.024

^[1] Asphalt content more than -0.5% below the JMF will be referee tested by the department's AASHTO accredited laboratory and HTCP certified personnel using automated extraction.

QV samples will be tested for Gmm, Gmb, and AC. Air voids and VMA will then be calculated using these test results.

Calculation of air voids shall use either the QC, QV, or retained split sample test results, as identified by conducting the paired t-test with the WisDOT PWL Test Strip Spreadsheet.

If QC and QV test results do not correlate as determined by the split sample comparison, the retained split sample will be tested by the department's AASHTO accredited laboratory and HTCP certified personnel as a referee test. Additional investigation shall be conducted to identify the source of the difference between QC and QV data. Referee data will be used to determine material conformance and pay.

C.2.2 Density

Compact all layers of test strip HMA mixture according to Table 460-3.

Nuclear density gauges are acceptable for use on the project only if correlation is completed for that gauge during the time of the test strip and the department issues documentation of acceptance stating the correlation offset value specific to the gauge and mix design. The offset is not to be entered into any nuclear density gauge as it will be applied by the department-furnished Field Density Worksheet.

C.2.3 Test Strip Approval and Material Conformance

All applicable laboratory and field testing associated with a test strip shall be completed prior to any additional mainline placement of the mix. All test reports shall be submitted to the department upon completion and approved before paving resumes. The department will notify the contractor within 24 hours from start of test strip regarding approval to proceed with paving unless an alternate time frame is agreed upon in writing with the department. The 24-hour approval time includes only working days as defined in standard spec 101.3.

The department will evaluate material conformance and make pay adjustments based on the PWL value of air voids and density for the test strip. The QC core densities and QC and QV mix results will be used to determine the PWL values as calculated according to Appendix A.

The PWL values for air voids and density shall be calculated after determining core densities. An approved test strip is defined as the individual PWL values for air voids and density both being equal to or greater than 75, mixture volumetric properties conforming to the limits specified in C.2.1, and an acceptable gauge-to-core correlation. Further clarification on PWL test strip approval and appropriate post-test strip actions are shown in the following table:

PWL TEST STRIP APPROVAL AND MATERIAL CONFORMANCE CRITERIA

PWL VALUE FOR AIR VOIDS AND DENSITY	TEST STRIP APPROVAL	MATERIAL CONFORMANCE	POST-TEST STRIP ACTION
Both PWL ≥ 75	Approved ¹	Material paid for according to Section E	Proceed with Production
50 <u><</u> Either PWL < 75	Not Approved	Material paid for according to Section E	Consult BTS to determine need for additional test strip
Either PWL < 50	Not Approved	Unacceptable material removed and replaced or paid for at 50% of the contract unit price according to Section E	Construct additional Volumetrics or Density test strip as necessary

2140-14-70 31 of 85

^[2] VMA limits based on minimum requirement for mix design nominal maximum aggregate size in table 460-1.

¹ In addition to these PWL criteria, mixture volumetric properties must conform to the limits specified in C.2.1, split sample comparison must have a passing result and an acceptable gauge-to-core correlation must be completed.

A maximum of two test strips will be allowed to remain in place per pavement layer per contract. If material is removed, a new test strip shall replace the previous one at no additional cost to the department. If the contractor changes the mix design for a given mix type during a contract, no additional compensation will be paid by the department for the required additional test strip and the department will assess the contractor \$2,000 for the additional test strip according to Section E of this special provision. For simultaneously conducted density and volumetric test strip components, the following must be achieved:

- i. Passing/Resolution of Split Sample Comparison
- ii. Volumetrics/mix PWL value ≥ 75
- iii. Density PWL value > 75
- iv. Acceptable correlation

If not conducted simultaneously, the mix portion of a test strip must accomplish (i) & (ii), while density must accomplish (iii) & (iv). If any applicable criteria are not achieved for a given test strip, the engineer, with authorization from the department's Bureau of Technical Services, will direct an additional test strip (or alternate plan approved by the department) be conducted to prove the criteria can be met prior to additional paving of that mix. For a density-only test strip, determination of mix conformance will be according to main production, i.e., HMA Pavement Percent Within Limits (PWL) QMP special provision.

D Measurement

The department will measure HMA Percent Within Limits (PWL) Test Strip as each unit of work, acceptably completed as passing the required air void, VMA, asphalt content, gradation, and density correlation for a Test Strip. Material quantities shall be determined according to standard spec 450.4 and detailed here within.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
460.0105.S	HMA Percent Within Limits (PWL) Test Strip Volumetrics	EACH
460.0110.S	HMA Percent Within Limits (PWL) Test Strip Density	EACH

These items are intended to compensate the contractor for the construction of the test strip for contracts paved under the HMA Pavement Percent Within Limits QMP article.

Payment for HMA Percent Within Limits (PWL) Test Strip Volumetrics is full compensation for volumetric sampling, splitting, and testing, and for the proper labeling, handling, and retention of the split samples.

Payment for HMA Percent Within Limits (PWL) Test Strip Density is full compensation for collecting and measuring of pavement cores, acceptably filling core holes, providing of nuclear gauges and operator(s), and all other work associated with completion of a core-to-gauge correlation, as directed by the engineer.

Acceptable HMA mixture placed on the project as part of a volumetric or density test strip will be compensated by the appropriate HMA Pavement bid item with any applicable pay adjustments. If a test strip is delayed as defined in C.1 of this document, the department will assess the contractor \$2,000 for each instance, under the HMA Delayed Test Strip administrative item. If an additional test strip is required because the initial test strip is not approved by the department or the mix design is changed by the contractor, the department will assess the contractor \$2,000 for each additional test strip (i.e., \$2,000 for each individual volumetrics or density test strip) under the HMA Additional Test Strip administrative item.

Pay adjustment will be calculated using 65 dollars per ton of HMA pavement. The department will pay for measured quantities of mix based on \$65/ton multiplied by the following pay adjustment:

2140-14-70 32 of 85

PAY ADJUSTMENT FOR HMA PAVEMENT AIR VOIDS & DENSITY

PERCENT WITHIN LIMITS	PAYMENT FACTOR, PF
(PWL)	(percent of \$65/ton)
≥ 90 to 100	PF = ((PWL - 90) * 0.4) + 100
≥ 50 to < 90	(PWL * 0.5) + 55
<50	50%[1]

where, PF is calculated per air voids and density, denoted PFair voids & PFdensity

[1] Material resulting in PWL value less than 50 shall be removed and replaced, unless the engineer allows for such material to remain in place. In the event the material remains in place, it will be paid at 50% of the contract unit price of HMA pavement.

For air voids, PWL values will be calculated using lower and upper specification limits of 2.0 and 4.3 percent, respectively. Lower specification limits for density will be according to Table 460-3. Pay adjustment will be determined for an acceptably completed test strip and will be computed as shown in the following equation:

Pay Adjustment = $(PF-100)/100 \times (WP) \times (tonnage) \times (\$65/ton)^*$

*Note: If Pay Factor = 50, the contract unit price will be used in lieu of \$65/ton and the weighted percentage (WP) will equal 1.0.

The following weighted percentage (WP) values will be used for the corresponding parameter:

<u>Parameter</u>	<u>WP</u>
Air Voids	0.5
Density	0.5

Individual Pay Factors for each air voids (PF_{air voids}) and density (PF_{density}) will be determined. PF_{air voids} will be multiplied by the total tonnage produced (i.e., from truck tickets), and PF_{density} will be multiplied by the calculated tonnage used to pave the mainline only (i.e., traffic lane excluding shoulder) as determined according to Appendix A.

The department will pay incentive for air voids under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
460.2005	Incentive Density PWL HMA Pavement	DOL
460.2010	Incentive Air Voids HMA Pavement	DOL

The department will administer disincentives under the Disincentive Density HMA Pavement and the Disincentive Air Voids HMA Pavement administrative items.

stp-460-040 (20230629)

36. HMA Pavement Percent Within Limits (PWL) QMP.

A Description

This special provision describes percent within limits (PWL) pay determination, providing and maintaining a contractor Quality Control (QC) Program, department Quality Verification (QV) Program, required sampling and testing, dispute resolution, corrective action, pavement density, and payment for HMA pavements. Pay is determined by statistical analysis performed on contractor and department test results conducted according to the Quality Management Program (QMP) as specified in standard spec 460, except as modified below.

B Materials

Conform to the requirements of standard spec 450, 455, and 460 except where superseded by this special provision. The department will allow only one mix design for each HMA mixture type per layer required for the contract, unless approved by the engineer. The use of more than one mix design for each HMA pavement layer will require the contractor to construct a new test strip according to HMA Pavement

2140-14-70 33 of 85

Percent Within Limits (PWL) QMP Test Strip Volumetrics and HMA Pavement Percent Within Limits (PWL) QMP Test Strip Density articles at no additional cost to the department.

Replace standard spec 460.2.8.2.1.3.1 Contracts with 5000 Tons of Mixture or Greater with the following:

460.2.8.2.1.3.1 Contracts under Percent within Limits

- (1) Furnish and maintain a laboratory at the plant site fully equipped for performing contractor QC testing. Have the laboratory on-site and operational before beginning mixture production.
- (2) Obtain random samples and perform tests according to this special provision and further defined in Appendix A: Test Methods & Sampling for HMA PWL QMP Projects. Obtain HMA mixture samples from trucks at the plant. For the sublot in which a QV sample is collected, discard the QC sample and test a split of the QV sample.
- (3) Perform sampling from the truck box according to WTM R97 and four-part splitting of HMA samples according to WTM R47. Sample size must be adequate to run the appropriate required tests in addition to one set of duplicate tests that may be required for dispute resolution (i.e., retained). This requires sample sizes which yield four splits for all random sampling per sublot. All QC samples shall provide the following: QC, QV, Retained, and Extra. Take possession of the QC and Extra split samples intended for QC testing. The department will observe the splitting and take possession of the QV and Retained split samples intended for QV testing. Additional sampling details are found in Appendix A. Label samples according to WTM R97.
- (4) Test the QC split sample using the test methods identified below at a frequency greater than or equal to that indicated. The Extra split sample shall be tested only when the Gmm and/or Gmb replicate tolerances are exceeded according to WTM T166 section 13.1.4 and WTM T209 section 14.1.1. When testing the Extra split sample, only the results from the test from which the tolerances were exceeded may replace the results from the QC split sample. The Rule of Retained according to CMM 836.1.2 applies.
 - Blended aggregate gradations according to WTM T30.
 - · Asphalt content (AC) in percent.

Determine AC using one of the following methods:

- AC by ignition oven according to WTM T308. If the department is using an ignition oven to determine AC, conform to WTP <u>H-003</u>. If the department is not using an ignition oven to determine AC, IOCFs must still be reverified for any of the reasons listed in <u>WTP</u> H-003 Table 2 and conform to WTP H-003 section 3.
- AC by chemical extraction according to AASHTO T 164 Method A or B.
- AC by automated extraction according to WTM D8159.
- Bulk specific gravity (Gmb) of the compacted mixture according to WTM T166.
- Maximum specific gravity (Gmm) according to WTM T209.
- Air voids (V_a) by calculation according to WTM T269.
- Voids in Mineral Aggregate (VMA) by calculation according to WTM R35 section 9.2.
- (5) Lot size shall consist of 3,750 tons with sublots of 750 tons. Test each design mixture at a frequency of 1 test per 750 tons of mixture type produced and placed as part of the contract. Add a random sample for any fraction of 750 tons at the end of production for a specific mixture design. Partial lots with less than three sublot tests will be included into the previous lot for data analysis and pay adjustment. Volumetric lots will include all tonnage of mixture type under specified bid item unless otherwise specified in the plan.
- (6) Conduct field tensile strength ratio tests according to WTM T283 on each qualifying mixture according to CMM 836.6.14. Test each full 50,000-ton production increment, or fraction of an increment, after the first 5,000 tons of production. Perform required increment testing in the first week of production of that increment. If field tensile strength ratio values are below the spec limit, notify the engineer. The engineer and contractor will jointly determine a corrective action.

Delete standard spec 460.2.8.2.1.5 and 460.2.8.2.1.6.

2140-14-70 34 of 85

Replace standard spec 460.2.8.2.1.7 Corrective Action with the following:

460.2.8.2.1.7 Corrective Action

(1) Material must conform to the following action and acceptance limits based on individual QC and QV test results (tolerances relative to the JMF used on the PWL Test Strip):

ITEM	ACTION LIMITS	ACCEPTANCE LIMITS
Percent passing given sieve:		
37.5-mm	+/- 8.0	
25.0-mm	+/- 8.0	
19.0-mm	+/- 7.5	
12.5-mm	+/- 7.5	
9.5-mm	+/- 7.5	
2.36-mm	+/- 7.0	
75-µm	+/- 3.0	
AC in percent	-0.3	-0.5
Va		- 1.5 & +2.0
VMA in percent ^[1]	- 0.5	-1.0

- [1] VMA limits based on minimum requirement for mix design nominal maximum aggregate size in table 460-1.
- QV samples will be tested for Gmm, Gmb, and AC. Air voids and VMA will then be calculated using these test results.
- (3) Notify the engineer if any individual test result falls outside the action limits, investigate the cause and take corrective action to return to within action limits. If two consecutive test results fall outside the action limits, stop production. Production may not resume until approved by the engineer. Additional QV samples may be collected upon resuming production, at the discretion of the engineer.
- (4) For any additional non-random tests outside the random number testing conducted for volumetrics, the data collected will not be entered into PWL calculations. Additional QV tests must meet acceptance limits or be subject to production stop. If the department's non-random test does not conform to the acceptance limits, the retained sample will be tested by the BTS lab. If the BTS results also do not meet the acceptance limits, the material will be considered unacceptable as described in (5) below.
- (5) Remove and replace unacceptable material at no additional expense to the department. Unacceptable material is defined as any individual QC or QV tests results outside the acceptance limits or a PWL value < 50. For AC in percent, unacceptable material is defined as any individual QV test result outside of the acceptance limit. The engineer may allow such material to remain in place with a price reduction. The department will pay for such HMA Pavement allowed to remain in place at 50 percent of the contract unit price.</p>

Replace standard spec 460.2.8.3.1.2 Personnel Requirements with the following:

460.2.8.3.1.2 Personnel Requirements

- (1) The department will provide at least one HTCP-certified Transportation Materials Sampling (TMS) Technician, to observe QV sampling of HMA mixtures.
- (2) Under departmental observation, a contractor TMS technician shall collect and split samples.
- (3) A department HTCP-certified Hot Mix Asphalt, Technician I, Production Tester (HMA-IPT) technician will ensure that all sampling is performed correctly and conduct testing, analyze test results, and report resulting data.
- (4) The department will make an organizational chart available to the contractor before mixture production begins. The organizational chart will include names, telephone numbers, and current certifications of all QV testing personnel. The department will update the chart with appropriate changes, as they become effective.

2140-14-70 35 of 85

Replace standard spec 460.2.8.3.1.4 Department Verification Testing Requirements with the following:

460.2.8.3.1.4 Department Verification Testing Requirements

- HTCP-certified department personnel will obtain QV random samples by directly supervising HTCP-certified contractor personnel sampling from trucks at the plant. Sample size must be adequate to run the appropriate required tests in addition to one set of duplicate tests that may be required for dispute resolution (i.e., retained). This requires sample sizes which yield four splits for all random sampling per sublot. All QV samples shall furnish the following: QC, QV, Retained, and Extra. The department will observe the splitting and take possession of the QV, Retained, and Extra split samples intended for QV testing. The department will take possession of retained samples accumulated to date each day QV samples are collected. The department will retain samples until surpassing the analysis window of up to 5 lots, as defined in standard spec 460.2.8.3.1.7(2) of this special provision. Additional sampling details are found in Appendix A.
- The department will verify product quality using the test methods specified here in standard spec 460.2.8.3.1.4(3). The department will identify test methods before construction starts and use only those methods during production of that material unless the engineer and contractor mutually agree otherwise.
- (3) The department will test the QV split sample using the test methods identified below at the frequency indicated. The Extra split sample will be tested only when the Gmm and/or Gmb replicate tolerances are exceeded according to WTM T166 section 13.1.4 and WTM T209 section 14.1.1. When testing the Extra split sample, only the results from the test from which the tolerances were exceeded may replace the results from the QV split sample. The Rule of Retained according to CMM 836.1.2 applies. In the event that both the department and contractor's replicate tolerances are exceeded, perform dispute resolution according to 460.2.8.3.1.7(2).
 - Bulk specific gravity (Gmb) of the compacted mixture according to WTM T166.
 - Maximum specific gravity (Gmm) according to WTM T209.
 - Air voids (Va) by calculation according to WTM T269.
 - · Voids in Mineral Aggregate (VMA) by calculation according to WTM R35 section 9.2.
 - Asphalt Content (AC) in percent determined by ignition oven method according to WTM T308 and conforming to WTP H-003, chemical extraction according to AASHTO T 164 Method A or B, or automated extraction according to WTM D8159.
- (4) The department will randomly test each design mixture at the minimum frequency of one test for each lot.

Delete standard spec 460.2.8.3.1.6.

Replace standard spec 460.2.8.3.1.7 Dispute Resolution with the following:

460.2.8.3.1.7 Data Analysis for Volumetrics

- (1) Analysis of test data for pay determination will be contingent upon QC and QV test results. Statistical analysis will be conducted on Gmm and Gmb test results for calculation of Va. If either Gmm or Gmb analysis results in non-comparable data as described in 460.2.8.3.1.7(2), subsequent testing will be performed for both parameters as detailed in the following paragraph.
- (t-test) of the QV test results with the QC test results. Additional comparisons incorporating the first 3 lots of data will be performed following completion of the 4th and 5th lots (i.e., lots 1-3, 1-4, and 1-5). A rolling window of 5 lots will be used to conduct F & t comparison for the remainder of the contract (i.e., lots 2-6, then lots 3-7, etc.), reporting comparison results for each individual lot. Analysis will use a set alpha value of 0.025. If the F- and t-tests report comparable data, the QC and QV data sets are determined to be statistically similar and QC data will be used to calculate the Va used in PWL and pay adjustment calculations. If the F- and t-tests result in non-comparable data, proceed to the *dispute resolution* steps found below. Note: if both QC and QV Va PWL result in a pay adjustment of 102% or greater, dispute resolution testing will not be conducted. Dispute resolution via further investigation is as follows:
 - The Retained portion of the split from the lot in the analysis window with a QV test result furthest from the QV mean (not necessarily the sublot identifying that variances or means do not compare) will be referee tested for Gmm, Gmb, and Asphalt Content by the bureau's AASHTO accredited

2140-14-70 36 of 85

laboratory and certified personnel. All previous lots within the analysis window are subject to referee testing and regional lab testing as deemed necessary. Referee test results will replace the QV data of the sublot(s).

- [2] Statistical analysis will be conducted with referee test results replacing QV results.
 - i. If the F- and t-tests indicate variances and means compare, no further testing is required for the lot and QC data will be used for PWL and pay factor/adjustment calculations.
 - ii. If the F- and t-tests indicate non-comparable variances or means, the Retained portion of the random QC sample will be tested for Gmm, Gmb, and Asphalt Content by the department's regional lab for the remaining 4 sublots of the lot which the F- and t-tests indicate non-comparable datasets. The department's regional lab and the referee test results will be used for PWL and pay factor/adjustment calculations. Upon the second instance of non-comparable variance or means and for every instance thereafter, the department will assess a pay reduction for the additional testing of the remaining 4 sublots at \$2,000/lot under the HMA Regional Lab Testing administrative item.
- The contractor may choose to dispute the regional test results on a lot basis within 7 days after receiving the results from the region. In this event, the retained portion of each sublot will be referee tested by the department's AASHTO accredited laboratory and certified personnel. The referee Gmm and Gmb test results will supersede the regional lab results for the disputed lot.
 - i. If referee testing results in an increased calculated pay factor, the department will pay for the cost of the additional referee testing.
 - ii. If referee testing of a disputed lot results in an equal or lower calculated pay factor, the department will assess a pay reduction for the additional referee testing at \$2,000/lot under the Referee Testing administrative item.
- (3) The department will notify the contractor of the referee test results within 3 working days after receipt of the samples by the department's AASHTO accredited laboratory. The intent is to provide referee test results within 7 calendar days from completion of the lot.
- (4) The department will determine mixture conformance and acceptability by analyzing referee test results, reviewing mixture data, and inspecting the completed pavement according to the standard spec, this special provision, and accompanying Appendix A.
- (5) Unacceptable material (i.e., resulting in a PWL value less than 50 or individual QC or QV test results not meeting the Acceptance Requirements of 460.2.8.2.1.7 as modified herein) will be referee tested by the bureau's AASHTO accredited laboratory and certified personnel and those test results used for analysis. Such material may be subject to remove and replace, at the discretion of the engineer. If the engineer allows the material to remain in place, it will be paid at 50% of the HMA Pavement contract unit price. Replacement or pay adjustment will be conducted on a sublot basis. If an entire PWL sublot is removed and replaced, the test results of the newly placed material will replace the original data for the sublot. Any remove and replace shall be performed at no additional cost to the department. Testing of replaced material must include a minimum of one QV result. [Note: If the removed and replaced material does not result in replacement of original QV data, an additional QV test will be conducted and under such circumstances will be entered into the HMA PWL Production spreadsheet for data analysis and pay determination.] The quantity of material paid at 50% the contract unit price will be deducted from PWL pay adjustments, along with accompanying data of this material.

Delete standard spec 460.2.8.3.1.8 Corrective Action.

C Construction

Replace standard spec 460.3.3.2 Pavement Density Determination with the following:

460.3.3.2 Pavement Density Determination

- The engineer will determine the target maximum density using department procedures described in WTM T355 and CMM 815. The engineer will determine density as soon as practicable after compaction and before placement of subsequent layers or before opening to traffic.
- Do not re-roll compacted mixtures with deficient density test results. Do not operate continuously below the specified minimum density. Stop production, identify the source of the problem, and make corrections to produce work meeting the specification requirements.

2140-14-70 37 of 85

- (3) A lot is defined as 7,500 lane feet with sublots of 1,500 lane feet (excluding shoulder, even if paved integrally) and placed within a single layer for each location and target maximum density category indicated in table 460-3. Complete three tests randomly per sublot and the department will randomly conduct one QV test per sublot. A partial quantity less than 750 lane feet will be included with the previous sublot. Partial lots with less than three sublots will be included in the previous lot for data analysis/acceptance and pay, by the engineer. If density lots/sublots are determined prior to construction of the test strip, any random locations within the test strip shall be omitted. Exclusions such as shoulders and appurtenances shall be tested and recorded according to WTM T355 and CMM 815. However, all acceptance testing of shoulders and appurtenances will be conducted by the department, and average lot (daily) densities must conform to standard spec Table 460-3 or else be subject to disincentives according to 460.5.2.2(5) herein. No density incentive will be applied to shoulders or appurtenances. Offsets will not be applied to nuclear density gauge readings for shoulders or appurtenances. Unacceptable shoulder material will be handled according to standard spec 460.3.3.1 and CMM 815.11.
- (4) The three QC locations per sublot represent the outside, middle, and inside of the paving lane. The QC density testing procedures are detailed in Appendix A.
- (5) QV nuclear testing will consist of one randomly selected location per sublot. The QV density testing procedures will be the same as the QC procedure at each testing location and are also detailed in Appendix A.
- (6) An HTCP-certified nuclear density technician (NUCDENSITYTEC-I) shall identify random locations and perform the testing for both the contractor and department. The responsible certified technician shall ensure that sample location and testing is performed correctly, analyze test results, and provide density results to the contractor weekly, or at the completion of each lot.
- (7) For any additional tests outside the random number testing conducted for density, the data collected will not be entered into PWL calculations. However, additional QV testing must meet the tolerances for material conformance as specified in the standard specification and this special provision. If additional density data identifies unacceptable material, proceed as specified in CMM 815.11.

Replace standard spec 460.3.3.3 Waiving Density Testing with Acceptance of Density Data with the following:

460.3.3.3 Analysis of Density Data

- (1) Analysis of test data for pay determination will be contingent upon test results from both the contractor (QC) and the department (QV).
- (2) As random density locations are paved, the data will be recorded in the HMA PWL Production Spreadsheet for analysis in chronological order. The engineer, upon completion of the first 3 lots, will compare the variances (F-test) and the means (t-test) of the QV test results with the QC test results. A rolling window of 3 lots will be used to conduct F & t comparison for the remainder of the contract (i.e., lots 2-4, then lots 3-5, etc.), reporting comparison results for each individual lot. Analysis will use a set alpha value of 0.025.
 - If the F- and t-tests indicate variances and means compare, the QC and QV data sets are determined to be statistically similar and QC data will be used for PWL and pay adjustment calculations.
 - ii. If the F- and t-tests indicate variances or means do not compare, the QV data will be used for subsequent calculations.
- (3) The department will determine mixture density conformance and acceptability by analyzing test results, reviewing mixture data, and inspecting the completed pavement according to standard spec, this special provision, and accompanying Appendix A.
- (4) Density resulting in a PWL value less than 50 or not meeting the requirements of 460.3.3.1 (any individual density test result falling more than 3.0 percent below the minimum required target maximum density as specified in standard spec Table 460-3) is unacceptable and may be subject to remove and replace at no additional cost to the department, at the discretion of the engineer.
 - i. Replacement may be conducted on a sublot basis. If an entire PWL sublot is removed and replaced, the test results of the newly placed material will replace the original data for the sublot.
 - ii. Testing of replaced material must include a minimum of one QV result. [Note: If the removed and replaced material does not result in replacement of original QV data, an additional QV test

2140-14-70 38 of 85

- must be conducted and under such circumstances will be entered into the data analysis and pay determination.]
- iii. If the engineer allows such material to remain in place, it will be paid for at 50% of the HMA Pavement contract unit price. The extent of unacceptable material will be addressed as specified in CMM 815.11. The quantity of material paid at 50% the contract unit price will be deducted from PWL pay adjustments, along with accompanying data of this material.

D Measurement

The department will measure the HMA Pavement bid items acceptably completed by the ton, as specified in standard spec 450.4 and as follows in standard spec 460.5, as modified in this special provision.

E Payment

Replace standard spec 460.5.2 HMA Pavement with the following:

460.5.2 HMA Pavement

460.5.2.1 General

- (1) Payment for HMA Pavement Type LT, MT, and HT mixes is full compensation for providing HMA mixture designs; for preparing foundation; for furnishing, preparing, hauling, mixing, placing, and compacting mixture; for HMA PWL QMP testing and aggregate source testing; for warm mix asphalt additives or processes; for stabilizer, hydrated lime and liquid antistripping agent, if required; and for all materials including asphaltic materials.
- (2) If provided for in the plan quantities, the department will pay for a leveling layer, placed to correct irregularities in an existing paved surface before overlaying, under the pertinent paving bid item. Absent a plan quantity, the department will pay for a leveling layer as extra work.

460.5.2.2 Calculation of Pay Adjustment for HMA Pavement using PWL

(1) Pay adjustments will be calculated using 65 dollars per ton of HMA pavement. The HMA PWL Production Spreadsheet, including data, will be made available to the contractor by the department as soon as practicable upon completion of each lot. The department will pay for measured quantities of mix based on this price multiplied by the following pay adjustment calculated according to the HMA PWL Production Spreadsheet:

PAY FACTOR FOR HMA PAVEMENT AIR VOIDS & DENSITY

PERCENT WITHIN LIMITS	PAYMENT FACTOR, PF
(PWL)	(percent of \$65/ton)
≥ 90 to 100	PF = ((PWL - 90) * 0.4) + 100
≥ 50 to < 90	(PWL * 0.5) + 55
<50	50% ^[1]

where PF is calculated per air voids and density, denoted PFair voids & PFdensity.

- Any material resulting in PWL value less than 50 shall be removed and replaced unless the engineer allows such material to remain in place. In the event the material remains in place, it will be paid at 50% of the contract unit price of HMA pavement.
- (2) For air voids, PWL values will be calculated using lower and upper specification limits of 2.0 and 4.3 percent, respectively. Lower specification limits for density shall be according to standard spec Table 460-3.
- (3) Pay adjustment will be determined on a lot basis and will be computed as shown in the following equation:

Pay Adjustment = $(PF-100)/100 \times (WP) \times (tonnage) \times (\$65/ton)^*$

*Note: If Pay Factor = 50%, the contract unit price will be used in lieu of \$65/ton and the weighted percentage (WP) will equal 1.0.

2140-14-70 39 of 85

The following weighted percentage (WP) values will be used for the corresponding parameter:

<u>Parameter</u>	<u>WP</u>
Air Voids	0.5
Density	0.5

- (4) Individual Pay Factors for each air voids (PF_{air voids}) and density (PF_{density}) will be determined. PF_{air voids} will be multiplied by the total tonnage placed (i.e., from truck tickets), and PF_{density} will be multiplied by the calculated tonnage used to pave the mainline only (i.e., travel lane excluding shoulder) as determined according to Appendix A.
- (5) Pay adjustment for shoulders and appurtenances accepted by department testing will be determined on a lot basis. If the lot density is less than the specified minimum in table 460-3, the department will reduce pay based on the contract unit price for the HMA pavement bid item for that lot as follows:

DISINCENTIVE PAY REDUCTION FOR HMA PAVEMENT DENSITY

PERCENT LOT DENSITY	PAYMENT FACTOR
BELOW SPECIFIED MINIMUM	(percent of contract price)
From 0.5 to 1.0 inclusive	98
From 1.1 to 1.5 inclusive	95
From 1.6 to 2.0 inclusive	91
From 2.1 to 2.5 inclusive	85
From 2.6 to 3.0 inclusive	70
More than 3.0 ^[1]	

- [1] Remove and replace the lot with a mixture at the specified density. When acceptably replaced, the department will pay for the replaced work at the contract unit price. Alternatively, the engineer may allow the nonconforming material to remain in place with a 50 percent payment factor.
- (6) The department will pay incentive for air voids and density under the following bid items:

ITEM NUMBER	DESCRIPTION	UNIT
460.2005	Incentive Density PWL HMA Pavement	DOL
460.2010	Incentive Air Voids HMA Pavement	DOL

The department will administer disincentives under the Disincentive Density HMA Pavement and the Disincentive Air Voids HMA Pavement administrative items.

The department will administer a disincentive under the Disincentive HMA Binder Content administrative item for each individual QV test result indicating asphalt binder content below the Action Limit in 460.2.8.2.1.7 presented herein. The department will adjust pay per sublot of mix at 65 dollars per ton of HMA pavement multiplied by the following pay adjustment calculated according to the HMA PWL Production Spreadsheet:

AC Binder Relative to JMF	Pay Adjustment / Sublot
-0.4% to -0.5%	75% ^[1]
More than -0.5%	50% ^{[1][2]}

- [1] Any material resulting in an asphalt binder content more than 0.3% below the JMF AC content will be referee tested by the department's AASHTO accredited laboratory and HTCP certified personnel using automated extraction according to automated extraction according to WTM D8159.
- Any material resulting in an asphalt binder content more than 0.5% below the JMF AC content shall be removed and replaced unless the engineer allows such material to remain in place. In the event the material remains in place, it will be paid at 50% of the contract unit price of HMA pavement.

Note: PWL value determination is further detailed in the PWL Production Spreadsheet Instructions located in the *Project Info & Instructions* tab of the HMA PWL Production spreadsheet.

stp-460-050 (20240105)

2140-14-70 40 of 85

37. Appendix A

Test Methods & Sampling for HMA PWL QMP Projects

The following procedures are included with the HMA Pavement Percent Within Limits (PWL) Quality Management Program (QMP) special provision:

- WisDOT Procedure for Nuclear Gauge/Core Correlation Test Strip
- · WisDOT Test Method for HMA PWL QMP Density Measurements for Main Production
- Sampling for WisDOT HMA PWL QMP
- · Calculation of PWL Mainline Tonnage Example

WisDOT Procedure for Nuclear Gauge/Core Correlation - Test Strip




Figure 1: Nuclear/Core Correlation Location Layout

The engineer will identify two zones in which gauge/core correlation is to be performed. These two zones will be randomly selected within each *half* of the test strip length. (Note: Density zones shall not overlap and must have a minimum of 100 feet between the two zones; therefore, random numbers may be shifted (evenly) in order to meet these criteria.) Each zone shall consist of five locations across the mat as identified in Figure 1. The following shall be determined at each of the five locations within both zones:


- two one-minute nuclear density gauge readings for QC team*
- two one-minute nuclear density gauge readings for QV team*
- pavement core sample

*If the two readings exceed 1.0 pcf of one another, a third reading is conducted in the same orientation as the first reading. In this event, all three readings are averaged, the individual test reading of the three which falls farthest from the average value is discarded, and the average of the remaining two values is used to represent the location for the gauge.

The zones are supposed to be undisclosed to the contractor/roller operators. The engineer will not lay out density/core test sites until rolling is completed and the cold/finish roller is beyond the entirety of the zone. Sites are staggered across the 12-foot travel lane, and do not include shoulders. The outermost locations shall be 1.5-feet from the center of the gauge to the edge of the lane. [NOTE: This staggered layout is only applicable to the test strip. All mainline density locations after test strip shall have a longitudinal and transverse random number to determine the location as detailed in the *WisDOT Test Method for HMA PWL QMP Density Measurements for Main Production* section of this document.]

The nuclear site is the same for QC and QV readings for the test strip, i.e., the QC and QV teams are to take nuclear density gauge readings in the same footprint. Each of the QC and QV teams are to take a minimum of two one-minute readings per nuclear site, with the gauge rotated 180 degrees between readings, as seen here:

2140-14-70 41 of 85






Figure 2: Nuclear Gauge Orientation for (a) 1st One-Minute Reading and (b) 2nd One-Minute Reading

Take photos of each of the 10 core/gauge locations of the test strip. Include gauge readings (pcf) and a labelled core within the gauge footprint. If a third reading is needed, record and document all three readings. Only raw readings in pcf shall be written on the pavement during the test strip, with a corresponding gauge ID/SN (generalized as QC-1 through QV-2 in the following Figure) in the following format:



Figure 3: Layout of Raw Gauge Readings as Recorded on the Pavement

Take each core from the center of the gauge footprint and correlate each gauge with the laboratory-measured bulk specific gravities of the pavement cores. One core in good condition must be obtained from each of the 10 locations. If a core is damaged at the time of extracting from the pavement, a replacement core should be taken immediately adjacent to the damaged core, i.e., from the same footprint. If a core is damaged during transport, it shall be recorded as damaged and excluded from the correlation. Coring after traffic is on the pavement shall be avoided. The contractor shall be responsible for coring of the pavement. Coring and filling of core holes must be approved by the engineer. The QV team is responsible for the labeling and safe transport of the cores from the field to the QC laboratory. Conduct core density testing with a witness by department personnel. Dry the cores following testing. The department will take possession of cores following initial testing and is responsible for any verification testing.

Each core 100 or 150 mm (4 or 6 inches) in diameter will be taken at locations as identified in Figure 1. Each random core will be full thickness of the layer being placed. Thoroughly dry cores obtained from the mat according to WTM R79 prior to using specimens for in-place density determination according to WTM T166.

Cut cores by the next day after completion of the test strip, except if the next day is not a working day, then cut within 48 hours of placement. Cores are cut under department/project staff observation. Relabel each core immediately after extruding or ensure that labels applied to pavement prior to cutting remain legible. The layer interface should also be marked immediately following extrusion. Cores should be cut at this interface, using a wet saw, to allow for density measurement of only the most recently placed layer. Cores should be protected from excessive temperatures such as direct sunlight. Also, there should be department custody (both in transport and storage) for the cores until they are tested whether that be immediately after the test strip or the subsequent day if agreed upon between department and contractor. Use of concrete cylinder molds works well to transport cores. Cores should be placed upside down (flat surface to bottom of cylinder mold) in the molds, one core per mold, cylinder molds stored upright, and ideally transported in a cooler. Avoid any stacking of pavement cores.

Fill all core holes with non-shrink rapid-hardening grout, mortar, or concrete, or with HMA. When using grout, mortar, or concrete, remove all water from the core holes prior to filling. Mix the mortar or concrete in a separate container prior to placement in the hole. If HMA is used, fill all core holes with hot-mix

2140-14-70 42 of 85

matching the same day's production mix type at same day compaction temperature +/- 20 F. Dry the core holes and coat with tack before filling, filled with a top layer no thicker than 2.25 inches, lower layers not to exceed 4 inches, and compacted with a Marshall hammer or similar tamping device using approximately 50 blows per layer. The finished surface shall be flush with the pavement surface. Any deviation in the surface of the filled core holes greater than ¼ inch at the time of final inspection will require removal of the fill material to the depth of the layer thickness and replacement.

WisDOT Test Method for HMA PWL QMP Density Measurements for Main Production

For nuclear density testing of the pavement beyond the test strip, QC tests shall be completed at three locations per sublot, with a sublot defined as 1,500 lane feet. The three locations shall represent the outside, middle, and inside of the paving lane (i.e., the lane width will be divided into thirds as shown by the dashed longitudinal lines in Figure 3 and random numbers shall be used to identify the specific transverse location within each third determined by WTM D3665). Longitudinal locations within each sublot shall be determined with 3 independent random numbers determined by WTM D3665. The PWL Density measurements do not include the shoulder and other appurtenances. Such areas are tested by the department and are not eligible for density incentive but are subject to disincentive according to 460.5.2.2(5) of the HMA PWL QMP article. Measure each location with two one-minute gauge readings oriented 180 degrees from one another, in the same footprint as detailed in Figure 2 above. Each location requires a minimum of two readings per gauge. The density gauge orientation for the first test shall be with the source rod towards the direction of paving. QV nuclear testing will consist of one randomly selected location per sublot. The QV is also comprised of two one-minute readings oriented 180 degrees from one another. For both QC and QV test locations, if the two readings exceed 1.0 pcf of one another, a third reading shall be conducted in the same orientation as the first reading. In this event, all three readings are averaged, the individual test reading of the three which falls farthest from the average value is discarded, and the average of the remaining two values is used to represent the location for the gauge. The sublot density testing layout is depicted in Figure 4, with QC test locations shown as solid black boxes and QV test locations shown as dashed red boxes.




Figure 4: Example Layout of Mainline HMA Nuclear Density Tests

Raw nuclear density data must be shared by both parties at the end of each shift. Paving may be delayed if the raw data is not shared in a timely manner. QC and QV nuclear density gauge readings will be statistically analyzed according to Section 460.3.3.3 of the HMA PWL QMP article. (Note: For density data, if F- and t-tests compare, QC data will be used for the subsequent calculations of PWL value and pay determination. However, if an F- or t-test does not compare, the QV data will be used in subsequent calculations.)

Investigative cores will be allowed on the approaching side of traffic outside of the footprint locations. Results shall be shared with the department.

The QV density technician is expected to be onsite within 1 hour of the start of paving operations and should remain on-site until all paving is completed. Perform footprint testing as soon as both the QC and QV nuclear density technician are onsite and a minimum of once per day to ensure the gauges are not drifting apart during a project. Footprint testing compares the density readings of two gauges at the same testing location and can be done at any randomly selected location on the project. Both teams are

2140-14-70 43 of 85

encouraged to conduct footprint testing as often as they feel necessary. Footprint testing does not need to be performed at the same time. At project start-up, the QV should footprint the first 10 QC locations. Individual density tests less than 0.5% above the lower limit should be communicated to the other party and be footprint tested. Each gauge conducts 2 to 3 1-minute tests according to WTM T355 and the final results from each gauge are compared for the location. If the difference between the QC and QV gauges exceeds 1.0 pcf (0.7 percent) for an average of 10 locations, investigate the cause, check gauge moisture and density standards and perform additional footprint testing. If the cause of the difference between gauge readings cannot be identified, the regional HMA Coordinator will consult the RSO, the regional PWL representative and the BTS HMA unit to determine necessary actions. If it is agreed that there is a gauge comparison issue, perform one of the following two options:

New Gauge Combination

- All 4 gauges used on the test strip must footprint 10 locations on the pavement. Pavement placed on a previous day may be used.
- The results of the footprint testing will be analyzed to see if a better combination of acceptable gauges is available.
- · If a better combination is found, those gauges should be used moving forward.
- If a better combination cannot be found, a new gauge correlation must be performed. (see below)

Re-correlation of Gauges

- Follow all test strip procedures regarding correlating gauges except the following:
- · The 10 locations can be QC or QV random locations.
- · The locations used may have been paved on a previous day.
- Retesting with gauges must be done immediately prior to coring.
- New gauge offsets will be used for that day's paving and subsequent paving days. New gauge offsets will not be used to recalculate density results from prior days.

Density Dispute Resolution Procedure

Density results may be disputed by the contractor on a lot-by-lot basis if one of the following criteria is met:

- · The lot average for either QC or QV is below the lower specification limit.
- The lot average for QC is different from the lot average for QV by more than 0.5%.
- The lot is in disincentive.

In lieu of using density gauges for acceptance of the lot, the lot will be cored in the QV locations. The results of the cores from the entire lot will be entered in the spreadsheet and used for payment. If the pay factor increases, the contractor will only receive the additional difference in payment for the disputed lot. If the pay factor does not increase, the department will assess the contractor \$2,000 for the costs of additional testing.

Notify the engineer in writing before dispute resolution coring. Immediately prior to coring, QC and QV will test the locations with nuclear density gauges.

Under the direct observation of the engineer, cut 100 or 150 mm (4 or 6 inch) diameter cores. Cut cores by the next day after completion of the lot, except if the next day is not a working day, then cut within 48 hours of placement. Prepare cores and determine density according to WTM T166. Dry cores after testing. Fill core holes according to Appendix A and obtain engineer approval before opening to traffic. The department will maintain custody of cores throughout the entire sampling and testing process. The department will label cores, transport cores to testing facilities, witness testing, store dried cores, and provide subsequent verification testing. If a core is damaged at the time of coring, immediately take a replacement core 1 ft ahead of the existing testing location in the direction of traffic at the same offset as the damaged core. If a core is damaged during transport, record it as damaged and notify the engineer immediately.

Sampling for WisDOT HMA PWL QMP Production

Sampling of HMA mix for QC, QV, Retained, and Extra split samples shall conform to WTM R97 and WTM R47.

2140-14-70 44 of 85

Sampling Hot Mix Asphalt

At the beginning of the contract, determine the anticipated tonnage to be produced. The frequency of sampling is 1 per 750 tons (sublot) for QC and Retained Samples and 1 per 3,750 tons (lot or 5 sublots) for QV as defined by the HMA PWL QMP article. A test sample is obtained randomly from each sublot. Each random sample shall be collected at the plant according to WTM R97. Submit the random numbers for all mix sampling to the department before production begins.

Example 1

Expected production for a contract is 12,400 tons. The number of required samples is determined based on this expected production (per HMA PWL QMP SPV) and is determined by the random sample calculation.

The approximate location of each sample within the prescribed sublots is determined by selecting random numbers using WTM D3665. The random numbers selected are used in determining when a sample is to be taken and will be multiplied by the sublot tonnage. This number will then be added to the final tonnage of the previous sublot to yield the approximate cumulative tonnage of when each sample is to be taken.

To allow for plant start-up variability, the procedure calls for the first random sample to be taken at 50 tons or greater per production day (not intended to be taken in the first two truckloads). Random samples calculated for 0-50 ton shall be taken in the next truck (51-75 ton).

This procedure is to be used for any number of samples per contract.

If the production is less than the final randomly generated sample tonnage, then the random sample is to be collected from the remaining portion of that sublot of production. If the randomly generated sample is calculated to be within the first 0-50 tons of the subsequent day of production, it shall be taken in the next truck. Add a random sample for any fraction of 750 tons at the end of the contract. Lot size will consist of 3750 tons with sublots of 750 tons. Partial lots with less than three sublot tests will be included into the previous lot, by the engineer.

It is intended that the plant operator is not advised ahead of time when samples are to be taken.

If belt samples are used during troubleshooting, the blended aggregate will be obtained when the mixture production tonnage reaches approximately the sample tonnage. For plants with storage silos, this could be up to 60 minutes in advance of the mixture sample that's taken when the required tonnage is shipped from the plant.

Collect QC, QV, Retained, and Extra split samples for all test strip and production mixture testing using a four-part splitting procedure according to WTM R47.

<u>Calculation of PWL Mainline Tonnage Example</u>

A mill and overlay project in being constructed with a 12-foot travel lane and an integrally paved 3-foot shoulder. The layer thickness is 2 inches for the full width of paving. Calculate the tonnage in each sublot eligible for density incentive or disincentive.

Solution:

$$\frac{1500\,ft\,\times\,12\,ft}{9\,sf/sy}\times\frac{2\,in\,\times112\,lb/sy/in}{2000\,lb/ton}=224\,tons$$

stp-460-055 (20240105)

2140-14-70 45 of 85

38. HMA Pavement Longitudinal Density

A Description

This special provision incorporates longitudinal joint density requirements into the contract and describes the data collection, acceptance, and procedure used for determination of pay adjustments for HMA pavement longitudinal joint density. Pay adjustments will be made on a linear foot basis, as applicable per pavement layer and paving lane. Applicable longitudinal joints are defined as those between any two or more traffic lanes including full-width passing lanes, turn lanes, or auxiliary lanes more than 1,500 lane feet, and those lanes must also include the 460.2005 Incentive Density PWL HMA Pavement bid item. This excludes any joint with one side defined as a shoulder and ramp lanes of any length. If echelon paving is required in the contract, the longitudinal joint density specification shall not apply for those joints. Longitudinal joints placed during a test strip will be tested for information only to help ensure the roller pattern will provide adequate longitudinal joint density during production. Longitudinal joint density test results collected during a test strip are not eligible for pay adjustment.

Pay is determined according to standard spec 460, HMA Pavement Percent Within Limits QMP special provisions, and as modified within.

B Materials

Compact all applicable HMA longitudinal joints to the appropriate density based on the layer, confinement, and mixture type shown in Table B-1.

	Percent of Target Maximum Density			
Layer	Unco	Unconfined		ined
	LT and MT	HT	LT and MT	HT
Lower (on crushed/recycled base)	88	89	89.5	90.5
Lower (on Concrete/HMA)	90[1]	90[1]	91.5 ^[1]	91.5 ^[1]
Upper	90	90	91.5	91.5

TABLE B-1 MINIMUM REQUIRED LONGITUDINAL JOINT DENSITY

C Construction

Add the following to standard spec 460.3.3.2:

- (5) Establish companion QC and QV density locations for each applicable joint. Each companion location shares longitudinal stationing with the respective QC or QV mainline density location within each sublot and is located transversely with the center of the gauge 6-inches from the final joint edge of the paving area. Sublot and lot numbering remains the same as mainline densities, however, in addition to conventional naming, joint identification must clearly indicate "M" for inside/median side of lane or "O" for outside shoulder side of lane, as well as "U" for an unconfined joint or "C" for a confined joint (e.g., XXXXX-MC or XXXXXX-OU).
- (6) Each joint shall be measured, reported, and accepted under methods, testing times, and procedures consistent with the program employed for mainline density, i.e., PWL.
- (7) For single nuclear density test results greater than 3.0% below specified minimums per Table B-1 herein, perform the following:
 - a) Testing at 50-foot increments both ahead and behind the unacceptable site.
 - b) Continued 50-foot incremental testing until test values indicate higher than or equal to -3.0 percent from target joint density.
 - c) Materials within the incremental testing indicating lower than -3.0 percent from target joint density are defined as unacceptable and will be handled with remedial action as defined in the payment section of this document.

2140-14-70 46 of 85

^[1] Minimum reduced by 1.0 percent for a 1.25-inch-thick No. 5 mix lower layer constructed on a paved or milled surface.

d) The remaining sublot average (exclusive of unacceptable material) will be determined by the first forward and backward 50-foot incremental tests that reach the criteria of higher than or equal to -3.0 percent from target joint density.

Note: If the 50-foot testing extends into a previously accepted sublot, remedial action is required up to and inclusive of such material; however, the results of remedial action must not be used to recalculate the previously accepted sublot density. When this occurs, the lane feet of any unacceptable material will be deducted from the sublot in which it is located, and the previously accepted sublot density will be used to calculate pay for the remainder of the sublot.

- (8) Joint density measurements shall be kept separate from all other density measurements and entered as an individual data set into Atwood Systems.
- (9) Placement and removal of excess material outside of the final joint edge, to increase joint density at the longitudinal joint nuclear testing location, shall be done at the contractor's discretion and cost. This excess material and related labor will be considered waste and will not be paid for by the department. Joints with excess material placed outside of the final joint edge to increase joint density or where a notched wedge is used will be considered unconfined joints.
- (10) When not required by the contract, echelon paving may be performed at the contractor's discretion to increase longitudinal joint density and still remain eligible to earn incentive. The additional costs incurred related to echelon paving will not be paid for by the department. If lanes are paved in echelon, the contractor may choose to use a longitudinal vertical joint or notched wedge longitudinal joint as described in SDD 13c19. Lanes paved in echelon shall be considered confined on both sides of the joint regardless of the selected joint design. The joint between echelon paved lanes shall be placed at the centerline or along lane lines.
- (11) When performing inlay paving below the elevation of the adjacent lane, the longitudinal joint along the adjacent lane to be paved shall be considered unconfined.

D Measurement

The department will measure each side of applicable longitudinal joints, as defined in Section A of this special provision, by the linear foot of pavement, acceptably placed. Measurement will be conducted independently for the inside or median side and for the outside or shoulder side of paving lanes with two applicable longitudinal joints. Each paving layer will be measured independently at the time the mat is placed.

E Payment

Add the following as 460.5.2.4 Pay Adjustment for HMA Pavement Longitudinal Joint Density:

(1) The department will administer longitudinal joint density adjustments under the Incentive Density HMA Pavement Longitudinal Joints and Disincentive Density HMA Pavement Longitudinal Joints items. The department will adjust pay based on density relative to the specified targets in Section B of this special provision, and linear foot of the HMA Pavement bid item for that sublot as follows:

PAY ADJUSTMENT FOR HMA PAVEMENT LONGITUDINAL JOINT DENSITY

PERCENT SUBLOT DENSITY

PAY ADJUSTMENT PER LINEAR FOOT

ABOVE/BELOW SPECIFIED MINIMUM

Equal to or greater than +1.0 confined, +2.0 unconfined	\$0.20
From 0.0 to +0.9 confined, 0.0 to +1.9 unconfined	\$0
From -0.1 to -1.0	\$(0.20)
From -1.1 to -2.0	\$(0.40)
From -2.1 to -3.0	\$(0.80)
More than -3.0	REMEDIAL ACTION [1]

^[1] Remedial action must be approved by the engineer and agreed upon at the time of the pre-pave meeting and may include partial sublots as determined and defined in 460.3.3.2(7) of this document. If unacceptable material is removed and replaced per guidance by the engineer, the removal and replacement will be for the full lane width of the side of which the joint was constructed with unacceptable material.

(2) The department will not assess joint density disincentives for pavement placed in cold weather because of a department-caused delay as specified in standard spec 450.5.2(3).

2140-14-70 47 of 85

- (3) The department will not pay incentive on the longitudinal joint density if the traffic lane is in disincentive A disincentive may be applied for each mainline lane and all joint densities if both qualify for a pay reduction.
- (4) Inlay paving operations will limit payment for additional material to 2 inches wider than the final paving lane width at the centerline.

The department will pay incentive for longitudinal joint density under the following bid items:

ITEM NUMBER DESCRIPTION UNIT 460.2007 Incentive Density HMA Pavement Longitudinal Joints DOL


The department will administer disincentives under the Disincentive Density HMA Pavement Longitudinal Joints administrative item.

Appendix

WisDOT Longitudinal Joint - Nuclear Gauge Density Layout

Each QC and QV density location must have a companion density location at any applicable joint. This companion location must share longitudinal stationing with each QC or QV density location and be located transversely with the center of the gauge 6-inches from the final joint edge of the paving area.

For HMA Pavement Percent Within Limits QMP projects, this appears as follows:



Further Explanation of PAY ADJUSTMENT FOR HMA PAVEMENT LONGITUDINAL JOINT DENSITY Table

	Confined				
	Lower Layer (On Base) Upper Layer				
	LT/MT	HT	LT/MT	HT	Pay Adjust
Mainline Target (SS 460-3)	91.0	92.0	93.0	93.0	-
Confined Target (mainline - 1.5)	89.5	90.5	91.5	91.5	-
Equal to or greater than +1.0	<u>≥</u> 90.5	<u>≥</u> 91.5	<u>≥</u> 92.5	<u>≥</u> 92.5	\$0.20
From 0.0 to +0.9	90.4 - 89.5	91.4 - 90.5	92.4 - 91.5	92.4 - 91.5	\$0
From -0.1 to -1.0	89.4 - 88.5	90.4 - 89.5	91.4 - 90.5	91.4 - 90.5	(\$0.20)
From -1.1 to -2.0	88.4 - 87.5	89.4 - 88.5	90.4 - 89.5	90.4 - 89.5	(\$0.40)
From -2.1 to -3.0	87.4 - 86.5	88.4 - 87.5	89.4 - 88.5	89.4 - 88.5	(\$0.80)
More than -3.0	< 86.5	< 87.5	< 88.5	< 88.5	REMEDIAL ACTION

2140-14-70 48 of 85

	Unconfined				
	Lower Laye	r (On Base)	Upper	Layer	
	LT/MT	HT	LT/MT	HT	Pay Adjust
Mainline Target (SS 460-3)	91.0	92.0	93.0	93.0	-
Unconfined Target (Mainline -3.0)	88.0	89.0	90.0	90.0	-
Equal to or greater than +2.0	<u>></u> 90.0	<u>></u> 91.0	<u>></u> 92.0	<u>></u> 92.0	\$0.20
From 0.0 to +1.9	89.9 - 88.0	90.9 - 89.0	91.9 - 90.0	91.9 - 90.0	\$0
From -0.1 to -1.0	87.9 - 87.0	88.9 - 88.0	89.9 - 89.0	89.9 - 89.0	(\$0.20)
From -1.1 to -2.0	86.9 - 86.0	87.9 - 87.0	88.9 - 88.0	88.9 - 88.0	(\$0.40)
From -2.1 to -3.0	85.9 - 85.0	86.9 - 86.0	87.9 - 87.0	87.9 - 87.0	(\$0.80)
More than -3.0	< 85.0	< 86.0	< 87.0	< 87.0	REMEDIAL ACTION

stp-460-075 (20240105)

39. Adjusting Manhole Covers, Item 611.8110.

This special provision describes adjusting manhole covers conforming to standard spec 611 as modified in this special provision.

Adjust manhole covers located in pavement areas in two separate operations. Initially, remove designated manhole covers along with sufficient pavement to permit installation of temporary cover plate over the opening. Fill the excavated area with asphaltic pavement mixture, which shall remain in place until contract milling and paving operations permit setting the manhole frames to grade. During the second phase, remove the asphaltic pavement mixture surrounding the manhole plus the temporary cover plate, and set the manhole cover to final grade. The department will measure and pay for the items of asphaltic pavement mixture, temporary cover plate, milling, and paving separately.

Supplement standard spec 611.3.7 with the following:

Set the manhole frames so that they comply with the surface requirements of standard spec 450.3.2.9. At the completion of the paving, a 6-foot straightedge shall be placed over the centerline of each manhole frame parallel to the direction of traffic. A measurement shall be made at each side of the frame. The two measurements shall be averaged. If this average is greater than 5/8 inches, reset the manhole frame to the correct plane and elevation. If this average is 5/8 inches or less but greater than 3/8 inches, the manhole frame shall be allowed to remain in place but shall be paid for at 50 percent of the contract unit price.

If the manhole frame is higher than the adjacent pavement, the two measurements shall be made at each end of the straightedge. These two measurements shall be averaged. The same criteria for acceptance and payment as above, shall apply.

stp-611-005 (20200629)

40. Cover Plates Temporary, Item 611.8120.S.

A Description

This special provision describes providing and removing steel plates to cover and support asphaltic pavement and traffic loading at manholes, inlets and similar structures during milling and paving operations.

B Materials

Provide a 0.25 inch minimum thickness steel plate that extends to the outside edge of the existing masonry.

C (Vacant)

2140-14-70 49 of 85

D Measurement

The department will measure Cover Plates Temporary as each individual unit, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT 611.8120.S Cover Plates Temporary EACH

Payment is full compensation for furnishing, installing, and removing the cover plates.

The steel plates shall become the property of the contractor when no longer needed in the contract work. stp-611-006 (20151210)

41. Fence Safety, Item 616.0700.S.

A Description

This special provision describes providing plastic fence at locations the plans show.

B Materials

Furnish notched conventional metal "T" or "U" shaped fence posts.

Furnish fence fabric meeting the following requirements.

Color: International orange (UV stabilized)

Roll Height: 4 feet

Mesh Opening: 1 inch min to 3 inch max

Resin/Construction: High density polyethylene mesh

Tensile Yield: Avg. 2000 lb per 4 ft. width (ASTM D638)

Ultimate Tensile Strength: Avg. 3000 lb per 4 ft. width (ASTM D638)

Elongation at Break (%): Greater than 100% (ASTM D638)

Chemical Resistance: Inert to most chemicals and acids

C Construction

Drive posts into the ground 12 to 18 inches. Space posts at 7 feet.

Use a minimum of three wire ties to secure the fence at each post. Weave tension wire through the top row of strands to provide a top stringer that prevents sagging.

Overlap two rolls at a post and secure with wire ties.

D Measurement

The department will measure Fence Safety by the linear foot along the base of the fence, center-to-center of posts, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNIT616.0700.SFence SafetyLF

Payment is full compensation for furnishing and installing fence and posts; maintaining the fence and posts in satisfactory condition; and for removing and disposing of fence and posts at project completion.

stp-616-030 (20160607)

2140-14-70 50 of 85

42. Connected Arrow Board, Item 643.0810.S.

A Description

This special provision describes providing, repositioning, operating, maintaining, monitoring, and removing connected arrow board(s) capable of reporting real-time work zone lane closure information to Wisconsin 511 and third-party vendors.

B Materials

Furnish items from the department's approved products list.

C Construction

C.1 General

Follow all requirements in Spec 643.3.

Place connected arrow board per plan or as the engineer directs.

Ensure the connected arrow board operates continuously when deployed on the project.

Ensure the connected arrow board and work zone location markers are from the same manufacturer.

Provide a local specialist to respond to emergency situations within 2 hours of being notified. Equip local specialist with sufficient resources to correct deficiencies in the connected work zone start and end location markers.

C.2 Testing and Configuration

Prior to deployment, test the connected arrow board with the engineer to ensure the device is showing in the WZDx Device Feed. Send an email to DOTBTOworkzone@dot.wi.gov to notify BTO that the devices have been turned on.

C.3 Programming

Connected arrow board may be switched between the following pattern displays per the plan:

- Blank
- Right Arrow Static
- Right Arrow Flashing
- · Right Arrow Sequential
- Left Arrow Static
- Left Arrow Flashing
- Left Arrow Sequential

When the connected arrow board is not displaying a pattern, the display shall be blank and the connected arrow board transmits its status to the data feed. When a connected arrow board is switched to a pattern, the connected arrow board transmits its location and its current operating mode to the data feed.

The connected arrow board and the remote management software shall provide a public GeoJSON/API feed, updated at least every minute, compliant with FHWA's Work Zone Data Exchange (WZDx) v4.2 (https://www.transportation.gov/av/data/wzdx) Device Feed specification.

C.3 Reporting

If requested by the engineer, provide real-time status change alerts to a list of designated personnel via text and/or email. Send an alert each time a connected arrow board is switched between operating modes (e.g., each time a connected arrow board is switched between blank, flashing left arrow mode and flashing right arrow mode). Include the current operating mode, the previous operating mode, the date and time of the mode switch, and the location (latitude and longitude) of the device at the time of the mode switch in the alert.

D Measurement

The department will measure the connected arrow board by the day, acceptably completed, measured per roadway.

2140-14-70 51 of 85

The department will not measure the connected arrow board on days it is not required.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNIT643.0810.SConnected Arrow BoardDAY

Payment is full compensation for providing, repositioning, operating, maintaining, monitoring, testing, and removing the connected arrow board.

The department will deduct one day for each calendar day the connected work zone start and end location markers is required but out of service for more than 2 hours.

stp-643-012 (20250108)

43. Connected Work Zone Start and End Location Markers, Item 643.1220.

A Description

This special provision describes providing, repositioning, operating, maintaining, monitoring, and removing connected work zone start and end location markers capable of reporting real-time work zone location information to Wisconsin 511 and third-party vendors.

B Materials

Furnish items from the department's approved products list.

C Construction

C.1 General

Follow all requirements in Spec 643.3.

Place work zone start location marker at the beginning of the work zone per plan or as the engineer directs. Clearly label the work zone start location marker so that it is easily distinguishable by field personnel.

Place work zone end location marker at the end of the work zone per plan or as the engineer directs. Clearly label the work zone end location marker so that it is easily distinguishable by field personnel.

Ensure the connected work zone start and end location markers operate continuously when deployed on the project.

Ensure the work zone location markers and connected arrow board are from the same manufacturer.

Provide a local specialist to respond to emergency situations within 2 hours of being notified. Equip local specialist with sufficient resources to correct deficiencies in the connected work zone start and end location markers.

C.2 Testing and Configuration

Prior to deployment, test the connected work zone start and end location markers with the engineer to ensure devices are showing in the WZDx Device Feed. Send an email to DOTBTOworkzone@dot.wi.gov to notify BTO that the devices have been turned on.

C.3 Programming

When the work zone start location marker is switched to the ON mode, the begin location marker transmits to the data feed its location and identity as a work zone start location marker. The end location marker functions similarly.

The connected work zone start and end location markers and their remote management software shall provide a public GeoJSON/API feed, updated at least every minute, compliant with FHWA's Work Zone Data Exchange (WZDx) v4.2 (https://www.transportation.gov/av/data/wzdx) Device Feed specification.

Switch the work zone start and end location markers to OFF mode when temporary traffic control is removed, and the normal traveled way is restored.

2140-14-70 52 of 85

C.4 Reporting

If requested by the engineer, provide real-time status change alerts to a list of designated personnel via text and/or email. Send an alert each time the connected work zone start and end location markers are switched between operating modes (e.g., each time a work zone start/end location marker is switched between ON mode and OFF mode). Include the date and time of the mode switch, and the location (latitude and longitude) of the device at the time of the mode switch in the alert.

D Measurement

The department will measure the connected work zone start and end location markers by the day, acceptably completed, measured per roadway.

The department will not measure the connected work zone start and end location markers on days they are not required.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT 643.1220.S Connected Work Zone Start and End Location Markers DAY

Payment is full compensation for providing, repositioning, operating, maintaining, monitoring, testing, and removing the complete system consisting of connected work zone start and end location markers.

The department will deduct one day for each calendar day the connected work zone start and end location markers is required but out of service for more than two hours.

stp-643-122 (20250108)

44. Temporary Audible Message Devices, Item 644.1900.S

A Description

This special provision describes providing, maintaining, and removing temporary audible message devices. These devices are used on temporary pedestrian facilities to guide individuals with sight disabilities.

B Materials

Furnish temporary audible message devices from the approved products lists.

C Construction

Provide and maintain temporary audible message device. Maintain and repair devices within two hours of being notified by the project engineer of an issue.

Contractors record messages as approved by the engineer.

Mount temporary audible message devices on drums, temporary sign supports, or other locations approved by the engineer. Locate motion detection areas that will be effective in activating the device to operate properly. Avoid locating motion detection areas that will cause activation by trees, traffic, or other known regular activity.

Move and adjust devices after disruptions by the work or the public.

Maintain devices in a working condition and replace batteries as needed. Replace any devices that are not working properly within 2 hours of being notified of an issue.

Use tamper-proof hardware for mounting.

D Measurement

The department will measure temporary audible message devices by the day, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT 644.1900.S Temporary Audible Message Device DAY

2140-14-70 53 of 85

Payment is full compensation for providing, maintaining, and removing temporary audible message device.

The department will not pay for devices that are inoperable.

stp-644-190 (20250108)

45. Electrical Service Meter Breaker Pedestal STH 181 & Florist Ave, Item 656.0201.01; Electrical Service Meter Breaker Pedestal STH 181 & Mill Rd, Item 656.0201.02; Electrical Service Meter Breaker Pedestal STH 181 & Acacia St, Item 656.0201.03; Electrical Service Meter Breaker Pedestal STH 181 \$ Green Tree Rd, Item 656.0201.04; Electrical Service Meter Breaker Pedestal STH 181 & Good Hope Rd, Item 656.0201.05; Electrical Service Meter Breaker Pedestal STH 181 & Calumet Rd, Item 656.0201.06; Electrical Service Meter Breaker Pedestal STH 181 & Bradley Rd, Item 656.0201.07; Electrical Service Meter Breaker Pedestal STH 181 & Tower Ave, Item 656.0201.08; Electrical Service Meter Breaker Pedestal STH 181 & Servite/Dean Rd, Item 656.0201.09; Electrical Service Meter Breaker Pedestal STH 181 & Northridge Dr, Item 656.0201.10; Electrical Service Meter Breaker Pedestal STH 181 & Northridge Lakes Blvd, Item 656.0201.11.

Append 656.2.3 of the standard specifications with the following:

- (2) The department will be responsible for the electrical service installation or relocation request for any department-maintained facility. Notify the maintaining authority if the signal is not state maintained that it is their responsibility to arrange for the electrical service installation.
- (3) Electrical utility company service installation and energy cost will be billed to and paid for by the department.
- (4) Install the cabinet base and meter breaker pedestal first, so the electrical utility company can install the service lateral. Install a 3" conduit from the point of service from the utility to the meter breaker pedestal. Finish grade the service trench, replace topsoil that is lost or contaminated with other materials, fertilize, seed, and mulch all areas that are disturbed by the electrical utility company.

Append 656.5 of the standard specifications with the following:

(8) Payment is full compensation for grading the service trench; replacing topsoil; and for fertilizing, seeding, and mulching to restore the disturbed area of the service trench.

46. Lamp, Ballast, LED, Switch Disposal by Contractor, Item 659.5000.S.

A Description

This special provision describes the packaging of lamps, ballasts, LEDs, and mercury containing switches (e.g., overhead roadway lighting, underdeck bridge, wall packs, pedestrian signals, traffic control stop lights and warning flashers, fluorescent bulbs, and thermostats) removed under this contract for disposal as hazardous materials.

For Lamp, Ballast, LED, Switch Disposal by Contractor, coordinate removal from the work site by the department's hazardous waste disposal vendor.

B Materials

Items removed under this contract will be considered the property of the department for waste generator identification. The contractor is responsible for coordinating with the department's hazardous waste vendor for disposal:

https://wisconsindot.gov/Documents/doing-bus/eng-consultants/cnslt-rsrces/environment/hazwaste-contacts.pdf

C Construction

Provide a secure, level location removed from the travelled way for storage of the material for disposal.

Pack intact fixtures in the packaging of the new lamps used to replace them, or packaging affording the equivalent protection. Place in full, closed stackable cartons.

2140-14-70 54 of 85

Pile cartons no more than four high if palletized and secure cartons with shrink wrap to prevent shifting or falling of the loads. Clearly mark each pallet with the words "Universal Waste Lamps" or "Universal Waste Ballasts", the date, and the number of fixtures on each pallet.

Pack broken fixtures into (min.) 6 mil thick plastic bags and place inside sturdy cardboard boxes or the equivalent. Mark the outer packaging with the term "Broken Fixtures/Lamps", the date and the number of broken fixtures clearly marked on the box.

The hazardous waste vendor will not accept fixtures improperly packaged. The vendor will reject any fixtures not removed as part of a contract pay item or otherwise required under this contract.

Pack ballasts and mercury containing switches in appropriate containers.

Complete the lamp and ballast inventory (https://wisconsindot.gov/Documents/doing-bus/eng-consultants/cnslt-rsrces/environment/dotlampballastinventory.dotx) and contact the hazardous waste vendor to coordinate pickup and disposal at a location specified by the contractor. Consolidate all pallets and boxes from one project at a single location. Contact the hazardous waste vendor to set up an appointment for pickup. The hazardous waste vendor requires a minimum of one week advance notice to schedule pickup.

D Measurement

The department will measure Lamp, Ballast, LED, Switch Disposal by Contractor as each individual unit received by the hazardous waste vendor, properly packaged and acceptably completed, matching the total number of units provided on the inventory form. The department will not measure broken fixtures that exceed a total of 10 percent of all fixtures to be disposed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER

DESCRIPTION

UNIT

659.5000.S

Lamp, Ballast, LED, Switch Disposal by Contractor

EACH

Payment for Lamp, Ballast, LED, Switch Disposal by Contractor is full compensation for handling, packaging, labeling, and scheduling disposal with the hazardous waste vendor; and scrapping and disposal of all other materials. The department will pay separately for the work under which the lamps, ballasts, LED or switches are removed from service.

47. Utility Line Opening (ULO), Item SPV.0060.01.

A Description

This special provision describes excavating to uncover utilities/infrastructure for the purpose of determining location and elevation and potential conflicts with proposed work as directed by the engineer. The location of existing utilities and infrastructure needed to complete the contract work shall be addressed independent of this provision. This item does not remove the contractor's obligation to locate utilities as specified by Wisconsin Administrative code Trans 220.

B (Vacant)

C Construction

Comply with s.182.0175 (2), Stats., with respect to precautions to be taken to avoid and prevent damage to utility facilities.

All ULO shall be directed by the engineer in writing. Notify the engineer and infrastructure/utility owner or their agents 3 working days in advance so that they may be present when excavation work commences.

Provide documentation to the engineer including coordinates/elevations or referenced to alignment/offset. Document the size and/or diameter, composition, and a description of each infrastructure/utility. Supply digital photographs of the uncovered infrastructure to the engineer in .jpeg format for future reference.

Backfill the excavation with suitable backfill, thoroughly compact, replace pavement over utility line opening trenches which are within the staged traffic area as directed by the engineer. Replace pavement and open to traffic within 24 hours of the excavation.

2140-14-70 55 of 85

D Measurement

The department will measure ULO by each individual unit, acceptably completed. Where utilities are within 6 feet of each other at a potential conflict location, only one utility line opening will be called for. In these cases, a single utility line opening will be considered full payment to locate multiple utilities. ULO include a trench up to 10 feet long as measured at the trench bottom, and of any depth required to locate the intended utility.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0060.01Utility Line Opening (ULO)EACH

Payment is full compensation for the excavation required to expose the utility line; measuring lateral and depth measurements of the utility line; providing required documentation of measurements to the engineer; backfilling with engineer approved material; compacting the backfill material; restoring the site; cleanup, and maintenance of ULO location during construction.

Existing pavement, concrete curb and gutter, and sidewalk removals necessary to facilitate utility line openings are not considered part of or paid for under ULO but are considered separate and measured and paid for separately as removal items. Granular backfill, pavement replacement material, concrete curb, gutter, and sidewalk items will also be considered separate from ULO and will be measured and paid for separately.

48. Tuck Point Storm Sewer Structure, Item SPV.0060.02.

A Description

This special provision describes repairing and tuck pointing storm sewer inlets.

B Materials

Furnish mortar materials according to standard spec 611.2.

C Construction

Inspect the structure for loose or failing mortar, remove loose or failing mortar, and clean the area prior to repairing. Fill large voids with sound pieces from bricks or blocks. Apply a plaster coat of mortar to the area of repair and make this plaster coat not less than ½-inch thick. Before applying a plaster coat, wet the surface with water and let the surface dry enough to prevent slipping.

Place mortar between storm sewer pipe and box culvert wall. Mortar shall be placed along the full circumference around the pipe, between all blocks and in all cracks as directed by the engineer.

D Measurement

The department will measure Tuck Point Storm Sewer Structure by each individual manhole or inlet, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0060.02Tuck Point Storm Sewer StructureEACH

Payment is full compensation for providing all materials and for furnishing all labor, equipment, tools, and incidentals necessary to complete the work.

49. Strapping C-40-53, Item SPV.0060.03.

A Description

This special provision describes securing a wing wall to a culvert or abutment body with a structural channel.

2140-14-70 56 of 85

B Materials

Use galvanized structural channel conforming to the size and material shown on the plans, and conforming to standard spec 506.

C Construction

Attach the structural channel with the number, size and spacing of anchors shown on the plans.

D Measurement

The department will measure Strapping C-40-53, as each wing for the repair work acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0060.03Strapping C-40-53EACH

Payment for Strapping C-40-53 is full compensation for furnishing and installing the channel.

50. Install Type 9 Pole, Item SPV.0060.04;

Install Type 9 Special Pole, Item SPV.0060.05

Install Type 10 Pole, Item SPV.0060.06;

Install Type 10 Special Pole, Item SPV.0060.07;

Install Monotube Arms 15-FT, Item SPV.0060.08;

Install Monotube Arms 20-FT, Item SPV.0060.09;

Install Monotube Arms 25-FT, Item SPV.0060.10;

Install Monotube Arms 30-FT, Item SPV.0060.11;

Install Monotube Arms 35-FT Special, Item SPV.0060.12;

Install Monotube Arms 40-FT Special, Item SPV.0060.13;

Install Monotube Arms 45-FT Special, Item SPV.0060.14;

Install Luminaire Arms Steel 15-FT, Item SPV.0060.15.

A Description

This special provision describes installing department furnished monotube poles, monotube arms, and luminaire arms as shown on the plans and as directed by the Engineer.

B Materials

Conform to the pertinent requirements of section 657.2 of the standard specifications and as shown on the plans.

C Construction

Conform to the pertinent requirements of section 657.3 of standard specifications and as shown on the plans.

D Measurement

Installing department furnished monotube poles, monotube arms, and luminaire arms shall be measured as each individual pole or arm installed and acceptably completed.

2140-14-70 57 of 85

E Payment

Installing department furnished monotube poles, monotube arms, and luminaire arms shall be paid for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0060.04	Install Type 9 Pole	EACH
SPV.0060.05	Install Type 9 Special Pole	EACH
SPV.0060.06	Install Type 10 Pole	EACH
SPV.0060.07	Install Type 10 Special Pole	EACH
SPV.0060.08	Install Monotube Arms 15-FT	EACH
SPV.0060.09	Install Monotube Arms 20-FT	EACH
SPV.0060.10	Install Monotube Arms 25-FT	EACH
SPV.0060.11	Install Monotube Arms 30-FT	EACH
SPV.0060.12	Install Monotube Arms 35-FT Special	EACH
SPV.0060.13	Install Monotube Arms 40-FT Special	EACH
SPV.0060.14	Install Monotube Arms 45-FT Special	EACH
SPV.0060.15	Install Luminaire Arms Steel 15-FT	EACH

Payment is full compensation for installing all materials, including all associated hardware, fittings, mounting devices, and attachments necessary to completely install the pole and arms.

51. Transport and Install State Furnished Traffic Signal Cabinet Florist Ave, Item SPV.0060.16;

Transport and Install State Furnished Traffic Signal Cabinet Mill Rd, Item SPV.0060.17; Transport and Install State Furnished Traffic Signal Cabinet Acacia St, Item SPV.0060.18; Transport and Install State Furnished Traffic Signal Cabinet Green Tree Rd, Item SPV.0060.19:

Transport and Install State Furnished Traffic Signal Cabinet Good Hope Rd, Item SPV.0060.20;

Transport and Install State Furnished Traffic Signal Cabinet Calumet Rd, Item SPV.0060.21:

Transport and Install State Furnished Traffic Signal Cabinet Bradley Rd, Item SPV.0060.22;

Transport and Install State Furnished Traffic Signal Cabinet Tower Ave, Item SPV.0060.23;

Transport and Install State Furnished Traffic Signal Cabinet Servite/Dean Rd, Item SPV.0060.24;

Transport and Install State Furnished Traffic Signal Cabinet Northridge Dr, Item SPV.0060.25;

Transport and Install State Furnished Traffic Signal Cabinet Northridge Lakes Blvd, Item SPV.0060.26.

A Description

This special provision describes the transporting and installing the state furnished traffic signal cabinet, signal controller, and other cabinet equipment for traffic signals, and for making the cabinet fully operational as shown in the plans.

B Materials

Use materials furnished by the department including: the traffic signal controller and the traffic signal cabinet.

Pick up the state furnished materials at the department's Electrical Shop located at 935 South 60th Street, West Allis. Notify the department's Electrical Field Unit at (414) 266-1170 and make arrangements for picking up the state furnished materials five (5) working days prior to picking up the materials.

2140-14-70 58 of 85

Provide all other needed materials in conformance with sections 651.2, 652.2, 653.2, 654.2, 655.2, 656.2, 657.2, 658.2 and 659.2 of the standard specifications.

C Construction

Perform work in accordance with sections 651.3, 652.3, 653.3, 654.3, 655.3, 656.3, 657.3, 658.3 and 659.3 of the standard specifications except as specified below.

Reinstall and reconnect the previously disconnected fiber optic gator patch cables into the new traffic signal cabinet.

Install the state furnished traffic signal cabinet on the concrete control cabinet base the same day it is delivered to the site location.

Request a signal inspection of the completed signal installation to the project engineer at least five (5) working days prior to the time of the requested inspection. The department's Region Electrical personnel will perform the inspection.

D Measurement

Transporting and Installing State Furnished Traffic Signal Cabinet will be measured as a single unit of work, acceptably completed.

E Payment

Transporting and Installing State Furnished Traffic Signal Cabinet will be paid for the measured quantity at the contract unit price under the following bid items:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0060.16	Transport and Install State Furnished Traffic Signal Cabinet Florist Ave	EACH
SPV.0060.17	Transport and Install State Furnished Traffic Signal Cabinet Mill Rd	EACH
SPV.0060.18	Transport and Install State Furnished Traffic Signal Cabinet Acacia St	EACH
SPV.0060.19	Transport and Install State Furnished Traffic Signal Cabinet Green Tree Rd	EACH
SPV.0060.20	Transport and Install State Furnished Traffic Signal Cabinet Good Hope Rd	EACH
SPV.0060.21	Transport and Install State Furnished Traffic Signal Cabinet Calumet Rd	EACH
SPV.0060.22	Transport and Install State Furnished Traffic Signal Cabinet Bradley Rd	EACH
SPV.0060.23	Transport and Install State Furnished Traffic Signal Cabinet Tower Ave	EACH
SPV.0060.24	Transport and Install State Furnished Traffic Signal Cabinet Servite/Dean Rd	EACH
SPV.0060.25	Transport and Install State Furnished Traffic Signal Cabinet Northridge Dr	EACH
SPV.0060.26	Transport and Install State Furnished Traffic Signal Cabinet Northridge Lakes Blvd	EACH

Payment is full compensation for installing and testing the Traffic Signal Cabinet and cabinet equipment; for furnishing and installing all other items necessary (such as, wire nuts, splice kits and/or connectors, tape, insulating varnish, ground lug fasteners, etc.) to make the proposed system complete from the source of supply to the most remote unit; and for clean-up and waste disposal.

2140-14-70 59 of 85

Transport Traffic Signal and Lighting Materials Florist Ave, Item SPV.0060.27;
Transport Traffic Signal and Lighting Materials Mill Rd, Item SPV.0060.28;
Transport Traffic Signal and Lighting Materials Acacia St, Item SPV.0060.29;
Transport Traffic Signal and Lighting Materials Green Tree Rd, Item SPV.0060.30;
Transport Traffic Signal and Lighting Materials Good Hope Rd, Item SPV.0060.31;
Transport Traffic Signal and Lighting Materials Calumet Rd, Item SPV.0060.32;
Transport Traffic Signal and Lighting Materials Bradley Rd, Item SPV.0060.33;
Transport Traffic Signal and Lighting Materials Tower Ave, Item SPV.0060.34;
Transport Traffic Signal and Lighting Materials Northridge Dr, Item SPV.0060.36;
Transport Traffic Signal and Lighting Materials Northridge Lakes Blvd, Item SPV.0060.37.

A Description

This special provision describes the transporting of department furnished materials for traffic signals and intersection lighting.

B Materials

Transport materials furnished by the department including: Monotube arms/poles and luminaire arms (to be installed on monotube assemblies).

Pick up the department furnished materials at the department's Electrical Shop located at 935 South 60th Street, West Allis. Notify the department's Electrical Field Unit at (414) 266-1170 and make arrangements for picking up the department furnished materials five (5) working days prior to picking the materials up.

Provide all other needed materials in conformance with sections 651.2, 652.2, 653.2, 654.2, 655.2, 656.2, 657.2, 658.2 and 659.2 of the standard specifications.

C Construction

Perform work in accordance with sections 651.3, 652.3, 653.3, 654.3, 655.3, 656.3, 657.3, 658.3 and 659.3 of the standard specifications except as specified below.

D Measurement

Transporting Traffic Signal and Intersection Lighting Materials [Location] will be measured as each unit acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid items:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0060.27	Transport Traffic Signal and Lighting Materials Florist Ave	EACH
SPV.0060.28	Transport Traffic Signal and Lighting Materials Mill Rd	EACH
SPV.0060.29	Transport Traffic Signal and Lighting Materials Acacia St	EACH
SPV.0060.30	Transport Traffic Signal and Lighting Materials Green Tree Rd	EACH
SPV.0060.31	Transport Traffic Signal and Lighting Materials Good Hope Rd	EACH
SPV.0060.32	Transport Traffic Signal and Lighting Materials Calumet Rd	EACH
SPV.0060.33	Transport Traffic Signal and Lighting Materials Bradley Rd	EACH
SPV.0060.34	Transport Traffic Signal and Lighting Materials Tower Ave	EACH
SPV.0060.35	Transport Traffic Signal and Lighting Materials Servite/Dean Rd	EACH
SPV.0060.36	Transport Traffic Signal and Lighting Materials Northridge Dr	EACH
SPV.0060.37	Transport Traffic Signal and Lighting Materials Northridge Lakes Blvd	EACH

Payment is full compensation for transporting the monotube poles/arms and luminaire arms (to be installed on monotubes). Installation of these materials is included under a separate pay item.

2140-14-70 60 of 85

53. Modify Traffic Signal STH 181 & STH 100, Item SPV.0060.38.

A Description

This special provision describes modifying the existing traffic signals at the intersection of STH 181 & STH 100, conforming to the standard specifications and as follows. This bid item includes all labor and materials not itemized elsewhere.

B (Vacant)

C Construction

Existing equipment that is to be retained in operation shall be protected from damage.

Modify the traffic signal installation to accommodate the new signal heads and operational configuration.

D Measurement

Modify Traffic Signals will be measured as a single unit of work for each intersection acceptably completed.

E Payment

Modify Traffic Signals will be paid for the measured quantity at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.0060.38 Modify Traffic Signal STH 181 & STH 100 EACH

Payment is full compensation for furnishing and installing all items not itemized elsewhere to make a complete and functioning traffic signal complying with the intent of the plans.

54. Inlet Covers Type H-D, Item SPV.0060.39

A Description

This special provision describes furnishing and installing inlet covers according to the plan details, the pertinent requirements of standard spec 611 and as provided in this special provision.

B Materials

Provide an Inlet Cover Type H frame and grate with the curb box removed and replaced with a solid flat curb plate designed for heavy traffic loading as shown in the plan details. Neenah R-3290-A or approved equal.

C Construction

Construct according to standard spec 611.3.

D Measurement

The department will measure Inlet Covers Type H-D as each individual unit, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0060.39Inlet Covers Type H-DEach

Payment is full compensation for providing covers, including frames, grates, curb plates, and all other required materials and for installing and adjusting each cover.

55. Cleaning Storm Sewer, Item SPV.0060.40

A Description

This special provision describes providing cleaning storm sewer pipes and the drainage structures where shown on the plans and as directed by the engineer.

B (Vacant)

2140-14-70 61 of 85

C Construction

Remove drainage structure cover, completely remove all solids removed from the sewer system and haul them off the project for disposal as specified in standard spec 205.3.12. Silts resulting from any flushing or jetting operation must be prevented from escaping into sewers or waterways. Inspect the drainage structure for repair work and reinstall cover.

D Measurement

The department will measure Cleaning Storm Sewer by each individual unit of acceptably completed work, measured structure to structure.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.0060.40 Cleaning Storm Sewer Each

Payment is full compensation for furnishing all materials to clean out drainage pipes and connected structures including silt and solid retention; for removing and properly disposing materials; paying all associated fees for permits, licenses or disposal of materials. Storm sewer structure covers damaged by the contractor's operations shall be replaced by the contractor, with no expense to the department.

56. Adjusting Water Valve Boxes, Item SPV.0060.41; Adjusting Water Manholes, Item SPV.0060.42.

A Description

This special provision describes adjusting, protecting, and maintaining accessibility, for the duration of the paving project, to all City of Milwaukee water service boxes, water valve boxes, and water manhole frames & lids located within the project limits.

B Materials

All material for the adjustment of these facilities shall meet City of Milwaukee specifications and will be provided by the City of Milwaukee by contacting Kevin Zagrodnik, Milwaukee Water Works, at (414)708-7033 (or Syreeta Woodley, Milwaukee Water Works at (414)286-6302). Milwaukee Water Works Distribution General Contact Number is (414) 286-3710.

If there is contractor damage, the materials must still be provided by the City of Milwaukee, however, in this case, the Contractor will be charged for all materials. Materials furnished by the City of Milwaukee and not used on the project shall be delivered back to DPW Field Headquarters – Infrastructure, Operations, Water Works at 3850 N. 35th St.

C Construction

The Contractor, or authorized project representative, shall contact Milwaukee Water Works prior to the start of construction. The City will locate, mark, inspect and repair all water service boxes, water valve boxes, and water manhole frames & lids within the limits of the project prior to commencement of work on the project.

All water service boxes, water valve boxes, and water manhole frames & lids within the project limits shall be adjusted to proposed elevations by the Contractor using materials meeting city specifications.

Throughout the duration of the project, the Contractor must ensure that all water service boxes, water valve boxes, and water manholes are adequately located and identified by blue paint, and that at all times, all water appurtenances remain accessible for operation by city forces. Exercise caution working adjacent to water facilities to avoid damage and ensure accessibility.

Upon completion of the contract, the City will inspect all water facilities to ensure the water boxes and manholes are clean, properly aligned, and accessible. The Contractor shall be responsible to make identified repairs and adjustments, and if any repairs or adjustments are made by the City, the cost will be charged to the Contractor.

D Measurement

The department will measure Adjusting Water Boxes and Adjusting Water Manholes as each individual unit of acceptably completed.

2140-14-70 62 of 85

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER	DESCRIPTION	UNIT
SPV.0060.41	Adjusting Water Valve Boxes	Each
SPV.0060.42	Adjusting Water Manholes	Each

Payment is full compensation for all excavation, backfilling, disposal of surplus materials, water box or water manhole adjustments, water box or water manhole clean-out, and restoration of the work site; and for furnishing all labor, tools, equipment, and incidentals necessary to complete the work.

57. Adjusting Sanitary Manholes, Item SPV.0060.43.

A Description

This work includes adjusting sanitary manholes to an elevation as determined by the engineer as well as installing frame and cover, internal frame/chimney seal, according to the Standard Specifications for Sewer and Water Construction in Wisconsin, latest edition and amendments (SSSW).

Add or remove masonry adjusting rings as needed. This item applies to structures to be lowered less than 6 inches or raised less than 12 inches.

B Materials

B.1 Adjusting Rings

Adjustment rings shall be concrete with steel reinforcement in conformance with ASTM C-478. Precast concrete rings shall have an inside diameter to match the manhole opening, be not less than 2 inches nor more than 6 inches high and have a wall thickness of 6 inches unless otherwise specified. The rings shall contain a minimum of one No. 2 reinforcing rod centered within the ring. Do not use any cracked or broken rings. The top of precast manhole cones shall be set a maximum of 18 inches lower than established grade in unimproved areas, with the top of the manhole cover being ringed up flush with the existing ground. The minimum number of adjusting rings shall be one 2-inch ring. The maximum height of adjusting rings shall be 8 inches in paved areas. All joints between the adjusting rings shall be filled with grout or mortar, including between the cone and the adjusting ring and the adjusting ring and the frame. Rings shall be grooved to receive a step.

B.2 Manhole Seal

Furnish new Cretex, NPC Flexrib, or approved equal internal frame/chimney Seal, as shown in the plans. The seal shall meet the material requirements of section 8.42.3 and the performance requirements of section 8.42.4 of the SSSW.

C Construction

C.1 General

The location of existing sanitary manholes to be adjusted is indicated on the plans. Adjust these items as shown in the plans. Reconstruct manholes as necessary so that the frames and cover when placed will be at the established required grade; remove the existing frame and cover. Any temporary adjustment (wood) shims shall be removed and backfilled with grout or mortar prior to installing the seal. Install seals according to the manufacturer's recommended installation procedures. Furnish and use Backfill Slurry in the manhole excavation area to existing surface or to appropriate depth for pavement restoration. Salvage the existing frame and cover.

C.2 Surface Preparation

Remove manhole cover and power wire brush the lower 3 inches of the manhole frame to remove any loose rust or scale and repair any imperfections by either grinding smooth or filling with mortar. A smooth, clean sealing surface is required. Realign the casting if it is offset more than approximately 2 inches from the chimney. Remove all loose and protruding mortar and brick from the upper 7-Inch chimney and clean surface by power wire brushing. Provide a 4-Inch wide sealing surface starting 2 inches down from the bottom of the frame.

All sealing surfaces must be circular, reasonably smooth, clean and free of any loose material or excessive voids. If such a surface does not exist for the bottom of the sleeve to seal against, use onecomponent, quick-set, high strength, non-shrink, polymer modified patching mortar which has been

2140-14-70 63 of 85

formulated for vertical or overhead use. If the bottom of the sleeve is to seal against the top of an eccentric (straight side) cone and an inadequately high vertical surface does not exist, contact the manufacturer to obtain details to build the required vertical surface.

Use caulk to fill minor irregularities in the bottom sealing surface. The caulk shall be a butyl rubber caulk conforming to AASHTO M 198, Type B. Apply a single bead of the caulk to the center portion of the lower sealing surface of the sleeve.

Any flaws in the manhole frame, such as minor cracks, pits or protrusions, shall be repaired by either filling with mortar or grinding smooth.

D Measurement

The department will measure Adjusting Sanitary Manholes as a unit per each adjustment, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0060.43Adjusting Sanitary ManholesEach

Payment is full compensation for furnishing and installing all materials including adjusting rings, masonry, and internal frame/chimney seals; for salvaging, storing, and reinstalling the existing frame and cover; for excavating, backfilling, and compacting; for disposing of surplus materials; and for cleaning out and restoring the structure.

58. Internal Manhole Seals, Item SPV.0060.44.

A Description

The work under this item consists of furnishing and installing internal manhole chimney seals for each sanitary manhole identified on the plans.

B Material

The contractor shall furnish and install frame-to-chimney seals on all sanitary manholes within the limits of this contract. The seals shall be as specified in the *Standard Specification for Sewer and Water Construction in Wisconsin (Sixth Edition with addendum) Chapter 8.42.0.*

C Construction

The inside diameter of the manhole frame and the manhole chimney shall be field measured, and a determination as to whether the inside face of the frame is vertical or tapered shall be made in order to obtain the proper size and shape rubber seal.

Internal rubber chimney seals shall be installed no sooner than 24 hours following chimney back plastering.

The surfaces against which the sleeve is to be compressed shall be circular, clean, reasonably smooth and free of any loose materials and excessive voids. Any flaws in these surfaces shall be repaired with the approved low-shrink mortar or ground smooth. A bead of butyl rubber caulk conforming to AASHTO M-198 Type B shall be applied to the lower sealing surface of sleeve.

The seal shall be installed according to the manufacturer's instructions. (Refer to the plan data for configuration of chimney seal.)

D Measurement

The item Install Sanitary Manhole Seals, furnished and installed at the locations indicated on the plans, will be measured and paid for as units in place and accepted according to the contract.

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.0060.44 Internal Manhole Seals Each

2140-14-70 64 of 85

Internal Sanitary Manhole Seals, measured as provided above, will be paid for at the contract unit price each, for the furnishing and installing internal rubber chimney seals and for all labor, tools, equipment and incidentals necessary to complete the work for each sanitary manhole.

59. Manhole Covers Type MS-58A, Item SPV.0060.45.

A Description

Perform work under these items in accordance with the requirements of Section 611 of the Standard Specifications and the details as shown on the plans.

B Material

Furnish materials under these items in accordance with the requirements of Section 611 of the Standard Specifications and the details as shown on the plans.

C Vacant

D Measurement

The department will measure Manhole Cover Type MS 58-A by the unit in place, furnished, installed, and acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0060.45Manhole Cover Type MS 58-AEach

Payment is full compensation for removing and salvaging the existing covers; providing new covers, including frames, lids, and for furnishing all labor, equipment, tools, and incidentals necessary for installing and adjusting each cover. Old covers removed shall be disposed of by the contractor.

60. Adjusting CUC Manhole Cover, Item SPV.0060.46.

A Description

This special provision describes adjusting the existing chimney of the block, precast, or brick round manholes; furnishing, installing and removing protection of the cables in the manhole during adjustment operations. Perform work in accordance with the standard specifications, the provisions of the article Adjusting Manhole Covers, as shown on the plans, and as hereinafter specified.

B Materials

Furnish and install materials that conform to the requirements of section 519 of the standard specifications. Salvage and reinstall existing covers on the manholes. The City will supply covers designated for replacement. Contractor shall contact Karen Rogney at (414) 286-3242 to obtain the "Castings Requisitions Form" required to obtain the covers. Contractor shall contact Ricardo Lopez, Inventory Clerk at (414) 286-6123 prior to obtaining the frames and lids from the DPW Field Headquarters at 3850 N. 35th St. Contractor must have the "Castings Requisitions Form" in hand in order to obtain the castings.

C Construction

Report any pre-existing problems to Mr. Curt Campagna, CUC Manhole Maintenance Manager at (414) 286-5967 three (3) working days in advance of any construction on manholes.

Before removing the pavement around the manhole, the contractor shall place a ¾-inch plywood cover or equal over existing active Street Lighting, Traffic Control, Communications or private vendor electrical cables. This cover shall be properly supported to/at the manhole floor.

Break out and remove pavement around manhole. Remove existing covers and store and secure them properly. Any damaged, lost, or stolen covers shall be the responsibility of the contractor and shall be replaced at contractor's expense.

Remove existing chimney to surface of concrete roof slab. If manhole does not have an existing concrete roof slab, remove sufficient chimney as to provide adequate corbel to fit new cast iron frame and cover.

2140-14-70 65 of 85

Adjust manhole cover to proposed grade using bricks or concrete rings as necessary. Completely underpin entire flange area of manhole frame with mortar, bricks and/or concrete rings. Remove wedges/shims. Fill voids with grout. Do not back plaster inside walls.

After completion of paving, remove the temporary ¾-inch plywood cover or equal which is over the existing electrical cables in the manhole as mentioned above.

Notify Mr. Campagna three (3) working days in advance of completion of each manhole adjustment, for inspection and acceptance of work performed. The contractor will receive no payment until the above work is approved by City Underground Conduits.

D Measurement

The department will measure Adjusting CUC Manhole Cover by the Each acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.0060.46 Adjusting CUC Manhole Cover EACH

Payment is full compensation for furnishing all required materials, exclusive of frames, grates, or lids available and designated for adjusting; for removing, reinstalling and adjusting the covers; and for furnishing all labor, tools, equipment and incidentals necessary for adjusting each cover, complete in accordance with the requirements of the plans and contract. Covers to be adjusted and which are rendered unfit for use by the contractor through the contractor's operations will be replaced by the contractor in kind at the contractor's own cost and expense.

61. 4' Diameter "Doghouse" Manhole Type CUC, Item SPV.0060.47.

A Description

The work under this item consists of a 4'-0" diameter precast concrete "doghouse" manhole for the City of Milwaukee Underground Conduit Section at locations shown in the plans, in accordance with sections 301, 611 and 501 of the standard specifications, and as hereinafter provided. This work includes providing and placing PVC pipe and associated fittings, cement encasement, and other appurtenances to extend existing conduit as required to provide a complete and fully functional communications manhole unit.

B Materials

B.1 Manhole

Furnish and install a 4' diameter precast concrete "doghouse" manhole. Concrete and steel reinforcement shall conform to ASTM specification: C478 (latest edition), except that the single cage of circumferential reinforcement in all vertical walls shall consist of lines of #6 steel wire spaced 3" horizontally and lines of #10 steel wire spaced 8" vertically both located in the center of the wall, and #6 hoop rebar centered in the wall 3" above the window knock-outs.

Two lifting inserts for 1-1/2" diameter lifting eyes shall be cast in the wall of the base and all other riser sections except the top cap section.

Up to four 7/8" diameter galvanized steel 1-11/16" pulling-in eyes shall be cast in the wall of the base section directly across from each duct entrance.

Four 5/8" diameter plastic threaded cable rack bolt inserts shall be cast in the wall of the riser section.

A continuous circumferential Butyl Rubber gasket shall be supplied, to be laid on the wall joint of the base and riser section when manhole is being assembled at job site.

The number of pulling-in eyes and/or cable rack bolt inserts may vary. Additionally, the size, location, shape and number of duct entrances and/or knock-out area may vary. Unit price of manhole shall not vary for number of openings, pulling-in eyes and/or rack bolt inserts.

Field verify window depth and locations prior to ordering manhole.

The City will supply a frame and lid for the manhole. Contractor shall contact Mr. Ricardo Lopez, Inventory Clerk at (414) 286-6123 prior to obtaining the frame and lid from the DPW Headquarters at 3850 N. 35th St. Contractor must have the "Casting Requisition Form" which shall be supplied by the City.

2140-14-70 66 of 85

B.2 Conduit

Furnish and install DB_60 polyvinyl chloride (PVC) conduit. Conduit will be accepted on the basis of a Manufacturer's Certificate of Compliance and WISDOT field inspection upon delivery to a project.

Manufacturers of PVC Conduit DB-60 shall request evaluation and approval of their products by filing with the Department's Research Supervisor, Bureau of Highway Construction, a certificate setting forth the name or brand of pipe to be furnished, the specified type, category, grade and PVC plastic cell classifications. The certificate shall have attached a certified test report from an approved independent testing laboratory showing specific results of tests performed on each diameter conduit to be furnished conforming to all requirements of these specifications. The conduit tested shall be randomly selected for test by the independent testing laboratory as being representative of that manufacturer's conduit. The manufacturer of the conduit shall also submit with the certification, a guarantee that all conduit furnished be of the same quality and composition and conform to the specification requirements as tested by the independent laboratory, as long as the manufacturer continues to furnish materials for WISDOT projects.

PVC conduit and fittings shall conform to the requirements of Standard Specifications for Smooth-Wall Poly (Vinyl Chloride) (PVC) Conduit and Fittings for Underground Installation, ASTM Designation: F512 (latest edition).

B.3 Concrete

The type of concrete mix to be used to encase the ducts will be:

Type IL Cement	280 lbs
Fly Ash	100 lbs
Sharp Torpedo Sand	3100 lbs
Water	35 gals
Chryso Air 260 or approved equal	2.0 ozs
Chryso Plast 209 or approved equal	7.0 ozs
Air	5%

Mix the materials to provide an approximate 3 inch slump

B.4 Slurry Backfill

Aggregate slurry backfill consists of No. 1 concrete aggregate Class 'C' concrete mix with the cement deleted.

Fly Ash (Class C) 75 lbs.

Concrete Sand (Damp) 1830 lbs. No. 1 Concrete Aggregate 1830 lbs.

Mix with water to inundate the aggregate sufficiently to provide an approximate 3 inch slump. Deposit the mix directly from a concrete transit mix truck.

For any questions on materials, contact Ms. Karen Rogney at (414) 286-3243.

C Construction

C.1 Conduit Alterations

Excavate to expose existing conduit. Break back by hand sections of cement encased conduit to facilitate excavation for the new proposed structure. Hand chip concrete away for the existing pipes. Carefully remove pipes from around the cables. Hand chip enough concrete away from the pipes to allow for the coupling of split ducts on to the ends of the pipes. Protect exposed pipe ends and existing cables from damage.

C.2 Manhole

Manhole Type CUC "Doghouse" shall be installed in accordance with subsection 611.3. The bottom section of the manhole shall be installed while avoiding damage to the live active cables. The excavation may need to be widened to slide the bottom under the existing cables. After the bottom section of the manhole has been set, the existing cables need to be placed within the window openings, splice cases and/or coils placed back into the manhole.

2140-14-70 67 of 85

Exercise extreme care in the handling of working cables within the excavation. When cables need to be moved, particularly lead sheathed cables, move cables slowly and gradually. Avoid sharp kinks that may damage the inner core of the cables and the sheath.

Complete the "doghouse" manhole installation without any damage or service disruption to the existing cables.

Install 4' Diameter "Doghouse" Manholes Type CUC in accordance with subsection 611.3.

Install the top of the roof deck at a standard depth of 18" below finished grade where possible. A minimum depth of 12" from finished grade to the top of the roof deck must be maintained.

Install manhole cover to proposed grade using concrete rings and/or bricks. Completely underpin entire flange area of manhole frame with mortar, bricks and/or concrete rings. Remove wedges/shims. Fill voids with grout. Do not back plaster inside walls.

C.3 Placing Duct

All ducts shall be inspected before placing to see that the bores are clean and free from mud, sand, etc. Only ducts with a smooth bore, free from burrs, rough projections etc. shall be used. Where burrs or other rough areas likely to damage cable are found in the duct, they shall be smoothed off by rasping or scraping.

All existing ducts shall be extended into the new manhole structure unless otherwise noted on the plan. Split PVC duct should be used on ducts containing cables. The split duct shall be installed per manufactures recommendations using tape and reinforced with plastic straps to produce a rigid, stable unit.

All ducts shall terminate on the inside wall of the manhole. A standard end bell fitting shall be installed on all duct access points into the manhole.

Where trace wires are present, reconnect and extend trace with #10 copper wire extended two feet past the inside wall of the manhole.

C.4 Concreting

Begin concreting after conduit has been laid and the trench and duct have been inspected. The minimum concrete encasement of the ducts is three (3) inches on the top, two (2) inches on the sides, and three (3) inches on the bottom. After placing, the concrete shall be puddled with a splicing bar or similar tool so that complete duct encasement is accomplished. Wood braces used to keep the conduit from floating shall be removed before the concrete sets completely and the resultant encasement voids filled with concrete.

Allow the concrete encasement to set for a minimum of 6 hours before backfilling is commenced.

C.5 Slurry Backfill

Commence backfilling immediately after the duct has been inspected, approved and has set to withstand the load.

An aggregate slurry as specified shall be used to backfill all concrete encased conduit. The trench shall be slurry backfilled to the proposed or existing subgrade. The mix shall be deposited in the trench directly from a concrete transit mix truck.

D Measurement

The department will measure 4' Diameter "Doghouse" Manholes Type CUC Installed over Conduit by each individual manhole acceptably completed.

Notify Mr. Ryan Gardiner at (414) 708-6948 or rgardn@milwaukee.gov a minimum of 3 business days for inspection and acceptance of the conduit prior to concrete encasement, and inspection and acceptance of the manhole structure prior to slurry backfill. The contractor will receive no payment until the above work is approved by City Underground Conduit.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

 ITEM NUMBER
 DESCRIPTION
 UNIT

 SPV.0060.47
 4' Diameter "Doghouse" Manhole Type CUC
 EACH

Payment is full compensation for all excavation work and disposal of material; for adjusting manhole frame to final grade, for furnishing and installing all materials, including precast manhole, conduit, conduit

2140-14-70 68 of 85

fittings, end bells, bricks, and coarse aggregate, bedding, concrete forms, concrete placement, appurtenances, and backfilling.

62. 5' Diameter "Doghouse" Manhole Type CUC, Item SPV.0060.48.

A Description

The work under this item consists of a 5'-0" diameter precast concrete "doghouse" manhole for the City of Milwaukee Underground Conduit Section at locations shown in the plans, in accordance with sections 301, 611 and 501 of the standard specifications, and as hereinafter provided. This work includes providing and placing PVC pipe and associated fittings, cement encasement, and other appurtenances to extend existing conduit as required to provide a complete and fully functional communications manhole unit.

B Materials

B.1 Manhole

Furnish and install a 5' diameter precast concrete "doghouse" manhole. Concrete and steel reinforcement shall conform to ASTM specification: C478 (latest edition), except that the single cage of circumferential reinforcement in all vertical walls shall consist of lines of #6 steel wire spaced 3" horizontally and lines of #10 steel wire spaced 8" vertically both located in the center of the wall, and #6 hoop rebar centered in the wall 3" above the window knock-outs.

Two lifting inserts for 1-1/2" diameter lifting eyes shall be cast in the wall of the base and all other riser sections except the top cap section.

Up to four 7/8" diameter galvanized steel 1-11/16" pulling-in eyes shall be cast in the wall of the base section directly across from each duct entrance.

Four 5/8" diameter plastic threaded cable rack bolt inserts shall be cast in the wall of the riser section.

A continuous circumferential Butyl Rubber gasket shall be supplied, to be laid on the wall joint of the base and riser section when manhole is being assembled at job site.

The number of pulling-in eyes and/or cable rack bolt inserts may vary. Additionally, the size, location, shape and number of duct entrances and/or knock-out area may vary. Unit price of manhole shall not vary for number of openings, pulling-in eyes and/or rack bolt inserts.

Field verify window depth and locations prior to ordering manhole.

The City will supply a frame and lid for the manhole. Contractor shall contact Mr. Ricardo Lopez, Inventory Clerk at (414) 286-6123 prior to obtaining the frame and lid from the DPW Headquarters at 3850 N. 35th St. Contractor must have the "Casting Requisition Form" which shall be supplied by the City.

B.2 Conduit

Furnish and install DB_60 polyvinyl chloride (PVC) conduit. Conduit will be accepted on the basis of a Manufacturer's Certificate of Compliance and WISDOT field inspection upon delivery to a project.

Manufacturers of PVC Conduit DB-60 shall request evaluation and approval of their products by filing with the Department's Research Supervisor, Bureau of Highway Construction, a certificate setting forth the name or brand of pipe to be furnished, the specified type, category, grade and PVC plastic cell classifications. The certificate shall have attached a certified test report from an approved independent testing laboratory showing specific results of tests performed on each diameter conduit to be furnished conforming to all requirements of these specifications. The conduit tested shall be randomly selected for test by the independent testing laboratory as being representative of that manufacturer's conduit. The manufacturer of the conduit shall also submit with the certification, a guarantee that all conduit furnished be of the same quality and composition and conform to the specification requirements as tested by the independent laboratory, as long as the manufacturer continues to furnish materials for WISDOT projects.

PVC conduit and fittings shall conform to the requirements of Standard Specifications for Smooth-Wall Poly (Vinyl Chloride) (PVC) Conduit and Fittings for Underground Installation, ASTM Designation: F512 (latest edition).

2140-14-70 69 of 85

B. 3 Concrete

The type of concrete mix to be used to encase the ducts will be:

Type IL Cement 280 lbs
Fly Ash 100 lbs
Sharp Torpedo Sand 3100 lbs
Water 35 gals
Chryso Air 260 or approved equal 2.0 ozs
Chryso Plast 209 or approved equal 7.0 ozs
Air 5%

Mix the materials to provide an approximate 3 inch slump

B.4 Slurry Backfill

Aggregate slurry backfill consists of No. 1 concrete aggregate Class 'C' concrete mix with the cement deleted.

Fly Ash (Class C) 75 lbs.

Concrete Sand (Damp) 1830 lbs.

No. 1 Concrete Aggregate 1830 lbs.

Mix with water to inundate the aggregate sufficiently to provide an approximate 3 inch slump. Deposit the mix directly from a concrete transit mix truck.

For any questions on materials, contact Ms. Karen Rogney at (414) 286-3243.

C Construction

C.1 Conduit Alterations

Excavate to expose existing conduit. Break back by hand sections of cement encased conduit to facilitate excavation for the new proposed structure. Hand chip concrete away for the existing pipes. Carefully remove pipes from around the cables. Hand chip enough concrete away from the pipes to allow for the coupling of split ducts on to the ends of the pipes. Protect exposed pipe ends and existing cables from damage.

C.2 Manhole

Manhole Type CUC "Doghouse" shall be installed in accordance with subsection 611.3. The bottom section of the manhole shall be installed while avoiding damage to the live active cables. The excavation may need to be widened to slide the bottom under the existing cables. After the bottom section of the manhole has been set, the existing cables need to be placed within the window openings, splice cases and/or coils placed back into the manhole.

Exercise extreme care in the handling of working cables within the excavation. When cables need to be moved, particularly lead sheathed cables, move cables slowly and gradually. Avoid sharp kinks that may damage the inner core of the cables and the sheath.

Complete the "doghouse" manhole installation without any damage or service disruption to the existing cables.

Install 5' Diameter "Doghouse" Manholes Type CUC in accordance with subsection 611.3.

Install the top of the roof deck at a standard depth of 18" below finished grade where possible. A minimum depth of 12" from finished grade to the top of the roof deck must be maintained.

Install manhole cover to proposed grade using concrete rings and/or bricks. Completely underpin entire flange area of manhole frame with mortar, bricks and/or concrete rings. Remove wedges/shims. Fill voids with grout. Do not back plaster inside walls.

C.3 Placing Duct

All ducts shall be inspected before placing to see that the bores are clean and free from mud, sand, etc. Only ducts with a smooth bore, free from burrs, rough projections etc. shall be used. Where burrs or other rough areas likely to damage cable are found in the duct, they shall be smoothed off by rasping or scraping.

2140-14-70 70 of 85

All existing ducts shall be extended into the new manhole structure unless otherwise noted on the plan. Split PVC duct should be used on ducts containing cables. The split duct shall be installed per manufactures recommendations using tape and reinforced with plastic straps to produce a rigid, stable unit.

All ducts shall terminate on the inside wall of the manhole. A standard end bell fitting shall be installed on all duct access points into the manhole.

Where trace wires are present, reconnect and extend trace with #10 copper wire extended two feet past the inside wall of the manhole.

C.4 Concreting

Begin concreting after conduit has been laid and the trench and duct have been inspected. The minimum concrete encasement of the ducts is three (3) inches on the top, two (2) inches on the sides, and three (3) inches on the bottom. After placing, the concrete shall be puddled with a splicing bar or similar tool so that complete duct encasement is accomplished. Wood braces used to keep the conduit from floating shall be removed before the concrete sets completely and the resultant encasement voids filled with concrete.

Allow the concrete encasement to set for a minimum of 6 hours before backfilling is commenced.

C.5 Slurry Backfill

Commence backfilling immediately after the duct has been inspected, approved and has set to withstand the load.

An aggregate slurry as specified shall be used to backfill all concrete encased conduit. The trench shall be slurry backfilled to the proposed or existing subgrade. The mix shall be deposited in the trench directly from a concrete transit mix truck.

D Measurement

The department will measure 5' Diameter "Doghouse" Manholes Type CUC Installed over Conduit by each individual manhole acceptably completed.

Notify Mr. Ryan Gardiner at (414) 708-6948 or rgardn@milwaukee.gov a minimum of 3 business days for inspection and acceptance of the conduit prior to concrete encasement, and inspection and acceptance of the manhole structure prior to slurry backfill. The contractor will receive no payment until the above work is approved by City Underground Conduit.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.0060.48 5' Diameter "Doghouse" Manhole Type CUC EACH

Payment is full compensation for all excavation work and disposal of material; for adjusting manhole frame to final grade, for furnishing and installing all materials, including precast manhole, conduit, conduit fittings, end bells, bricks, and coarse aggregate, bedding, concrete forms, concrete placement, appurtenances, and backfilling.

63. Removing CUC Manhole, Item SPV.0060.49.

A Description

The work under this item describes removing various manholes for the City of Milwaukee Underground Conduit Department at locations shown in the plans, in accordance to section 204. Removal means removal of the existing structure and any necessary conduit alterations required.

B (Vacant)

C Construction

C.1 General Requirements

Complete all operations necessary to remove the existing structure and that might endanger the new construction before constructing new work.

2140-14-70 71 of 85

Manholes designated for removal and subsequent reconstruction will ordinarily contain working cables which must be maintained during the course of this phase of work. Protective measures against damage must be observed when handling and working around these cables.

C.2 Frame and Cover Removal

Remove the frame and cover on all manholes designated for removal. If the castings are to be salvaged as directed in the plans, exercise caution with frames embedded in concrete so unnecessary damage to the frame does not occur during the process of breaking concrete. Remove all mortar and concrete from the frame. Store salvaged castings at location approved of by the engineer.

C.3 Protection of Cables

Extreme care must be exercised in the handling of working cables in manholes or exposed conduit package areas while removal work is going on. Cables may carry high voltage that may be life threatening.

No cable removed from its racks and spanning the manhole opening is to be permitted to sag appreciably from its own weight across such opening. Provide temporary supports for all cables.

When cables need to be moved, particularly lead sheathed cables, move cables slowly and bend gradually. Avoid sharp kinks that may damage inner core of cables and the sheath.

Cables must be left as stationary as is practicable after the cables have been temporarily located. Exercise care if further shifting is required while construction work progresses and if needed, re-support.

Guard against damage to the exposed cables by falling objects such as tools, equipment and debris. Avoid stepping on cables. Do not use cables to support any objects during the course of the construction work.

Promptly notify Mr. Tremel Rembert at (414) 286-5970 (work) of any visible cable defects discovered at the time the cable is exposed. Report any signs of abrasion, sheath rupture, kinking in the cable or evidence of sheath cracks.

The contractor will be held liable for all damage due to carelessness and to neglect and is responsible for protecting and safeguarding cables. All damage will be repaired at the contractor's expense

C.4 Removing Existing Structure

After removal of the castings and protecting and supporting the cables, carefully remove the manhole roof, walls, floor and all hardware. No portion of the existing structure is to remain. The increase in the size of the excavation will be determined by the size of the manhole to be reconstructed as indicated in the detail plans. Remove all waste material accumulated by the removal of the existing structure from the work site. No part of this waste material can be used as backfill material.

C.5 Conduit Alterations

Break back by hand sections of cement encased conduit to facilitate excavation for the new proposed structure. Hand chip concrete away for the existing pipes. Carefully remove pipes from around the cables. Hand chip enough concrete away from the pipes to allow for the coupling of split ducts on to the ends of the pipes. Protect exposed pipe ends and existing cables from damage.

D Measurement

The department will measure Removing CUC Manhole by each individual manhole acceptably removed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.0060.49 Removing CUC Manhole EACH

Payment is full compensation for breaking down and removing structure; conduit alterations; for providing cable protection; for hauling and disposing of materials.

2140-14-70 72 of 85

64. Section Corner Monuments, Item SPV.0060.50.

A Description

Coordinate with Southeastern Wisconsin Regional Planning Commission (SEWRPC) for the perpetuation and replacement of a section corner (Public Land Survey System- PLSS) monument.

B Materials

SEWRPC will provide a pre-cast concrete monument or brass disk to be used to mark the PLSS corner.

Furnish base aggregate dense materials that conform to standard spec 305. Furnish concrete, asphalt, topsoil or other materials depending on the surface surrounding the corner.

C Construction

SEWRPC will perpetuate existing section corner monument. The CONTRACTOR is responsible to coordinate with SEWRPC and the WisDOT Project Manager throughout the perpetuation and replacement process. The CONTRACTOR will contact the engineer and SEWRPC at (262) 853-8463 at least two (2) weeks before starting construction operations or the preconstruction meeting to allow for section corner monument perpetuation.

CONTRACTOR must excavate and completely remove the existing monument. CONTRACTOR is responsible for providing a backfilled 3 to 4 foot deep hole where existing monument was removed. CONTRACTOR is responsible to coordinate the materials and methodology to complete the construction of the surface surrounding the monument. This may include but is not limited to a 2' x 2' "box out" or 24" diameter core hole in concrete, asphalt pavement/paving rings, coring to facilitate poured in place monuments, topsoil, seed and mulching or other materials or methodologies as agreed to by the CONTRACTOR and SEWPRC.

Contact Information:

Attn: Andy Traeger (Construction Coordinator)

Southeastern Wisconsin Regional Planning Commission

W239 N1812 Rockwood Drive

P.O. Box 1607

Waukesha, WI 53187-1607

Phone (262) 953-4296

Cell (262) 853-8463

Fax (262) 547-1103

D Measurement

The department will measure Section Corner Monuments Special by the individual unit acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

 ITEM NUMBER
 DESCRIPTION
 UNIT

 SPV.0060.50
 Section Corner Monuments
 EACH

Payment is full compensation for all excavating; removal of existing monument, for placing and compacting backfill material; for disposing of surplus materials; for concrete or asphalt material, finishing of roadway or other surfaces, for all coordination with SEWRPC.

SER-621-001 (20210924)

65. Removing Fence, R-40-76, Item SPV.0060.51.

A Description

This special provision describes the removal of chain link fence on R-40-76. Limits are shown on the plans.

2140-14-70 73 of 85

B Materials

Furnish non-shrink commercial grout from the department's approved product list.

C Construction

Existing fence posts are placed in embedded sleeves and set with non-shrink grout. Remove posts to the top of the existing concrete wall by either pulling them out of the sleeves or cutting them off at the surface. Care should be taken to protect the existing concrete and any damage caused during the removal shall be repaired at no cost to the department. Any remaining metal shall be cut or ground smooth at the surface.

Once posts are removed, embedded sleeves and/or remaining segments of embedded posts shall be cleaned of any debris or loose material and filled with non-shrink grout.

D Measurement

The department will measure Removing Fence, R-40-76 as a single unit for the full removal of the limits shown on the plans, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0060.51Removing Fence, R-40-76EACH

Payment is full compensation for removal and disposal of the fence, cleaning, filling the existing embedded sleeves with grout, providing materials, and for furnishing all labor, equipment, tools, and incidentals necessary to complete the work.

66. Field Facilities Office Space, Item SPV.0060.52.

A Description

This special provision describes furnishing, equipping, and maintaining a field office as required in the contract at engineer-approved locations conforming to standard spec 642 and as follows.

B Materials

Provide Field Facilities Office Space conforming to standard spec 642.2.1 except delete paragraphs (1), (8), and (10).

Replace standard spec 642.2.1(4) with the following:

Provide and maintain suitable interior sanitary facilities conforming to State and local health requirements, in clean and good working condition, and stock with sanitary supplies for the duration of the contract. Furnish office space in an existing office building or existing building converted to office space with a minimum of 1200 square feet. The facility shall have no fee parking with a minimum parking for 15 cars. The space shall include a meeting room with a minimum of 350 square feet. The exterior door(s) shall have locks in good working order and keys provided for all field staff. The office space shall be located within 2 miles of the construction project.

Equip the office as specified in standard spec 642.2.2.1 except delete paragraph (1) and (5) and add the following:

- 1. 8 suitable office desks with drawers and locks.
- 2. 8 ergonomically correct office chairs in working condition with at a minimum: 5-legged base with casters, seat adjustable from 15 to 22 inches from the floor with a seamless waterfall, rounded, front edge, and high backrest with no arms or adjustable arms.
- 3. 4 six foot folding tables.
- 4. 1 ten foot folding table.
- 5. 5 two-drawer file cabinets.
- 6. 3 four-shelf bookcases.
- 7. 20 folding chairs.

Provide for the professional cleaning of the field office during regular business hours twice monthly. Provide clearly marked recycling and waste receptacles within the field office, and separate recycling and

2140-14-70 74 of 85

waste dumpsters near the field office. Cover outdoor containers to keep out rain, snow, and wind-driven debris. Provide regularly scheduled recycling and waste pick-up.

C Construction

Conform to standard spec 642.3 except delete paragraph (2).

D Measurement

The department will measure the Field Facilities Office Space as each office acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.0060.52 Field Facilities Office Space EACH

Payment is full compensation for providing, equipping, securing, and maintaining the facility; for parking, for telecommunications equipment, installation, and service fees; and for providing bottled water, utilities, fuel, ventilation, and toilet facilities as required, either independently or jointly with the field laboratory, for the time specified in 642.3.

The department will pay for the cost of telecommunications usage fees incurred by department staff.

SER-642-002 (20240112)

67. Street Sweeping, Item SPV.0075.01.

A Description

This special provision describes removing small dirt and dust particles from the roadway using a street sweeper periodically during the project as the engineer directs.

B Materials

Furnish a vacuum-type street sweeper equipped with a power broom, water spray system and a vacuum collection system.

Use vacuum equipment with a self-contained particulate collector capable of preventing discharge from the collection bin into the atmosphere.

Use a vacuum-type sweeper as the primary sweeper, except as specified in this special provision or approved by the engineer.

Use a vacuum, water spray system, or other engineer-approved method to clear debris from scuppers in existing concrete barrier walls.

C Construction

Provide sweeping of pavement, sidewalk, driveways, curb lanes and gutters as directed by the engineer.

D Measurement

The department will measure Street Sweeping by the hour that the street sweeper is on the project actively picking up and removing debris from the roadway.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.00755. 01 Street Sweeping HRS

Payment is full compensation for mobilization; sweeping, vacuuming and water spray; disposing of materials; and submitting the hourly meter tickets each day the sweeper is used.

2140-14-70 75 of 85

68. Concrete Curb and Gutter 6-Inch Sloped 18-Inch Type J, SPV.0090.01.

A Description

Work under this contract shall be according to standard spec 601.1.

B Materials

Conform to standard spec 601.2.

C Construction

Conform to standard spec 601.3.

D Measurement

Conform to standard spec 601.4.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.0090.01 Concrete Curb and Gutter 6-Inch Sloped 18-Inch Type J LF

Payment is full compensation for foundation preparation; special construction required at driveway and alley entrances, or curb ramps; for providing materials, including concrete, expansion joints; for placing, finishing, protecting, and curing; for sawing joints; and for restoring the site. The department will pay for excavation required for this work as specified in the contract by other bid items.

69. Marking Crosswalk Epoxy Block Style 12-Inch White, SPV.0090.02.

A Description

This special provision describes furnishing and installing Marking Crosswalk Epoxy Block Style 12-inch White as directed by the engineer, as shown on the drawings and as hereinafter provided.

Perform work under these items in accordance with the requirements of section 646 of the WisDOT Standard Specifications and the details as shown on the plans, with the exception of the differences noted here within.

B Materials

Furnish epoxy pavement marking and glass bead material according to the standard spec 646.

C Construction

Construction of pavement markings shall be in accordance with manufacturer application and installation procedures, standard spec 646, and Engineer.

All pavement marking areas shall be laid out by the contractor and then reviewed by the Engineer. Approval of the marking layout shall be approved by the Engineer prior to placement of material.

The Contractor shall protect the pavement markings from damage and allow them to fully cure prior to allowing traffic to drive over markings. Any damage shall be corrected by the Contractor at the Contractor's expense.

D Measurement

The department will measure Marking Crosswalk Epoxy Block Style 12-inch White by the linear foot, acceptably completed.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0090.02Marking Crosswalk Epoxy Block Style 12-inch WhiteLF

Payment is full compensation for preparing the surface, furnishing, and installing all materials and incidentals necessary to complete the work.

2140-14-70 76 of 85

70. Excavation, Hauling, and Disposal of Lead Contaminated Soil, Item SPV.0195.01.

This special provision describes excavating, loading, hauling, and disposing of lead-contaminated soil at a DNR approved landfill facility. The closest DNR approved landfill facilities are:

Waste Management Orchard Ridge Landfill W124 N9355 Boundary Road Menomonee Falls, WI 53051 (262) 253-8626

GFL Environmental Emerald Park Landfill W124 S10629 124th Street Muskego, WI 53150 (414) 529-1360

Waste Management Metro Landfill 10712 South 124th Street Franklin, WI 53132 (414) 529-6180

Perform this work conforming to standard spec 205 and with pertinent parts of Chapters NR 700-754 of the Wisconsin Administrative Code, as supplemented herein. Per NR 718.07, a solid waste collection and transportation service-operating license is required under NR 502.06 for each vehicle used to transport contaminated soil.

A.2 Notice to the Contractor – Contaminated Soil Locations

The department completed testing for soil contamination for locations within this project where excavation is required. Testing indicated that lead-contaminated soil is present at the following location where excavation is required, as shown on the plans:

STH 181 Station 180+00 to 183+00, from reference line to project limits left, from 1' below ground surface (bgs) to maximum excavation depth. Soil contains lead and must be managed. Approximately **28** cubic yards (approximately **47.6** tons at an estimated 1.7 tons per cubic yard) of soil will be excavated from this location.

Directly load soil excavated by the project at the above locations into trucks that will transport the soil to a WDNR-licensed landfill facility for treatment and disposal.

If contaminated soils are encountered elsewhere on the project, terminate excavation activities in the area and notify the engineer. If dewatering is required at the above locations, conduct the dewatering in accordance with Section C below.

The excavation management plan for this project has been designed to minimize the offsite treatment or disposal of contaminated material. The excavation management plan, including these special provisions, has been developed in cooperation with the WDNR. The WDNR concurrence letter is on file at the Wisconsin Department of Transportation. For further information regarding previous investigation and remediation activities near this project, contact:

Name: Mr. Andrew Malsom

Address: 141 NW Barstow Street, PO Box 798, Waukesha, WI 53187-0798

Phone: 262-548-6705 Fax: 262-548-6891

E-mail: Andrew.Malsom@dot.wi.gov

A.3 Coordination

Coordinate work under this contract with the environment consultant:

Consultant: Ramboll

Address: 234 W. Florida Street, Fifth Floor, Milwaukee, WI 53204

Contact: Mr. Mark Walter, PE Phone: 414-837-3563 Fax: 414-837-3608

E-mail: Mark.Walter@ramboll.com

2140-14-70 77 of 85

The role of the environmental consultant will be limited to:

- 1. Determining the location and limits of contaminated soil to be excavated based on soil analytical results from previous investigations, visual observations, and field screening of soil that is excavated;
- 2. Identifying contaminated soils to be hauled to the landfill facility;
- 3. Documenting that activities associated with management of contaminated soil are in conformance with the contaminated soil management methods for this project as specified herein; and
- 4. Obtaining the necessary approvals for disposal of contaminated soil from the landfill facility.

Provide at least a 14-calendar day notice of the preconstruction conference date to the environmental consultant. At the preconstruction conference, provide a schedule for all excavation activities in the areas of contamination to the environmental consultant. Also notify the environmental consultant at least three calendar days before beginning excavation activities in each of the contaminated areas.

Coordinate with the environmental consultant to ensure that the environmental consultant is present during excavation activities in the contaminated areas. Perform excavation work in each of the contaminated areas on a continuous basis until excavation work is completed.

Identify the DNR approved landfill facility that will be used for disposal of contaminated soils and provide this information to the environmental consultant no later than 30 calendar days before beginning excavation activities in the contaminated areas or at the preconstruction conference, whichever comes first. The environmental consultant will be responsible for obtaining the necessary approvals for disposal of contaminated soils from the landfill facility. Do not transport contaminated soil offsite without prior approval from the environmental consultant.

A.4 Health and Safety Requirements

Add the following to standard spec 107.1:

During excavation activities, expect to encounter soil contaminated with lead. Site workers taking part in activities that will result in the reasonable probability of exposure to safety and health hazards associated with hazardous materials shall have completed health and safety training that meets the Occupational Safety and Health Administration (OSHA) requirements for Hazardous Waste Operations and Emergency Response (HAZWOPER), as provided in 29 CFR 1910.120.

Prepare a site-specific Health and Safety Plan, and develop, delineate, and enforce the health and safety exclusion zones for each contaminated site location as required by 29 CFR 1910.120. Submit the site-specific health and safety plan and written documentation of up-to-date OSHA training to the engineer before the start of work.

B (Vacant)

C Construction

Add the following to standard spec 205.3:

Control operations in the contaminated areas to minimize the quantity of contaminated soil excavated.

The environmental consultant will periodically evaluate soil excavated from the contaminated areas to determine if the soil will require offsite landfill disposal. The environmental consultant will evaluate excavated soil based on field screening results, visual observations, and soil analytical results from previous environmental investigations. Assist the environmental consultant in collecting soil samples for evaluation using excavation equipment. The sampling frequency shall be a maximum of one sample for every 15 cubic yards excavated.

Directly load and haul soils designated by the environmental consultant for offsite landfill disposal to the DNR approved landfill facility. Use loading and hauling practices that are appropriate to prevent any spills or releases of contaminated soils or residues. Before transport, sufficiently dewater soils designated for off-site landfill disposal so as not to contain free liquids.

If dewatering is required in areas of known contamination, water generated from dewatering activities will likely contain lead. Such water may be discharged to the storm sewer or surface water with WDNR approval under a Wisconsin Pollution Discharge Elimination System (WPDES) General Permit, or to the sanitary sewer or at the treatment facility with approval from the Milwaukee Metropolitan Sewerage District (MMSD). Pretreatment may be required prior to discharge.

Contractor shall meet all applicable requirements, including the control of suspended solids. Perform all necessary monitoring to document compliance with requirements. Furnish, install, operate, maintain, disassemble, and remove treatment equipment necessary to comply with requirements.

2140-14-70 78 of 85

Ensure continuous dewatering and excavation safety at all times. Provide, operate, and maintain adequate pumping equipment and drainage and disposal facilities.

Notify the engineer of any dewatering activities and obtain any permits necessary to discharge water. Provide copies of such permits to the engineer. Meet any requirements and pay any costs for obtaining and complying with such permit use. Follow all applicable legislative statutes, judiciary decisions, and regulations of the State of Wisconsin.

Costs associated with excavation dewatering in the contaminated areas are considered incidental to this pay item. The Wisconsin Department of Transportation will be the generator of regulated solid waste from this construction project.

D Measurement

The department will measure Excavation, Hauling, and Disposal of Lead-Contaminated Soil in tons of contaminated soil, accepted by the landfill facility as documented by weight tickets generated by the landfill facility.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0195.01Excavation, Hauling, and Disposal of Lead Contaminated SoilTON

Payment is full compensation for excavating, segregating, loading, hauling, and disposal of contaminated soil; obtaining solid waste collection and transportation service operating licenses; assisting in the collection soil samples for field evaluation; and dewatering of soils before transport, if necessary. Management and disposal of contaminated water is considered incidental to other bid items in the contract. The department will not pay directly for management and disposal/treatment of contaminated water.

stp-205-003 (20230113)

71. Excavation, Hauling, and Disposal of PAH Contaminated Soil, Item SPV.0195.02.

A Description

A.1 General

This special provision describes excavating, loading, hauling, and disposing of polycyclic aromatic hydrocarbon (PAH)-contaminated soil at a DNR approved landfill facility. The closest DNR approved landfill facilities are:

Waste Management Orchard Ridge Landfill W124 N9355 Boundary Road Menomonee Falls, WI 53051 (262) 253-8626

GFL Environmental Emerald Park Landfill W124 S10629 124th Street Muskego, WI 53150 (414) 529-1360

Waste Management Metro Landfill 10712 South 124th Street Franklin, WI 53132 (414) 529-6180

Perform this work conforming to standard spec 205 and with pertinent parts of Chapters NR 700-754 of the Wisconsin Administrative Code, as supplemented herein. Per NR 718.07, a solid waste collection and transportation service-operating license is required under NR 502.06 for each vehicle used to transport contaminated soil.

2140-14-70 79 of 85

A.2 Notice to the Contractor – Contaminated Soil Locations

The department completed testing for soil contamination for locations within this project where excavation is required. Testing indicated that PAHs-contaminated soil is present at the following location where excavation is required, as shown on the plans:

STH 181 Station 65+25 to 67+50, from project limits left to project limits right, from 1' below ground surface (bgs) to maximum excavation depth. Soil contains PAHs and must be managed.

Approximately 1 cubic yards (approximately 1.7 tons at an estimated 1.7 tons per cubic yard) of soil will be excavated from this location.

Directly load soil excavated by the project at the above locations into trucks that will transport the soil to a WDNR-licensed landfill facility for treatment and disposal.

If contaminated soils are encountered elsewhere on the project, terminate excavation activities in the area and notify the engineer. If dewatering is required at the above locations, conduct the dewatering in accordance with Section C below.

The excavation management plan for this project has been designed to minimize the offsite treatment or disposal of contaminated material. The excavation management plan, including these special provisions, has been developed in cooperation with the WDNR. The WDNR concurrence letter is on file at the Wisconsin Department of Transportation. For further information regarding previous investigation and remediation activities near this project, contact:

Name: Mr. Andrew Malsom

Address: 141 NW Barstow Street, PO Box 798, Waukesha, WI 53187-0798

Phone: 262-548-6705 Fax: 262-548-6891

E-mail: Andrew.Malsom@dot.wi.gov

A.3 Coordination

Coordinate work under this contract with the environment consultant:

Consultant: Ramboll

Address: 234 W. Florida Street, Fifth Floor, Milwaukee, WI 53204

Contact: Mr. Mark Walter, PE Phone: 414-837-3563 Fax: 414-837-3608

E-mail: Mark.Walter@ramboll.com

The role of the environmental consultant will be limited to:

- 1. Determining the location and limits of contaminated soil to be excavated based on soil analytical results from previous investigations, visual observations, and field screening of soil that is excavated;
- 2. Identifying contaminated soils to be hauled to the landfill facility;
- 3. Documenting that activities associated with management of contaminated soil are in conformance with the contaminated soil management methods for this project as specified herein; and
- 4. Obtaining the necessary approvals for disposal of contaminated soil from the landfill facility.

Provide at least a 14-calendar day notice of the preconstruction conference date to the environmental consultant. At the preconstruction conference, provide a schedule for all excavation activities in the areas of contamination to the environmental consultant. Also notify the environmental consultant at least three calendar days before beginning excavation activities in each of the contaminated areas.

Coordinate with the environmental consultant to ensure that the environmental consultant is present during excavation activities in the contaminated areas. Perform excavation work in each of the contaminated areas on a continuous basis until excavation work is completed.

Identify the DNR approved landfill facility that will be used for disposal of contaminated soils and provide this information to the environmental consultant no later than 30 calendar days before beginning excavation activities in the contaminated areas or at the preconstruction conference, whichever comes first. The environmental consultant will be responsible for obtaining the necessary approvals for disposal of contaminated soils from the landfill facility. Do not transport contaminated soil offsite without prior approval from the environmental consultant.

2140-14-70 80 of 85

A.4 Health and Safety Requirements

Add the following to standard spec 107.1:

During excavation activities, expect to encounter soil contaminated with PAHs. Site workers taking part in activities that will result in the reasonable probability of exposure to safety and health hazards associated with hazardous materials shall have completed health and safety training that meets the Occupational Safety and Health Administration (OSHA) requirements for Hazardous Waste Operations and Emergency Response (HAZWOPER), as provided in 29 CFR 1910.120.

Prepare a site-specific Health and Safety Plan, and develop, delineate, and enforce the health and safety exclusion zones for each contaminated site location as required by 29 CFR 1910.120. Submit the site-specific health and safety plan and written documentation of up-to-date OSHA training to the engineer before the start of work.

B (Vacant)

C Construction

Add the following to standard spec 205.3:

Control operations in the contaminated areas to minimize the quantity of contaminated soil excavated.

The environmental consultant will periodically evaluate soil excavated from the contaminated areas to determine if the soil will require offsite landfill disposal. The environmental consultant will evaluate excavated soil based on field screening results, visual observations, and soil analytical results from previous environmental investigations. Assist the environmental consultant in collecting soil samples for evaluation using excavation equipment. The sampling frequency shall be a maximum of one sample for every 15 cubic yards excavated.

Directly load and haul soils designated by the environmental consultant for offsite landfill disposal to the DNR approved landfill facility. Use loading and hauling practices that are appropriate to prevent any spills or releases of contaminated soils or residues. Before transport, sufficiently dewater soils designated for off-site landfill disposal so as not to contain free liquids.

If dewatering is required in areas of known contamination, water generated from dewatering activities will likely contain PAHs. Such water may be discharged to the storm sewer or surface water with WDNR approval under a Wisconsin Pollution Discharge Elimination System (WPDES) General Permit, or to the sanitary sewer or at the treatment facility with approval from the Milwaukee Metropolitan Sewerage District (MMSD). Pretreatment may be required prior to discharge.

Contractor shall meet all applicable requirements, including the control of suspended solids. Perform all necessary monitoring to document compliance with requirements. Furnish, install, operate, maintain, disassemble, and remove treatment equipment necessary to comply with requirements.

Ensure continuous dewatering and excavation safety at all times. Provide, operate, and maintain adequate pumping equipment and drainage and disposal facilities.

Notify the engineer of any dewatering activities and obtain any permits necessary to discharge water. Provide copies of such permits to the engineer. Meet any requirements and pay any costs for obtaining and complying with such permit use. Follow all applicable legislative statutes, judiciary decisions, and regulations of the State of Wisconsin.

Costs associated with excavation dewatering in the contaminated areas are considered incidental to this pay item. The Wisconsin Department of Transportation will be the generator of regulated solid waste from this construction project.

D Measurement

The department will measure Excavation, Hauling, and Disposal of PAH-Contaminated Soil in tons of contaminated soil, accepted by the landfill facility as documented by weight tickets generated by the landfill facility.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT SPV.0195.02 Excavation, Hauling, and Disposal of PAH Contaminated Soil TON

Payment is full compensation for excavating, segregating, loading, hauling, and disposal of contaminated soil; obtaining solid waste collection and transportation service operating licenses; assisting in the

2140-14-70 81 of 85

collection soil samples for field evaluation; and dewatering of soils before transport, if necessary. Management and disposal of contaminated water is considered incidental to other bid items in the contract. The department will not pay directly for management and disposal/treatment of contaminated water.

stp-205-003 (20230113)

72. Excavation, Hauling, and Disposal of Petroleum Contaminated Soil, Item SPV.0195.03.

A Description

A.1 General

This special provision describes excavating, loading, hauling, and disposing of petroleum-contaminated soil at a DNR approved landfill facility. The closest DNR approved landfill facilities are:

Waste Management Orchard Ridge Landfill W124 N9355 Boundary Road Menomonee Falls, WI 53051 (262) 253-8626

GFL Environmental Emerald Park Landfill W124 S10629 124th Street Muskego, WI 53150 (414) 529-1360

Waste Management Metro Landfill 10712 South 124th Street Franklin, WI 53132 (414) 529-6180

Perform this work conforming to standard spec 205 and with pertinent parts of Chapters NR 700-754 of the Wisconsin Administrative Code, as supplemented herein. Per NR 718.07, a solid waste collection and transportation service-operating license is required under NR 502.06 for each vehicle used to transport contaminated soil.

A.2 Notice to the Contractor - Contaminated Soil Locations

The department completed testing for soil contamination for locations within this project where excavation is required. Testing indicated that petroleum-contaminated soil is present at the following locations where excavation is required, as shown on the plans:

- STH 181 Station 73+00 to 74+50, from reference line to project limits left, from 6' below ground surface (bgs) to maximum excavation depth. Soil contains petroleum volatile organic compounds (PVOCs) and must be managed. Approximately 8 cubic yards (approximately 13.6 tons at an estimated 1.7 tons per cubic yard) of soil will be excavated from this location.
- STH 181 Station 101+00 to 101+75, from reference line to project limits left, from 1' bgs to 8' bgs. Soil contains PVOCs and must be managed. Approximately **5** cubic yards (approximately **8.5** tons at an estimated 1.7 tons per cubic yard) of soil will be excavated from this location.
- STH 181 Station 245+50 to 256+00, from reference line to project limits left, from 1' bgs to maximum excavation depth. Soil contains PVOCs and must be managed. Approximately **66** cubic yards (approximately **112.2** tons at an estimated 1.7 tons per cubic yard) of soil will be excavated from this location.

Directly load soil excavated by the project at the above locations into trucks that will transport the soil to a WDNR-licensed landfill facility for treatment and disposal.

If contaminated soils are encountered elsewhere on the project, terminate excavation activities in the area and notify the engineer. If dewatering is required at the above locations, conduct the dewatering in accordance with Section C below.

The excavation management plan for this project has been designed to minimize the offsite treatment or disposal of contaminated material. The excavation management plan, including these special provisions, has been developed in cooperation with the WDNR. The WDNR concurrence letter is on file at the

2140-14-70 82 of 85

Wisconsin Department of Transportation. For further information regarding previous investigation and remediation activities near this project, contact:

Name: Mr. Andrew Malsom

Address: 141 NW Barstow Street, PO Box 798, Waukesha, WI 53187-0798

Phone: 262-548-6705 Fax: 262-548-6891

E-mail: Andrew.Malsom@dot.wi.gov

A.3 Coordination

Coordinate work under this contract with the environment consultant:

Consultant: Ramboll

Address: 234 W. Florida Street, Fifth Floor, Milwaukee, WI 53204

Contact: Mr. Mark Walter, PE Phone: 414-837-3563 Fax: 414-837-3608

E-mail: Mark.Walter@ramboll.com

The role of the environmental consultant will be limited to:

- 1. Determining the location and limits of contaminated soil to be excavated based on soil analytical results from previous investigations, visual observations, and field screening of soil that is excavated;
- 2. Identifying contaminated soils to be hauled to the landfill facility;
- 3. Documenting that activities associated with management of contaminated soil are in conformance with the contaminated soil management methods for this project as specified herein; and
- 4. Obtaining the necessary approvals for disposal of contaminated soil from the landfill facility.

Provide at least a 14-calendar day notice of the preconstruction conference date to the environmental consultant. At the preconstruction conference, provide a schedule for all excavation activities in the areas of contamination to the environmental consultant. Also notify the environmental consultant at least three calendar days before beginning excavation activities in each of the contaminated areas.

Coordinate with the environmental consultant to ensure that the environmental consultant is present during excavation activities in the contaminated areas. Perform excavation work in each of the contaminated areas on a continuous basis until excavation work is completed.

Identify the DNR approved landfill facility that will be used for disposal of contaminated soils and provide this information to the environmental consultant no later than 30 calendar days before beginning excavation activities in the contaminated areas or at the preconstruction conference, whichever comes first. The environmental consultant will be responsible for obtaining the necessary approvals for disposal of contaminated soils from the landfill facility. Do not transport contaminated soil offsite without prior approval from the environmental consultant.

A.4 Health and Safety Requirements

Add the following to standard spec 107.1:

During excavation activities, expect to encounter soil contaminated with PVOCs. Site workers taking part in activities that will result in the reasonable probability of exposure to safety and health hazards associated with hazardous materials shall have completed health and safety training that meets the Occupational Safety and Health Administration (OSHA) requirements for Hazardous Waste Operations and Emergency Response (HAZWOPER), as provided in 29 CFR 1910.120.

Prepare a site-specific Health and Safety Plan, and develop, delineate, and enforce the health and safety exclusion zones for each contaminated site location as required by 29 CFR 1910.120. Submit the site-specific health and safety plan and written documentation of up-to-date OSHA training to the engineer before the start of work.

B (Vacant)

C Construction

Add the following to standard spec 205.3:

Control operations in the contaminated areas to minimize the quantity of contaminated soil excavated.

2140-14-70 83 of 85

The environmental consultant will periodically evaluate soil excavated from the contaminated areas to determine if the soil will require offsite landfill disposal. The environmental consultant will evaluate excavated soil based on field screening results, visual observations, and soil analytical results from previous environmental investigations. Assist the environmental consultant in collecting soil samples for evaluation using excavation equipment. The sampling frequency shall be a maximum of one sample for every 15 cubic yards excavated.

Directly load and haul soils designated by the environmental consultant for offsite landfill disposal to the DNR approved landfill facility. Use loading and hauling practices that are appropriate to prevent any spills or releases of contaminated soils or residues. Before transport, sufficiently dewater soils designated for off-site landfill disposal so as not to contain free liquids.

If dewatering is required in areas of known contamination, water generated from dewatering activities will likely contain PVOCs, polycyclic aromatic hydrocarbons (PAHs), and metals. Such water may be discharged to the storm sewer or surface water with WDNR approval under a Wisconsin Pollution Discharge Elimination System (WPDES) General Permit, or to the sanitary sewer or at the treatment facility with approval from the Milwaukee Metropolitan Sewerage District (MMSD). Pretreatment may be required prior to discharge.

Contractor shall meet all applicable requirements, including the control of suspended solids. Perform all necessary monitoring to document compliance with requirements. Furnish, install, operate, maintain, disassemble, and remove treatment equipment necessary to comply with requirements.

Ensure continuous dewatering and excavation safety at all times. Provide, operate, and maintain adequate pumping equipment and drainage and disposal facilities.

Notify the engineer of any dewatering activities and obtain any permits necessary to discharge water. Provide copies of such permits to the engineer. Meet any requirements and pay any costs for obtaining and complying with such permit use. Follow all applicable legislative statutes, judiciary decisions, and regulations of the State of Wisconsin.

Costs associated with excavation dewatering in the contaminated areas are considered incidental to this pay item. The Wisconsin Department of Transportation will be the generator of regulated solid waste from this construction project.

D Measurement

The department will measure Excavation, Hauling, and Disposal of Petroleum-Contaminated Soil in tons of contaminated soil, accepted by the landfill facility as documented by weight tickets generated by the landfill facility.

E Payment

The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBERDESCRIPTIONUNITSPV.0195.03Excavation, Hauling, and Disposal of Petroleum Contaminated SoilTON

Payment is full compensation for excavating, segregating, loading, hauling, and disposal of contaminated soil; obtaining solid waste collection and transportation service operating licenses; assisting in the collection soil samples for field evaluation; and dewatering of soils before transport, if necessary. Management and disposal of contaminated water is considered incidental to other bid items in the contract. The department will not pay directly for management and disposal/treatment of contaminated water.

stp-205-003 (20230113)

73. Asphaltic Repair, Item SPV.0195.04.

A Description

This special provision describes repairing areas of existing asphalt pavement with asphaltic mixtures for overlaying with new pavement.

B Material

Furnish nominal size No. 3 (19mm) aggregate blend graded as specified in 460.2.2.3 and conform to the other material and mixture requirements specified for asphaltic surface in 465. Use tack coat as required under 450.3.2.7.

2140-14-70 84 of 85

C Construction

- (1) Remove areas of existing asphalt pavement, including existing patching or surfacing materials, at locations the plans show or the engineer directs in the field as specified for removing asphaltic surface milling in 204.3.2.2.2. Mill the connecting edges as true and perpendicular as possible, both parallel and perpendicular to the roadway, creating a vertical edge on all sides. Remove the pavement without injury to the remaining pavement. Dispose of removed material as specified in 204.3.1.3.
- (2) As an option for areas of full depth removal, the contractor may remove areas of existing asphalt pavement, including existing patching or surfacing materials, as specified for removing asphaltic surface in 204.3.2.2.1. Saw cut the connecting edges as true and perpendicular as possible, as specified for sawing pavement in 690. Remove the pavement without injury to the remaining pavement. Dispose of removed material as specified in 204.3.1.3.
- (3) Construct as specified for asphaltic surface under 465.3 except as modified here.
 - Replace standard spec 465.3.1(2) with the following:
- (2) Place using self-propelled pavers. Pave at a constant speed, appropriate for the paver and mixture, that ensures uniform spreading and strike-off with a smooth, dense texture and no tearing or segregation.
 - Replace standard spec 465.3.1(3) with the following:
- (3) Immediately after placement, compact the mixture to produce a dense smooth surface using ordinary compaction procedures as specified in 450.3.2.6. Unless the engineer directs otherwise, compact each layer to a thickness of 6 inches or less so that the finished surface is 1/16 inch to 1/8 inch above the existing pavement surface.

D Measurement

The department will measure Asphaltic Repair by the ton acceptably completed as specified for asphaltic pavement in 450.4.

E Payment

(1) The department will pay for measured quantities at the contract unit price under the following bid item:

ITEM NUMBER DESCRIPTION UNIT

SPV.0195.02. Asphaltic Repair TON

- Payment is full compensation for removing old pavement; for preparing the foundation; and for providing and compacting asphaltic mixture including asphaltic binder. Sawing existing asphalt pavement as a contractor option is incidental to the Asphaltic Repair bid item.
- (3) The department will pay separately for tack coat under the Tack Coat bid item as specified in 455.5. SER-390-001 (20220408)

2140-14-70 85 of 85

ADDITIONAL SPECIAL PROVISION 1 (ASP 1) HIGHWAY CONSTRUCTION SKILLS TRAINING (HCST) PROGRAM EMPLOYMENT PLACEMENTS AND APPRENTICESHIPS

The Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU), Section 5204(e) – Surface Transportation Workforce Development Training and Education, provides for 100 percent Federal funding if the core program funds are used for training, education, or workforce development purposes, including "pipeline" activities. The core programs include: Congestion Mitigation and Air Quality Improvement (CMAQ) Program, Highway Bridge Program (HBP), Interstate Maintenance (IM), National Highway System (NHS), and Surface Transportation Program (STP). These workforce development activities cover surface transportation workers, including OJT/SS programs for women and minorities as authorized in 23 U.S.C. §140(b).

The Wisconsin Department of Transportation OJT program was originally established in 1995. Highway Construction Skills Training (HCST) was previously known as Transportation Alliance for New Solutions (TrANS) and underwent a name change in early 2023. HCST is an industry driven plan of services to address the outreach, preparation, placement and retention of women, minorities, and disadvantaged persons as laborers and apprentices in the highway skilled trades. Candidate preparation and contractor coordination services (OJT Supportive Services) are provided by contracted community-based organizations.

I. BASIC CONCEPTS

Training reimbursements to employing contractors for new placements, rehires or advancement to apprenticeship of Highway Construction Skills Training (HCST) graduates <u>and</u> employing eligible trainees in qualifying trades will be made as follows:

1)	On-the-Job Training, Item ASP.1T0G, ASP 1 HCST Graduate. At the rate of \$5.00 per hour on
	Federal-aid projects when HCST graduates are initially hired, or seasonally rehired, as unskilled
	laborers or equivalent.
	Eligibility and Duration: To the employing contractor, for up to 2,000 hours or two years, whichever
	comes first from the point of initial hire as a HCST placement.
	Contract Goal: To maintain the intent of the Equal Employment Opportunity program, it is a goal
	that18 HCST Graduate(s) be utilized for17280 hours on this contract.
2)	On-the-Job Training, Item ASP.1T0A, ASP 1 Apprentice. At the rate of \$5.00 per hour on
	Federal-aid projects at the point when an employee who came out of the HCST Program is
	subsequently entered into an apprenticeship contract in a qualifying trade.
	Eligibility and Duration: To the employing contractor, for the length of time that the HCST graduate
	is in apprenticeship status.
	Contract Goal: To maintain the intent of the Equal Employment Opportunity program, it is a goal
	that7 HCST Apprentice(s) be utilized for8400 hours on this contract.
3)	The maximum duration of reimbursement is two years as a HCST graduate plus time in apprentice status.

4) If a HCST program is not available in the contractor's area and another training program is utilized, payment of On-the-Job Training hours may be approved by the Wisconsin Department of Transportation (WisDOT) if the training program meets the established acceptance criteria. Only On-the-Job Training Hours accumulated after WisDOT approval will be reimbursed as specified

- under Items ASP.1T0G and ASP.1T0A. For more information, contact the Department of Transportation Labor Development Specialist at the phone number listed below.
- 5) WisDOT reserves the right to deny payments under items ASP.1T0G and ASP.1T0A if the contractor either fails to provide training or there is evidence of a lack of good faith in meeting the requirements of this training special provision.

II. RATIONALE AND SPECIAL NOTE

The \$5.00 per hour now being paid for HCST placements is intended to cover the duration of two years to allow for reaching entry-level laborer status. An additional incentive, the \$5.00 rate, would promote movement into the underutilized skilled trades' apprenticeships and applies until the individual completes their apprenticeship. These incentives benefit HCST candidates by giving them a better opportunity to enter a skilled trade; benefits contractors who will be assisted in meeting their EEO profiles and goals; and benefits the public who will see the program reinforce larger public-private employment reform in Wisconsin. The pool of HCST graduates was created for the purpose of addressing underutilization in the skilled trades, an objective that is further reinforced by a parallel retention pilot program, known as the Companywide Reporting. Whether or not reimbursement is involved, the WisDOT reassures contractors who are in the Companywide Program that HCST placements still contribute toward fulfilling the new hire goal of 50% women and minorities. Based on data administered by United States Department of Labor (US DOL), the highway skilled trades remain underutilized for women statewide (less than 6.9%); and for minorities in all counties (% varies by county).

<u>NOTE</u>: Unless using other advancement strategies, contractors are encouraged to use some or all of this monetary incentive to offset the cut in hourly wages an individual may incur when entering an apprenticeship if the full general laborer hourly rate has been previously paid. No special accounting measures are required.

III. IMPLEMENTATION

The implementation of ASP 1 is intended to cover only the amount of time it takes for underutilization to be resolved across the trades. This will be measured annually at the county and/or state levels using data administered by WisDWD in relation to goals set by the USDOL page 2 Dated January 2012 OFCCP. With appropriate state and federal approvals, we may also do some measurement at the company level. It is the contractor's responsibility to note on their Certified Payrolls if their employee is a HCST graduate or a HCST apprentice. The compliance specialists utilize the information on the Certified Payrolls to track the hours accumulated by HCST Graduates and HCST apprentices on WisDOT contracts. Payment under this ASP 1 is made based on the hours recorded off of the Certified Payrolls. Tracking may eventually include improved linkages with the WisDWD apprentice database, information from company and committee level sources. HCST is nondiscriminatory by regulation and is a tool for optional use by contractors to address the underutilization of women and minorities as laborers and apprentices in our industry's skilled trades.

IV. HCST TRAINING

As part of the contractor's equal employment opportunity affirmative action program, training shall be provided to employees enrolled in apprenticeship and on-the-job training programs as follows: The contractor shall provide on-the-job training aimed at developing full journey workers in the type of trade or job classifications involved. In the event the contractor subcontracts a portion of the contract work, the contractor shall determine how many, if any, of the trainees are to be trained by the subcontractor provided, however, that the contractor shall retain the primary responsibility for meeting the training requirements imposed by this special provision. The contractor shall also ensure that this training special provision is made applicable to such subcontract. Training and upgrading of minorities and women toward journey workers status is a primary objective of this training special provision. Accordingly, the contractor shall make every effort to enroll minority trainees and women (e.g., by conducting systematic and direct recruitment through public and private sources likely to yield minority trainees and women trainees); to the extent such persons are available within a reasonable area of recruitment. The contractor will be given an opportunity and will be responsible for demonstrating the steps that they have taken in pursuance thereof, prior to determination as to whether the contractor is in compliance with this training

special provision. This training commitment is not intended, and shall not be used, to discriminate against any applicant for training, whether a member of a minority group or not. No employee shall be employed as a trainee in any classification in which they have successfully completed a training course leading to journey workers status or in which they have been employed as a journey worker. The contractor should satisfy this requirement by including appropriate questions in the employee application or by other suitable means. Regardless of the method used, the contractor's records should document the findings in each case.

V. APPRENTICESHIP TRAINING

The Federal Highway Administration's (FHWA) policy is to require full use of all available training and skill improvement opportunities to assure increased participation of minority groups, disadvantaged persons, and women in all phases of the highway construction industry. The FHWA On-the-Job Training (OJT) Program requires the State transportation agencies (STAs) to establish apprenticeships and training programs targeted to move women, minorities, and disadvantaged individuals into journey-level positions to ensure that a competent workforce is available to meet highway construction hiring needs, and to address the historical underrepresentation of members of these groups in highway construction skilled crafts.

The OJT Supportive Services (OJT/SS) Program was established in Title 23 Code of Federal Regulations (CFR), Part 230) to supplement the OJT program and support STA training programs by providing services to highway construction contractors and assistance to highway construction apprentices and trainees. The primary objectives of OJT/SS are:

- (1) To increase the overall effectiveness of the State highway agencies' approved training programs.
- (2) To seek other ways to increase the training opportunities for women, minorities, and disadvantaged individuals.

The STAs are responsible for establishing procedures, subject to the availability of Surface Transportation and Bridge Funds under 23 U.S.C. §140(b) (Nondiscrimination), for the provision of supportive services with respect to training programs approved under 23 CFR, Part 230(a) (Equal Employment Opportunity on Federal and Federal-aid Construction Contracts – including Supportive Services).

The contractor and subcontractor shall maintain records to demonstrate compliance with these apprenticeship requirements. Reasonable exemptions and modifications to and from any or all of these requirements will be determined by the Wisconsin Department of Transportation-Office of Business Opportunity & Equity Compliance (OBOEC). A request for an exemption or modification, with justification, shall be made in writing, addressed to WisDOT OBOEC - Labor Development, 141 NW Barstow Street, Suite 411, PO Box 798, Waukesha, WI 53187.

VI. PROGRAM CONTACTS

Marguerite (Maggie) Givings, Labor Development Specialist Margueritel.Givings@dot.wi.gov | 608-789-7876

Deborah Seip, Labor Development Specialist <u>Deborah.Seip@dot.wi.gov</u> | 262-548-8702

ADDITIONAL SPECIAL PROVISION 3

DISADVANTAGED BUSINESS ENTERPRISE (DBE) PROGRAM IMPLEMENTATION

Authority

Wisconsin Department of Transportation (WisDOT) is a recipient of funds from the US Department of Transportation's Federal Highway Administration. The DBE program is a federal program applicable on all contracts administered by WisDOT that include federal-aid highway funds. The authority for the DBE program is the Transportation Bill as approved by Congress periodically. DBE program guidance and requirements are outlined in the Code of Federal Regulations at 49 CFR Part 26. This contract is subject to DBE provisions because it is financed with federal-aid-highway funds. Additionally, this contract is subject to the *State of Wisconsin Standard Specifications for Highway and Structure Construction* and all applicable contract documents.

Requirements

Pursuant to the federal DBE program regulation at 49 CFR Part 26, a contractor's failure to comply with any provision of the DBE program regulatory provisions will be considered a material breach of contract. This is nonnegotiable.

If a contractor fails to carry out the DBE program requirements and/or the Required Contract Provisions for Federal Aid Contracts (FHWA 1273) referenced in this document, sanctions will be assessed depending upon the facts, reasoning, severity, and remedial efforts of the contractor that may include: termination of contract, withholding payment, assessment of monetary sanctions, and/or suspension/debarment proceedings that could result in the disqualification of the contractor from bidding for a designated period of time.

- (1) The Commitment to Subcontract to DBE (Form DT1506 or digital submittal), Attachments A, and Good Faith Effort Documentation (Form DT1202) will be submitted as described in Section 2.
- (2) Any change to DBE Commitments thereafter must follow modification of DBE subcontracting commitment as described in Section 9.
- (3) The Department requires this list of DBE subcontractors from all bidders at time of bid to ensure the lowest possible cost to taxpayers and fairness to other bidders and subcontractors. Bid shopping is prohibited.
- (4) The contractor must utilize the specific DBE firms listed in the approved DBE Commitment to perform the work and/or supply the materials for which the DBE firm is listed unless the contractor obtains written consent in advance from WisDOT. The contractor will not be entitled to payment for any work or materials on the approved DBE Commitment that is not performed or supplied by the listed DBE without WisDOT's written consent.

Description

The Wisconsin Department of Transportation is committed to the compliant administration of the DBE Program. The DBE provisions work in tandem with FHWA 1273 and WisDOT's *Standard Specifications for Highway and Structure Construction* and *Construction and Materials Manual*. The WisDOT Secretary is signatory to assurances of department-wide compliance.

The Department assigns the contract DBE goal as a percentage of work items that could be performed by certified DBE firms on the contract. The assigned DBE goal is expressed on the bid proposal as a percentage applicable to the total contract bid amount.

(1) WisDOT identifies the assigned DBE goal in its contract advertisements and posts the contract DBE goal on the cover of the bidding proposal. The contractor can meet the assigned contract DBE goal by subcontracting work to a DBE firm or by procuring services or materials from a DBE firm.

- (2) Under the contract, the prime contractor should inform, advise, and develop participating DBE firms to be more knowledgeable contractors who are prepared to successfully complete their contractual agreement through the proactive provision of assistance in the following areas:
 - Produce accurate and complete quotes
 - Understand highway plans applicable to their work
 - Understand specifications and contract requirements applicable to their work
 - Understand contracting reporting requirements
- (3) The Department encourages contractors to assist DBE subcontractors more formally by participating in WisDOT's Business Development program as a mentor, coach, or resource. For comprehensive information on the Disadvantaged Business Enterprise Program, visit the Department's Civil Rights and Compliance Section website at: http://wisconsindot.gov/Pages/doing-bus/civil-rights/dbe/default.aspx

1. Definitions

Interpret these terms, used throughout this additional special provision, as follows:

- a. Assigned DBE Contract Goal: The percentage shown on the cover of the Highway Work Proposal that represents the feasible level of DBE participation for each contract. The goal is calculated using the Engineer's Estimate and DBE Interest Report. Goal assignment includes review of FHWA funds, analyzes bid items for subcontract opportunity and compatibility with DBE certified firm work codes. Additional factors considered include proximity, proportion, and regulations.
- b. **Bid Shopping:** In construction law, bid shopping is the practice of divulging a subcontractor's bid to another prospective contractor(s) before or after the award of a contract to secure a lower bid.
- c. **DBE:** Disadvantaged Business Enterprise A for-profit small business concern where socially and economically disadvantaged individuals own at least a 51% interest and control management and daily business operations.
- d. DBE Commitment: The DBE Commitment is identified in the Commitment to Subcontract to DBE (Form DT1506) and is expressed as the amount of DBE participation the prime contractor has secured. The DT1506, a contract document completed by the bidder, is required to be considered a responsive bidder on an FHWA-funded contract that has an assigned DBE goal. The prime contractor will have the option to submit the DT1506 digitally, as an entry with the bid in Bid Express, or as an attachment to the bid.
- e. **DBE Utilization:** The actual participation of a DBE subcontractor on a project. WisDOT verifies DBE utilization through review of the DBE Commitment, payments to subcontractors, and contract documentation. The Prime Contractor receives DBE credit for payments made to the DBE firms performing the work listed on the approved DBE Commitment, and those submitted after approved commitment with Attachment A.
- f. **Good Faith Effort:** Legal term describing a diligent and honest effort taken by a reasonable person under the same set of facts or circumstances. For DBE subcontracting, the bidder must show that it took all necessary and reasonable steps to achieve the assigned DBE goal by the scope, intensity, and appropriateness of effort that could reasonably be expected for a contractor to obtain sufficient DBE participation.
- g. **Manufacturer:** A firm that operates or maintains a factory or establishment that produces, on the premises, the materials, supplies, articles, or equipment required under the contract.
- h. **Reasonable Price:** Contractors are expected to assess reasonable price by analyzing the contract scope for DBE subcontract feasibility and comparing common line items in DBE and non-DBE subcontract quotes for the same work. Per federal regulation, reasonable price is not necessarily the lowest price.
- Supplier: A firm that owns, operates, or maintains a store, warehouse, or other establishment in which the
 materials, supplies, articles, or equipment required under the contract are bought, kept in stock, and regularly sold
 or leased to the public.
- j. **Tied quote:** Subcontractor quote that groups multiple bid/line items at a bundled/package price with a notation that the items within the quote will not be separated.

2. WisDOT DBE Program Compliance

a. Documentation Submittal

- The Commitment to Subcontract to DBE (Form DT1506 or digital submittal) must be submitted at the time
 of bid (Tuesday) by all prime contractors.
- Attachments A OR quotes from all DBEs included in the Commitment must be submitted at bid (Tuesday)
 OR
- Within one-hour following bid submittal by ALL prime contractors via eSubmit (Tuesday).
- If only DBE quotes were submitted, all remaining signed Attachments A must be submitted within 24-hours of bid closing via eSubmit (Wednesday).
- If the assigned DBE contract goal is not met, Documentation of Good Faith Effort (Form DT1202) and supporting documentation must be submitted within 24-hours of bid closing (Wednesday) via eSubmit.
 Instructions for eSubmit.

**Bidders have the option of submitting the DBE Commitment at the time of bid via direct entry through Bid Express OR with attachment of Form DT1506 (Commitment to Subcontract to DBE). The DBE Commitment entered with bid is the digital form of the DT1506. Separate submission of Form DT1506 is not required if the DBE Commitment is entered in Bid Express. Form DT1202, if applicable, is no longer required to be submitted at time of bid; submit DT1202 within the 24-hour supplemental time frame following bid closing.

The DBE Office will not certify Good Faith Effort and the Bureau of Project Development will consider the bid nonresponsive if the contractor fails to furnish the DBE Commitment (digitally entered into the bid OR Form DT1506 as an attachment), Attachments A, and Form DT1202 if applicable, as required. See sample forms in the Appendix.

b. Verification of DBE Commitment

The documentation related to DBE subcontract commitment submitted prior to contract award is evaluated as follows:

(1) DBE Goal Met

If the bidder indicates that the contract DBE goal is met, the Department will evaluate the DBE Commitment submitted with bid OR Form DT1506, and Attachments A to verify the actual DBE percentage calculation. If the DBE Commitment is verified, the contract is eligible for award with respect to the DBE Commitment.

(2) DBE Goal Not Met

- a) If the bidder indicates a bid percentage on the DBE Commitment that does not meet the assigned DBE contract goal, the bidder must request alternative evaluation of good faith effort through submission of Form DT1202 (Documentation of Good Faith Effort) within 24-hours of bid including narrative description. Supplementary documentation of good faith effort that supports the DT1202 submission is also due within 24-hours of bid submission and prior to bid posting. The Department will review the bidder's DBE Commitment and evaluate the bidder's good faith efforts submission.
- b) Following evaluation of the bidder's Good Faith Effort documentation the bidder will be notified that the Department intends to:
 - 1. Approve the request (adequate documentation of GFE has been submitted) no conditions placed on the contract with respect to the DBE Commitment;
 - 2. *Deny* the request (inadequate documentation of GFE has been submitted) the contract is viewed as non-responsive per Wisconsin Standard Specifications for Highway and Structure Construction and will not be executed.

c) If the Department denies the bidder's request, the contract is ineligible for award. The Department will provide a written explanation for denying the request to the bidder. The bidder may appeal the Department's denial (see Section 4).

Supplemental good faith effort documentation must be submitted through eSubmit.

3. Department's Criteria for Good Faith Effort Documentation

The Federal-aid Construction Contract Provision, referenced as FHWA-1273, explicitly states that the prime contractor shall be responsible for all work performed on the contract by piecework, station work, or subcontract.

The contractor shall take all necessary and reasonable steps to ensure nondiscrimination in the administration of the contract including assurances of equal employment opportunity laws, DBE regulations, and affirmative action. Compliance encompasses responsible and responsive action, documentation, and good faith effort.

Contractually, all contractors, subcontractors, and service providers on the contract are bound by FHWA 1273 and DBE program provisions. **Prime contractors should encourage subcontractors to utilize DBE firms whenever possible to contribute to the assigned DBE contract goal.**

Bidders are required to document good faith effort. Per 49 CFR Part 26.53, good faith effort is demonstrated in one of two ways. The bidder:

- (1) Documents that it has obtained enough DBE participation to meet the goal; OR
- (2) Documents that it made adequate good faith efforts to meet the goal, even though it did not succeed

Appendix A of 49 CFR Part 26 provides guidance concerning good faith efforts. WisDOT evaluates good faith effort on a contract basis just as each contract award is evaluated individually.

The efforts employed by the bidder should be those that WisDOT can reasonably expect a bidder to take to actively and aggressively obtain DBE participation sufficient to meet the DBE contract goal. The Department will only approve demonstration of good faith effort if the bidder documents the quality, quantity, and intensity of the variety of activities undertaken that are commensurate with expected efforts to meet the stated goal.

The Department, in conjunction with industry stakeholders, has developed the following guidance for contractor good faith effort activity. The guidance and the attached appendices provide a framework for the actions required by all parties in the processing and evaluation of bidder's total efforts to achieve the project specific DBE goal prior to the bid letting date.

a. Solicitation Guidance for Prime Contractors:

- (1) Document all efforts and decisions made toward achieving the DBE goal on the contract. The bidder should use WisDOT-approved DBE outreach tools, including the UCP DBE Directory and the Bid Express Small Business Network to foster DBE participation on all applicable contracts.
- (2) As needed, request assistance with DBE outreach and follow-up by contacting the Department's DBE Support Services Office by phone or email request at least 14 days prior to the bid letting date. Phone numbers are (414) 438-4584 and/or (608) 267-3849; Fax: (414) 438-5392; E-mail: DBE_Alert@dot.wi.gov
- (3) Participate in and document a substantive conversation with at least one DBE firm per Let, to discuss questions, concerns, and any other contract related matters that may be applicable to the DBE firm. Guidelines for this conversation are provided in Appendix A of ASP-3.
- (4) Request quotes by identifying potential items to subcontract and solicit. In their initial contacts, contractors are strongly encouraged to include a single page, detailed list of items for which they are accepting quotes, by project, within a letting. See attached sample entitled "Sample Contractor Solicitation Letter" in Appendix B. Prime contractors should also indicate a willingness to accept quotes in areas they are planning to perform themselves, as required by federal rules. In some cases, it might be appropriate to use DBE firms to do work in a prime contractor's area of specialization.

- i. Solicit quotes from certified DBE firms who match possible items to subcontract using all reasonable and available means. Additionally, forward copies of solicitations highlighting the work areas for which quotes are being sought to DBE Alert@dot.wi.gov
- ii. Acceptable outreach tools include SBN (Small Business Network, see Appendix C): https://www.bidx.com/wi/main, postal mail, email, fax, and phone.
 - a. Contractors must ask DBE firms for a response in their solicitations. See Sample Contractor Solicitation Letter, Appendix B. This letter may be included as an attachment to the sub-quote request.
 - b. Solicit quotes at least 10 calendar days prior to the letting date to allow DBE firms sufficient time to respond. Prime contractors should contact DBE firms early, asking if they need help organizing their quote, assistance confirming equipment needs, or other assistance supporting their submission of a competitive quote for their services.
 - c. A follow up solicitation should take place within 5 calendar days of the letting date. Email and/or SBN are the preferred method for the solicitation.
- iii. Upon request, provide interested DBE firms with adequate information about plans, specifications, and the requirements of the contract by letter, information session, email, phone call, and/or referral.
- iv. When potential exists, the contractor should advise interested DBE firms on how to obtain bonding, line of credit, or insurance if requested.
- v. Document DBE firm's interest in quoting by taking appropriate steps to follow up initial solicitation with:
 - a. Email to all prospective DBE firms in relevant work areas
 - b. Phone call log to DBE firms who express interest via written response or call
 - c. Fax/letter confirmation
 - d. Signed copy of record of subcontractor outreach effort

b. Guidance for Evaluating DBE quotes

- (1) Quote evaluation practices required to evaluate DBE quotes:
 - i. Reasonable Price: Contractors are expected to assess reasonable price by analyzing the contract scope for DBE subcontract feasibility and comparing common line items in DBE and non-DBE subcontract quotes for the same work. Per federal regulation, reasonable price is not necessarily the lowest price. See 49 CFR Part 26, Appendix A. IV.D(2).
- (2) Documentation submitted by the prime of the following evaluation is required to evaluate DBE quotes by contractors:
 - i. Evaluation of DBE firm's ability to perform "possible items to subcontract" using legitimate reasons, including but not limited to, a discussion between the prime and DBE firm regarding its capabilities prior to the bid letting. If lack of capacity is the reason for not utilizing the DBE firm's quote, the prime is required to contact the DBE by phone and email regarding their ability to perform the work indicated in the UCP directory listed as their work area by NAICS code. Only the work area indicated by the NAICS code(s) listed in the UCP directory can be counted toward DBE credit. Documentation of the conversation is required.
 - a In striving to meet an assigned DBE contract goal, contractors are expected to use DBE quotes that are responsive and reasonable. This includes DBE quotes that are not the low quote.
 - Additional evaluation Evaluation of DBE quotes with <u>tied bid items</u>. Typically, this type of quoting represents a cost saving but is not clearly stated as a discount. Tied quotes are usually presented as an 'all or none' quote. When non-DBE subcontractors submit tied bid items in their quotes, the DBE firm's quote may not appear competitive. In such a case, the following steps are taken in comparing the relevant quotes. These are qualitative examples:

- i Compare bid items common to both quotes, noting the reasonableness in the price comparison.
- Review quotes from other firms for the bid items not quoted by the DBE firm to see if combining both can provide the same competitive advantage that the tied bid items offered.

See Appendix D - Good Faith Effort Evaluation Measures and Appendix E - Good Faith Effort Best Practices.

- c. Requesting Good Faith Effort Evaluation At the time of bid- if the DBE goal is not met in full, the prime contractor must indicate they will file form DT1202- Documentation of Good Faith Effort within 24-hours of bid submission. Supplementary documentation of good faith effort that supports the DT1202 submission is also due within 24-hours of bid submission and prior to bid posting. Supporting documentation for the DT1202 is to include the following:
 - (1) Solicitation Documentation: The names, addresses, email addresses, and telephone numbers of DBE firms contacted along with the dates of both initial and follow-up contact; electronic copies of all written solicitations to DBE firms. A printed copy of SBN solicitation is acceptable.
 - (2) Selected Work Items Documentation: Identify economically feasible work units to be performed by DBEs to include activities such as: list of work items to be performed; breaking up of large work items into smaller tasks or quantities; flexible time frames for performance and delivery schedules.
 - (3) Documentation of Project Information provided to interested DBEs: A description of information provided to the DBE firms regarding the plans, specifications, and estimated quantities for portions of the work to be performed by that DBE firm.
 - (4) Documentation of Negotiation with Interested DBEs: Provide sufficient evidence to demonstrate that good faith negotiations took place. Merely sending out solicitations requesting bids from DBEs does not constitute sufficient good faith efforts.
 - (5) Documentation of Sound Reasoning for Rejecting DBEs and copies of each quote received from a DBE firm and, if rejected, copies of quotes from non-DBEs for same items.
 - (6) Documentation of Assistance to Interested DBEs- Bonding, Credit, Insurance, Equipment, Supplies/Materials
 - (7) Documentation of outreach to Minority, Women, and Community Organizations and other DBE Business Development Support: Contact organizations and agencies for assistance in contacting, recruiting, and providing support to DBE subcontractors, suppliers, manufacturers, and truckers at least 14 days before bid opening. Participate in or host activities such as networking events, mentor-protégé programs, small business development workshops, and others consistent with DBE support.

If the Good Faith Effort documentation is deemed adequate, the request will be approved and the DBE office will promptly notify the Prime Contractor and Bureau of Project Development.

If the DBE Office denies the request, the Prime Contractor will receive written correspondence outlining the reasons. The Department encourages the Prime Contractor to communicate with DBE staff to clarify any questions related to meeting goals and/or contractor demonstration of good faith efforts.

If the contract is awarded, the Prime Contractor must obtain written consent from the DBE Office to change or replace any DBE firm listed on the approved DBE Commitment. No contractor, prime or subsequent tier, shall be paid for completing work assigned to a DBE subcontractor on an approved DBE Commitment unless WisDOT has granted permission for the reduction, replacement, or termination of the assigned DBE in writing. If a prime contractor or a subcontractor on any tier uses its own forces to perform work assigned to a DBE on an approved DBE Commitment, they will not be paid for the work. Any changes to DBE Commitment after the approval of the DBE Commitment must be reviewed and approved by the DBE Office prior to the change (see Section 9).

Additional resources for demonstrating and tracking good faith effort can be found on the "Contracting with a DBE" webpage in the <u>ASP-3 and Good Faith Effort Guidance</u> section.

4. Bidder's Documentation of Good Faith Effort Evaluation Request Appeal Process

A bidder can appeal the Department's decision to deny the bidder's demonstration of Good Faith Effort through Administrative Reconsideration. The bidder must provide a written justification refuting the specific reasons for denial as stated in the Department's denial notice. The bidder may meet in person with the Department if so requested. Failure to appeal within 5 business days after receiving the Department's written notice denying the request constitutes a forfeiture of the bidder's right of appeal. Receipt of appeal is confirmed by email date stamp or certified mail signed by WisDOT staff. A contract will not be executed without documentation that the DBE provisions have been fulfilled.

The Department will appoint a representative who did not participate in the original good faith effort determination, to assess the bidder's appeal. The Department will issue a written decision within 5 business days after the bidder presents all written and oral information. In that written decision, the Department will explain the basis for finding that the bidder did or did not demonstrate an adequate good faith effort to meet the contract DBE goal. The Department's decision is final.

5. Determining DBE Eligibility

Directory of DBE firms

- a. The only resource for DBE firms certified in the State of Wisconsin is the Wisconsin Unified Certification Program (UCP) DBE Directory. WisDOT maintains a current list of certified DBE firms at: http://wisconsindot.gov/Documents/doing-bus/civil-rights/dbe/dbe-ucp-directory.xlsx
- b. The DBE Program office is available to assist with contracting DBE firms:(608) 267-3849.
- c. DBE firms are certified based on various factors including the federal standards from the Small Business Administration that assigns a North American Industrial Classification (NAICS) Codes. DBE firms are only eligible for credit when performing work in their assigned NAICS code(s). If a DBE subcontractor performs work that is not with its assigned NAICS code, the prime contractor should contact the DBE Office to inquire about compatibility with the Business Development Program.

6. Counting DBE Participation

Assessing DBE Work

The Department will only count the DBE usage towards the contract DBE goal if the DBE firm is certified as a DBE by one of the UCP agencies. The Department only counts the value of the work a DBE actually performs towards the DBE goal. The Department assesses the DBE work as follows:

- a. The Department counts work performed by the DBE firm's own resources. The Department includes the cost of materials and supplies the DBE firm obtains for the work. The Department also includes the cost of equipment the DBE firm leases for the work. The Department will not include the cost of materials, supplies, or equipment the DBE firm purchases or leases from the prime contractor or its affiliate, with the exception of non-project specific leases the DBE has in place before the work is advertised.
- b. The Department counts fees and commissions the DBE subcontractor charges for providing bona fide professional, technical, consultant, or managerial services. The Department also counts fees and commissions the DBE charges for providing bonds or insurance. The Department will only count costs the program engineer deems reasonable based on experience or prevailing market rates.
- c. If a DBE firm subcontracts work, the Department counts the value of the work subcontracted to a DBE subcontractor.
- **d.** The contractor will maintain records and may be required to furnish periodic reports documenting its performance under this item.
- e. It is the Prime Contractor's responsibility to determine whether the work that is committed and/or contracted to a DBE firm can be counted for DBE credit by referencing the work type and NAICS code listed for the DBE firm on the Wisconsin UCP DBE Directory.

- f. It is the Prime Contractor's responsibility to assess the DBE firm's ability to perform the work for which it is committing/contracting the DBE to do. Note that the Department encourages the Prime Contractor to assist and develop DBE firms to become fully knowledgeable contractors to successfully perform on its contracts.
- g. The Prime Contractor will inform the DBE office via email of all DBE subcontractors added to the project following execution of the contract. The Prime Contractor may omit submission of another form DT1506, but must submit signed Attachment A forms for additional DBE firms.
- **h.** See Section 7 for DBE credit evaluation for Trucking and Section 8 for DBE credit evaluation for Manufacturers, Suppliers, and Brokers

Naming conventions: When emailing files, please use the following language to identify your submission- "Project #, Proposal #, Let date, Business Name, Attachment A" Email: DBE Alert@dot.wi.gov

*Note: A sublet request is required for DBE work, regardless of subcontract tier, and also for reporting materials or supplies furnished by a DBE.

- Sublet Requests via form DT1925 or WS1925 are required for 1st Tier DBEs
- For all 2nd Tier and below notification of DBE sublet is indicated by the contractor entering them in CRCS

7. Credit Evaluation for Trucking

All bidders are expected to adhere to the Department's current trucking policy posted on the HCCl website at: http://wisconsindot.gov/Documents/doing-bus/civil-rights/dbe/trucking-utilization-policy.pdf

The prime contractor is responsible for ensuring that all subcontractors including trucking firms, receive Form FHWA 1273: https://www.fhwa.dot.gov/programadmin/contracts/1273/1273.pdf

See Section 8 for Broker credit.

8. Credit Evaluation for Manufacturers, Suppliers, Brokers

The Department will calculate the amount of DBE credit awarded to a prime using a DBE firm for the provisions of materials and supplies on a contract-by-contract basis. The Department will count the material and supplies that a DBE firm provides under the contract for DBE credit based on whether the DBE firm is a manufacturer, supplier, or broker. Generally, DBE credit is determined through evaluation of the DBE owner's role, responsibility, and contribution to the transaction. Maximum DBE credit is awarded when the DBE firm manufactures materials or supplies. DBE credit decreases when the DBE firm solely supplies materials, and minimal credit is allotted when the DBE firm's role is administrative or transactional. It is the bidder's responsibility to confirm that the DBE firm is considered a supplier or a manufacturer before listing them on Commitment to Subcontract to DBE form DT1506 or DBE Commitment submitted with the bid.

a. Manufacturers

- (1) A manufacturer is a firm that operates or maintains a factory or establishment that produces, on the premises, the materials, supplies, articles, or equipment required under the contract and of the general character described by the specifications.
- (2) If the materials or supplies are obtained from a DBE manufacturer, **100**% percent of the cost of the materials or supplies counts toward DBE goals.

b. Regular Dealers of Material and/or Supplies

(1) A regular dealer is a firm that owns, operates, or maintains a store, warehouse, or other establishment in which the materials, supplies, articles or equipment of the general character described by the specifications

- and required under the contract are bought, kept in stock, and regularly sold or leased to the public in the usual course of business.
- (2) If the materials or supplies are purchased from a DBE regular dealer, count **60%** percent of the cost of the materials or supplies toward DBE goals.
- (3) At a minimum, a regular dealer must meet the following criteria to be counted for DBE credit:
 - i. The DBE firm must be an established, regular business that engages, as its principal business and under its own name, in the purchase and sale or lease of the products in question.
 - ii. The DBE firm must both own and operate distribution equipment for the product--bulk items such as petroleum products, steel, cement, gravel, stone, or asphalt. If some of the distribution equipment is leased, the lease agreement must accompany the DBE Commitment form for evaluation of the dealer's control before the DBE office approves the DBE credit.
- (4) When DBE suppliers are contracted, additional documentation must accompany the DBE Commitment and Attachment A forms. An invoice or bill-of-sale that includes names of the bidder and the DBE supplier, along with documentation of the calculations used as the basis for the purchase agreement, subcontract, or invoice. WisDOT recognizes that the amount on the Attachment A form may be more or less than the amount on the invoice per b.(1) above.
 - i. The bidder should respond to the following questions and include with submission of form DT1506 or the DBE Commitment entered with bid:
 - a. What is the product or material?
 - b. Is this item in the prime's inventory or was the item purchased when contract was awarded?
 - c. Which contract line items were referenced to develop this quote?
 - d. What is the amount of material or product used on the project?
- (5) Supplies purchased in **bulk** from DBE firms at the beginning of the season may be credited to current contracts if submitted with appropriate documentation to the DBE office.
 - i. To ensure that the appropriate credit is assigned, follow the procedure below:
 - a. When DBE suppliers are contracted for bulk supply or commodity purchases, an invoice or bill-of-sale that includes names of the contractor and the DBE supplier should be submitted to the DBE Office via eSubmit (preferred during letting) or the DBE_Alert email box. The supply/commodity credit may be applied during the federal fiscal year (October- September) in which the purchase was made.
 - b. When the contractor intends to apply the credit to a particular project, submit a copy of the original invoice, documentation of the calculations for supplies/commodities to be used on the project, and an Attachment A. Indicate on the Attachment A:
 - c. This supply/commodity is in the prime's inventory or pre-paid in case of commodities
 - d. The full value of the original invoice submitted to the DBE Office, above in (1)
 - e. The amount of material or product used on this project
 - f. Fuel estimate listed on Attachment A will be recorded as a deduction from the full fuel purchase amount shown on the invoice
 - ii. DBE Office Process (Applies only to bulk purchases)
 - Supply/Commodity commitment is received
 - Engineer verifies amount listed on invoice and enters the full amount into spreadsheet
 - c. The amount of credit applied for each project is updated on the spreadsheet until the bulk purchase is exhausted
 - d. Engineer informs contractor when full amount of bulk purchase has been applied

c. Brokers, Transaction Expediters, Packagers, Manufacturers' Representatives

- (1) No portion of the cost of the materials, supplies, services themselves will count for DBE credit. However, WisDOT will evaluate the fees or commissions charged when a prime purchases materials, supplies, or services from a DBE certified firm which is neither a manufacturer nor a regular dealer, namely: brokers, packagers, manufacturers' representatives, or other persons who arrange or expedite transactions.
- (2) Brokerage fees are calculated as 10% of the purchase amount.
- (3) WisDOT may count the amount of fees or commissions charged for assistance in the procurement of the materials and supplies, fees, or transportation charges for the delivery of materials or supplies required on a job site.
- (4) Evaluation of DBE credit includes review of the contract need for the item/service, the sub-contract or invoice for the item/service, and a comparison of the fees customarily allowed for similar services to determine whether they are reasonable.

9. DBE Commitment Modification Policy (Formerly "DBE Replacement Policy")

a. Issuing a Contract Change Order

Any changes or modifications to the contract once executed are considered contract modifications and as such require a change order. In addition, the DBE office must provide consent for reduction, termination, or replacement of subcontractors approved on the DBE Commitment *in advance* of the modification for the prime contractor to receive payment for work or supplies. Additions to the DBE Commitment do not require advance notification of the DBE office. (see below e. DBE Utilization beyond the approved DBE Commitment)

b. Contractor Considerations

- (1) A prime contractor cannot modify the DBE Commitment through reduction in participation, termination, or replacement of a DBE subcontractor listed on the approved DBE Commitment without prior written consent from the DBE Office. This includes, but is not limited to, instances in which a prime contractor seeks to perform work originally designated for a DBE subcontractor with its own forces or those of an affiliate, a non-DBE firm, or with another DBE firm.
- (2) If a prime contractor reduces participation, replaces, or terminates a DBE subcontractor who has been approved for DBE credit toward its contract, the prime is required to provide documentation supporting its inability to fulfill the contractual commitment made to the Department regarding the DBE utilization.
- (3) The Prime Contractor is required to demonstrate efforts to find another DBE subcontractor to perform at least the same amount of work under the contract as the DBE subcontractor that was terminated, to the extent needed to meet the assigned DBE contract goal. When additional opportunity is available by contract modifications, the Prime Contractor must utilize DBE subcontractors that were committed to equal work items, in the original contract.
- (4) In circumstances when a DBE subcontractor fails to complete its work on the contract for any reason, or is terminated from a contract, the Prime Contractor must undertake efforts to maintain its commitment to the assigned DBE goal.
- (5) The DBE subcontractor should communicate with the Prime Contractor regarding its schedule and capacity in the context of the contract. If the DBE firm anticipates that it cannot fulfill its subcontract, they will advise the Prime Contractor and suggest a DBE subcontractor that may replace their services and provide written consent to be released from its subcontract.
 - i. Before the Prime Contractor can request modification to the approved DBE Commitment, the Prime Contractor must:
 - a. Make every effort to fulfill the DBE Commitment by working with the listed DBE subcontractor to ensure that the firm is fully knowledgeable of the Prime Contractor's expectations for successful performance on the contract. Document these efforts in writing.

- b. If those efforts fail, provide written notice to the DBE subcontractor of the Prime Contractor's intent to request to modify the Commitment through reduction in participation, termination, and/or replacement of the subcontractor including the reason(s) for pursuing this action.
- c. Copy the DBE Office on all correspondence related to changing a DBE subcontractor who has been approved for DBE credit on a contract, including preparation and coordination efforts.
- d. Clearly state the amount of time the DBE firm has to remedy and/or respond to the notice of intent to replace/terminate. The DBE must be allowed five days from the date notice was received as indicated by email time stamp or signed certified mail, to respond, in writing. EXCEPTION: The Prime Contractor must provide a verifiable reason for a response period shorter than five days. For example, a WisDOT project engineer or project manager confirms that WisDOT has eliminated an item the DBE subcontractor was contracted for.
- e. The DBE subcontractor must acknowledge the contract modification with written response to the Prime Contractor and the DBE Office. If objecting to the subcontract modification, the DBE subcontractor must outline the basis for objection to the proposed modification, providing sound reasoning for WisDOT to reject the prime's request.

c. Request to Modify DBE Subcontracting Commitment

The written request referenced above may be delivered by email or fax. The request must contain the following:

- (1) Project ID number
- (2) WisDOT Contract Project Engineer's name and contact information
- (3) DBE subcontractor name and work type and/or NAICS code
- (4) Contract's progress schedule
- (5) Reason(s) for requesting that the DBE subcontractor be replaced or terminated
- (6) Attach/include all communication with the DBE subcontractor to deploy/address/resolve work completion

Naming conventions: When emailing files, please use the following language to identify your submission- "Project #, Proposal #, Let date, Business Name, MODIFICATION" Email: DBE Alert@dot.wi.gov + Project Engineer

WisDOT will review the request and any supporting documentation submitted to evaluate if the circumstance and the reasons constitute good cause for replacing or terminating the approved DBE subcontractor.

Good Causes to Replace a DBE subcontractor according to the federal DBE program guidelines {49 CFR part 26.53}

- The listed DBE subcontractor fails or refuses to execute a written contract
- The listed DBE subcontractor fails or refuses to perform the work of its subcontract in a way consistent with normal industry standards. Provided, however, that good cause does not exist if the failure or refusal of the DBE subcontractor to perform its work on the subcontract results from the bad faith or discriminatory action of the prime contractor
- The listed DBE subcontractor fails or refuses to meet the prime contractor's reasonable, nondiscriminatory bond requirements
- The listed DBE subcontractor becomes bankrupt, insolvent, or exhibits credit unworthiness
- The listed DBE subcontractor is ineligible to work on public works projects because of suspension and debarment proceedings pursuant 2 CFR Parts 180, 215, and 1,200 or applicable state law
- The prime has determined that the listed DBE subcontractor is not a responsible contractor
- The listed DBE subcontractor voluntarily withdraws from the project and provides written notice of its withdrawal
- The listed DBE subcontractor is ineligible to receive DBE credit for the type of work required

• A DBE firm owner dies or becomes disabled with the result that the listed DBE subcontractor is unable to complete its work on the contract.

d. Evaluation and Response to the Request

WisDOT's timely response to the Prime Contractor's request for modification of the approved DBE Commitment will be provided to the prime and the WisDOT project engineer via email.

If WisDOT determines that the Prime Contractor's basis for reduction in participation, replacement, or termination of the DBE subcontractor is not consistent with the good cause guidelines, the DBE office will provide a response via email within 48-hours of receipt of request from the Prime Contractor as indicated by email time stamp. The communication will include: the requirement to utilize the committed DBE, actions to support the completion of the contractual commitment, a list of available WisDOT support services, and administrative remedies, including withholding payment to the prime, that may be invoked for failure to comply with federal DBE guidelines for DBE replacement.

The WisDOT contact for all actions related to modification of the approved DBE Commitment is the DBE Program Engineer who can be reached at DBE_Alert@dot.wi.gov or (414) 335-0413.

e. DBE Utilization beyond the approved DBE Commitment

When the prime or a subcontractor increases the scope of work for an approved DBE subcontractor or adds a DBE subcontractor who was not on the approved form DT1506 or DBE Commitment submitted with bid at any time after contract execution, this is referred to as voluntary DBE contract goal achievement. The contractor must follow these steps to ensure that the participation is accurately credited toward the DBE goal:

- (1) Forward a complete, signed Attachment A form to the DBE Office. A complete Attachment A includes DBE subcontractor contact information, signatures, subcontract value, and description of the work areas to be performed by the DBE. The DBE Office will verify the DBE participation and revise the DBE Commitment based on the email/discussion and the new Attachment A.
- (2) When adding to an existing DBE Commitment, submit a new Attachment A to the DBE Alert mailbox
- (3) OR Submit a final Attachment A to DBE Alert during the Finals Process when Compliance receives notice of "Substantially Complete"

Naming conventions: When emailing files, please use the following language to identify your submission-"Project #, Proposal #, Let date, Business Name, New Attachment A" Email: DBE Alert@dot.wi.gov

Special note on trucking

- DBE truckers added to the sublets in CRCS will be approved without DBE credit (You will see a "N" in CRCS instead of "Y")
- Prime Contractors may enter a "place holder" e.g. \$1000.00, for DBE Trucking in CRCS if the full amount of trucking is unknown for sublet purposes only
- The hiring contractor may obtain the Attachment A with DBE signature included but the **Prime Contractor** must sign the Attachment A before submitting
- DBE truckers need to be added to the DBE commitment once. If the DBE trucker is on the initial commitment (DT1506/E1506) there is no requirement to submit another Attachment A for that trucker for that contract.

10. Commercially Useful Function

- **a.** Commercially Useful Function (CUF) is evaluated after the contract has been executed, while the DBE certified firm is performing contracted work items.
- **b.** The Department uses Form DT1011, DBE Commercially Useful Function Review and Certification to evaluate if the DBE is performing a commercially useful function. WisDOT counts expenditures of a DBE toward the DBE goal only if the DBE is performing a commercially useful function on that contract.

- c. A DBE firm is performing a commercially useful function if the following conditions are met:
 - (1) For contract work, the DBE is responsible for executing a distinct portion of the work and is carrying out its responsibilities by actually performing, managing, and supervising that work.
 - (2) For materials and supplies, the DBE is responsible for negotiating price, determining quality and quantity, ordering, and paying for those materials and supplies.
- **d**. Offsite Hauling when DBE truck will haul between a pit and plant or location other than the construction site associated with the commitment
 - (1) Indicate Offsite Hauling on Attachment A
 - (2) Discuss offsite hauling at weekly progress meetings with Project Engineer (PE)
 - (3) PE conducts spot checks of pits/plants to verify DBE truck is hauling and/or verifying hauling log
 - (4) Prime should be prepared to submit haul tickets, plant/pit tickets, timecards, and other pertinent documentation if requested by PE or DBE Office

11. Credit Evaluation for DBE Primes

WisDOT calculates DBE credit based on the amount and type of work performed by DBE certified firms for work submitted with required documentation. If the prime contractor is a DBE certified firm, the Department will only count the work that the DBE prime performs with its own forces for DBE neutral credit. The Department will also calculate DBE credit for work performed by any other DBE certified subcontractor, DBE certified supplier, and DBE certified manufacturer on the contract in each firm's approved NAICS code/work areas that are submitted with required documentation. Crediting for manufacturers and suppliers is calculated consistent with Section 8 of this document and 49 CFR Part 26.

12. Joint Venture

A joint venture is an association of a DBE firm and one or more other firms to carry out a single, for-profit business enterprise, for which the parties combine their property, capital, efforts, skills and knowledge, and in which the DBE is responsible for a distinct, clearly defined portion of the work of the contract and whose share in the capital contribution, control, management, risks, and profits of the joint venture are commensurate with its ownership interest. If a DBE performs as a participant in a joint venture, the Department will only credit the portion of the total dollar value of the contract equal to the portion of the work that the DBE performs with its own forces.

13. Mentor-Protégé

- **a.** If a DBE performs as a participant in a mentor-protégé agreement, the Department will credit the portion of the work performed by the DBE protégé firm.
- **b.** DBE credit is evaluated and confirmed by the DBE Office for any contracts on which the mentor-protégé team identifies itself to the DBE Office as a current participant of the Mentor-Protégé Program.
 - (1) DBE credit may only be awarded to a non-DBE mentor firm for using its own protégé firm for less than one half of its goal on any contract; and
 - (2) Not award DBE credit to a non-DBE mentor firm for using its own protégé firm for more than every other contract performed by the protégé firm.
- **c.** A DBE protégé firm may be eligible for conditional NAICS code extension for training with the mentor. Request permission from the DBE Office- Certification area.
- **d.** Refer to WisDOT's Mentor-Protégé guidelines for guidance on the number of contracts and amount of DBE credit allowed on WisDOT projects.

14. Use of Joint Checks

The use of joint checks is allowable if it is a commonly recognized business practice in the material industry. A joint check is defined as a two-party check between a DBE subcontractor, a prime contractor, and the regular dealer or materials supplier who is neither the prime nor an affiliate of the prime. Typically, the prime contractor issues one check as payor to the DBE subcontractor and to the supplier jointly (to guarantee payment to the supplier) as payment for the material/supplies used by the DBE firm in cases where the DBE subcontractor and materials have been approved for DBE credit. The DBE subcontractor gains the opportunity to establish a direct contracting relationship with the supplier to potentially facilitate a business rapport that results in a line of credit or increased partnering opportunities.

The cost of material and supplies purchased by the DBE firm is part of the value of work performed by the DBE to be counted toward the goal. To receive credit, the DBE firm must be responsible for negotiating price, determining quality and quantity, ordering the materials, and installing (where applicable) and "paying for the material itself." See 49 CFR 26.55(c)(1).

The approval to use joint checks constitutes a commitment to provide further information to WisDOT, upon request by staff. WisDOT will allow the use of joint checks when the following conditions are met:

- **a.** The Prime Contractor must request permission to use joint checks from the DBE Office by submitting the Application to Use Joint Checks.
 - (1) Request should be made when the DBE Commitment or the Request to Sublet is submitted; the request will not be considered if submitted after the DBE Subcontractor starts its work.
 - (2) Approval/Permission must be granted prior to the issuance of any joint checks.
 - (3) The payment schedule for the supplier must be presented to the DBE office before the first check is issued.
 - (4) The joint check for supplies must be strictly for the cost of approved supplies.
- b. The DBE subcontractor is responsible for furnishing and/or installing the material/work item and is not an 'extra participant' in the transaction. The DBE firm's role in the transaction cannot be limited solely to signing the check(s) to release payment to the material supplier. At a minimum, the DBE subcontractor's tasks should include the following:
 - (1) The DBE subcontractor (not the prime/payor) negotiates the quantities, price, and delivery of materials.
 - (2) The DBE subcontractor consents to sign/release the check to the supplier by signing the <u>Application to Use</u> <u>Joint Checks</u> after establishing the conditions and documentation of payment within the subcontract terms or in a separate written document.
- c. The Prime contractor/payor acts solely as a guarantor.
 - (1) The Prime Contractor agrees to furnish the check used for the payment of materials/supplies under the contract.
 - (2) The prime contractor/payor cannot require the subcontractor to use a specific supplier or the prime contractor's negotiated unit price.

15. Payment

Costs for conforming to this Additional Special Provision (ASP) and any associated DBE requirements are incidental to the contract.

Appendix A Substantive Conversation Guidelines

The substantive conversation is critical to all bidders' demonstration of good faith effort to meet the DBE goal prior to bid opening. Relationship building between primes and subcontractors is crucial to DBE goal attainment. Responsible bidders seek to build rapport with potential DBE subcontractors to understand capacity, areas of expertise, and assess contracting feasibility. Bidders who compete for WisDOT contracts are specialty contractors responding to a growing and changing contract environment. Just as these specialists are responsible for care of the roads, they are likewise responsible for contributing to the health of the industry. The substantive conversation drives collaboration that will build industry health and capacity. The following is intended to provide guidance for such discussions but is not an exhaustive list. Contractors are encouraged to incorporate their existing strategies for cultivating business relationships as well.

Prior to Bid Opening- this discussion should happen as early as possible (WisDOT advertisements are released weeks prior to each Let)

- 1. Determine DBE subcontractor's interest in quoting
- 2. If response indicates inexperience with quoting- offer support/assistance to the DBE in understanding the industry including fundamentals a subcontractor needs to know, required reading and/or resources.
- 3. Assess their interest and experience in the road construction industry by asking questions such as:
 - Have you competed for other WisDOT contracts? Ratio of competed/to wins
 - Have you performed on any transportation industry contracts (locally or with other states)?
 - What the largest contract you've completed?
 - Have you worked in the industry: apprentice, journeyman, safety, inspection etc.?
 - Does this project fit into your schedule? Are you working on any contracts now?
 - Have you reviewed a copy of the plans? Are you comfortable performing within the scope and quantity considerations of this contract?
 - What region do you work in? Home base?
 - Which line items are you considering?
 - Have you read/are you familiar with WisDOT Standard Specifications? Construction Material Manual?
 - Do you understand where your work fits in the project schedule, project phases?

Following Bid Opening- this discussion can happen at any time

- 1. After reviewing their quote, note the following in your discussion:
 - Does the quote look complete? Irregular?
 - Are there errors in the quote? Are items very high or very low?
 - In general, does the quote look competitive?
- 2. Questions and Advice for the bidder to share with the potential DBE subcontractor:
 - What line items would typically be in a competitive quote for a subcontractor of their specialty?
 - How many employees and what is their role/experience/expertise in your firm?
 - Do you have resources for labor (union member, family-based, community-resourced) and capital (banking relationship, bond agent, CPA)?
 - Where have you worked: cities, states, government, commercial, residential/private sector, etc. Explain similarities or differences.
 - Refer them to reliable, trusted, industry resources that can educate or connect them to relevant resources, education/certification resources, more appropriate contract opportunities.
 - Discussion about prime contract and subcontract liability, critical path items, contract quantities, schedule risks, and potential profit/loss (for upcoming known projects or in general).
 - Discussion of bonding, insurance, and overall business risk considerations.

Appendix B

Sample Contractor Solicitation Letter Page 1 (This sample is provided as a guide, not a formatting requirement)

DBE Solicitation - [Month] [Day], [Year] WisDOT Bid Letting

- Attention all DBEs. [Prime Contractor] is actively seeking your quote for the [Month][Day], [Year] Bid Letting. [Prime Contractor] is considering bidding on the projects listed on page 2 as a prime contractor. Please see page 2 for instructions and the sub-contractable opportunities for each proposal.
- **Does [Prime Contractor] accept quotes in areas we might self-perform?** Yes, we do! We support this federal rule and (if needed) we consider areas we might self-perform an opportunity to provide in the field assistance and training if we award your quote.
- Where can DBEs find the plans, specifications & addenda? Please visit [Prime Contractor's] plan room [LINK] or on WisDOT's Highway Construction Contract Information HCCI website: Wisconsin Department of Transportation Highway Construction Contract Information (wisconsindot.gov). This same website can be checked for the contract status.
- What should your quote include? All the costs required to complete the items you propose to perform including labor, equipment, material, and related bonding or insurance. The quote should also note items that you are DBE certified to perform, tied items, and any special terms. Please use page 2 as your cover sheet for your quote.
- **Do you have a question regarding bonding, credit, insurance, equipment, or supplies/materials?** We welcome all DBE questions! Please call [Prime Contractor] and ask to speak with [Contact]. [Prime Contractor] can provide basic information as well as a referral to a trusted industry partner for insurance and bonding needs.

When are quotes due?

- [Month] [Day], [Year] at [Time]. We accept quotes via SBN, email, or fax. Please make every effort to have your quotes in by this time or earlier. Quality check your quote so it includes the correct letting date, project ID, proposal number, unit price and extension.
- Who can DBEs contact for questions, information, clarification or for a quote evaluation? [Project Manager Name] [Phone] [Email]. If you are quoting [Prime Contractor] for the first time, we encourage you to come meet with us in person to discuss the project. Our office hours are 7:30 a.m. 5:00 p.m. On bid day, we are in the office by 6:30 a.m.

Why partner with [Prime Contractor]?

DBE partnership is a core part of [Prime Contractor's] mission. Including DBEs at the beginning of each project is essential in the success of each project. We consider DBEs to be important industry partners who bring dedication and knowledge at various stages during construction. We are proud to be an industry leader with our DBE partnership. Your success as a DBE is our success.

Please check all that apply:

Signs/Posts/Markers

Survey/Staking

Yes, we will be quoting the projects & items listed below

Please take our name off your monthly DBE contact list

No, we are not interested in quoting on the letting or its items referenced below

Sample Contractor Solicitation Letter Page 2

(This sample is provided as a guide, not a formatting requirement)

REQUEST FOR QUOTE

[Prime Contractor] Letting Date: [Month] [Day], [Year] Project IDs: 1234-56-00 (Proposal #1) & 1234-01-78 (Proposal #6)

rime Contractor Contact:	DBE:		
none:			
mail:			
Please circle the proposals an	nd items you will be quoting below and	d contact us with any question	
Proposal	1	6	
County	Dane County	Crawford County	
Clearing & Grubbing	X	Х	
Dump Truck Hauling	X	Х	
Curb/Gutter/Sidewalk	X		
Erosion Control Items		Х	
Excavation	X	Х	
Pavement Marking		Х	
Traffic Control	X		
Sawing	X	Х	
QMP, Base		Х	
Pipe Underdrain	X		
Landscape		Х	
Beam Guard	X		
Electrical	X		

Again, please make every effort to have your quotes into our office by time deadline prior to the letting date.

X

X

Sample Contractor Solicitation Email - Simplified

(This sample is provided as a guide, not a formatting requirement)

ATTENTION DBEs

- [Prime Contractor] specializes in municipal projects in the XX Region(s)
- We have successfully competed for and completed XX WisDOT projects over the past XX years
- Consider [Prime Contractor] your partner on WisDOT Projects

[Prime Contractor] is seeking <u>your</u> subcontractor quote for the XX/XX/20XX WisDOT bid letting on the below projects:

Project	Proposal	County	Region
1234-56-00	2	Dane	SW
1234-01-78	6	Crawford	SW

- Please review the attachments [attach Solicitation Letter] and respond with your intent to quote (or not) along with the work items you are interested in performing and respond via fax or email by <u>date</u>. The quote should note items that you are DBE certified to perform, tied items, and any special terms. Please include labor, equipment, material, and related bonding or insurance.
- If you have any questions regarding bonding, credit, insurance, equipment and/or materials/supplies, please feel free to call [Prime Contractor] and ask for [Contact]. (Include if your company is willing to answer these types of DBE questions)
- o Plans and Specifications can be found: WisDOT HCCI Website: List webpage where plans are located
- If you do choose to quote, please make every effort to have your quote into our office by <u>time and date.</u>
 Make sure the correct letting date, project number, unit price and extension are included in your quote.
- Should you have questions regarding the mentioned project, please call our office at (414) 555-5555 and we will direct you to the correct estimator/project manager.
 Our office hours are 7:30 a.m. 5:00 p.m.

Thank you - we look forward to working with your company on this project!

Prime Contractor Project Manager

Direct: 414-555-555 Cell: 414-555-556

Sample Contractor Solicitation Email to non-DBE WisDOT Subcontractors - Simplified

(This sample is provided as a guide, not a formatting requirement)

ATTENTION WISDOT SUBCONTRACTORS

[Prime Contractor] is considering bidding on the below projects for the XX/XX/20XX WisDOT Bid Letting:

Project	Proposal	County	Region	DBE Goal
1234-56-00	2	Dodge	sw	6.00%
1234-01-78	11	Adams	NC	3.00%
1234-00-99	20	Buffalo	NW	5.00%
1234-00-98	33	Portage	NC	6.00%

The above projects have DBE goals and [Prime Contractor] is committed to DBE inclusion with every project. As such, we are requesting:

- All WisDOT Subcontractors to <u>solicit and utilize</u> DBEs in your quotes.
- DBE participation can be achieved through purchasing materials from DBE suppliers, using DBE subcontractors and/or DBE trucking firms or any combination of these.
- If there is an opportunity to untie an item in your quote so a DBE can be utilized, please look for those opportunities as well.
- Your quote will be evaluated based on the amount of DBE participation your company is able to provide when compared to other quotes for the same work.

If you do choose to quote, please make every effort to have your quote into our office by <u>time and date.</u> Please submit all quotes to [Email]. Make sure the correct letting date, project number, unit price and extension are included in your quote.

Should you have questions regarding the mentioned project, the Project Manager contact is: [Name] [Phone Number] [Email]

Thank you for utilizing DBEs who are trusted industry partners with WisDOT projects.

Prime Contractor Project Manager Direct: 414-555-5555 Cell: 414-555-5566

Appendix C Small Business Network (SBN) Overview

The Small Business Network is a part of the Bid Express® service that was created to ensure that prime bidders have a centralized online location to find subs - including small and disadvantaged business enterprises (DBEs). It is available for prime bidders to use as part of their Basic Service subscription. Within the Small Business Network, **Prime Contractors** can:

- 1. Easily select proposals, work types and items:
 - a. After adding applicable work types, select items that you wish to quote. Enter the sub-quote quantities and add comments, if desired. Adding or removing items and work types can be done quickly. If needed, you can save the sub-quote for later completion.
- 2. Create sub-quotes for the subcontracting community:
 - a. Create sub-quotes with ease using the intuitive sub-quote creator. In seven short steps, you can rapidly create a custom sub-quote directed to all subcontractors that bid on the applicable work types. Steps include: provide contact information and sub-quote expiration date, select letting and proposal, add work types and items, specify terms and conditions, upload attachments, and select vendors.
 - b. Create a sub-quote to send to subcontractors or suppliers that lists the items in a proposal that you want quoted
 - c. Create an unlimited number of sub-quotes for items you want quoted, and optionally mark them as a DBE preferred request.
 - d. Add attachments to sub-quotes.
- 3. View sub-quote requests & responses:
 - a. After logging into the Bid Express service, you can quickly review all of your sub-quote requests and all unsolicited sub-quote requests from subcontractors. To simplify the Small Business Network home screen, sub-quote requests can be hidden with one click if they are not applicable.
 - b. View or receive unsolicited sub-quotes that subcontractors have posted, complete with terms, conditions and pricing.
- 4. View Record of Subcontractor Outreach Effort:
 - a. For each sub-quote produced, a *Record of Subcontractor Outreach Effort* is generated that shows the response statistics for a particular sub-quote. If accepted by the letting agency, this report may serve as proof of a "Good Faith" effort in reaching out to the DBE community.
 - b. Easily locate pre-qualified and certified small and disadvantaged businesses.
 - c. Advertise to small and disadvantaged businesses more efficiently and cost effectively.
 - d. Document your interactions with subs/DBEs by producing an Outreach Report (may be accepted as proof of DBE outreach at the discretion of each agency).

The Small Business Network help small businesses learn more about opportunities, compete more effectively, network with other contractors and subcontractors, and win more jobs. The DBE will provide free SBN accounts to DBEs when requested. Use DBE_Alert@dot.wi.gov to request an account. **DBE firms can:**

- 1. View and reply to sub-quote requests from primes:
 - a. After logging into the Bid Express service, you can quickly review all incoming sub-quote requests and all unsolicited sub-quotes created by your company. Receive notifications by selected work type. To simplify on the Small Business Network home screen, sub-quote requests can be filtered by work types relevant to your interests or hidden with one click if they are not applicable.
- 2. Select items when responding to sub-quote requests from primes:
 - a. You have the freedom to choose and price any number of items when responding to a sub-quote request. Quantities can be modified, and per-item comments are also available.
 - b. View requests for sub-quotes for work that primes have posted for projects they are bidding, add your pricing, terms, and conditions, and submit completed sub-quotes to the requesting primes. c. Add attachments to a sub-quote.
- 3. Create and send unsolicited sub-quotes to specific contractors:
 - a. Create unsolicited sub-quotes with ease using the intuitive sub-quote creator. In eight short steps, you can rapidly create a custom sub-quote directed at any number of specific vendors of your choosing. Steps include: provide contact information and sub-quote expiration date, select letting and proposal, add work types and items, specify terms and conditions, upload attachments, and select vendors.
- 4. Easily select and price items for unsolicited sub-quotes:
 - a. After adding applicable work types, select items that you wish to quote. The extended price calculates automatically, cutting out costly calculation errors. Comments can be provided on a per-item basis as well.
 - b. Create an unsolicited sub-quote that lists the items from a proposal that you want to quote, include pricing, terms and conditions, and send it to selected prime/plan holder.
 - c. Add attachments to a sub-quote.
 - d. Add unsolicited work items to sub-quotes that you are responding to.
- 5. Easy Access to Valuable Information
 - a. Receive a confirmation that your sub-quote was opened by a prime.
 - b. View Bid Tab Analysis data from past bids, including the high, average and low prices of items.
 - c. View important notices and publications from DOT targeted to small and disadvantaged businesses.
- 6. Accessing Small Business Network for WisDOT contracting opportunities
 - a. If you are a contractor not yet subscribing to the Bid Express service, go to **www.bidx.com** and select "Order Bid Express." The Small Business Network is a part of the Bid Express Basic Service.

Appendix D

Good Faith Effort Evaluation Measures by categories referenced in DBE regulations

Bidders must demonstrate that they took all necessary and reasonable steps to achieve the assigned DBE contract goal. For each contract, all bidders must submit documentation indicating the goal has been met <u>or</u> if falling short of meeting the assigned goal, must request a DBE Goal Waiver and document all efforts employed to secure DBE subcontractor participation on Form DT1202.

DBE staff analyze the bidder's documented good faith efforts to determine if action taken was sufficient to meet the goal. Sufficiency is measured contract-by-contract. WisDOT evaluates active and aggressive efforts, quality, quantity, scope, intensity, and appropriateness of the bidder's efforts as a scale of the principles of Good Faith outlined in 49 CFR Part 26, Appendix A. Additional emphasis is placed on the bidder's demonstration of timely submission of documentation and communication with DBE subcontractors, and business development initiatives undertaken to support DBE firm growth.

The following is a sample of good faith effort activities that are rated according to the accompanying rubric. Contractors are encouraged to identify additional activities that align with their business type(s).

- Personal, tailored solicitation to firms that specialize in work types planned or desired for subcontracting
- Follow up to initial solicitation via email or phone
- Substantive conversation including topics such as contract liability, critical path work items, schedule risks, and potential profit/loss
- SBN utilization including posting quotes
- Review and response to DBE quotes including provision of information about plans, specifications, and requirements as applicable
- Documentation requesting subcontractors support DBE goal by solicitation and inclusion of DBE subcontractor quotes
- Responsive and timely submission of organized documentation
- Analysis of number of DBE firms who do work types that you typically subcontract
- Analysis of number of DBE firms who reside in geographical areas where prime seeks work
- Analysis of firms who express interest in bidding/quoting including the number of firms who declined your solicitation
- Reference check of DBE subcontractor work or training (documentation of questions and response required)
- Number of different efforts undertaken to meet the assigned DBE goal as documented in accompanying Form DT1202
- Submission of all DBE quotes received matched with a variety of work to be performed by DBEs
- Number and names of DBE firms provided written advice, or referral to industry-specific business development resources
- Overall pattern of DBE utilization on all WisDOT contracts which may include contracting with municipalities
- Documentation of resources expended to meet assigned DBE goal (#of hours, staff titles, average pay rate, actions taken)
- Analysis of subcontractable work items to be completed by prime beyond prime contractor's 30%
- Risk analysis of work items that are typically in tied quotes that could be unbundled
- List of contract work items in smallest economically feasible units, identifying schedule impact
- Submission of a Gap Analysis identifying DBE skillset and/or industry needs
- Staff training in EEO and Civil Rights laws as documented in training logs
- Written Capacity Assessment completed with DBE firm documenting its ability to perform the work quoted
- DBE engagement efforts beyond simple solicitation that include a substantive discussion, initiated as early in the acquisition process as possible (points added for each day prior to letting)
- Outreach and marketing efforts with minority, women, and veteran-focused organizations at least 10 days prior to bid opening
- Active involvement in WisDOT's Business Development Program, TrANS training, facilitated networking efforts, workshops
- Customized teaching/training efforts for future opportunities with DBE subcontractor, contract specific and/or annually
- Introduction and reference provided for DBE subcontractor to a prime who has not previously contracted with the DBE firm
- Prime utilization of a DBE subcontractor the prime has not contracted with previously
- Written referral/recommendation to bond/insurance agents, manufacturer, supplier
- Documented efforts fostering DBE participation through administrative and/or technical assistance
- Evidence of negotiation with the DBE firm about current and future Let opportunities
- Recommendation of local and state services that support small business and access to opportunity: DOA, SBA, WEDC, WPI, etc.

GFE Evaluation Rubric – Phase 1 – Initial Review

DT1202	Examples	Rating	OBOEC Feedback
Solicitation Documentation	Identify all reasonable and available activities performed to solicit the interest of all certified DBEs who have capacity and ability to perform work on the project. Such as: Updated solicitation letter and email, timely		
	solicitation, and follow-up, and/or utilized various methods to communicate solicitation (ex: letter, email, publication, posting and/or website)		
Selected Work Items Documentation	All work items are broken out into economically feasible units to facilitate DBE participation.		
	Such as: Selected work items are specific to each proposal and clearly identified in all solicitation(s)		
Documentation of Project Information provided to Interested DBEs	Provide interested DBEs with adequate information about the plans, specifications, and any other contractual requirements in a timely manner to assist DBEs in response to solicitation.		
	Such as: Project information is clearly identified in all solicitation(s)		
Documentation of Negotiation with Interested DBEs	Provide sufficient evidence demonstrating that good faith negotiations took place during the bid letting.		
	Such as: Documented attempts with DBEs or on behalf of DBEs to increase DBE participation		
Documentation of Sound Reason for Rejecting DBEs	Provide sufficient evidence demonstrating that DBEs are rejected for sound reasons.		
	Such as: Detailed and thoughtful analysis that considers both the percentage and dollar difference when rejecting a DBE including past performance, relevant business experience and stability, safety record, business ethic and integrity, technical capacity, and other tangible factors.		
Documentation of Assistance to Interested DBEs- bonding, credit, insurance, equipment, supplies/materials	Documented assistance in both solicitation(s) and outreach to DBEs.		
Documentation of Outreach to Minority, Women, and Community organizations and other DBE Business Development Support	Effectively use the services of minority, women, and community organizations as well as contractors' groups, local, state, and federal business assistance offices and organization that provide assistance in recruiting and supporting DBEs, as well participation in activities that support DBE business development.		
	Such as: Variety of activities that translate into meaningful DBE participation		
Documentation of other GFE activities	Such as: Used DT1202 Excel Workbook, Diversity & Inclusion company policy, Mentor-Protégé participant, awarded neutral DBE after bid submission, included company GFE overview/strategy information and/or company website highlights DBE opportunities and participation		
Overall Demonstration of GFE			

GFE EVALUATION RATING LEGEND – PHASE 1 – Initial Review

Documentation provided by bidder is evaluated and rated on the rubric. Bidders should include activities characterized by the following types of effort:

ACTIVE & AGGRESSIVE: Demonstrated through engaged and assertive activity

QUALITY: Demonstrated through essential character of conscientious and serious activity

QUANTITY: Demonstrated through a measurable number of activities

SCOPE & INTENSITY: Demonstrated through a rigorous approach to an appropriate and purposeful range of activities

TIMING: Demonstrated through engagement efforts beyond simple solicitation, initiated early in the process

GFE EVALUATION - PHASE 2 - Team Review

GFE Team completes:

- Review of activities included on the rubric
- Review of the intent to award and sound reasoning submitted by Prime
- Bid analysis to confirm if any bid submitted met the DBE goal
- Review average of other bidders DBE goal achievement
- Team review of combined efforts documented in Phase 1 and 2 constitute final GFE determination

Rating Scale:

GFE Approval:

Bona Fide = 6 or more categories color coded green.

Genuine effort characterized by sincere and earnest activities - "Solicitation" and "Sound Reasoning" must be green

GFE Approval:

Sufficient = 5 or more categories color coded green or yellow

Adequate effort documented with a variety of quality activities – "Solicitation" and "Sound Reasoning" must be green or yellow

GFE Denial:

Pro Forma efforts = 4 or less categories color coded green or yellow. Perfunctory effort characterized by routine or superficial activities

Green = Exceeds expectations

Yellow = Meets expectations

Red = Areas in need of attention and/or absence of documentation

See OBOEC Rubric Analysis Feedback

Excerpt from Appendix A to 49 CFR Part 26:

V. In determining whether a bidder has made good faith efforts, it is essential to scrutinize its documented efforts. At a minimum, you must review the performance of other bidders in meeting the contract goal. For example, when the apparent successful bidder fails to meet the contract goal, but others meet it, you may reasonably raise the question of whether, with additional efforts, the apparent successful bidder could have met the goal. If the apparent successful bidder fails to meet the goal but meets or exceeds the average DBE participation obtained by other bidders, you may view this, in conjunction with other factors, as evidence of the apparent successful bidder having made good faith efforts. As provided in §26.53(b)(2)((vi), you must also require the contractor to submit copies of each DBE and non-DBE subcontractor quote submitted to the bidder when a non-DBE subcontractor was selected over a DBE for work on the contract to review whether DBE prices were substantially higher; and contact the DBEs listed

GFE RUBRIC ANALYSIS	GFE RUBRIC ANALYSIS				
OBOEC DECISION	APPROVAL OR DENIAL				
Prime Contractor					
Proposal					
Project					
Bid Letting					
DBE Goal Amount					
DBE Goal Amount Achieved					
Bid Analysis					
Goal %	Achieved %				
Apparent Low Bidder	%				
Bidder B					
Bidder C					
Average of OTHER Bidders (Not including Apparent Low Bidder)					
DBE Quotes Received					
DBE Quotes Awarded					
DBE Quote(s) Rejected	Rejected Quote Analysis				
DBE Quote(s) Awarded	Awarded DBE Amount				

Appendix E Good Faith Effort Best Practices

This list is not a set of requirements; it is a list of potential strategies

Primes

- Prime contractor open houses inviting DBE firms to see the bid "war room" or providing technical assistance.
- Participate in speed networking and mosaic exercises as arranged by DBE office.
- Host information sessions not directly associated with a bid letting.
- Participate in a formal mentor protégé or joint venture with a DBE firm.
- Participate in WisDOT advisory committees i.e. TRANSAC, or Mega Project committee meetings.
- Facilitate a small group DBE 'training session' clarifying how your firm prepares for bid letting, evaluates subcontractors, preferred qualifications, and communication methods.
- > Encourage subcontractors to solicit and highlight DBE participation in their quotes to you.
- Quality of communication, not quantity creates the best results. Contractors should be thorough in communicating with DBE firms before the bid and provide any assistance requested to assure best possible bid.

DBE

- ➤ DBE firms should contact primes as soon as possible with questions regarding their quotes or bid; seven days prior is optimal.
- Continually check for contract addendums on the HCCI website through the Thursday prior to letting to stay abreast of changes.
- Review the status of contracts on the HCCI website reviewing the 'apparent low bidder' list and bid tabs at a minimum.
- Prepare a portfolio or list of related projects and prime and supplier references; be sure to note transportation related projects of similar size and scope, firm expertise and staffing.
- Participate in DBE office assessment programs.
- Participate on advisory and mega-project committees.
- Sign up to receive the DBE Contracting Update.
- Consider membership in relevant industry or contractor organizations.
- Active participation is a must. Quote as many projects as you can reasonably work on; quoting the primes and bidding as a prime with the Department are the only ways to get work.

Appendix F Good Faith Effort Evaluation Guidance Appendix A of 49 CFR Part 26

I. When, as a recipient, you establish a contract goal on a DOT-assisted contract for procuring construction, equipment, services, or any other purpose, a bidder must, in order to be responsible and/or responsive, make sufficient good faith efforts to meet the goal. The bidder can meet this requirement in either of two ways. First, the bidder can meet the goal, documenting commitments for participation by DBE firms sufficient for this purpose. Second, even if it doesn't meet the goal, the bidder can document adequate good faith efforts. This means that the bidder must show that it took all necessary and reasonable steps to achieve a DBE goal or other requirement of this part which, by their scope, intensity, and appropriateness to the objective, could reasonably be expected to obtain sufficient DBE participation, even if they were not fully successful.

II. In any situation in which you have established a contract goal, Part 26 requires you to use the good faith efforts mechanism of this part. As a recipient, you have the responsibility to make a fair and reasonable judgment whether a bidder that did not meet the goal made adequate good faith efforts. It is important for you to consider the quality, quantity, and intensity of the different kinds of efforts that the bidder has made, based on the regulations and the guidance in this Appendix.

The efforts employed by the bidder should be those that one could reasonably expect a bidder to take if the bidder were actively and aggressively trying to obtain DBE participation sufficient to meet the DBE contract goal. Mere pro forma efforts are not good faith efforts to meet the DBE contract requirements. We emphasize, however, that your determination concerning the sufficiency of the firm's good faith efforts is a judgment call. Determinations should not be made using quantitative formulas.

- III. The Department also strongly cautions you against requiring that a bidder meet a contract goal (i.e., obtain a specified amount of DBE participation) in order to be awarded a contract, even though the bidder makes an adequate good faith efforts showing. This rule specifically prohibits you from ignoring bona fide good faith efforts.
- IV. The following is a list of types of actions which you should consider as part of the bidder's good faith efforts to obtain DBE participation. It is not intended to be a mandatory checklist, nor is it intended to be exclusive or exhaustive. Other factors or types of efforts may be relevant in appropriate cases.
- A. (1) Conducing market research to identify small business contractors and suppliers and soliciting through all reasonable and available means the interest of all certified DBEs that have the capability to perform the work of the contract. This may include attendance at pre-bid and business matchmaking meetings and events, advertising and/or written notices, posting of Notices of Sources Sought and/or Requests for Proposals, written notices or emails to all DBEs listed in the State's directory of transportation firms that specialize in the areas of work desired (as noted in the DBE directory) and which are located in the area or surrounding areas of the project.
- (2) The bidder should solicit this interest as early in the acquisition process as practicable to allow the DBEs to respond to the solicitation and submit a timely offer for the subcontract. The bidder should determine with certainty if the DBEs are interested by taking appropriate steps to follow up initial solicitations.

- B. Selecting portions of the work to be performed by DBEs in order to increase the likelihood that the DBE goals will be achieved. This includes, where appropriate, breaking out contract work items into economically feasible units (for example, smaller tasks or quantities) to facilitate DBE participation, even when the prime contractor might otherwise prefer to perform these work items with its own forces. This may include, where possible, establishing flexible timeframes for performance and delivery schedules in a manner that encourages and facilitates DBE participation.
- C. Providing interested DBEs with adequate information about the plans, specifications, and requirements of the contract in a timely manner to assist them in responding to a solicitation with their offer for the subcontract.
- D. (1) Negotiating in good faith with interested DBEs. It is the bidder's responsibility to make a portion of the work available to DBE subcontractors and suppliers and to select those portions of the work or material needs consistent with the available DBE subcontractors and suppliers, so as to facilitate DBE participation. Evidence of such negotiation includes the names, addresses, and telephone numbers of DBEs that were considered; a description of the information provided regarding the plans and specifications for the work selected for subcontracting; and evidence as to why additional Agreements could not be reached for DBEs to perform the work.
- (2) A bidder using good business judgment would consider a number of factors in negotiating with subcontractors, including DBE subcontractors, and would take a firm's price and capabilities as well as contract goals into consideration. However, the fact that there may be some additional costs involved in finding and using DBEs is not in itself sufficient reason for a bidder's failure to meet the contract DBE goal, as long as such costs are reasonable. Also, the ability or desire of a prime contractor to perform the work of a contract with its own organization does not relieve the bidder of the responsibility to make good faith efforts. Prime contractors are not, however, required to accept higher quotes from DBEs if the price difference is excessive or unreasonable.
- E. (1) Not rejecting DBEs as being unqualified without sound reasons based on a thorough investigation of their capabilities. The contractor's standing within its industry, membership in specific groups, organizations, or associations and political or social affiliations (for example union vs. non-union status) are not legitimate causes for the rejection or non-solicitation of bids in the contractor's efforts to meet the project goal. Another practice considered an insufficient good faith effort is the rejection of the DBE because its quotation for the work was not the lowest received. However, nothing in this paragraph shall be construed to require the bidder or prime contractor to accept unreasonable quotes in order to satisfy contract goals.
- (2) A prime contractor's inability to find a replacement DBE at the original price is not alone sufficient to support a finding that good faith efforts have been made to replace the original DBE. The fact that the contractor has the ability and/or desire to perform the contract work with its own forces does not relieve the contractor of the obligation to make good faith efforts to find a replacement DBE, and it is not a sound basis for rejecting a prospective replacement DBE's reasonable quote.
- F. Making efforts to assist interested DBEs in obtaining bonding, lines of credit, or insurance as required by the recipient or contractor.
- G. Making efforts to assist interested DBEs in obtaining necessary equipment, supplies, materials, or related assistance or services.

H. Effectively using the services of available minority/women community organizations; minority/women contractors' groups; local, State, and Federal minority/women business assistance offices; and other organizations as allowed on a case-by-case basis to provide assistance in the recruitment and placement of DBEs.

V. In determining whether a bidder has made good faith efforts, it is essential to scrutinize its documented efforts. At a minimum, you must review the performance of other bidders in meeting the contract goal. For example, when the apparent successful bidder fails to meet the contract goal, but others meet it, you may reasonably raise the question of whether, with additional efforts, the apparent successful bidder could have met the goal. If the apparent successful bidder fails to meet the goal, but meets or exceeds the average DBE participation obtained by other bidders, you may view this, in conjunction with other factors, as evidence of the apparent successful bidder having made good faith efforts. As provided in §26.53(b)(2)((vi), you must also require the contractor to submit copies of each DBE and non-DBE subcontractor quote submitted to the bidder when a non-DBE subcontractor was selected over a DBE for work on the contract to review whether DBE prices were substantially higher; and contact the DBEs listed on a contractor's solicitation to inquire as to whether they were contacted by the prime. Pro forma mailings to DBEs requesting bids are not alone sufficient to satisfy good faith efforts under the rule.

VI. A promise to use DBEs after contract award is not considered to be responsive to the contract solicitation or to constitute good faith efforts.

[79 FR 59600, Oct. 2, 2014]

Appendix G

(SAMPLE) Forms DT1506 and DT1202

Official Form DT1506 can be found here: https://wisconsindot.gov/Documents/formdocs/dt1506.pdf

COMMITMENT TO SU						Departmen		sportation
DT1506 12/2021 s.84.06(2)			40 . 50	Project ID: Proposal#				
Prime Contractor: County:				Letting Date:				
This contract requires that a spec	ified percentage	of the work be subcontra	acted to a	Total \$ Value of				
disadvantaged business enterpris described in ASP-3. The submitte	se and that this i	nformation be submitted h the bid proposal consti	as utes vour	Prime Contract: DBE Contract Go	\$	%		
DBE commitment. Include Attach	ment A for DBE	s included on commitmer	t.	DBE Goal Achiev	-	0.00%		
This form must be completed	and returne	d for this proposal.			1			
1. DBE Firm	2. Work or Ite	ms to be subcontracted	3. Supplier Y/N	4. Trucking Only	5. DBE F Subconti		6. DBE a	
				O# L#				
				O# L#				
				O# L#				
				O# L#				
				0#				
				L# O#				
				L# O#				
				L#				
				O# L#				
				O# L#				
				O# L#				
				O# L#				
				0#				
				L# O#				
				L# O#				
	<u>, </u>			L# O#				
				L#				
				L#				
				O# L#				
				O# L#				
				O# L#				
				O#				
				L# O#				
	-			L# O#				
				L#				
					\$	0.00	\$	0.00
Government L Approved Ar	nounts							
A = \$ V = \$	% %		3	Deima Daueraset	Aire Circ	otum- O 7		
V - 5 Total = \$	%			Prime Representa	uve Sign	ature & L	Jate	
Signature:								
Date: Good faith effort approved:	Yes 🗌 N	lo 🗆		DBE Office Signat	ure & Da	te Appro	ved	

1

COMMITMENT TO SUBCONTRACT TO DBE ATTACHMENT A

CONFIRMATION OF PARTICIPATION

Project I.D.:		Prop	osal Number:		
Letting Date:					
Name of DBE Firm Participat	ing in this Contract:				
Name of the Prime/Subcontra	actor who hired the DBE	Firm:	(list all names of tiers if more th	nan one)	
Type of Work or Type of Mate	erial Supplied:				
Total Subcontract Value:			Total DBE Credit Value:		
		Prime	e Contractor Representative's Sigr	ature	
FOR PRIME CONTRACTORS O	ts with the participating	Prime	e Contractor Representative's Nan	ne (Print Nam	ne)
	DBE firm to perform the type of work listed or supply the material indicated above for the subcontract value listed		Prime Contractor (Print Company Name)		
		Date			
FOR PARTICIPATING DBE FIR	s with the Prime	Parti	cipating DBE Firm Representative	s Signature	Date
Contractor or the Hiring Contract work or supply the material indic subcontract value listed above.		Participating DBE Firm Representative's Name (Print Name)			
FOR DBE TRUCKING FIRMS C	credit, only trucks listed	Participating DBE Firm (Print Company Name)			
on my WisDOT approved Schedule of Owned/Leased Vehicles for DBE Credit form and I will be utilizing the number of trucks as listed below.		DBE	Firm's Address:		
# Owned Trucks	# Leased Trucks		# DBE-Owned Leased Trucks	00 00000	-DBE-Owned sed Trucks
Off site Hauling					



DOCUMENTATION:OF:GOOD:FAITH:EFFORT:

Wisconsin-Department-of-Transportation DT1202......3/2020

+

Project ID	Proposal-No.	Letting
Prime Contractor		County
Person Submitting Document		Telephone-Number
Address		Email-Address

All-bidders-must-undertake-necessary-and-reasonable-steps-to-achieve-the-assigned-DBE-contract-goal-per-federal-regulatory-guidance-at-49-CFR-Part-26.-Bidders-use-this-form-to-document-all-efforts-employed-to-meet-the-assigned-goal-as-a-record-of-contractor-good-faith-efforts-(GFE).-Refer-to-ASP3-or-49-CFR-Part-26-for-guidance-on-actions-that-demonstrate-good-faith-effort.

It is critical to list-all-efforts, attach-documentation, and follow the instructions to complete this submission.

Documentation of good faith effort includes copies of each DBE and non-DBE subcontractor quote submitted to the bidder for the same line items. Utilize the sample documentation logs to document and organize efforts.

Submit-good faith effort documentation per ASP-3 guidelines.

Instructions: Provide a narrative description of all activities pursued to demonstrate good faith efforts, any corresponding documentation, and applicable explanation on separate pages. Include the following items, organized in the order listed below.

1.→ Solicitation Documentation:

- a. Purpose: To identify all-reasonable and available activities the bidder-performed to solicit the interest of all-certified DBEs who have the capacity and ability to perform work on the project. All-solicitation efforts should begin as early as possible to ensure DBEs have ample time to respond and ask-questions.
- b. Action: Identify and list-all activities engaged in to solicit DBEs using all reasonable and available means such as written notice and follow-up communications; substantive conversations; pre-bid-meetings; networking events; market-research; advertising.

2.→ Selected·Work·Items·Documentation:

- a.→ Purpose: To ensure that all work items are broken out into economically feasible units to facilitate DBE participation. This must occur-even when you prefer to perform the work yourself.
- b. Action: Identify economically feasible work units to be performed by DBEs to include activities such as: list of work items to be performed; breaking up of large work items into smaller tasks or quantities; flexible time frames for performance and delivery schedules.

3.→ Documentation of Project Information provided to Interested DBEs:

- a.→ Purpose: To provide interested DBEs with adequate information about the plans, specifications, and any other contractual requirements in a timely manner to assist DBEs in response to solicitation.
- b.→ Action: Provide DBEs · access · to · plans, · specifications, · and · other · contract · requirements . · Early · solicitation · allows · ample · opportunity · to · provide · project · information, · links · to · Let · advertisements, · and · substantive · engagement · with · DBEs.

4.→ Documentation of Negotiation with Interested DBEs:

- a.→ Purpose: To ensure that negotiations with interested DBEs were made in good faith providing evidence as to why agreements could not be reached for DBEs to perform work.
- b. Action: Provide-sufficient evidence to demonstrate that good-faith negotiations took-place. Merely-sending-out-solicitations requesting-bids from DBEs does not constitute sufficient good-faith efforts. A bidder using good-business judgment considers a number of factors in negotiating with all subcontractors, and the firm's price and capabilities in addition to contract goals are taken into consideration. However, the fact that there may be some additional costs involved in finding and using DBEs is not in itself sufficient reason for failing to meet the DBE goal as long as costs are reasonable. (see 49 CFR Part 26 Appendix A)

5.→ Documentation·of·Sound·Reason·for·Rejecting·DBEs:

- a.→ Purpose: To ensure that bidders avoid rejecting DBEs as unqualified without sound reasons. Reasons for rejection must be based on thorough investigation of DBE capabilities.
- b. Action: Provide-sufficient-evidence to demonstrate that DBE-was rejected for sound reasons such as past-performance, relevant business experience and stability, safety record, business ethic and integrity, technical capacity, other tangible factors.

6.→ Documentation·of·Assistance·to·Interested·DBEs-·Bonding,·Credit,·Insurance,·Equipment,· Supplies/Materials:·

- a.→ Purpose: To assist interested DBEs in obtaining bonds, lines of credit, insurance, equipment, supplies, materials, and other assistance or services.
- b. Action: Assist-interested DBEs in obtaining bonding, lines of credit or insurance, and provide technical assistance or information related to plans, specifications, and project requirements. Assist DBEs in obtaining equipment, supplies, materials or other services related to meeting project requirements (excluding supplies or equipment the DBE purchases from the prime).

7.→ Documentation of outreach to Minority, Women, and Community Organizations and other DBE Business Development Support:

- a.→ Purpose: To effectively use the services of minority, women, and community organizations as well as contractors groups, local, state, and federal business assistance offices and organization that provide assistance in recruiting and supporting DBEs, as well as participation in activities that support DBE business development.
- b.→Action: Contact-organizations and agencies for assistance in contacting, recruiting, and providing support to DBE subcontractors, suppliers, manufacturers, and truckers at least 14 days before bid opening. Participate in or host activities such as networking events, mentor-protégé programs, small business development workshops, and others consistent with DBE support.

Return to: Wisconsin-Department of Transportation DBE-Program-Office PO-Box-7965 Madison, WI-53707-7965 DBE_Alert@dot.wi.gov

I-certify-that-I-have-utilized-comprehensive-good-faith-efforts-to-solicit-and-utilize-DBE-firms-to-meet-the-DBE-participation-requirements-of-this-contract-proposal, as-demonstrated-by-my-responses-and-as-specified-in-Additional-Special-Provision-3-(ASP-3). I-certify-that-the-information-given-in-the-Documentation-of-Good-Faith-Efforts-is-true-and-correct-to-the-best-of-my-knowledge-and-belief I-further-understand-that-any-willful-falsification,-fraudulent-statement,-or-misrepresentation-will-result-in-appropriate-sanctions,-which-ma							
involve debarment and/or prosecution under applicable state (Tra	ns·504)·and·Federal·laws.						
	(Bidder/Authorized Representative Signature)						
	00000						
	(Print-Name)						
	2000						
}	(Title)						

Good·Faith·Effort·-·Sample·Documentation·Logs

The sample logs below are provided as guides rather than exhaustive list. See ASP3, Appendix A for additional examples of demonstrable good faith efforts. Attach documentation for each activity listed.

Acceptable forms of documentation include copies of solicitations sent to DBEs, notes from substantive conversations and negotiations with DBEs, copies of advertisements placed, email-communications, all quotes received from DBEs and from all subcontractors who were considered alongside DBE quotes, proof of attendance at applicable networking events; flyers for events or workshops for DBEs offered by the prime, and other physical records of good faith efforts activities.

SOLICITATION-LOG-

Date	Activity	Name-of-DBE-Solicited	Follow-up
4/1/2020	Sent-May-Let-solicitation	Winterland Electric	Spoke-with-Mark-Winterland-on-4/15/20-to-ask-if- he-would-quote-

SELECTED WORK-ITEMS-SOLICITED LOG

Work-Type	DBE-Firm	Contact-Person	Date	Contact·Mode
Payament Madrine	ABC-Marking	Leslie·Lynch	4/1/2020	Email; phone
Pavement-Marking	#1-Marking-Co.	Mark-Smart	4/1/2020	Email;·left·VM
El-atrical	Winterland·Electric	Tabitha-Tinker	4/3/2020	Email,·left·VM
Electrical	Superstar-Wiring	Jose-Huascar	4/3/2020	Email; phone

INFORMATION-PROVIDED-LOG

Request- Date	DBE-Firm	Information·Requested·&·Provided	Response- Date
4/1/2020		Requested-info-on-electrical-requirements;-provided- plan-and-link-to-specs	4/3/2020
4/21/2020	Absolute-Construction	Wanted to know how and when supplies are paid for by WisDOT; referred to spec that covers stockpiling	4/21/2020

NEGOTIATIONS:LOG

Date	DBE-Firm	Contact-Name	Work-Type	Quotes- Rec'd?	Considere d-for- project?	If-not-selected, why?
4/12/2020	ABC-Landscape	John-Dean	Erosion-Control	Yes	No	Cannot-perform-all-items
4/17/2020	Wild-Ferns	Sandy-Lynn	Erosion-Control	Yes	Yes	
4/20/2020	#1·Marking	Mark-Smart	Electrical	Yes	Yes	

ASSISTANCE-LOG

Date	DBE-Firm	Contact-Person	Assistance-Provided
4/1/2020	ABC-Sawing	Jackie-Swiggle	Informed·DBE·on·how·to·obtain·bonding
4/17/2020	Supreme-Construction		Provided-contact-for-wholesale-supply- purchase

OUTREACH & BUSINESS DEVELOPMENT LOG

Date	Agency/Organization· Contacted	Contact-Person	Assistance Requested
4/1/2020	Women-in-Construction	LaTonya-Klein	Contact-information-for-woman-owned-suppliers
4/28/2020	WBIC	Sam-Smith	Asked-for-information-to-provide-to-DBE-regarding- financing-programs-through-WBIC

Official Form DT1202 can be found here: https://wisconsindot.gov/pages/global-footer/formdocs/default.aspx

ADDITIONAL SPECIAL PROVISION 4

This special provision does not limit the right of the department, prime contractor, or subcontractors at any tier to withhold payment for work not acceptably completed or work subject to an unresolved contract dispute.

Payment to First-Tier Subcontractors

Within 10 calendar days of receiving a progress payment for work completed by a subcontractor, pay the subcontractor for that work. The prime contractor may withhold payment to a subcontractor if, within 10 calendar days of receipt of that progress payment, the prime contractor provides written notification to the subcontractor and the department documenting "just cause" for withholding payment.

The prime contractor is not allowed to withhold retainage from payments due subcontractors.

Payment to Lower-Tier Subcontractors

Ensure that subcontracting agreements at all tiers provide prompt payment rights to lower-tier subcontractors that parallel those granted first-tier subcontractors in this provision.

Acceptance and Final Payment

Within 30 calendar days of receiving the semi-final estimate from the department, submit written certification that subcontractors at all tiers are paid in full for acceptably completed work.

Additional Special Provision 6 (ASP-6) Modifications to the standard specifications

Make the following revisions to the standard specifications.

107 Legal Relations and Responsibility to the Public

Add subsection 107.27 effective with the November 2024 letting.

107.27 Drones or Unmanned Aircraft Systems (UAS)

107.27.1 Licensing and Compliance

- (1) Obtain and possess the necessary Federal Aviation Administration (FAA) licenses and certifications to operate drones commercially (https://www.faa.gov/uas).
- (2) Comply with all FAA regulations, airspace restrictions, and local laws. Operators of small drones that are less than 55 pounds for work or business must follow all requirements as listed in Title 14, Chapter 1, Subchapter F, Part 107 of the Code of Federal Regulations (14 CFR) and obtain a remote pilot certificate (https://www.faa.gov/uas/commercial_operators).
- (3) Comply with Wisconsin State Statute 942.10. Limit operations to the specific approved purpose and employ reasonable precautions to avoid capturing images of the public except those that are incidental to the project.
- (4) Provide copies of waivers required for specific project conditions to the engineer prior to any flight.

107.27.2 Flight Approval, Safety, and Incident Reporting

- (1) Submit information in 107.27.2(2) to obtain written drone flight approval from the engineer at least 3 business days prior to operating a drone within the right-of-way. Do not operate a drone within the right-of-way unless approved by the engineer.
- (2) Drone flight application for review and approval must include:
 - UAS pilot information and qualifications, images of certification
 - UAS drone information and FAA tail numbers
 - Max/ Min allowable flight parameters (weather)
 - Specifics of flight mission: capture scope
 - Estimated flight duration
 - Pre-flight checklist
 - Site-specific parameters
 - Notification protocols Federal/Local/Agency/Owner/Responsible in Charge
 - Confirmation and verification of approved operators and hardware
 - Flight plan map diagram (including launch and landing location)
 - FAA-Airspace flight map classification and confirmation with graphics
 - UAS incident management protocol
- (3) If contractor is requesting multiple types of the same flight, a simplified request can be submitted listing weekly flight plan.
- (4) Safety measures must include but are not limited to:
 - Regular training and updates on drone regulations are required and must be provided upon request.
 - Drones must be operated in accordance with safety guidelines, including maintaining a safe distance from people, structures, vehicles, etc.
 - Conduct a pre-flight safety assessment, considering weather conditions, airspace restrictions, and potential hazards.
 - Emergency procedures (e.g., drone malfunction, loss of control) must be documented and followed.
 - All incidents must be reported to the engineer.
- (5) If the drone has an incident during flight, report the following to the engineer:
 - Incident background and details.
 - FAA (14 CFR 107.9) and NTSB (49 CFR 870) notification protocol.
 - Contractor internal notification protocol.

107.27.3 Insurance Requirements

- (1) Maintain drone liability insurance with the following limits.
 - 1. For drones weighing 10 pounds or less, a liability policy with a minimum limit of \$1,000,000.00 is required.

- 2. For drones weighing more than 10 pounds and less than or equal to 20 pounds, a liability policy with a minimum limit of \$2,000,000.00 is required.
- 3. For drones weighing more than 20 pounds, notify engineer and department will determine appropriate liability policy coverage levels based on size, use, location, and other risk factors.

646 Pavement Markings

646.3.2.4 Black Epoxy

Replace paragraph (1) with the following effective with the November 2024 letting.

(1) Apply black epoxy in a grooved slot directly after the white marking. Apply epoxy at a wet mil thickness of 20. Apply black aggregate at or exceeding 25 pounds per gallon of epoxy. Do not apply glass beads to black epoxy.

ERRATA

204.3.1.3 Salvaging or Disposal of Materials

Replace paragraph (2) to correct link from 203.3.4 to 203.3.5 effective with the November 2024 letting.

(2) Dispose of concrete, stone, brick, and other material not designated for salvage as specified for disposing of materials under 203.3.5.

204.3.2.3 Removing Buildings

Replace paragraph (2) to correct link from 203.3.4 to 203.3.5 effective with the November 2024 letting.

(2) Buildings removed and materials resulting from building removal become the contractor's property unless the contract specifies otherwise. Dispose of unclaimed and removed material as specified for disposing of materials in 203.3.5.

335.3.2 Rubblizing

Replace paragraph (6) to correct link from 203.3.4 to 203.3.5 effective with the November 2024 letting.

(6) Remove reinforcing steel exposed at the surface by cutting below the surface and disposing of the steel as specified in 203.3.5. Do not remove unexposed reinforcing steel.

335.3.3 Compacting

Replace paragraph (2) to correct link from 203.3.4 to 203.3.5 effective with the November 2024 letting.

(2) Remove loose asphaltic patching material, joint fillers, expansion material, or other similar materials from the compacted surface. Also remove pavement or patches that have a maximum dimension greater than or equal to 6 inches that are either not well seated or projecting more than one inch. Dispose of removed material as specified in 203.3.5.

526.3.4 Construction, Backfilling, Inspection and Maintenance

Replace paragraph (3) to correct link from 203.3.4 to 203.3.5 effective with the November 2024 letting.

(3) Maintain temporary structures and approaches in place until no longer needed. Unless the engineer directs otherwise, completely remove and dispose of as specified in 203.3.5. Contractor-furnished materials remain the contractor's property upon removal.

602.3.6 Concrete Rumble Strips

Replace paragraph (5) to correct link from 203.3.4 to 203.3.5 effective with the November 2024 letting.

(5) At the end of each workday, move equipment and material out of the clear zone and sweep or vacuum the traveled way pavement and shoulder areas. Sweep away or vacuum up milling debris before opening adjacent lanes to traffic. Dispose of waste material as specified in 203.3.5; do not place on the finished shoulder surface.

604.2 Materials

Replace paragraph (1) with the following information to remove line and link for crushed aggregate effective with the November 2024 letting. The crushed aggregate gradation information for slope paving is now found in 604.2(3).

(1) Furnish materials conforming to the following:

Water	501.2
Select crushed material	312.2
Concrete	501
Reinforcement	
Expansion joint filler	415.2.3
Asphaltic materials	455.2

ADDITIONAL SPECIAL PROVISION 7

- A. Reporting 1st Tier and DBE Payments During Construction
 - 1. Comply with reporting requirements specified in the department's Civil Rights Compliance, Contractor's User Manual, Sublets and Payments.
 - 2. Report payments to all DBE firms within 10 calendar days of receipt of a progress payment by the department or a contractor for work performed, materials furnished, or materials stockpiled by a DBE firm. Report the payment as specified in A(1) for all work satisfactorily performed and for all materials furnished or stockpiled.
 - 3. Report payments to all first tier subcontractor relationships within 10 calendar days of receipt of a progress payment by the department for work performed. Report the payment as specified in A(1) for all work satisfactorily performed.
 - 4. All tiers shall report payments as necessary to comply with the DBE payment requirement as specified in A(2).
 - 5. DBE firms must enter all payments to DBE and non-DBE firms regardless of tier.
 - 6. Require all first tier relationships, DBE firms and all other tier relationships necessary to comply with the DBE payment requirement in receipt of a progress payment by contractor to acknowledge receipt of payment as specified in A(1), (2), (3) and (4).
 - 7. All agreements made by a contractor shall include the provisions in A(1), (2), (3), (4), (5), and (6), and shall be binding on all first tier subcontractor relationships, all contractors and subcontractors utilizing DBE firms on the project, and all payments from DBE firms.
- B. Costs for conforming to this special provision are incidental to the contract.

NOTE: CRCS Prime Contractor payment is currently not automated and will need to be manually loaded into the Civil Rights Compliance System. Copies of prime contractor payments received (check or ACH) will have to be forwarded to paul.ndon@dot.wi.gov within 5 days of payment receipt to be logged manually.

***Additionally, for information on Subcontractor Sublet assignments, Subcontractor Payments and Payment Tracking, please refer to the CRCS Payment and Sublets manual at:

https://wisconsindot.gov/Documents/doing-bus/civil-rights/labornwage/crcs-payments-sublets-manual.pdf

ADDITIONAL SPECIAL PROVISION 9

Electronic Certified Payroll or Labor Data Submittal

- (1) Use the department's Civil Rights Compliance System (CRCS) for projects with a LET date on or before December 2024 and AASHTOWare Project Civil Rights and Labor (AWP CRL) for projects with a LET date on or after January 2025 to electronically submit Certified Payroll Reports for contracts with federal funds and labor data for contracts with state funds only. Details are available online through the department's Highway Construction Contractor Information (HCCI) site on the Labor, Wages, and EEO Information page at: https://wisconsindot.gov/Pages/doing-bus/civil-rights/labornwage/default.aspx
- (2) Ensure that all tiers of subcontractors, including all trucking firms, either submit their weekly certified payroll reports (contracts with federal funds) or labor data (contracts with state funds only) electronically through CRCS or AWP CRL. These payrolls or labor data are due within seven calendar days following the close of the payroll period. Every firm providing physical labor towards completing the project is a subcontractor under this special provision.
- (3) Upon receipt of contract execution, promptly make all affected firms aware of the requirements under this special provision and arrange for them to receive CRCS or AWP CRL training as they are about to begin their submittals. The department will provide training either in a classroom setting at one of our regional offices, via the online AWP Knowledge Base, or by telephone. to schedule CRCS specific training. The AWP Knowledge Base is at: https://awpkb.dot.wi.gov/
- (4) The department will reject all paper submittals for information required under this special provision. All costs for conforming to this special provision are incidental to the contract.
- (5) For firms wishing to export payroll/labor data from their computer system, have their payroll coordinator contact:
 - For CRCS: Paul Ndon at paul.ndon@dot.wi.gov. Information about exporting payroll/labor data. Not every contractor's payroll system can produce export files. For details, see Section 4.8 CPR Auto Submit (Data Mapping) on pages 49-50; 66-71 of the CRCS Payroll Manual at: https://wisconsindot.gov/Documents/doing-bus/civil-rights/labornwage/crcs-payroll-manual.pdf
 - For AWP CRL: Contact AWP Support at awpsupport@dot.wi.gov. Additional information can be found in the AWP Knowledge Base at https://awpkb.dot.wi.gov/Content/crl/Payrolls-PrimesAndSubs/PayrollXMLFileCreationProcess.htm

REQUIRED CONTRACT PROVISIONS FEDERAL-AID CONSTRUCTION CONTRACTS

- I General
- II. Nondiscrimination
- III. Non-segregated Facilities
- IV. Davis-Bacon and Related Act Provisions
- Contract Work Hours and Safety Standards Act Provisions
- VI. Subletting or Assigning the Contract
- VII. Safety: Accident Prevention
- VIII. False Statements Concerning Highway Projects
- IX. Implementation of Clean Air Act and Federal Water Pollution Control Act
- X. Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion
- Certification Regarding Use of Contract Funds for Lobbying
- XII. Use of United States-Flag Vessels:

ATTACHMENTS

A. Employment and Materials Preference for Appalachian Development Highway System or Appalachian Local Access Road Contracts (included in Appalachian contracts only)

I. GENERAL

1. Form FHWA-1273 must be physically incorporated in each construction contract funded under title 23, United States Code, as required in 23 CFR 633.102(b) (excluding emergency contracts solely intended for debris removal). The contractor (or subcontractor) must insert this form in each subcontract and further require its inclusion in all lower tier subcontracts (excluding purchase orders, rental agreements and other agreements for supplies or services). 23 CFR 633.102(e).

The applicable requirements of Form FHWA-1273 are incorporated by reference for work done under any purchase order, rental agreement or agreement for other services. The prime contractor shall be responsible for compliance by any subcontractor, lower-tier subcontractor or service provider. 23 CFR 633.102(e).

Form FHWA-1273 must be included in all Federal-aid designbuild contracts, in all subcontracts and in lower tier subcontracts (excluding subcontracts for design services, purchase orders, rental agreements and other agreements for supplies or services) in accordance with 23 CFR 633.102. The design-builder shall be responsible for compliance by any subcontractor, lower-tier subcontractor or service provider.

Contracting agencies may reference Form FHWA-1273 in solicitation-for-bids or request-for-proposals documents, however, the Form FHWA-1273 must be physically incorporated (not referenced) in all contracts, subcontracts and lower-tier subcontracts (excluding purchase orders, rental agreements and other agreements for supplies or services related to a construction contract). 23 CFR 633.102(b).

2. Subject to the applicability criteria noted in the following sections, these contract provisions shall apply to all work

performed on the contract by the contractor's own organization and with the assistance of workers under the contractor's immediate superintendence and to all work performed on the contract by piecework, station work, or by subcontract. 23 CFR 633.102(d).

- 3. A breach of any of the stipulations contained in these Required Contract Provisions may be sufficient grounds for withholding of progress payments, withholding of final payment, termination of the contract, suspension / debarment or any other action determined to be appropriate by the contracting agency and FHWA.
- 4. Selection of Labor: During the performance of this contract, the contractor shall not use convict labor for any purpose within the limits of a construction project on a Federal-aid highway unless it is labor performed by convicts who are on parole, supervised release, or probation. 23 U.S.C. 114(b). The term Federal-aid highway does not include roadways functionally classified as local roads or rural minor collectors. 23 U.S.C. 101(a).
- II. NONDISCRIMINATION (23 CFR 230.107(a); 23 CFR Part 230, Subpart A, Appendix A; EO 11246)

The provisions of this section related to 23 CFR Part 230, Subpart A, Appendix A are applicable to all Federal-aid construction contracts and to all related construction subcontracts of \$10,000 or more. The provisions of 23 CFR Part 230 are not applicable to material supply, engineering, or architectural service contracts.

In addition, the contractor and all subcontractors must comply with the following policies: Executive Order 11246, 41 CFR Part 60, 29 CFR Parts 1625-1627, 23 U.S.C. 140, Section 504 of the Rehabilitation Act of 1973, as amended (29 U.S.C. 794), Title VI of the Civil Rights Act of 1964, as amended (42 U.S.C. 2000d et seq.), and related regulations including 49 CFR Parts 21, 26, and 27; and 23 CFR Parts 200, 230, and 633.

The contractor and all subcontractors must comply with: the requirements of the Equal Opportunity Clause in 41 CFR 60-1.4(b) and, for all construction contracts exceeding \$10,000, the Standard Federal Equal Employment Opportunity Construction Contract Specifications in 41 CFR 60-4.3.

Note: The U.S. Department of Labor has exclusive authority to determine compliance with Executive Order 11246 and the policies of the Secretary of Labor including 41 CFR Part 60, and 29 CFR Parts 1625-1627. The contracting agency and the FHWA have the authority and the responsibility to ensure compliance with 23 U.S.C. 140, Section 504 of the Rehabilitation Act of 1973, as amended (29 U.S.C. 794), and Title VI of the Civil Rights Act of 1964, as amended (42 U.S.C. 2000d et seq.), and related regulations including 49 CFR Parts 21, 26, and 27; and 23 CFR Parts 200, 230, and 633.

The following provision is adopted from 23 CFR Part 230, Subpart A, Appendix A, with appropriate revisions to conform to the U.S. Department of Labor (US DOL) and FHWA requirements.

- 1. Equal Employment Opportunity: Equal Employment Opportunity (EEO) requirements not to discriminate and to take affirmative action to assure equal opportunity as set forth under laws, executive orders, rules, regulations (see 28 CFR Part 35, 29 CFR Part 1630, 29 CFR Parts 1625-1627, 41 CFR Part 60 and 49 CFR Part 27) and orders of the Secretary of Labor as modified by the provisions prescribed herein, and imposed pursuant to 23 U.S.C. 140, shall constitute the EEO and specific affirmative action standards for the contractor's project activities under this contract. The provisions of the Americans with Disabilities Act of 1990 (42 U.S.C. 12101 et seq.) set forth under 28 CFR Part 35 and 29 CFR Part 1630 are incorporated by reference in this contract. In the execution of this contract, the contractor agrees to comply with the following minimum specific requirement activities of EEO:
- a. The contractor will work with the contracting agency and the Federal Government to ensure that it has made every good faith effort to provide equal opportunity with respect to all of its terms and conditions of employment and in their review of activities under the contract. 23 CFR 230.409 (g)(4) & (5).
- b. The contractor will accept as its operating policy the following statement:

"It is the policy of this Company to assure that applicants are employed, and that employees are treated during employment, without regard to their race, religion, sex, sexual orientation, gender identity, color, national origin, age or disability. Such action shall include: employment, upgrading, demotion, or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship, pre-apprenticeship, and/or on-the-job training."

- 2. EEO Officer: The contractor will designate and make known to the contracting officers an EEO Officer who will have the responsibility for and must be capable of effectively administering and promoting an active EEO program and who must be assigned adequate authority and responsibility to do so.
- 3. Dissemination of Policy: All members of the contractor's staff who are authorized to hire, supervise, promote, and discharge employees, or who recommend such action or are substantially involved in such action, will be made fully cognizant of and will implement the contractor's EEO policy and contractual responsibilities to provide EEO in each grade and classification of employment. To ensure that the above agreement will be met, the following actions will be taken as a minimum:
- a. Periodic meetings of supervisory and personnel office employees will be conducted before the start of work and then not less often than once every six months, at which time the contractor's EEO policy and its implementation will be reviewed and explained. The meetings will be conducted by the EEO Officer or other knowledgeable company official.
- b. All new supervisory or personnel office employees will be given a thorough indoctrination by the EEO Officer, covering all major aspects of the contractor's EEO obligations within thirty days following their reporting for duty with the contractor.
- c. All personnel who are engaged in direct recruitment for the project will be instructed by the EEO Officer in the contractor's procedures for locating and hiring minorities and women

- d. Notices and posters setting forth the contractor's EEO policy will be placed in areas readily accessible to employees, applicants for employment and potential employees.
- e. The contractor's EEO policy and the procedures to implement such policy will be brought to the attention of employees by means of meetings, employee handbooks, or other appropriate means.
- **4. Recruitment:** When advertising for employees, the contractor will include in all advertisements for employees the notation: "An Equal Opportunity Employer." All such advertisements will be placed in publications having a large circulation among minorities and women in the area from which the project work force would normally be derived.
- a. The contractor will, unless precluded by a valid bargaining agreement, conduct systematic and direct recruitment through public and private employee referral sources likely to yield qualified minorities and women. To meet this requirement, the contractor will identify sources of potential minority group employees and establish with such identified sources procedures whereby minority and women applicants may be referred to the contractor for employment consideration.
- b. In the event the contractor has a valid bargaining agreement providing for exclusive hiring hall referrals, the contractor is expected to observe the provisions of that agreement to the extent that the system meets the contractor's compliance with EEO contract provisions. Where implementation of such an agreement has the effect of discriminating against minorities or women, or obligates the contractor to do the same, such implementation violates Federal nondiscrimination provisions.
- c. The contractor will encourage its present employees to refer minorities and women as applicants for employment. Information and procedures with regard to referring such applicants will be discussed with employees.
- **5. Personnel Actions:** Wages, working conditions, and employee benefits shall be established and administered, and personnel actions of every type, including hiring, upgrading, promotion, transfer, demotion, layoff, and termination, shall be taken without regard to race, color, religion, sex, sexual orientation, gender identity, national origin, age or disability. The following procedures shall be followed:
- a. The contractor will conduct periodic inspections of project sites to ensure that working conditions and employee facilities do not indicate discriminatory treatment of project site personnel.
- b. The contractor will periodically evaluate the spread of wages paid within each classification to determine any evidence of discriminatory wage practices.
- c. The contractor will periodically review selected personnel actions in depth to determine whether there is evidence of discrimination. Where evidence is found, the contractor will promptly take corrective action. If the review indicates that the discrimination may extend beyond the actions reviewed, such corrective action shall include all affected persons.
- d. The contractor will promptly investigate all complaints of alleged discrimination made to the contractor in connection with its obligations under this contract, will attempt to resolve such complaints, and will take appropriate corrective action

within a reasonable time. If the investigation indicates that the discrimination may affect persons other than the complainant, such corrective action shall include such other persons. Upon completion of each investigation, the contractor will inform every complainant of all of their avenues of appeal.

6. Training and Promotion:

- a. The contractor will assist in locating, qualifying, and increasing the skills of minorities and women who are applicants for employment or current employees. Such efforts should be aimed at developing full journey level status employees in the type of trade or job classification involved.
- b. Consistent with the contractor's work force requirements and as permissible under Federal and State regulations, the contractor shall make full use of training programs (i.e., apprenticeship and on-the-job training programs for the geographical area of contract performance). In the event a special provision for training is provided under this contract, this subparagraph will be superseded as indicated in the special provision. The contracting agency may reserve training positions for persons who receive welfare assistance in accordance with 23 U.S.C. 140(a).
- c. The contractor will advise employees and applicants for employment of available training programs and entrance requirements for each.
- d. The contractor will periodically review the training and promotion potential of employees who are minorities and women and will encourage eligible employees to apply for such training and promotion.
- 7. Unions: If the contractor relies in whole or in part upon unions as a source of employees, the contractor will use good faith efforts to obtain the cooperation of such unions to increase opportunities for minorities and women. 23 CFR 230.409. Actions by the contractor, either directly or through a contractor's association acting as agent, will include the procedures set forth below:
- a. The contractor will use good faith efforts to develop, in cooperation with the unions, joint training programs aimed toward qualifying more minorities and women for membership in the unions and increasing the skills of minorities and women so that they may qualify for higher paying employment.
- b. The contractor will use good faith efforts to incorporate an EEO clause into each union agreement to the end that such union will be contractually bound to refer applicants without regard to their race, color, religion, sex, sexual orientation, gender identity, national origin, age, or disability.
- c. The contractor is to obtain information as to the referral practices and policies of the labor union except that to the extent such information is within the exclusive possession of the labor union and such labor union refuses to furnish such information to the contractor, the contractor shall so certify to the contracting agency and shall set forth what efforts have been made to obtain such information.
- d. In the event the union is unable to provide the contractor with a reasonable flow of referrals within the time limit set forth in the collective bargaining agreement, the contractor will, through independent recruitment efforts, fill the employment vacancies without regard to race, color, religion, sex, sexual orientation, gender identity, national origin, age, or disability; making full efforts to obtain qualified and/or qualifiable minorities and women. The failure of a union to provide

sufficient referrals (even though it is obligated to provide exclusive referrals under the terms of a collective bargaining agreement) does not relieve the contractor from the requirements of this paragraph. In the event the union referral practice prevents the contractor from meeting the obligations pursuant to Executive Order 11246, as amended, and these special provisions, such contractor shall immediately notify the contracting agency.

- 8. Reasonable Accommodation for Applicants / Employees with Disabilities: The contractor must be familiar with the requirements for and comply with the Americans with Disabilities Act and all rules and regulations established thereunder. Employers must provide reasonable accommodation in all employment activities unless to do so would cause an undue hardship.
- 9. Selection of Subcontractors, Procurement of Materials and Leasing of Equipment: The contractor shall not discriminate on the grounds of race, color, religion, sex, sexual orientation, gender identity, national origin, age, or disability in the selection and retention of subcontractors, including procurement of materials and leases of equipment. The contractor shall take all necessary and reasonable steps to ensure nondiscrimination in the administration of this contract.
- a. The contractor shall notify all potential subcontractors, suppliers, and lessors of their EEO obligations under this contract.
- b. The contractor will use good faith efforts to ensure subcontractor compliance with their EEO obligations.

10. Assurances Required:

- a. The requirements of 49 CFR Part 26 and the State DOT's FHWA-approved Disadvantaged Business Enterprise (DBE) program are incorporated by reference.
- b. The contractor, subrecipient or subcontractor shall not discriminate on the basis of race, color, national origin, or sex in the performance of this contract. The contractor shall carry out applicable requirements of 49 CFR part 26 in the award and administration of DOT-assisted contracts. Failure by the contractor to carry out these requirements is a material breach of this contract, which may result in the termination of this contract or such other remedy as the recipient deems appropriate, which may include, but is not limited to:
 - (1) Withholding monthly progress payments;
 - (2) Assessing sanctions;
 - (3) Liquidated damages; and/or
- (4) Disqualifying the contractor from future bidding as non-responsible.
- c. The Title VI and nondiscrimination provisions of U.S. DOT Order 1050.2A at Appendixes A and E are incorporated by reference. 49 CFR Part 21.
- 11. Records and Reports: The contractor shall keep such records as necessary to document compliance with the EEO requirements. Such records shall be retained for a period of three years following the date of the final payment to the contractor for all contract work and shall be available at reasonable times and places for inspection by authorized representatives of the contracting agency and the FHWA.
- a. The records kept by the contractor shall document the following:

- (1) The number and work hours of minority and nonminority group members and women employed in each work classification on the project;
 - (2) The progress and efforts being made in cooperation with unions, when applicable, to increase employment opportunities for minorities and women; and
 - (3) The progress and efforts being made in locating, hiring, training, qualifying, and upgrading minorities and women.
- b. The contractors and subcontractors will submit an annual report to the contracting agency each July for the duration of the project indicating the number of minority, women, and non-minority group employees currently engaged in each work classification required by the contract work. This information is to be reported on Form FHWA-1391. The staffing data should represent the project work force on board in all or any part of the last payroll period preceding the end of July. If on-the-job training is being required by special provision, the contractor will be required to collect and report training data. The employment data should reflect the work force on board during all or any part of the last payroll period preceding the end of July.

III. NONSEGREGATED FACILITIES

This provision is applicable to all Federal-aid construction contracts and to all related construction subcontracts of more than \$10,000. 41 CFR 60-1.5.

As prescribed by 41 CFR 60-1.8, the contractor must ensure that facilities provided for employees are provided in such a manner that segregation on the basis of race, color, religion, sex, sexual orientation, gender identity, or national origin cannot result. The contractor may neither require such segregated use by written or oral policies nor tolerate such use by employee custom. The contractor's obligation extends further to ensure that its employees are not assigned to perform their services at any location under the contractor's control where the facilities are segregated. The term "facilities" includes waiting rooms, work areas, restaurants and other eating areas, time clocks, restrooms, washrooms, locker rooms and other storage or dressing areas, parking lots, drinking fountains, recreation or entertainment areas, transportation, and housing provided for employees. The contractor shall provide separate or single-user restrooms and necessary dressing or sleeping areas to assure privacy between sexes.

IV. DAVIS-BACON AND RELATED ACT PROVISIONS

This section is applicable to all Federal-aid construction projects exceeding \$2,000 and to all related subcontracts and lower-tier subcontracts (regardless of subcontract size), in accordance with 29 CFR 5.5. The requirements apply to all projects located within the right-of-way of a roadway that is functionally classified as Federal-aid highway. 23 U.S.C. 113. This excludes roadways functionally classified as local roads or rural minor collectors, which are exempt. 23 U.S.C. 101. Where applicable law requires that projects be treated as a project on a Federal-aid highway, the provisions of this subpart will apply regardless of the location of the project. Examples include: Surface Transportation Block Grant Program projects funded under 23 U.S.C. 133 [excluding recreational trails projects], the Nationally Significant Freight and Highway

Projects funded under 23 U.S.C. 117, and National Highway Freight Program projects funded under 23 U.S.C. 167.

The following provisions are from the U.S. Department of Labor regulations in 29 CFR 5.5 "Contract provisions and related matters" with minor revisions to conform to the FHWA-1273 format and FHWA program requirements.

1. Minimum wages (29 CFR 5.5)

- a. Wage rates and fringe benefits. All laborers and mechanics employed or working upon the site of the work (or otherwise working in construction or development of the project under a development statute), will be paid unconditionally and not less often than once a week, and without subsequent deduction or rebate on any account (except such payroll deductions as are permitted by regulations issued by the Secretary of Labor under the Copeland Act (29 CFR part 3)), the full amount of basic hourly wages and bona fide fringe benefits (or cash equivalents thereof) due at time of payment computed at rates not less than those contained in the wage determination of the Secretary of Labor which is attached hereto and made a part hereof, regardless of any contractual relationship which may be alleged to exist between the contractor and such laborers and mechanics. As provided in paragraphs (d) and (e) of 29 CFR 5.5, the appropriate wage determinations are effective by operation of law even if they have not been attached to the contract. Contributions made or costs reasonably anticipated for bona fide fringe benefits under the Davis-Bacon Act (40 U.S.C. 3141(2)(B)) on behalf of laborers or mechanics are considered wages paid to such laborers or mechanics, subject to the provisions of paragraph 1.e. of this section; also, regular contributions made or costs incurred for more than a weekly period (but not less often than quarterly) under plans, funds, or programs which cover the particular weekly period, are deemed to be constructively made or incurred during such weekly period. Such laborers and mechanics must be paid the appropriate wage rate and fringe benefits on the wage determination for the classification(s) of work actually performed, without regard to skill, except as provided in paragraph 4. of this section. Laborers or mechanics performing work in more than one classification may be compensated at the rate specified for each classification for the time actually worked therein: Provided, That the employer's payroll records accurately set forth the time spent in each classification in which work is performed. The wage determination (including any additional classifications and wage rates conformed under paragraph 1.c. of this section) and the Davis-Bacon poster (WH-1321) must be posted at all times by the contractor and its subcontractors at the site of the work in a prominent and accessible place where it can be easily seen by the workers.
- b. Frequently recurring classifications. (1) In addition to wage and fringe benefit rates that have been determined to be prevailing under the procedures set forth in 29 CFR part 1, a wage determination may contain, pursuant to § 1.3(f), wage and fringe benefit rates for classifications of laborers and mechanics for which conformance requests are regularly submitted pursuant to paragraph 1.c. of this section, provided that:
 - (i) The work performed by the classification is not performed by a classification in the wage determination for which a prevailing wage rate has been determined;

- (ii) The classification is used in the area by the construction industry; and
- (iii) The wage rate for the classification bears a reasonable relationship to the prevailing wage rates contained in the wage determination.
- (2) The Administrator will establish wage rates for such classifications in accordance with paragraph 1.c.(1)(iii) of this section. Work performed in such a classification must be paid at no less than the wage and fringe benefit rate listed on the wage determination for such classification.
- c. Conformance. (1) The contracting officer must require that any class of laborers or mechanics, including helpers, which is not listed in the wage determination and which is to be employed under the contract be classified in conformance with the wage determination. Conformance of an additional classification and wage rate and fringe benefits is appropriate only when the following criteria have been met:
 - (i) The work to be performed by the classification requested is not performed by a classification in the wage determination; and
 - (ii) The classification is used in the area by the construction industry; and
 - (iii) The proposed wage rate, including any bona fide fringe benefits, bears a reasonable relationship to the wage rates contained in the wage determination.
- (2) The conformance process may not be used to split, subdivide, or otherwise avoid application of classifications listed in the wage determination.
- (3) If the contractor and the laborers and mechanics to be employed in the classification (if known), or their representatives, and the contracting officer agree on the classification and wage rate (including the amount designated for fringe benefits where appropriate), a report of the action taken will be sent by the contracting officer by email to DBAconformance@dol.gov. The Administrator, or an authorized representative, will approve, modify, or disapprove every additional classification action within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30–day period that additional time is necessary.
- (4) In the event the contractor, the laborers or mechanics to be employed in the classification or their representatives, and the contracting officer do not agree on the proposed classification and wage rate (including the amount designated for fringe benefits, where appropriate), the contracting officer will, by email to <code>DBAconformance@dol.gov</code>, refer the questions, including the views of all interested parties and the recommendation of the contracting officer, to the Administrator for determination. The Administrator, or an authorized representative, will issue a determination within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30–day period that additional time is necessary.
- (5) The contracting officer must promptly notify the contractor of the action taken by the Wage and Hour Division

- under paragraphs 1.c.(3) and (4) of this section. The contractor must furnish a written copy of such determination to each affected worker or it must be posted as a part of the wage determination. The wage rate (including fringe benefits where appropriate) determined pursuant to paragraph 1.c.(3) or (4) of this section must be paid to all workers performing work in the classification under this contract from the first day on which work is performed in the classification.
- d. Fringe benefits not expressed as an hourly rate. Whenever the minimum wage rate prescribed in the contract for a class of laborers or mechanics includes a fringe benefit which is not expressed as an hourly rate, the contractor may either pay the benefit as stated in the wage determination or may pay another bona fide fringe benefit or an hourly cash equivalent thereof.
- e. Unfunded plans. If the contractor does not make payments to a trustee or other third person, the contractor may consider as part of the wages of any laborer or mechanic the amount of any costs reasonably anticipated in providing bona fide fringe benefits under a plan or program, Provided, That the Secretary of Labor has found, upon the written request of the contractor, in accordance with the criteria set forth in § 5.28, that the applicable standards of the Davis-Bacon Act have been met. The Secretary of Labor may require the contractor to set aside in a separate account assets for the meeting of obligations under the plan or program.
- f. *Interest*. In the event of a failure to pay all or part of the wages required by the contract, the contractor will be required to pay interest on any underpayment of wages.

2. Withholding (29 CFR 5.5)

- a. Withholding requirements. The contracting agency may, upon its own action, or must, upon written request of an authorized representative of the Department of Labor, withhold or cause to be withheld from the contractor so much of the accrued payments or advances as may be considered necessary to satisfy the liabilities of the prime contractor or any subcontractor for the full amount of wages and monetary relief, including interest, required by the clauses set forth in this section for violations of this contract, or to satisfy any such liabilities required by any other Federal contract, or federally assisted contract subject to Davis-Bacon labor standards, that is held by the same prime contractor (as defined in § 5.2). The necessary funds may be withheld from the contractor under this contract, any other Federal contract with the same prime contractor, or any other federally assisted contract that is subject to Davis-Bacon labor standards requirements and is held by the same prime contractor, regardless of whether the other contract was awarded or assisted by the same agency, and such funds may be used to satisfy the contractor liability for which the funds were withheld. In the event of a contractor's failure to pay any laborer or mechanic, including any apprentice or helper working on the site of the work all or part of the wages required by the contract, or upon the contractor's failure to submit the required records as discussed in paragraph 3.d. of this section, the contracting agency may on its own initiative and after written notice to the contractor. take such action as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds until such violations have ceased.
- b. Priority to withheld funds. The Department has priority to funds withheld or to be withheld in accordance with paragraph

- 2.a. of this section or Section V, paragraph 3.a., or both, over claims to those funds by:
- (1) A contractor's surety(ies), including without limitation performance bond sureties and payment bond sureties;
 - (2) A contracting agency for its reprocurement costs;
- (3) A trustee(s) (either a court-appointed trustee or a U.S. trustee, or both) in bankruptcy of a contractor, or a contractor's bankruptcy estate;
 - (4) A contractor's assignee(s);
 - (5) A contractor's successor(s); or
- (6) A claim asserted under the Prompt Payment Act, <u>31</u> U.S.C. 3901–3907.

3. Records and certified payrolls (29 CFR 5.5)

- a. Basic record requirements (1) Length of record retention. All regular payrolls and other basic records must be maintained by the contractor and any subcontractor during the course of the work and preserved for all laborers and mechanics working at the site of the work (or otherwise working in construction or development of the project under a development statute) for a period of at least 3 years after all the work on the prime contract is completed.
- (2) Information required. Such records must contain the name; Social Security number; last known address, telephone number, and email address of each such worker; each worker's correct classification(s) of work actually performed; hourly rates of wages paid (including rates of contributions or costs anticipated for bona fide fringe benefits or cash equivalents thereof of the types described in 40 U.S.C. 3141(2)(B) of the Davis-Bacon Act); daily and weekly number of hours actually worked in total and on each covered contract; deductions made; and actual wages paid.
- (3) Additional records relating to fringe benefits. Whenever the Secretary of Labor has found under paragraph 1.e. of this section that the wages of any laborer or mechanic include the amount of any costs reasonably anticipated in providing benefits under a plan or program described in 40 U.S.C. 3141(2)(B) of the Davis-Bacon Act, the contractor must maintain records which show that the commitment to provide such benefits is enforceable, that the plan or program is financially responsible, and that the plan or program has been communicated in writing to the laborers or mechanics affected, and records which show the costs anticipated or the actual cost incurred in providing such benefits.
- (4) Additional records relating to apprenticeship. Contractors with apprentices working under approved programs must maintain written evidence of the registration of apprenticeship programs, the registration of the apprentices, and the ratios and wage rates prescribed in the applicable programs.
- b. Certified payroll requirements (1) Frequency and method of submission. The contractor or subcontractor must submit weekly, for each week in which any DBA- or Related Actscovered work is performed, certified payrolls to the contracting

- agency. The prime contractor is responsible for the submission of all certified payrolls by all subcontractors. A contracting agency or prime contractor may permit or require contractors to submit certified payrolls through an electronic system, as long as the electronic system requires a legally valid electronic signature; the system allows the contractor, the contracting agency, and the Department of Labor to access the certified payrolls upon request for at least 3 years after the work on the prime contract has been completed; and the contracting agency or prime contractor permits other methods of submission in situations where the contractor is unable or limited in its ability to use or access the electronic system.
- (2) Information required. The certified payrolls submitted must set out accurately and completely all of the information required to be maintained under paragraph 3.a.(2) of this section, except that full Social Security numbers and last known addresses, telephone numbers, and email addresses must not be included on weekly transmittals. Instead, the certified payrolls need only include an individually identifying number for each worker (e.g., the last four digits of the worker's Social Security number). The required weekly certified payroll information may be submitted using Optional Form WH-347 or in any other format desired. Optional Form WH-347 is available for this purpose from the Wage and Hour Division website at https://www.dol.gov/sites/dolgov/files/WHD/ legacy/files/wh347/.pdf or its successor website. It is not a violation of this section for a prime contractor to require a subcontractor to provide full Social Security numbers and last known addresses, telephone numbers, and email addresses to the prime contractor for its own records, without weekly submission by the subcontractor to the contracting agency.
- (3) Statement of Compliance. Each certified payroll submitted must be accompanied by a "Statement of Compliance," signed by the contractor or subcontractor, or the contractor's or subcontractor's agent who pays or supervises the payment of the persons working on the contract, and must certify the following:
 - (i) That the certified payroll for the payroll period contains the information required to be provided under paragraph 3.b. of this section, the appropriate information and basic records are being maintained under paragraph 3.a. of this section, and such information and records are correct and complete;
 - (ii) That each laborer or mechanic (including each helper and apprentice) working on the contract during the payroll period has been paid the full weekly wages earned, without rebate, either directly or indirectly, and that no deductions have been made either directly or indirectly from the full wages earned, other than permissible deductions as set forth in 29 CFR part 3; and
 - (iii) That each laborer or mechanic has been paid not less than the applicable wage rates and fringe benefits or cash equivalents for the classification(s) of work actually performed, as specified in the applicable wage determination incorporated into the contract.
- (4) Use of Optional Form WH–347. The weekly submission of a properly executed certification set forth on the reverse side of Optional Form WH–347 will satisfy the requirement for submission of the "Statement of Compliance" required by paragraph 3.b.(3) of this section.

- (5) Signature. The signature by the contractor, subcontractor, or the contractor's or subcontractor's agent must be an original handwritten signature or a legally valid electronic signature.
- (6) Falsification. The falsification of any of the above certifications may subject the contractor or subcontractor to civil or criminal prosecution under 18 U.S.C. 1001 and 31 U.S.C. 3729.
- (7) Length of certified payroll retention. The contractor or subcontractor must preserve all certified payrolls during the course of the work and for a period of 3 years after all the work on the prime contract is completed.
- c. Contracts, subcontracts, and related documents. The contractor or subcontractor must maintain this contract or subcontract and related documents including, without limitation, bids, proposals, amendments, modifications, and extensions. The contractor or subcontractor must preserve these contracts, subcontracts, and related documents during the course of the work and for a period of 3 years after all the work on the prime contract is completed.
- d. Required disclosures and access (1) Required record disclosures and access to workers. The contractor or subcontractor must make the records required under paragraphs 3.a. through 3.c. of this section, and any other documents that the contracting agency, the State DOT, the FHWA, or the Department of Labor deems necessary to determine compliance with the labor standards provisions of any of the applicable statutes referenced by § 5.1, available for inspection, copying, or transcription by authorized representatives of the contracting agency, the State DOT, the FHWA, or the Department of Labor, and must permit such representatives to interview workers during working hours on the job.
- (2) Sanctions for non-compliance with records and worker access requirements. If the contractor or subcontractor fails to submit the required records or to make them available, or refuses to permit worker interviews during working hours on the job, the Federal agency may, after written notice to the contractor, sponsor, applicant, owner, or other entity, as the case may be, that maintains such records or that employs such workers, take such action as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds. Furthermore, failure to submit the required records upon request or to make such records available, or to permit worker interviews during working hours on the job, may be grounds for debarment action pursuant to § 5.12. In addition, any contractor or other person that fails to submit the required records or make those records available to WHD within the time WHD requests that the records be produced will be precluded from introducing as evidence in an administrative proceeding under 29 CFR part 6 any of the required records that were not provided or made available to WHD. WHD will take into consideration a reasonable request from the contractor or person for an extension of the time for submission of records. WHD will determine the reasonableness of the request and may consider, among other things, the location of the records and the volume of production.
- (3) Required information disclosures. Contractors and subcontractors must maintain the full Social Security number and last known address, telephone number, and email address

of each covered worker, and must provide them upon request to the contracting agency, the State DOT, the FHWA, the contractor, or the Wage and Hour Division of the Department of Labor for purposes of an investigation or other compliance action

4. Apprentices and equal employment opportunity (29 CFR 5.5)

- a. Apprentices (1) Rate of pay. Apprentices will be permitted to work at less than the predetermined rate for the work they perform when they are employed pursuant to and individually registered in a bona fide apprenticeship program registered with the U.S. Department of Labor, Employment and Training Administration, Office of Apprenticeship (OA), or with a State Apprenticeship Agency recognized by the OA. A person who is not individually registered in the program, but who has been certified by the OA or a State Apprenticeship Agency (where appropriate) to be eligible for probationary employment as an apprentice, will be permitted to work at less than the predetermined rate for the work they perform in the first 90 days of probationary employment as an apprentice in such a program. In the event the OA or a State Apprenticeship Agency recognized by the OA withdraws approval of an apprenticeship program, the contractor will no longer be permitted to use apprentices at less than the applicable predetermined rate for the work performed until an acceptable program is approved.
- (2) Fringe benefits. Apprentices must be paid fringe benefits in accordance with the provisions of the apprenticeship program. If the apprenticeship program does not specify fringe benefits, apprentices must be paid the full amount of fringe benefits listed on the wage determination for the applicable classification. If the Administrator determines that a different practice prevails for the applicable apprentice classification, fringe benefits must be paid in accordance with that determination.
- (3) Apprenticeship ratio. The allowable ratio of apprentices to journeyworkers on the job site in any craft classification must not be greater than the ratio permitted to the contractor as to the entire work force under the registered program or the ratio applicable to the locality of the project pursuant to paragraph 4.a.(4) of this section. Any worker listed on a payroll at an apprentice wage rate, who is not registered or otherwise employed as stated in paragraph 4.a.(1) of this section, must be paid not less than the applicable wage rate on the wage determination for the classification of work actually performed. In addition, any apprentice performing work on the job site in excess of the ratio permitted under this section must be paid not less than the applicable wage rate on the wage determination for the work actually performed.
- (4) Reciprocity of ratios and wage rates. Where a contractor is performing construction on a project in a locality other than the locality in which its program is registered, the ratios and wage rates (expressed in percentages of the journeyworker's hourly rate) applicable within the locality in which the construction is being performed must be observed. If there is no applicable ratio or wage rate for the locality of the project, the ratio and wage rate specified in the contractor's registered program must be observed.
- b. Equal employment opportunity. The use of apprentices and journeyworkers under this part must be in conformity with

the equal employment opportunity requirements of Executive Order 11246, as amended, and 29 CFR part 30.

c. Apprentices and Trainees (programs of the U.S. DOT).

Apprentices and trainees working under apprenticeship and skill training programs which have been certified by the Secretary of Transportation as promoting EEO in connection with Federal-aid highway construction programs are not subject to the requirements of paragraph 4 of this Section IV. 23 CFR 230.111(e)(2). The straight time hourly wage rates for apprentices and trainees under such programs will be established by the particular programs. The ratio of apprentices and trainees to journeyworkers shall not be greater than permitted by the terms of the particular program.

- **5. Compliance with Copeland Act requirements.** The contractor shall comply with the requirements of 29 CFR part 3, which are incorporated by reference in this contract as provided in 29 CFR 5.5.
- **6. Subcontracts**. The contractor or subcontractor must insert FHWA-1273 in any subcontracts, along with the applicable wage determination(s) and such other clauses or contract modifications as the contracting agency may by appropriate instructions require, and a clause requiring the subcontractors to include these clauses and wage determination(s) in any lower tier subcontracts. The prime contractor is responsible for the compliance by any subcontractor or lower tier subcontractor with all the contract clauses in this section. In the event of any violations of these clauses, the prime contractor and any subcontractor(s) responsible will be liable for any unpaid wages and monetary relief, including interest from the date of the underpayment or loss, due to any workers of lower-tier subcontractors, and may be subject to debarment, as appropriate. 29 CFR 5.5.
- **7. Contract termination: debarment.** A breach of the contract clauses in 29 CFR 5.5 may be grounds for termination of the contract, and for debarment as a contractor and a subcontractor as provided in 29 CFR 5.12.
- **8.** Compliance with Davis-Bacon and Related Act requirements. All rulings and interpretations of the Davis-Bacon and Related Acts contained in 29 CFR parts 1, 3, and 5 are herein incorporated by reference in this contract as provided in 29 CFR 5.5.
- 9. Disputes concerning labor standards. As provided in 29 CFR 5.5, disputes arising out of the labor standards provisions of this contract shall not be subject to the general disputes clause of this contract. Such disputes shall be resolved in accordance with the procedures of the Department of Labor set forth in 29 CFR parts 5, 6, and 7. Disputes within the meaning of this clause include disputes between the contractor (or any of its subcontractors) and the contracting agency, the U.S. Department of Labor, or the employees or their representatives.
- 10. Certification of eligibility. a. By entering into this contract, the contractor certifies that neither it nor any person or firm who has an interest in the contractor's firm is a person or firm ineligible to be awarded Government contracts by virtue of $\underline{40}$ $\underline{\text{U.S.C. }3144(b)}$ or § 5.12(a).

- b. No part of this contract shall be subcontracted to any person or firm ineligible for award of a Government contract by virtue of 40 U.S.C. 3144(b) or § 5.12(a).
- c. The penalty for making false statements is prescribed in the U.S. Code, Title 18 Crimes and Criminal Procedure, $\underline{18}$ U.S.C. 1001.
- **11. Anti-retaliation**. It is unlawful for any person to discharge, demote, intimidate, threaten, restrain, coerce, blacklist, harass, or in any other manner discriminate against, or to cause any person to discharge, demote, intimidate, threaten, restrain, coerce, blacklist, harass, or in any other manner discriminate against, any worker or job applicant for:
- a. Notifying any contractor of any conduct which the worker reasonably believes constitutes a violation of the DBA, Related Acts, this part, or 29 CFR part 1 or 3;
- b. Filing any complaint, initiating or causing to be initiated any proceeding, or otherwise asserting or seeking to assert on behalf of themselves or others any right or protection under the DBA, Related Acts, this part, or 29 CFR part 1 or 3;
- c. Cooperating in any investigation or other compliance action, or testifying in any proceeding under the DBA, Related Acts, this part, or 29 CFR part 1 or 3; or
- d. Informing any other person about their rights under the DBA, Related Acts, this part, or 29 CFR part 1 or 3.

V. CONTRACT WORK HOURS AND SAFETY STANDARDS ACT

Pursuant to 29 CFR 5.5(b), the following clauses apply to any Federal-aid construction contract in an amount in excess of \$100,000 and subject to the overtime provisions of the Contract Work Hours and Safety Standards Act. These clauses shall be inserted in addition to the clauses required by 29 CFR 5.5(a) or 29 CFR 4.6. As used in this paragraph, the terms laborers and mechanics include watchpersons and guards.

- 1. Overtime requirements. No contractor or subcontractor contracting for any part of the contract work which may require or involve the employment of laborers or mechanics shall require or permit any such laborer or mechanic in any workweek in which he or she is employed on such work to work in excess of forty hours in such workweek unless such laborer or mechanic receives compensation at a rate not less than one and one-half times the basic rate of pay for all hours worked in excess of forty hours in such workweek. 29 CFR 5.5.
- 2. Violation; liability for unpaid wages; liquidated damages. In the event of any violation of the clause set forth in paragraph 1. of this section the contractor and any subcontractor responsible therefor shall be liable for the unpaid wages and interest from the date of the underpayment. In addition, such contractor and subcontractor shall be liable to the United States (in the case of work done under contract for the District of Columbia or a territory, to such District or to such territory), for liquidated damages shall be computed with respect to each individual laborer or

mechanic, including watchpersons and guards, employed in violation of the clause set forth in paragraph 1. of this section, in the sum currently provided in 29 CFR 5.5(b)(2)* for each calendar day on which such individual was required or permitted to work in excess of the standard workweek of forty hours without payment of the overtime wages required by the clause set forth in paragraph 1. of this section.

* \$31 as of January 15, 2023 (See 88 FR 88 FR 2210) as may be adjusted annually by the Department of Labor, pursuant to the Federal Civil Penalties Inflation Adjustment Act of 1990.

3. Withholding for unpaid wages and liquidated damages

- a. Withholding process. The FHWA or the contracting agency may, upon its own action, or must, upon written request of an authorized representative of the Department of Labor, withhold or cause to be withheld from the contractor so much of the accrued payments or advances as may be considered necessary to satisfy the liabilities of the prime contractor or any subcontractor for any unpaid wages; monetary relief, including interest; and liquidated damages required by the clauses set forth in this section on this contract, any other Federal contract with the same prime contractor, or any other federally assisted contract subject to the Contract Work Hours and Safety Standards Act that is held by the same prime contractor (as defined in § 5.2). The necessary funds may be withheld from the contractor under this contract, any other Federal contract with the same prime contractor, or any other federally assisted contract that is subject to the Contract Work Hours and Safety Standards Act and is held by the same prime contractor, regardless of whether the other contract was awarded or assisted by the same agency, and such funds may be used to satisfy the contractor liability for which the funds were withheld.
- b. *Priority to withheld funds*. The Department has priority to funds withheld or to be withheld in accordance with Section IV paragraph 2.a. or paragraph 3.a. of this section, or both, over claims to those funds by:
- (1) A contractor's surety(ies), including without limitation performance bond sureties and payment bond sureties;
 - (2) A contracting agency for its reprocurement costs;
- (3) A trustee(s) (either a court-appointed trustee or a U.S. trustee, or both) in bankruptcy of a contractor, or a contractor's bankruptcy estate:
 - (4) A contractor's assignee(s);
 - (5) A contractor's successor(s); or
- (6) A claim asserted under the Prompt Payment Act, <u>31</u> U.S.C. 3901–3907.
- **4. Subcontracts.** The contractor or subcontractor must insert in any subcontracts the clauses set forth in paragraphs 1. through 5. of this section and a clause requiring the subcontractors to include these clauses in any lower tier subcontracts. The prime contractor is responsible for compliance by any subcontractor or lower tier subcontractor with the clauses set forth in paragraphs 1. through 5. In the

event of any violations of these clauses, the prime contractor and any subcontractor(s) responsible will be liable for any unpaid wages and monetary relief, including interest from the date of the underpayment or loss, due to any workers of lower-tier subcontractors, and associated liquidated damages and may be subject to debarment, as appropriate.

- **5. Anti-retaliation.** It is unlawful for any person to discharge, demote, intimidate, threaten, restrain, coerce, blacklist, harass, or in any other manner discriminate against, or to cause any person to discharge, demote, intimidate, threaten, restrain, coerce, blacklist, harass, or in any other manner discriminate against, any worker or job applicant for:
- a. Notifying any contractor of any conduct which the worker reasonably believes constitutes a violation of the Contract Work Hours and Safety Standards Act (CWHSSA) or its implementing regulations in this part;
- b. Filing any complaint, initiating or causing to be initiated any proceeding, or otherwise asserting or seeking to assert on behalf of themselves or others any right or protection under CWHSSA or this part;
- c. Cooperating in any investigation or other compliance action, or testifying in any proceeding under CWHSSA or this part; or
- d. Informing any other person about their rights under CWHSSA or this part.

VI. SUBLETTING OR ASSIGNING THE CONTRACT

This provision is applicable to all Federal-aid construction contracts on the National Highway System pursuant to 23 CFR 635.116.

- 1. The contractor shall perform with its own organization contract work amounting to not less than 30 percent (or a greater percentage if specified elsewhere in the contract) of the total original contract price, excluding any specialty items designated by the contracting agency. Specialty items may be performed by subcontract and the amount of any such specialty items performed may be deducted from the total original contract price before computing the amount of work required to be performed by the contractor's own organization (23 CFR 635.116).
- a. The term "perform work with its own organization" in paragraph 1 of Section VI refers to workers employed or leased by the prime contractor, and equipment owned or rented by the prime contractor, with or without operators. Such term does not include employees or equipment of a subcontractor or lower tier subcontractor, agents of the prime contractor, or any other assignees. The term may include payments for the costs of hiring leased employees from an employee leasing firm meeting all relevant Federal and State regulatory requirements. Leased employees may only be included in this term if the prime contractor meets all of the following conditions: (based on longstanding interpretation)
- the prime contractor maintains control over the supervision of the day-to-day activities of the leased employees;
 - (2) the prime contractor remains responsible for the quality of the work of the leased employees;

- (3) the prime contractor retains all power to accept or exclude individual employees from work on the project; and
 - (4) the prime contractor remains ultimately responsible for the payment of predetermined minimum wages, the submission of payrolls, statements of compliance and all other Federal regulatory requirements.
- b. "Specialty Items" shall be construed to be limited to work that requires highly specialized knowledge, abilities, or equipment not ordinarily available in the type of contracting organizations qualified and expected to bid or propose on the contract as a whole and in general are to be limited to minor components of the overall contract. 23 CFR 635.102.
- 2. Pursuant to 23 CFR 635.116(a), the contract amount upon which the requirements set forth in paragraph (1) of Section VI is computed includes the cost of material and manufactured products which are to be purchased or produced by the contractor under the contract provisions.
- 3. Pursuant to 23 CFR 635.116(c), the contractor shall furnish (a) a competent superintendent or supervisor who is employed by the firm, has full authority to direct performance of the work in accordance with the contract requirements, and is in charge of all construction operations (regardless of who performs the work) and (b) such other of its own organizational resources (supervision, management, and engineering services) as the contracting officer determines is necessary to assure the performance of the contract.
- 4. No portion of the contract shall be sublet, assigned or otherwise disposed of except with the written consent of the contracting officer, or authorized representative, and such consent when given shall not be construed to relieve the contractor of any responsibility for the fulfillment of the contract. Written consent will be given only after the contracting agency has assured that each subcontract is evidenced in writing and that it contains all pertinent provisions and requirements of the prime contract. (based on long-standing interpretation of 23 CFR 635.116).
- 5. The 30-percent self-performance requirement of paragraph (1) is not applicable to design-build contracts; however, contracting agencies may establish their own self-performance requirements. 23 CFR 635.116(d).

VII. SAFETY: ACCIDENT PREVENTION

This provision is applicable to all Federal-aid construction contracts and to all related subcontracts.

- 1. In the performance of this contract the contractor shall comply with all applicable Federal, State, and local laws governing safety, health, and sanitation (23 CFR Part 635). The contractor shall provide all safeguards, safety devices and protective equipment and take any other needed actions as it determines, or as the contracting officer may determine, to be reasonably necessary to protect the life and health of employees on the job and the safety of the public and to protect property in connection with the performance of the work covered by the contract. 23 CFR 635.108.
- 2. It is a condition of this contract, and shall be made a condition of each subcontract, which the contractor enters into pursuant to this contract, that the contractor and any subcontractor shall not permit any employee, in performance of the contract, to work in surroundings or under conditions which are unsanitary, hazardous or dangerous to his/her health or safety, as determined under construction safety and

health standards (29 CFR Part 1926) promulgated by the Secretary of Labor, in accordance with Section 107 of the Contract Work Hours and Safety Standards Act (40 U.S.C. 3704). 29 CFR 1926.10.

3. Pursuant to 29 CFR 1926.3, it is a condition of this contract that the Secretary of Labor or authorized representative thereof, shall have right of entry to any site of contract performance to inspect or investigate the matter of compliance with the construction safety and health standards and to carry out the duties of the Secretary under Section 107 of the Contract Work Hours and Safety Standards Act (40 U.S.C. 3704).

VIII. FALSE STATEMENTS CONCERNING HIGHWAY PROJECTS

This provision is applicable to all Federal-aid construction contracts and to all related subcontracts.

In order to assure high quality and durable construction in conformity with approved plans and specifications and a high degree of reliability on statements and representations made by engineers, contractors, suppliers, and workers on Federal-aid highway projects, it is essential that all persons concerned with the project perform their functions as carefully, thoroughly, and honestly as possible. Willful falsification, distortion, or misrepresentation with respect to any facts related to the project is a violation of Federal law. To prevent any misunderstanding regarding the seriousness of these and similar acts, Form FHWA-1022 shall be posted on each Federal-aid highway project (23 CFR Part 635) in one or more places where it is readily available to all persons concerned with the project:

18 U.S.C. 1020 reads as follows:

"Whoever, being an officer, agent, or employee of the United States, or of any State or Territory, or whoever, whether a person, association, firm, or corporation, knowingly makes any false statement, false representation, or false report as to the character, quality, quantity, or cost of the material used or to be used, or the quantity or quality of the work performed or to be performed, or the cost thereof in connection with the submission of plans, maps, specifications, contracts, or costs of construction on any highway or related project submitted for approval to the Secretary of Transportation; or

Whoever knowingly makes any false statement, false representation, false report or false claim with respect to the character, quality, quantity, or cost of any work performed or to be performed, or materials furnished or to be furnished, in connection with the construction of any highway or related project approved by the Secretary of Transportation; or

Whoever knowingly makes any false statement or false representation as to material fact in any statement, certificate, or report submitted pursuant to provisions of the Federal-aid Roads Act approved July 11, 1916, (39 Stat. 355), as amended and supplemented;

Shall be fined under this title or imprisoned not more than 5 years or both."

IX. IMPLEMENTATION OF CLEAN AIR ACT AND FEDERAL WATER POLLUTION CONTROL ACT (42 U.S.C. 7606; 2 CFR 200.88; EO 11738)

This provision is applicable to all Federal-aid construction contracts in excess of \$150,000 and to all related subcontracts. 48 CFR 2.101; 2 CFR 200.327.

By submission of this bid/proposal or the execution of this contract or subcontract, as appropriate, the bidder, proposer, Federal-aid construction contractor, subcontractor, supplier, or vendor agrees to comply with all applicable standards, orders or regulations issued pursuant to the Clean Air Act (42 U.S.C. 7401-7671q) and the Federal Water Pollution Control Act, as amended (33 U.S.C. 1251-1387). Violations must be reported to the Federal Highway Administration and the Regional Office of the Environmental Protection Agency. 2 CFR Part 200, Appendix II.

The contractor agrees to include or cause to be included the requirements of this Section in every subcontract, and further agrees to take such action as the contracting agency may direct as a means of enforcing such requirements. 2 CFR 200.327.

X. CERTIFICATION REGARDING DEBARMENT, SUSPENSION, INELIGIBILITY AND VOLUNTARY EXCLUSION

This provision is applicable to all Federal-aid construction contracts, design-build contracts, subcontracts, lower-tier subcontracts, purchase orders, lease agreements, consultant contracts or any other covered transaction requiring FHWA approval or that is estimated to cost \$25,000 or more – as defined in 2 CFR Parts 180 and 1200. 2 CFR 180.220 and 1200.220.

1. Instructions for Certification – First Tier Participants:

- a. By signing and submitting this proposal, the prospective first tier participant is providing the certification set out below.
- b. The inability of a person to provide the certification set out below will not necessarily result in denial of participation in this covered transaction. The prospective first tier participant shall submit an explanation of why it cannot provide the certification set out below. The certification or explanation will be considered in connection with the department or agency's determination whether to enter into this transaction. However, failure of the prospective first tier participant to furnish a certification or an explanation shall disqualify such a person from participation in this transaction. 2 CFR 180.320.
- c. The certification in this clause is a material representation of fact upon which reliance was placed when the contracting agency determined to enter into this transaction. If it is later determined that the prospective participant knowingly rendered an erroneous certification, in addition to other remedies available to the Federal Government, the contracting agency may terminate this transaction for cause of default. 2 CFR 180.325.
- d. The prospective first tier participant shall provide immediate written notice to the contracting agency to whom this proposal is submitted if any time the prospective first tier participant learns that its certification was erroneous when submitted or has become erroneous by reason of changed circumstances. 2 CFR 180.345 and 180.350.

- e. The terms "covered transaction," "debarred,"
 "suspended," "ineligible," "participant," "person," "principal,"
 and "voluntarily excluded," as used in this clause, are defined
 in 2 CFR Parts 180, Subpart I, 180.900-180.1020, and 1200.
 "First Tier Covered Transactions" refers to any covered
 transaction between a recipient or subrecipient of Federal
 funds and a participant (such as the prime or general contract).
 "Lower Tier Covered Transactions" refers to any covered
 transaction under a First Tier Covered Transaction (such as
 subcontracts). "First Tier Participant" refers to the participant
 who has entered into a covered transaction with a recipient or
 subrecipient of Federal funds (such as the prime or general
 contractor). "Lower Tier Participant" refers any participant who
 has entered into a covered transaction with a First Tier
 Participant or other Lower Tier Participants (such as
 subcontractors and suppliers).
- f. The prospective first tier participant agrees by submitting this proposal that, should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department or agency entering into this transaction. 2 CFR 180.330.
- g. The prospective first tier participant further agrees by submitting this proposal that it will include the clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transactions," provided by the department or contracting agency, entering into this covered transaction, without modification, in all lower tier covered transactions and in all solicitations for lower tier covered transactions exceeding the \$25,000 threshold. 2 CFR 180.220 and 180.300.
- h. A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. 2 CFR 180.300; 180.320, and 180.325. A participant is responsible for ensuring that its principals are not suspended, debarred, or otherwise ineligible to participate in covered transactions. 2 CFR 180.335. To verify the eligibility of its principals, as well as the eligibility of any lower tier prospective participants, each participant may, but is not required to, check the System for Award Management website (https://www.sam.gov/). 2 CFR 180.300, 180.320, and 180.325.
- i. Nothing contained in the foregoing shall be construed to require the establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of the prospective participant is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.
- j. Except for transactions authorized under paragraph (f) of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible, or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department or agency may terminate this transaction for cause or default. 2 CFR 180.325.

* * * * *

2. Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion – First Tier Participants:

- a. The prospective first tier participant certifies to the best of its knowledge and belief, that it and its principals:
- (1) Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participating in covered transactions by any Federal department or agency, 2 CFR 180.335;.
- (2) Have not within a three-year period preceding this proposal been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (Federal, State, or local) transaction or contract under a public transaction; violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements, or receiving stolen property, 2 CFR 180.800;
- (3) Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State or local) with commission of any of the offenses enumerated in paragraph (a)(2) of this certification, 2 CFR 180.700 and 180.800: and
- (4) Have not within a three-year period preceding this application/proposal had one or more public transactions (Federal, State or local) terminated for cause or default. 2 CFR 180.335(d).
- (5) Are not a corporation that has been convicted of a felony violation under any Federal law within the two-year period preceding this proposal (USDOT Order 4200.6 implementing appropriations act requirements); and
- (6) Are not a corporation with any unpaid Federal tax liability that has been assessed, for which all judicial and administrative remedies have been exhausted, or have lapsed, and that is not being paid in a timely manner pursuant to an agreement with the authority responsible for collecting the tax liability (USDOT Order 4200.6 implementing appropriations act requirements).
- b. Where the prospective participant is unable to certify to any of the statements in this certification, such prospective participant should attach an explanation to this proposal. 2 CFR 180.335 and 180.340.

* * * * *

3. Instructions for Certification - Lower Tier Participants:

(Applicable to all subcontracts, purchase orders, and other lower tier transactions requiring prior FHWA approval or estimated to cost \$25,000 or more - 2 CFR Parts 180 and 1200). 2 CFR 180.220 and 1200.220.

- a. By signing and submitting this proposal, the prospective lower tier participant is providing the certification set out below.
- b. The certification in this clause is a material representation of fact upon which reliance was placed when this transaction was entered into. If it is later determined that the prospective lower tier participant knowingly rendered an erroneous certification, in addition to other remedies available to the Federal Government, the department, or agency with which

this transaction originated may pursue available remedies, including suspension and/or debarment.

- c. The prospective lower tier participant shall provide immediate written notice to the person to which this proposal is submitted if at any time the prospective lower tier participant learns that its certification was erroneous by reason of changed circumstances. 2 CFR 180.365.
- d. The terms "covered transaction," "debarred," "suspended," "ineligible," "participant," "person," "principal," and "voluntarily excluded," as used in this clause, are defined in 2 CFR Parts 180, Subpart I, 180.900 – 180.1020, and 1200. You may contact the person to which this proposal is submitted for assistance in obtaining a copy of those regulations. "First Tier Covered Transactions" refers to any covered transaction between a recipient or subrecipient of Federal funds and a participant (such as the prime or general contract). "Lower Tier Covered Transactions" refers to any covered transaction under a First Tier Covered Transaction (such as subcontracts). "First Tier Participant" refers to the participant who has entered into a covered transaction with a recipient or subrecipient of Federal funds (such as the prime or general contractor). "Lower Tier Participant" refers any participant who has entered into a covered transaction with a First Tier Participant or other Lower Tier Participants (such as subcontractors and suppliers).
- e. The prospective lower tier participant agrees by submitting this proposal that, should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department or agency with which this transaction originated. 2 CFR 1200.220 and 1200.332.
- f. The prospective lower tier participant further agrees by submitting this proposal that it will include this clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transaction," without modification, in all lower tier covered transactions and in all solicitations for lower tier covered transactions exceeding the \$25,000 threshold. 2 CFR 180.220 and 1200.220.
- g. A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A participant is responsible for ensuring that its principals are not suspended, debarred, or otherwise ineligible to participate in covered transactions. To verify the eligibility of its principals, as well as the eligibility of any lower tier prospective participants, each participant may, but is not required to, check the System for Award Management website (https://www.sam.gov/), which is compiled by the General Services Administration. 2 CFR 180.300, 180.320, 180.330, and 180.335.
- h. Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of participant is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.
- i. Except for transactions authorized under paragraph e of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible, or voluntarily

excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department or agency with which this transaction originated may pursue available remedies, including suspension and/or debarment. 2 CFR 180.325.

* * * * *

4. Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion--Lower Tier Participants:

- a. The prospective lower tier participant certifies, by submission of this proposal, that neither it nor its principals:
- (1) is presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participating in covered transactions by any Federal department or agency, 2 CFR 180.355;
- (2) is a corporation that has been convicted of a felony violation under any Federal law within the two-year period preceding this proposal (USDOT Order 4200.6 implementing appropriations act requirements); and
- (3) is a corporation with any unpaid Federal tax liability that has been assessed, for which all judicial and administrative remedies have been exhausted, or have lapsed, and that is not being paid in a timely manner pursuant to an agreement with the authority responsible for collecting the tax liability. (USDOT Order 4200.6 implementing appropriations act requirements)
- b. Where the prospective lower tier participant is unable to certify to any of the statements in this certification, such prospective participant should attach an explanation to this proposal.

* * * * *

XI. CERTIFICATION REGARDING USE OF CONTRACT FUNDS FOR LOBBYING

This provision is applicable to all Federal-aid construction contracts and to all related subcontracts which exceed \$100,000. 49 CFR Part 20, App. A.

- 1. The prospective participant certifies, by signing and submitting this bid or proposal, to the best of his or her knowledge and belief. that:
- a. No Federal appropriated funds have been paid or will be paid, by or on behalf of the undersigned, to any person for influencing or attempting to influence an officer or employee of any Federal agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with the awarding of any Federal contract, the making of any Federal grant, the making of any Federal loan, the entering into of any cooperative agreement, and the extension, continuation, renewal, amendment, or modification of any Federal contract, grant, loan, or cooperative agreement.
- b. If any funds other than Federal appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of any Federal agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with this Federal contract, grant, loan, or

cooperative agreement, the undersigned shall complete and submit Standard Form-LLL, "Disclosure Form to Report Lobbying," in accordance with its instructions.

- 2. This certification is a material representation of fact upon which reliance was placed when this transaction was made or entered into. Submission of this certification is a prerequisite for making or entering into this transaction imposed by 31 U.S.C. 1352. Any person who fails to file the required certification shall be subject to a civil penalty of not less than \$10,000 and not more than \$100,000 for each such failure.
- 3. The prospective participant also agrees by submitting its bid or proposal that the participant shall require that the language of this certification be included in all lower tier subcontracts, which exceed \$100,000 and that all such recipients shall certify and disclose accordingly.

XII. USE OF UNITED STATES-FLAG VESSELS:

This provision is applicable to all Federal-aid construction contracts, design-build contracts, subcontracts, lower-tier subcontracts, purchase orders, lease agreements, or any other covered transaction. 46 CFR Part 381.

This requirement applies to material or equipment that is acquired for a specific Federal-aid highway project. 46 CFR 381.7. It is not applicable to goods or materials that come into inventories independent of an FHWA funded-contract.

When oceanic shipments (or shipments across the Great Lakes) are necessary for materials or equipment acquired for a specific Federal-aid construction project, the bidder, proposer, contractor, subcontractor, or vendor agrees:

- 1. To utilize privately owned United States-flag commercial vessels to ship at least 50 percent of the gross tonnage (computed separately for dry bulk carriers, dry cargo liners, and tankers) involved, whenever shipping any equipment, material, or commodities pursuant to this contract, to the extent such vessels are available at fair and reasonable rates for United States-flag commercial vessels. 46 CFR 381.7.
- 2. To furnish within 20 days following the date of loading for shipments originating within the United States or within 30 working days following the date of loading for shipments originating outside the United States, a legible copy of a rated, 'on-board' commercial ocean bill-of-lading in English for each shipment of cargo described in paragraph (b)(1) of this section to both the Contracting Officer (through the prime contractor in the case of subcontractor bills-of-lading) and to the Office of Cargo and Commercial Sealift (MAR-620), Maritime Administration, Washington, DC 20590. (MARAD requires copies of the ocean carrier's (master) bills of lading, certified onboard, dated, with rates and charges. These bills of lading may contain business sensitive information and therefore may be submitted directly to MARAD by the Ocean Transportation Intermediary on behalf of the contractor). 46 CFR 381.7.

ATTACHMENT A - EMPLOYMENT AND MATERIALS PREFERENCE FOR APPALACHIAN DEVELOPMENT HIGHWAY SYSTEM OR APPALACHIAN LOCAL ACCESS ROAD CONTRACTS (23 CFR 633, Subpart B, Appendix B) This provision is applicable to all Federal-aid projects funded under the Appalachian Regional Development Act of 1965.

- 1. During the performance of this contract, the contractor undertaking to do work which is, or reasonably may be, done as on-site work, shall give preference to qualified persons who regularly reside in the labor area as designated by the DOL wherein the contract work is situated, or the subregion, or the Appalachian counties of the State wherein the contract work is situated, except:
- a. To the extent that qualified persons regularly residing in the area are not available.
- b. For the reasonable needs of the contractor to employ supervisory or specially experienced personnel necessary to assure an efficient execution of the contract work.
- c. For the obligation of the contractor to offer employment to present or former employees as the result of a lawful collective bargaining contract, provided that the number of nonresident persons employed under this subparagraph (1c) shall not exceed 20 percent of the total number of employees employed by the contractor on the contract work, except as provided in subparagraph (4) below.
- 2. The contractor shall place a job order with the State Employment Service indicating (a) the classifications of the laborers, mechanics and other employees required to perform the contract work, (b) the number of employees required in each classification, (c) the date on which the participant estimates such employees will be required, and (d) any other pertinent information required by the State Employment Service to complete the job order form. The job order may be placed with the State Employment Service in writing or by telephone. If during the course of the contract work, the information submitted by the contractor in the original job order is substantially modified, the participant shall promptly notify the State Employment Service.
- 3. The contractor shall give full consideration to all qualified job applicants referred to him by the State Employment Service. The contractor is not required to grant employment to any job applicants who, in his opinion, are not qualified to perform the classification of work required.
- 4. If, within one week following the placing of a job order by the contractor with the State Employment Service, the State Employment Service is unable to refer any qualified job applicants to the contractor, or less than the number requested, the State Employment Service will forward a certificate to the contractor indicating the unavailability of applicants. Such certificate shall be made a part of the contractor's permanent project records. Upon receipt of this certificate, the contractor may employ persons who do not normally reside in the labor area to fill positions covered by the certificate, notwithstanding the provisions of subparagraph (1c) above
- 5. The provisions of 23 CFR 633.207(e) allow the contracting agency to provide a contractual preference for the use of mineral resource materials native to the Appalachian region
- 6. The contractor shall include the provisions of Sections 1 through 4 of this Attachment A in every subcontract for work which is, or reasonably may be, done as on-site work.

NON-DISCRIMINATION PROVISIONS

During the performance of this contract, the contractor, for itself, its assignees, and successors in interest (hereinafter referred to as the "contractor") agrees as follows:

- **1. Compliance with Regulations:** The contractor (hereinafter includes consultants) will comply with the Acts and the Regulations relative to Non-discrimination in Federally-assisted programs of the U.S. Department of Transportation, Federal Highway Administration, as they may be amended from time to time, which are herein incorporated by reference and made a part of this contract.
- **2. Non-discrimination:** The contractor, with regard to the work performed by it during the contract, will not discriminate on the grounds of race, color, or national origin in the selection and retention of subcontractors, including procurements of materials and leases of equipment. The contractor will not participate directly or indirectly in the discrimination prohibited by the Acts and the Regulations, including employment practices when the contract covers any activity, project, or program set forth in Appendix B of 49 CFR Part 21.
- **3. Solicitations for Subcontracts, Including Procurements of Materials and Equipment:** In all solicitations, either by competitive bidding, or negotiation made by the contractor for work to be performed under a subcontract, including procurements of materials, or leases of equipment, each potential subcontractor or supplier will be notified by the contractor of the contractor's obligations under this contract and the Acts and the Regulations relative to Non-discrimination on the grounds of race, color, or national origin.
- **4. Information and Reports:** The contractor will provide all information and reports required by the Acts, the Regulations, and directives issued pursuant thereto and will permit access to its books, records, accounts, other sources of information, and its facilities as may be determined by the Recipient or the Federal Highway Administration to be pertinent to ascertain compliance with such Acts, Regulations, and instructions. Where any information required of a contractor is in the exclusive possession of another who fails or refuses to furnish the information, the contractor will so certify to the Recipient or the Federal Highway Administration, as appropriate, and will set forth what efforts it has made to obtain the information.
- **5. Sanctions for Noncompliance:** In the event of a contractor's noncompliance with the Non-discrimination provisions of this contract, the Recipient will impose such contract sanctions as it or the Federal Highway Administration may determine to be appropriate, including, but not limited to:
 - a. Withholding payments to the contractor under the contract until the contractor complies; and/or
 - b. Cancelling, terminating, or suspending a contract, in whole or in part.
- **6. Incorporation of Provisions:** The contractor will include the provisions of paragraphs one through six in every subcontract, including procurements of materials and leases of equipment, unless exempt by the Acts, the Regulations and directives issued pursuant thereto. The contractor will take action with respect to any subcontract or procurement as the Recipient or the Federal Highway Administration may direct as a means of enforcing such provisions including sanctions for noncompliance. Provided, that if the contractor becomes involved in, or is threatened with litigation by a subcontractor, or supplier because of such direction, the contractor may request the Recipient to enter into any litigation to protect the interests of the Recipient. In addition, the contractor may request the United States to enter into the litigation to protect the interests of the United States.

During the performance of this contract, the contractor, for itself, its assignees, and successors in interest (hereinafter referred to as the "contractor") agrees to comply with the following non-discrimination statutes and authorities; including but not limited to:

Pertinent Non-Discrimination Authorities:

- Title VI of the Civil Rights Act of 1964 (42 U.S.C. § 2000d et seq., 78 stat. 252), (prohibits discrimination on the basis of race, color, national origin); and 49 CFR Part 21.
- The Uniform Relocation Assistance and Real Property Acquisition Policies Act of 1970, (42 U.S.C. § 4601), (prohibits unfair treatment of persons displaced or whose property has been acquired because of Federal or Federal-aid programs and projects);
- Federal-Aid Highway Act of 1973, (23 U.S.C. § 324 et seq.), (prohibits discrimination on the basis of sex);
- Section 504 of the Rehabilitation Act of 1973, (29 U.S.C. § 794 et seq.), as amended, (prohibits discrimination on the basis of disability); and 49 CFR Part 27;
- The Age Discrimination Act of 1975, as amended, (42 U.S.C. § 6101 et seq.), (prohibits discrimination on the basis of age);
- Airport and Airway Improvement Act of 1982, (49 USC § 471, Section 47123), as amended, (prohibits discrimination based on race, creed, color, national origin, or sex);
- The Civil Rights Restoration Act of 1987, (PL 100-209), (Broadened the scope, coverage and applicability of Title VI of the Civil Rights Act of 1964, The Age Discrimination Act of 1975 and Section 504 of the Rehabilitation Act of 1973, by expanding the definition of the terms "programs or activities" to include all of the programs or activities of the Federal-aid recipients, subrecipients and contractors, whether such programs or activities are Federally funded or not);
- Titles II and III of the Americans with Disabilities Act, which prohibit discrimination on the basis of disability in the operation of public entities, public and private transportation systems, places of public accommodation, and certain testing entities (42 U.S.C. §§ 12131-12189) as implemented by Department of Transportation regulations at 49 C.F.R. parts 37 and 38;
- The Federal Aviation Administration's Non-discrimination statute (49 U.S.C. § 47123) (prohibits discrimination on the basis of race, color, national origin, and sex);
- Executive Order 12898, Federal Actions to Address Environmental Justice in Minority Populations and Low-Income Populations, which ensures Non-discrimination against minority populations by discouraging programs, policies, and activities with disproportionately high and adverse human health or environmental effects on minority and low-income populations;
- Executive Order 13166, Improving Access to Services for Persons with Limited English
 Proficiency, and resulting agency guidance, national origin discrimination includes discrimination
 because of Limited English proficiency (LEP). To ensure compliance with Title VI, you must take
 reasonable steps to ensure that LEP persons have meaningful access to your programs (70 Fed.
 Reg. at 74087 to 74100);
- Title IX of the Education Amendments of 1972, as amended, which prohibits you from discriminating because of sex in education programs or activities (20 U.S.C. 1681 et seq).

NOTICE OF REQUIREMENT FOR AFFIRMATIVE ACTION TO ENSURE EQUAL EMPLOYMENT OPPORTUNITY (EXECUTIVE ORDER 11246)

- 1. The Offeror's or Bidder's attention is called to the "Employment Practices" and "Equal Opportunity Clause" set forth in the Required Contract Provisions, FHWA 1273.
- 2. The goals and timetables for minority and female participation expressed in percentage terms for the contractor's aggregate work force in each trade, on all construction work in the covered area, are as follows:

Goals for Minority Participation for Each Trade:

County	<u>%</u>	County	<u>%</u>	County	%
Adams	1.7	Iowa	1.7	Polk	2.2
Ashland	1.2	Iron	1.2	Portage	0.6
Barron	0.6	Jackson	0.6	Price	0.6
Bayfield	1.2	Jefferson	7.0	Racine	8.4
Brown	1.3	Juneau	0.6	Richland	1.7
Buffalo	0.6	Kenosha	3.0	Rock	3.1
Burnett	2.2	Kewaunee	1.0	Rusk	0.6
Calumet	0.9	La Crosse	0.9	St. Croix	2.9
Chippewa	0.5	Lafayette	0.5	Sauk	1.7
Clark	0.6	Langlade	0.6	Sawyer	0.6
Columbia	1.7	Lincoln	0.6	Shawano	1.0
Crawford	0.5	Manitowoc	1.0	Sheboygan	7.0
Dane	2.2	Marathon	0.6	Taylor	0.6
Dodge	7.0	Marinette	1.0	Trempealeau	0.6
Door	1.0	Marquette	1.7	Vernon	0.6
Douglas	1.0	Menominee	1.0	Vilas	0.6
Dunn	0.6	Milwaukee	8.0	Walworth	7.0
Eau Claire	0.5	Monroe	0.6	Washburn	0.6
Florence	1.0	Oconto	1.0	Washington	8.0
Fond du Lac	1.0	Oneida	0.6	Waukesha	8.0
Forest	1.0	Outagamie	0.9	Waupaca	1.0
Grant	0.5	Ozaukee	8.0	Waushara	1.0
Green	1.7	Pepin	0.6	Winnebago	0.9
Green Lake	1.0	Pierce	2.2	Wood	0.6

Goals for female participation for each trade: 6.9%

These goals are applicable to all the contractor's construction work, (whether or not it is federal or federally assisted), performed in the covered area. If the contractor performs construction work in the geographical area located outside of the covered area, it shall apply the goals established for such geographical area where the work is actually performed. With regard to this second area, the contractor also is subject to the goals for both its federally involved and nonfederally involved construction.

The contractor's compliance with the Executive Order and the Regulations in 41 CFR Part 60-4 shall be based on its implementation of the Equal Opportunity Clause, specific affirmative action obligations required by the specifications set forth in 41 CFR 60-4.3(a), and its efforts to meet the goals. The hours of minority and female employment and training must be substantially uniform throughout the length of the contract, and in each trade, and the contractor shall make a good faith effort to employ minorities and women evenly on each of its projects. The transfer of minority or female employees or trainees from contractor to contractor or from project to project for the sole purpose of meeting the contractor's goals shall be a violation of the contract, the Executive Order and the Regulations in 41 CFR Part 60-4. Compliance with the goals will be measured against the total work hours performed.

3. The contractor shall provide written notification to the Director of the Office of Federal Contract Compliance Programs within ten (10) working days of award of any construction subcontract in excess of \$10,000.00 at any tier for construction work under the contract resulting from this solicitation. The notification shall list the name, address and telephone number of the subcontractor, employer identification number of the subcontractor; estimated dollar amount of the subcontract; estimated starting and completion dates of the subcontract; and the geographical area in which the subcontract is to be performed.

As referred to in this section, the Director means:

Director
Office of Federal Contract Compliance Programs
Ruess Federal Plaza
310 W. Wisconsin Ave., Suite 1115
Milwaukee, WI 53202

The "Employer Identification Number" means the Federal Social Security number used on the Employer's Quarterly Federal Tax Return, U.S. Treasury Department Form 941.

4. As used in this notice, and in the contract resulting from solicitation, the "covered area" is the county(ies) in Wisconsin to which this proposal applies.

ADDITIONAL FEDERAL-AID PROVISIONS

NOTICE TO ALL BIDDERS

To report bid rigging activities call:

1-800-424-9071

The U.S. Department of Transportation (DOT) operates the above toll-free "hotline" Monday through Friday, 8:00 a.m. to 5:00 p.m., Eastern Time. Anyone with knowledge of possible bid rigging, bidding collusion, or other fraudulent activities should use the "hotline" to report such activities.

The "hotline" is part of the DOT's continuing effort to identify and investigate highway construction contract fraud and abuse and is operated under the direction of the DOT Inspector General. All information will be treated confidentially and caller anonymity will be respected.

DOMESTIC MATERIALS PREFERENCE PROVISION

Domestic Materials Preference (in accordance with the Buy America Act per 23 CFR 635.410, and the Build America-Buy America Act (BABA) per 2 CFR Part 184, and 2 CFR Part 200) shall be articles, materials, or supplies permanently incorporated in this project as classified in the following four categories, and as described in the Construction and Materials Manual (CMM):

1. Iron and Steel

To be considered domestic, all steel and iron products used, and all products predominantly manufactured from steel or iron must be produced in the United States in accordance with the steel and iron product standards in 23 CFR 635.410.

This includes smelting, coating, bending, shaping, and all other manufacturing processes performed on the product. Coating includes all processes which protect or enhance the value of the material to which the coating is applied.

Products that are predominantly iron or steel or a combination of both as defined in 23 CFR 635.410 are considered Steel and Iron products and must comply with this section.

2. Construction Materials

To be considered domestic, all construction materials used must be produced in the United States in accordance with the construction material standards in 2 CFR 184.6:

- Non-ferrous metals: All manufacturing processes, from initial smelting or melting through final shaping, coating, and assembly, occurred in the United States.
- <u>Plastic and polymer-based products</u>: All manufacturing processes, from initial combination of constituent plastic or polymer-based inputs, or, where applicable, constituent composite materials, until the item is in its final form, occurred in the United States.
- Glass. All manufacturing processes, from initial batching and melting of raw materials through annealing, cooling, and cutting, occurred in the United States.
- <u>Fiber optic cable (including drop cable)</u>: All manufacturing processes, from the initial ribboning (if applicable), through buffering, fiber stranding and jacketing, occurred in the United States. All manufacturing processes also include the standards for glass and optical fiber, but not for nonferrous metals, plastic and polymer-based products, or any others.
- Optical fiber: All manufacturing processes, from the initial preform fabrication stage through the completion of the draw, occurred in the United States.
- <u>Lumber</u>: All manufacturing processes, from initial debarking through treatment and planning, occurred in the United States.
- <u>Drywall</u>: All manufacturing processes, from initial blending of mined or synthetic gypsum plaster and additives through cutting and drying of sandwiched panels, occurred in the United States.
- Engineered wood: All manufacturing processes from the initial combination of constituent materials until the wood product is in its final form, occurred in the United States.

3. Manufactured Products

To be considered domestic, all manufactured products used must be produced in the United States as defined in 23 CFR 635.410(c)(1)(vii):

- For projects with let dates on or after October 1, 2025, the final step in the manufacturing process must occur in the United States.
- For projects with let dates on or after October 1, 2026, the final step in the manufacturing process must occur in the United States and the cost of the components of the manufactured product that are mined, produced, or manufactured in the United States must be greater than 55 percent of the total cost of all components of the manufactured product.

Manufactured products means articles, materials, or supplies that have been processed into a specific form and shape, or combined with other articles, materials, or supplies to create a product with different properties than the individual articles, materials, or supplies. If an item is classified as an iron or steel product, an excluded material, or construction material, then it is not a manufactured product. An article, material, or supply classified as a manufactured product may include components that are iron or steel

products, excluded materials, or construction materials. Mixtures of excluded materials delivered to a work site without final form for incorporation into a project are not a manufactured product.

Items that consist of two or more construction materials that have been combined together through a manufacturing process, and items that include at least one construction material combined with a material that is not a construction material (including steel/iron) through a manufacturing process are treated as manufactured products, rather than as construction materials.

Products that are classified as predominantly iron or steel do not meet the definition of a manufactured product and must comply with section 1.

With respect to precast concrete products that are classified as manufactured products, components of precast concrete products that consist wholly or predominantly of iron or steel or a combination of both shall meet the requirements of section 1. The cost of such components shall be included in the applicable calculation for purposes of determining whether the precast concrete product is produced in the United States.

With respect to intelligent transportation systems and other electronic hardware systems that are installed in the highway right of way or other real property **and classified as manufactured products**, the cabinets or other enclosures of such systems that consist wholly or predominantly of iron or steel or a combination of both shall meet the requirements of section 1. The cost of cabinets or other enclosures shall be included in the applicable calculation for purposes of determining whether systems referred to in the preceding sentence are produced in the United States.

4. Temporary and Excluded Materials

Temporary materials, and excluded materials meeting the definition of Section 70917(c) Materials as defined in <u>2 CFR 184</u>, do not have any domestic materials requirements. Section 70917(c) Materials means cement and cementitious materials; aggregates such as stone, sand, or gravel; or aggregate binding agents or additives. Mixtures of excluded materials delivered to a work site without final form for incorporation into a project are not a manufactured product.

The classification of an article, material, or supply as falling into one of the categories listed in this section will be made based on its status at the time it is brought to the work site for incorporation into the project. Except as otherwise provided, an article, material, or supply incorporated into an infrastructure project must meet the Domestic Material Preference for only the single category in which it is classified.

Requirements do not preclude a minimal use of foreign steel and iron provided the cost of such materials do not exceed 0.1 percent (0.1%) of the total contract cost or \$2500 whichever is greater. The total contract cost is the contract amount at award.

For each iron or steel product subject to meeting domestic materials requirements, that doesn't fully meet Buy America Act requirements, the following documentation must be provided by the Contractor to verify the foreign steel value. Ensure the threshold is not exceeded and place the documentation in the project files.

- Pay Item,
- · Description of associated foreign iron or steel product, or component,
- Invoiced cost of associated foreign iron or steel product, or component, and
- Current cumulative list of all foreign iron or steel products with the total dollar amount of foreign products in relation to the total contract amount.

The minimal use of foreign iron or steel under the minimal usage threshold must be approved by the Engineer prior to incorporation into the project and any associated payment under the contract. The use of foreign iron or steel under the minimal usage threshold does not need to be approved by FHWA. This amount is not considered a waiver to the domestic materials requirements. The Contractor must ensure that the minimal usage amount is not exceeded.

The contractor shall take actions and provide documentation conforming to CMM 228.5 to ensure compliance with this Domestic Material provision.

https://wisconsindot.gov/rdwy/cmm/cm-02-28.pdf

Upon completion of the project, certify to the engineer, in writing using department form DT4567 that all iron and steel, construction materials, and manufactured products conform to this domestic material provision.

Form DT4567 is available at: https://wisconsindot.gov/Documents/formdocs/dt4567.docx

Attach a list of foreign iron or steel and their associated costs to the certification form using the Domestic Material Exemption Tracking Tool, available at:

 $\underline{https://wisconsindot.gov/hccidocs/contracting-info/buy-america-exemption-tracking-tool.xlsx}$

CARGO PREFERENCE ACT REQUIREMENT

All Federal-aid projects shall comply with 46 CFR 381.7 (a) – (b) as follows:

- (a) Agreement Clauses. "Use of United States-flag vessels:"
- (1) Pursuant to Pub. L. 664 (43 U.S.C. 1241(b)) at least 50 percent of any equipment, materials or commodities procured, contracted for or otherwise obtained with funds granted, guaranteed, loaned, or advanced by the U.S. Government under this agreement, and which may be transported by ocean vessel, shall be transported on privately owned United States-flag commercial vessels, if available.
- (2) Within 20 days following the date of loading for shipments originating within the United States or within 30 working days following the date of loading for shipments originating outside the United States, a legible copy of a rated, 'on-board' commercial ocean bill-of-lading in English for each shipment of cargo described in paragraph (a)(1) of this section shall be furnished to both the Contracting Officer (through the prime contractor in the case of subcontractor bills-of-lading) and to the Division of National Cargo, Office of Market Development, Maritime Administration, Washington, DC 20590."
- (b) Contractor and Subcontractor Clauses. "Use of United States-flag vessels: The contractor agrees—"
- (1) To utilize privately owned United States-flag commercial vessels to ship at least 50 percent of the gross tonnage (computed separately for dry bulk carriers, dry cargo liners, and tankers) involved, whenever shipping any equipment, material, or commodities pursuant to this contract, to the extent such vessels are available at fair and reasonable rates for United States-flag commercial vessels.
- (2) To furnish within 20 days following the date of loading for shipments originating within the United States or within 30 working days following the date of loading for shipments originating outside the United States, a legible copy of a rated, 'on-board' commercial ocean bill-of-lading in English for each shipment of cargo described in paragraph (b) (1) of this section to both the Contracting Officer (through the prime contractor in the case of subcontractor bills-of-lading) and to the Division of National Cargo, Office of Market Development, Maritime Administration, Washington, DC 20590.
- (3) To insert the substance of the provisions of this clause in all subcontracts issued pursuant to this contract.

WISCONSIN DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION AND SYSTEM DEVELOPMENT

SUPPLEMENTAL REQUIRED CONTRACT PROVISIONS FOR PROJECTS WITH FEDERAL AID

I. PREVAILING WAGE RATES

The attached U.S. Department of Labor (Davis-Bacon Minimum Wage Rates) furnishes the minimum prevailing wage rates pursuant to the Davis-Bacon and Related Acts. The wage rates shown are the minimum rates required by the contract to be paid during its life, however this is not a representation that labor can be obtained at these rates. It is the responsibility of bidders to inform themselves as to the local labor conditions and prospective changes or adjustments of wage rates. No increase in the contract price will be allowed or authorized on account of the payment of wage rates in excess of those listed herein.

II. COVERAGE OF TRUCK DRIVERS

Truck drivers are covered by Davis-Bacon Minimum Wage Rates in the following circumstances:

- Drivers of a contractor or subcontractor for time spent working on the site of the work.
- Drivers of a contractor or subcontractor for time spent loading and/or unloading materials and supplies on the site of the work, if such time is not de minimis. https://www.dol.gov/whd/FOH/FOH Ch15.pdf
- Truck drivers transporting materials or supplies between a facility that is deemed part of the site of the work and the actual construction site.
- Truck drivers transporting portions of the building or work between a site established specifically for the performance of the contract where a significant portion of such building or work is constructed and the physical place where the building or work called for in the contract will remain.

Truck drivers are not covered by Davis-Bacon Minimum Wage Rates in the following circumstances:

- Material delivery truck drivers while off the site of the work.
- Drivers of a contractor or subcontractor traveling between a Davis-Bacon job and a commercial supply facility while they are off the site of the work."
- Truck drivers whose time spent on the site of the work is de minimis, such as only a few
 minutes at a time merely to pick up or drop off materials or supplies.

Details are available online at:

https://www.dol.gov/whd/recovery/pwrb/Tab9.pdf

https://wisconsindot.gov/Pages/doing-bus/civil-rights/labornwage/trckng.aspx

III. POSTINGS AT THE SITE OF THE WORK

In addition to the required postings furnished by the department, the contractor shall post the following in at least one conspicuous and accessible place at the site of work:

a. A copy of the contractor's Equal Employment Opportunity Policy.

All required documents shall be posted by the first day of work and be accurate and complete. Postings must be readable, in an area where they will be noticed, and maintained until the last day of work.

IV. RESOURCES

Required information regarding compliance with federal provisions is found in the following resources:

- FHWA-1273 included in this contract
- U.S. Department of Labor Prevailing Wage Resource Book
- U.S. Department of Labor Field Operations Handbook
- U.S. Code of Federal Regulations
- Any applicable law, Act, or Executive Order enacted by the federal government at the time of the letting of this contract

"General Decision Number: WI20250010 08/29/2025

Superseded General Decision Number: WI20240010

State: Wisconsin

Construction Type: Highway

Counties: Wisconsin Statewide.

HIGHWAY, AIRPORT RUNWAY & TAXIWAY CONSTRUCTION PROJECTS (does not include bridges over navigable waters; tunnels; buildings

in highway rest areas; and railroad construction)

Note: Contracts subject to the Davis-Bacon Act are generally required to pay at least the applicable minimum wage rate required under Executive Order 14026 or Executive Order 13658. Please note that these Executive Orders apply to covered contracts entered into by the federal government that are subject to the Davis-Bacon Act itself, but do not apply to contracts subject only to the Davis-Bacon Related Acts, including those set forth at 29 CFR 5.1(a)(1).

IIf the contract is entered linto on or after January 30. 2022, or the contract is renewed or extended (e.g., an |. The contractor must pay option is exercised) on or after January 30, 2022:

- . Executive Order 14026 generally applies to the contract.
- all covered workers at least \$17.75 per hour (or the applicable wage rate listed on this wage determination, if it is higher) for all hours spent performing on the contract in 2025.

If the contract was awarded on . Executive Order 13658 or between January 1, 2015 and January 29, 2022, and the contract is not renewed or extended on or after January 30, 2022:

- generally applies to the contract.
- . The contractor must pay all covered workers at least \$13.30 per hour (or the applicable wage rate listed on this wage determination, if it is higher) for all hours spent performing on that contract in 2025.

The applicable Executive Order minimum wage rate will be adjusted annually. If this contract is covered by one of the Executive Orders and a classification considered necessary for performance of work on the contract does not appear on this wage determination, the contractor must still submit a conformance request.

Additional information on contractor requirements and worker protections under the Executive Orders is available at http://www.dol.gov/whd/govcontracts.

Modification Number	Publication Date
0	01/03/2025
1	02/07/2025
2	02/21/2025
3	05/23/2025
4	06/06/2025
5	06/27/2025
6	07/04/2025
7	07/11/2025
8	07/25/2025
9	08/15/2025
10	08/29/2025

BRWI0001-002 06/01/2025

CRAWFORD, JACKSON, JUNEAU, LA CROSSE, MONROE, TREMPEALEAU, AND VERNON COUNTIES

	Rates	Fringes
BRICKLAYER	\$ 40.09	28.10
BRWI0002-002 06/01/2025		
ASHLAND, BAYFIELD, DOUGLAS, AND	IRON COUNTIES	
	Rates	Fringes
BRICKLAYER	\$ 48.60	29.31
BRWI0002-005 06/01/2025		

ADAMS, ASHLAND, BARRON, BROWN, BURNETT, CALUMET, CHIPPEWA, CLARK, COLUMBIA, DODGE, DOOR, DUNN, FLORENCE, FOND DU LAC,

FOREST, GREEN LAKE, IRON, JEFFERSON, KEWAUNEE, LANGLADE, LINCOLN, MANITOWOC, MARATHON, MARINETTE, MARQUETTE, MENOMINEE, OCONTO, ONEIDA, OUTAGAMIE, POLK, PORTAGE, RUSK, ST CROIX, SAUK, SHAWANO, SHEBOYGAN, TAYLOR, VILAS, WALWORTH, WAUPACA, WAUSHARA, WINNEBAGO, AND WOOD COUNTIES

	Rates	Fringes
CEMENT MASON/CONCRETE FINISHER	.\$ 46.01	29.31
BRWI0003-002 06/01/2024		
BROWN, DOOR, FLORENCE, KEWAUNEE,	MARINETTE, AND	OCONTO COUNTIES
	Rates	Fringes
BRICKLAYER	.\$ 38.45	27.41
BRWI0004-002 06/01/2025		
KENOSHA, RACINE, AND WALWORTH CO	UNTIES	
	Rates	Fringes
BRICKLAYER	.\$ 44.71	28.90
BRWI0006-002 06/01/2025		
ADAMS, CLARK, FOREST, LANGLADE, ONEIDA, PORTAGE, PRICE, TAYLOR,		
	Rates	Fringes
BRICKLAYER	.\$ 39.36	28.83
BRWI0007-002 06/01/2025		
GREEN, LAFAYETTE, AND ROCK COUNT	IES	
	Rates	Fringes
BRICKLAYER	.\$ 40.34	29.49
BRWI0008-002 06/01/2025		

MILWAUKEE, OZAUKEE, WASHINGTON, AND WAUKESHA COUNTIES

	Rates	Fringes
BRICKLAYER	•	27.42
BRWI0011-002 06/01/2024		
CALUMET, FOND DU LAC, MANITOWOC	, AND SHEBOYGA	N COUNTIES
	Rates	Fringes
BRICKLAYER	\$ 38.45	27.41
BRWI0019-002 06/01/2025		
BARRON, BUFFALO, BURNETT, CHIPPI PIERCE, POLK, RUSK, ST. CROIX, S		
	Rates	Fringes
BRICKLAYER	\$ 39.50	28.69
BRWI0034-002 06/01/2025		
COLUMBIA AND SAUK COUNTIES		
	Rates	Fringes
BRICKLAYER	\$ 41.17	28.66
CARP0068-011 05/05/2025		
BURNETT (W. of Hwy 48), PIERCE (35, 48 & 65), AND ST. CROIX (W.		
	Rates	Fringes
CARPENTER	\$ 47.71	31.17 30.98
CARP0231-002 06/01/2025		
KENOSHA, MILWAUKEE, OZAUKEE, RAG COUNTIES	CINE, WASHINGT	ON, AND WAUKESHA

Rates Fringes

CARPENTER\$	47.73	31.52
CARP0310-002 06/03/2024		
ADAMS, ASHLAND, BAYFIELD (Eastern LANGLADE, LINCOLN, MARATHON, ONEID. (Western Portion of the County), T. COUNTIES	A, PORTAGE, PR	ICE, SHAWANO
	Rates	Fringes
CARPENTER\$ Piledriver\$		28.44 28.44
CARP0314-001 06/02/2025		
COLUMBIA, DANE, DODGE, GRANT, GREE LAFAYETTE, RICHLAND, ROCK, SAUK, A		
	Rates	Fringes
Carpenter\$ Piledrivermen\$		28.78 28.78
CARP0361-004 05/05/2025		
BAYFIELD (West of Hwy 63) AND DOUG	LAS COUNTIES	
	Rates	Fringes
CARPENTER\$	46.82	31.92
CARP0731-002 06/03/2024		
CALUMET (Eastern Portion of the Co Portion of the County), MANITOWOC,		
	Rates	Fringes
CARPENTER\$ Piledriver\$	42.44	28.44 28.44
CARP0955-002 06/03/2024		

CARP0955-002 06/03/2024

CALUMET (Western Portion of the County), FOND DU LAC (Western Portion of the County), GREEN LAKE, MARQUETTE, OUTAGAMIE,

	Rates	Fringes
CARPENTER		28.44
PILEDRIVER	\$ 42.44	28.44

CARP1056-002 06/01/2024

ADAMS, ASHLAND, BARRON, BAYFIELD, BROWN, BUFFALO, BURNETT, CALUMET, CHIPPEWA, CLARK, COLUMBIA, CRAWFORD, DANE, DODGE, DOOR, DUNN, EAU CLAIRE, FLORENCE, FOND DU LAC, FOREST, GRANT, GREEN, GREEN LAKE, IOWA, IRON, JACKSON, JEFFERSON, JUNEAU, KEWAUNEE, LA CROSSE, LAFAYETTE, LANGLADE, LINCOLN, MANITOWOC, MARATHON, MARINETTE, MARQUETTE, MENOMINEE, MONROE, OCONTO, ONEIDA, OUTAGAMIE, PEPIN, PIERCE (E. of Hwy. 29 & 65), POLK (E. of Hwy. 35, 48 & 65), PORTAGE, PRICE, RICHLAND, ROCK, RUSK, SAUK, SAWYER, SHAWANO, SHEBOYGAN, ST. CROIX (E. of Hwy. 65), TAYLOR, TREMPEALEAU, VERNON, VILAS, WALWORTH, WASHBURN, WAUPACA, WAUSHARA, WINNEBAGO, AND WOOD COUNTIES

	Rates	Fringes	
MILLWRIGHT	\$ 42.00	28.85	_
			_

CARP1074-002 06/03/2024

BARRON, BURNETT, CHIPPEWA, CLARK, DUNN, EAU CLAIRE, PEPIN, PIERCE (E. of Hwy. 29 & 65), POLK (E. of Hwy. 35, 48 & 65), RUSK, SAWYER, ST. CROIX (E. of Hwy. 65), AND WASHBURN

	Rates	Fringes
CARPENTER		28.44
PILEDRIVER\$	6 42.44 	28.44

CARP1143-002 06/03/2024

BUFFALO, CRAWFORD, JACKSON, LA CROSSE, MONROE, TREMPEALEAU AND VERNON COUNTIES

	Rates	Fringes
CARPENTER	\$ 42.44	28.44
PILEDRIVER	\$ 42.44	28.44

CARP1146-002 06/03/2024

BROWN, DOOR, FLORENCE, KEWAUNEE, MARINETTE, MENOMINEE, OCONTO, AND SHAWANO (Western Portion of the County) COUNTIES

	Rates	Fringes	
CARPENTER		28.44	
PILEDRIVER	\$ 42.44	28.44	
640000000000000000000000000000000000000			

CARP2337-009 06/03/2024

KENOSHA, MILWAUKEE, OZAUKEE, RACINE, WASHINGTON, AND WAUKESHA

	,	
	Rates	Fringes
PILEDRIVERMAN	.\$ 42.21	34.07
FLFC0014 002 0F /2F /202F		

ELEC0014-002 05/25/2025

ASHLAND, BARRON, BAYFIELD, BUFFALO, BURNETT, CHIPPEWA, CLARK (except Maryville, Colby, Unity, Sherman, Fremont, Lynn & Sherwood), CRAWFORD, DUNN, EAU CLAIRE, GRANT, IRON, JACKSON, LA CROSSE, MONROE, PEPIN, PIERCE, POLK, PRICE, RICHLAND, RUSK, ST CROIX, SAWYER, TAYLOR, TREMPEALEAU, VERNON, AND WASHBURN COUNTIES

	Rates	Fringes
Electricians:	\$ 44.29	25.21

ELEC0014-007 05/25/2025

ADAMS, ASHLAND, BARRON, BAYFIELD, BROWN, BUFFALO, BURNETT, CALUMET, CHIPPEWA, CLARK, COLUMBIA, CRAWFORD, DANE, DODGE, DOOR, DOUGLAS, DUNN, EAU CLAIRE, FLORENCE, FOND DU LAC, FOREST, GRANT, GREEN, GREEN LAKE, IOWA, IRON, JACKSON, JEFFERSON, JUNEAU, KENOSHA, KEWAUNEE, LA CROSSE, LAFAYETTE, LANGLADE, LINCOLN, MARATHON, MARINETTE, MARQUETTE, MENOMINEE, MONROE, OCONTO, ONEIDA, OUTAGAMIE, PEPIN, PIERCE, POLK, PORTAGE, PRICE, RACINE, RICHLAND, ROCK, RUSK, SAUK, SAWYER, SHAWANO, SHEBOYGAN, ST CROIX, TAYLOR, TREMPEALEAU, VERNON, VILAS, WALWORTH, WASHBURN, WAUPACA, WAUSHARA, WINNEBAGO AND WOOD COUNTIES

Rates Fringes

Teledata System Installer	
<pre>Installer/Technician\$ 31.17</pre>	20.08

Low voltage construction, installation, maintenance and removal of teledata facilities (voice, data, and video) including outside plant, telephone and data inside wire, interconnect, terminal equipment, central offices, PABX, fiber optic cable and equipment, micro waves, V-SAT, bypass, CATV, WAN (wide area networks), LAN (local area networks), and ISDN (integrated systems digital network).

ELEC0127-002 06/01/2023

KENOSHA COUNTY

Rates Fringes

Electricians:.....\$ 46.05 30%+13.15

ELEC0158-002 06/01/2024

BROWN, DOOR, KEWAUNEE, MANITOWOC (except Schleswig), MARINETTE(Wausuakee and area South thereof), OCONTO, MENOMINEE (East of a ine 6 miles West of the West boundary of Oconto County), SHAWANO (Except Area North of Townships of Aniwa and Hutchins) COUNTIES

Rates Fringes

ELECTRICIAN.....\$ 40.25 29.75%+11.17

ELEC0159-003 05/26/2024

COLUMBIA, DANE, DODGE (Area West of Hwy 26, except Chester and Emmet Townships), GREEN, LAKE (except Townships of Berlin, Seneca, and St. Marie), IOWA, MARQUETTE (except Townships of Neshkoka, Crystal Lake, Newton, and Springfield), and SAUK COUNTIES

Rates Fringes

ELECTRICIAN.....\$ 48.55 25.93

.----

ELEC0219-004 06/01/2019

FLORENCE COUNTY (Townships of Aurora, Commonwealth, Fern, Florence and Homestead) AND MARINETTE COUNTY (Township of Niagara)

	Rates	Fringes
Electricians:		
Electrical contracts over \$180,000	.\$ 33.94	21.80
Electrical contracts under	•	
\$180,000	.\$ 31.75	21.73
ELEC0242-005 06/01/2025		
DOUGLAS COUNTY		
	Rates	Fringes
Electricians:	•	33.34
ELEC0388-002 06/01/2024		
ADAMS, CLARK (Colby, Freemont, Lynn, Mayville, Sherman, Sherwood, Unity), FOREST, JUNEAU, LANGLADE, LINCOLN, MARATHON, MARINETTE (Beecher, Dunbar, Goodman & Pembine), MENOMINEE (Area West of a line 6 miles West of the West boundary of Oconto County), ONEIDA, PORTAGE, SHAWANO (Aniwa and Hutchins), VILAS AND WOOD COUNTIES		
	Rates	Fringes
Electricians:	.\$ 40.19	26%+12.45
ELEC0430-002 06/01/2024		
RACINE COUNTY (Except Burlington Township)		
	Rates	Fringes
Electricians:	•	26.25
ELEC0494-005 06/01/2025		
MILWAUKEE, OZAUKEE, WASHINGTON,	AND WAUKESHA CO	OUNTIES

Rates Fringes

CALUMET (Township of New Holstein), DODGE (East of Hwy 26 including Chester Township), FOND DU LAC, MANITOWOC (Schleswig), and SHEBOYGAN COUNTIES

	Rates	Fringes
Electricians:	\$ 45.20	25.27

ELEC0494-013 05/26/2024

DODGE (East of Hwy 26 including Chester Twp, excluding Emmet Twp), FOND DU LAC (Except Waupuin), MILWAUKEE, OZAUKEE, MANITOWOC (Schleswig), WASHINGTON, AND WAUKESHA COUNTIES

	Rates	Fringes
Sound & Communications		
Installer	\$ 36.03	18.87
Technician	\$ 36.03	18.87

Installation, testing, maintenance, operation and servicing of all sound, intercom, telephone interconnect, closed circuit TV systems, radio systems, background music systems, language laboratories, electronic carillion, antenna distribution systems, clock and program systems and low-voltage systems such as visual nurse call, audio/visual nurse call systems, doctors entrance register systems. Includes all wire and cable carrying audio, visual, data, light and radio frequency signals. Includes the installation of conduit, wiremold, or raceways in existing structures that have been occupied for six months or more where required for the protection of the wire or cable, but does not mean a complete conduit or raceway system. work covered does not include the installation of conduit, wiremold or any raceways in any new construction, or the installation of power supply outlets by means of which external electric power is supplied to any of the foregoing equipment or products

ELEC0577-003 05/26/2024

CALUMET (except Township of New Holstein), GREEN LAKE (N. part

including Townships of Berlin, St Marie, and Seneca), MARQUETTE (N. part including Townships of Crystal Lake, Neshkoro, Newton, and Springfield), OUTAGAMIE, WAUPACA, WAUSHARA, AND WINNEBAGO COUNTIES

	Rates	Fringes
Electricians:	40.00	22.69
ELEC0890-003 06/01/2024		
DODGE (Emmet Township only), GREEN RACINE (Burlington Township), ROCK	N, JEFFERSON, L K AND WALWORTH	AFAYETTE, COUNTIES
	Rates	Fringes
Electricians:		95%+12.26
ELEC0953-001 06/02/2019		
	Rates	Fringes
Line Construction: (1) Lineman		21.43
Operator		19.80
(3) Equipment Operator(4) Heavy Groundman Driver		18.40 16.88
(5) Light Groundman Driver		16.11
(6) Groundsman		14.60
ENGI0139-005 06/01/2025		
	Rates	Fringes
Power Equipment Operator Group 1	\$ 47.87 \$ 46.77 \$ 46.51	30.30 30.30 30.30 30.30 30.30
Group 6	40.32	30.30
HAZARDOUS WASTE PREMIUMS: EPA Level ""A"" protection - \$3.00 EPA Level ""B"" protection - \$2.00 EPA Level ""C"" protection - \$1.00	90 per hour	

- GROUP 1: Cranes, tower cranes, and derricks with or without attachments with a lifting capacity of over 100 tons; or cranes, tower cranes, and derricks with boom, leads and/or jib lengths measuring 176 feet or longer.
- GROUP 2: Cranes, tower cranes and derricks with or without attachments with a lifting capacity of 100 tons or less; or cranes, tower cranes, and derricks with boom, leads, and/or jibs lengths measuring 175 feet or under and Backhoes (excavators) weighing 130,000 lbs and over; caisson rigs; pile driver; dredge operator; dredge engineer; Boat Pilot.
- GROUP 3: Mechanic or welder Heavy duty equipment; cranes with a lifting capacity of 25 tons or under; concrete breaker (manual or remote); vibratory/sonic concrete breaker: concrete laser screed: concrete slipform paver: concrete batch plant operator; concrete pvt. spreader heavy duty (rubber tired); concrete spreader & distributor; automatic subgrader (concrete); concrete grinder & planing machine; concrete slipform curb & gutter machine; slipform concrete placer; tube finisher; hydro blaster (10,000 psi & over); bridge paver; concrete conveyor system; concrete pump; Rotec type Conveyor; stabilizing mixer (self-propelled); shoulder widener; asphalt plant engineer; bituminious paver; bump cutter & grooving machine; milling machine; screed (bituminous paver); asphalt heater, planer & scarifier; Backhoes (excavators) weighing under 130,000 lbs; grader or motor patrol; tractor (scraper, dozer, pusher, loader); scraper - rubber tired (single or twin engine); endloader; hydraulic backhoe (tractor type); trenching machine; skid rigs; tractor, side boom (heavy); drilling or boring machine (mechanical heavy); roller over 5 tons: percussion or rotary drilling machine: air track: blaster: loading machine (conveyor); tugger: boatmen: winches & A-frames; post driver; material hoist.
- GROUP 4: Greaser, roller steel (5 tons or less); roller (pneumatic tired) self propelled; tractor (mounted or towed compactors & light equipment); shouldering machine; self- propelled chip spreader; concrete spreader; finishing machine; mechanical float; curing machine; power subgrader; joint sawer (multiple blade) belting machine; burlap machine; texturing machine; tractor endloader (rubber tired) light; jeep digger; forklift; mulcher; launch operator; fireman, environmental burner

GROUP 5: Air compressor; power pack; vibrator hammer and extractor; heavy equipment, leadman; tank car heaters; stump chipper; curb machine operator; Concrete proportioning plants; generators; mudjack operator; rock breaker; crusher or screening plant; screed (milling machine); automatic belt conveyor and surge bin; pug mill operator; Oiler, pump (over 3 inches); Drilling Machine Tender, day light machine

GROUP 6: Off-road material hauler with or without ejector.

IRON0008-002 06/01/2025

BROWN, CALUMET, DOOR, FOND DU LAC, KEWAUNEE, MANITOWOC, MARINETTE, OCONTO, OUTAGAMI, SHAWANO, SHEBOYGAN, AND WINNEBAGO COUNTIES:

Rates Fringes

IRONWORKER.....\$ 44.66 33.67

Paid Holidays: New Year's Day, Memorial Day, July 4th, Labor Day, Thanksgiving Day & Christmas Day.

IRON0008-003 06/01/2025

KENOSHA, MILWAUKEE, OZAUKEE, RACINE, WALWORTH (N.E. 2/3), WASHINGTON, AND WAUKESHA COUNTIES

Rates Fringes

IRONWORKER.....\$ 47.52 33.67

Paid Holidays: New Year's Day, Memorial Day, July 4th, Labor Day, Thanksgiving Day & Christmas Day.

IRON0383-001 06/01/2025

ADAMS, COLUMBIA, CRAWFORD, DANE, DODGE, FLORENCE, FOREST, GRANT, GREENE, (Excluding S.E. tip), GREEN LAKE, IOWA, JEFFERSON, JUNEAU, LA CROSSE, LAFAYETTE, LANGLADE, MARATHON, MARQUETTE, MENOMINEE, MONROE, PORTAGE, RICHLAND, ROCK (Northern area, vicinity of Edgerton and Milton), SAUK, VERNON, WAUPACA, WAUSHARA, AND WOOD COUNTIES

	Rates	Fringes
IRONWORKER	\$ 44.00	32.66
IRON0498-005 06/01/2025		
GREEN (S.E. 1/3), ROCK (South o WALWORTH (S.W. 1/3) COUNTIES:	f Edgerton a	and Milton), and
	Rates	Fringes
IRONWORKER	\$ 48.74	49.65
IRON0512-008 05/01/2025		
BARRON, BUFFALO, CHIPPEWA, CLARK, DUNN, EAU CLAIRE, JACKSON, PEPIN, PIERCE, POLK, RUSK, ST CROIX, TAYLOR, AND TREMPEALEAU COUNTIES		
	Rates	Fringes
IRONWORKER	\$ 46.35	36.86
IRON0512-021 05/01/2025		
ASHLAND, BAYFIELD, BURNETT, DOU PRICE, SAWYER, VILAS AND WASHB		
	Rates	Fringes
IRONWORKER	\$ 42.89	36.86
LAB00113-002 06/02/2025		
MILWAUKEE AND WAUKESHA COUNTIES		
	Rates	Fringes
LABORER Group 1	\$ 38.96 \$ 39.16 \$ 39.31	25.53 25.53 25.53 25.53 25.53

	Group	6\$	35.30	25.53
--	-------	-----	-------	-------

LABORERS CLASSIFICATIONS

GROUP 1: General Laborer; Tree Trimmer; Conduit Layer; Demolition and Wrecking Laborer; Guard Rail, Fence, and Bridge Builder; Landscaper; Multiplate Culvert Assembler; Stone Handler; Bituminous Worker (Shoveler, Loader, and Utility Man); Batch Truck Dumper or Cement Handler; Bituminous Worker (Dumper, Ironer, Smoother, and Tamper); Concrete Handler

GROUP 2: Air Tool Operator; Joint Sawer and Filler (Pavement); Vibrator or Tamper Operator (Mechanical Hand Operated); Chain Saw Operator; Demolition Burning Torch Laborer

GROUP 3: Bituminous Worker (Raker and Luteman); Formsetter (Curb, Sidewalk, and Pavement); Strike Off Man

GROUP 4: Line and Grade Specialist

GROUP 5: Blaster and Powderman

GROUP 6: Flagperson; traffic control person

.....

LABO0113-003 06/02/2025

OZAUKEE AND WASHINGTON COUNTIES

	Rates	Fringes
LABORER		
Group 1	\$ 38.06	25.53
Group 2	\$ 38.16	25.53
Group 3	\$ 38.21	25.53
Group 4	\$ 38.41	25.53
Group 5	\$ 38.26	25.53
Group 6	\$ 35.15	25.53

LABORERS CLASSIFICATIONS

GROUP 1: General Laborer; Tree Trimmer; Conduit Layer; Demolition and Wrecking Laborer; Guard Rail, Fence, and Bridge Builder; Landscaper; Multiplate Culvert Assembler; Stone Handler; Bituminous Worker (Shoveler, Loader, and Utility Man); Batch Truck Dumper or Cement Handler; Bituminous Worker (Dumper, Ironer, Smoother, and Tamper);

Concrete Handler

GROUP 2: Air Tool Operator; Joint Sawer and Filler (Pavement); Vibrator or Tamper Operator (Mechanical Hand Operated);

GROUP 3: Bituminous Worker (Raker and Luteman); Formsetter (Curb, Sidewalk, and Pavement); Strike Off Man

GROUP 4: Line and Grade Specialist

GROUP 5: Blaster; powderman

GROUP 6: Flagperson and Traffic Control Person

LABO0113-011 06/02/2025

KENOSHA AND RACINE COUNTIES

		Rates	Fringes
LABORER			
Group	1	\$ 37.87	25.53
Group	2	\$ 38.02	25.53
Group	3	\$ 38.22	25.53
Group	4	\$ 38.19	25.53
Group	5	\$ 38.52	25.53
Group	6	\$ 35.02	25.53

LABORERS CLASSIFICATIONS:

GROUP 1: General laborer; Tree Trimmer; Conduit Layer; Demolition and Wrecking Laborer; Guard Rail, Fence, and Bridge Builder; Landscaper; Multiplate Culvert Assembler; Stone Handler; Bituminous Worker (Shoveler, Loader, and Utility Man); Batch Truck Dumper or Cement Handler; Bituminous worker (Dumper, Ironer, Smoother, and Tamper); Concrete Handler

GROUP 2: Air Tool Operator; Joint Sawer and Filler (Pavement); Vibrator or Tamper Operator (Mechanical Hand Operated); Chain Saw Operator; Demolition Burning Torch Laborer

GROUP 3: Bituminous Worker (Raker and Luteman); Formsetter (Curb, Sidewalk, and Pavement); Strike Off Man

GROUP 4: Line and Grade Specialist

GROUP 5: Blaster and Powderman

GROUP 6: Flagman; traffic control person

LAB00140-002 06/02/2025

ADAMS, ASHLAND, BARRON, BAYFIELD, BROWN, BUFFALO, BURNETT, CALUMET, CHIPPEWA, CLARK, COLUMBIA, CRAWFORD, DODGE, DOOR, DOUGLAS, DUNN, EAU CLAIRE, FLORENCE, FOND DU LAC, FOREST, GRANT, GREEN, GREEN LAKE, IRON, JACKSON, JUNEAU, IOWA, JEFFERSON, KEWAUNEE, LA CROSSE, LAFAYETTE, LANGLADE, LINCOLN, MANITOWOC, MARATHON, MARINETTE, MARQUETTE, MENOMINEE, MONROE, OCONTO, ONEIDA, OUTAGAMIE, PEPIN, PIERCE, POLK, PORTAGE, PRICE, RICHLAND, ROCK, RUSK, SAUK, SAWYER, SHAWANO, SHEBOYGAN, ST. CROIX, TAYLOR, TREMPEALEAU, VERNON, VILLAS, WALWORTH, WASHBURN, WAUPACA, WAUSHARA, WINNEBAGO, AND WOOD COUNTIES

		Rates	Fringes
LABORER			
Group	1	.\$ 43.77	19.97
Group	2	.\$ 43.87	19.97
Group	3	.\$ 43.92	19.97
Group	4	.\$ 44.12	19.97
Group	5	.\$ 43.97	19.97
Group	6	.\$ 40.40	19.97

LABORER CLASSIFICATIONS

GROUP 1: General Laborer; Tree Trimmer; Conduit Layer; Demolition and Wrecking Laborer; Guard Rail, Fence, and Bridge Builder; Landscaper; Multiplate Culvert Assembler; Stone Handler; Bitminous Worker (Shoveler, Loader, and Utility Man); Batch Truck Dumper or Cement Handler; Bituminous Worker (Dumper, Ironer, Smoother and Tamper); Concrete Handler

GROUP 2: Air Tool Operator; Joint Sawer and Filler (Pavement); Vibrator or Tamper Operator (Mechanical Hand Operated); Chain Saw Operator, Demolition Burning Torch Laborer

GROUP 3: Bituminous Worker (Raker and Luteman); Formsetter (Curb, Sidewalk and Pavement); Strike Off Man

GROUP 4: Line and Grade Secialist

GROUP 5: Blaster; powderman

GROUP 6: Flagperson; Traffic Control

LAB00464-003 06/02/2025

DANE COUNTY

		Rates	Fringes
LABORER			
Group	1	\$ 44.05	19.97
Group	2	\$ 44.15	19.97
Group	3	\$ 44.20	19.97
Group	4	\$ 44.40	19.97
Group	5	\$ 44.25	19.97
Group	6	\$ 40.40	19.97

LABORERS CLASSIFICATIONS:

GROUP 1: General Laborer; Tree Trimmer; Conduit Layer; Demolition and Wrecking Laborer; Guard Rail, Fence, and Bridge Builder; Landscaper; Multiplate Culvert Assembler; Stone Handler; Bituminous Worker (Shoveler, Loader, and Utility Man); Batch Truck Dumper or Cement Handler; Bituminious Worker (Dumper, Ironer, Smoother, and Tamper); Concrete Handler

GROUP 2: Air Tool Operator; Joint Sawer and Filler (Pavement); Vibrator or Tamper Operator (Mechanical Hand Operated); Chain Saw Operator; Demolition Burning Torch Laborer

GROUP 3: Bituminous Worker (Raker and Luteman); Formsetter (Curb, Sidewalk, and Pavement); Strike Off Man

GROUP 4: Line and Grade Specialist

GROUP 5: Blaster; Powderman

GROUP 6: Flagperson and Traffic Control Person

PAIN0106-008 05/05/2025

ASHLAND, BAYFIELD, BURNETT, AND DOUGLAS COUNTIES

	Rates	Fringes
Painters: New:		
Brush, Roller		27.26
Spray, Sandblast, Steel	.\$ 38.77	27.26
Repaint: Brush, Roller	.\$ 36.67	27.26
Spray, Sandblast, Steel	.\$ 37.27	27.26
PAIN0108-002 06/01/2025		
RACINE COUNTY		
	Rates	Fringes
Painters:		
Brush, Roller		23.35
Spray & Sandblast		23.35
PAIN0259-002 05/01/2008		
BARRON, CHIPPEWA, DUNN, EAU CLAI SAWYER, ST. CROIX, AND WASHBURN		PIERCE, POLK, RUSK,
	Rates	Fringes
PAINTER	.\$ 24.11	12.15
PAIN0259-004 05/01/2015		
BUFFALO, CRAWFORD, JACKSON, LA C VERNON COUNTIES	ROSSE, MONRO	DE, TREMPEALEAU, AND
	Rates	Fringes
PAINTER		12.45
PAIN0781-002 06/01/2025		
JEFFERSON, MILWAUKEE, OZAUKEE, W	ASHINGTON,	AND WAUKESHA COUNTIES
	Rates	Fringes
Painters:		
Bridge	.\$ 43.19	24.87
Brush	.\$ 42.44	24.87

	\$ 43.19	24.87
PAIN0802-002 06/01/2025		
COLUMBIA, DANE, DODGE, GRANT, ROCK, AND SAUK COUNTIES	GREEN, IOWA, L	AFAYETTE, RICHLAND,
	Rates	Fringes
PAINTER Brush	\$ 37.65	21.17
PREMIUM PAY: Structural Steel, Spray, Br hour.	idges = \$1.00	additional per
PAIN0802-003 06/01/2025		
ADAMS, BROWN, CALUMET, CLARK, LAKE, IRON, JUNEAU, KEWAUNEE, MARATHON, MARINETTE, MARQUETT OUTAGAMIE, PORTAGE, PRICE, SH. WAUSHARA, WAUPACA, WINNEBAGO,	LANGLADE, LINC E, MENOMINEE, AWANO, SHEBOYG AND WOOD COUNT	OLN, MANITOWOC, OCONTO, ONEIDA, AN, TAYLOR, VILAS,
	Rates	Fringes
DATNITED	Rates	Fringes
PAINTER PAIN0934-001 06/01/2025		Fringes 21.17
PAINTER PAIN0934-001 06/01/2025 KENOSHA AND WALWORTH COUNTIES	\$ 37.65	· ·
PAIN0934-001 06/01/2025	\$ 37.65	· ·
PAIN0934-001 06/01/2025	Rates\$ 40.62\$ 41.62\$ 40.77	21.17
PAIN0934-001 06/01/2025 KENOSHA AND WALWORTH COUNTIES Painters: Brush	Rates\$ 40.62\$ 41.62\$ 40.77	21.17 Fringes 26.37 26.37
PAIN0934-001 06/01/2025 KENOSHA AND WALWORTH COUNTIES Painters: Brush	Rates\$ 40.62\$ 41.62\$ 40.77	21.17 Fringes 26.37 26.37
PAIN0934-001 06/01/2025 KENOSHA AND WALWORTH COUNTIES Painters: Brush	Rates\$ 40.62\$ 41.62\$ 40.77	21.17 Fringes 26.37 26.37

* PLAS0599-002 06/01/2025

	Rates	Fringes
CEMENT MASON/CONCRETE FINISHER		
Area A	.\$ 47.17	30.35
Area B	.\$ 41.62	26.34
Area C	.\$ 40.06	28.65
Area D	.\$ 42.28	26.43
Area E	.\$ 41.16	27.54
Area F	.\$ 37.33	31.38

AREA DESCRIPTIONS

AREA A: ASHLAND, BURNETT, BAYFIELD, DOUGLAS, IRON, PRICE, SAWYER, AND WASHBURN COUNTIES

AREA B: ADAMS, BARRON, BROWN, CALUMET, CHIPPEWA, CLARK, COLUMBIA, DODGE, DOOR, DUNN, FLORENCE, FOND DU LAC, FOREST, GREEN LAKE, JEFFERSON, KEWAUNEE, LANGLADE, LINCOLN, MANITOWOC, MARATHON, MARINETTE, MARQUETTE, MENOMINEE, OCONTO, ONEIDA, OUTAGAMIE, POLK, PORTAGE, RUSK, ST. CROIX, SAUK, SHAWANO, SHEBOYGAN, TAYLOR, VILAS, WALWORTH, WAUPACA, WAUSHARA, WINNEBAGO, AND WOOD COUNTIES

AREA C: BUFFALO, CRAWFORD, EAU CLAIRE, JACKSON, JUNEAU, LA CROSSE, MONROE, PEPIN, PIERCE, RICHLAND, TREMPEALEAU, AND VERNON COUNTIES

AREA D: MILWAUKEE, OZAUKEE, WASHINGTON, AND WAUKESHA COUNTIES

AREA E: DANE, GRANT, GREEN, IOWA, LAFAYETTE, AND ROCK COUNTIES

AREA F: KENOSHA AND RACINE COUNTIES

TEAM0039-001 06/01/2025

	Rates	Fringes
TRUCK DRIVER 1 & 2 Axles	\$ 39.57	28.70
<pre>3 or more Axles; Euclids, Dumptor & Articulated, Truck Mechanic</pre>	\$ 39.72	28.70

WELDERS - Receive rate prescribed for craft performing operation to which welding is incidental.

Note: Executive Order (EO) 13706, Establishing Paid Sick Leave for Federal Contractors applies to all contracts subject to the Davis-Bacon Act for which the contract is awarded (and any solicitation was issued) on or after January 1, 2017. If this contract is covered by the EO, the contractor must provide employees with 1 hour of paid sick leave for every 30 hours they work, up to 56 hours of paid sick leave each year. Employees must be permitted to use paid sick leave for their own illness, injury or other health-related needs, including preventive care; to assist a family member (or person who is like family to the employee) who is ill, injured, or has other health-related needs, including preventive care; or for reasons resulting from, or to assist a family member (or person who is like family to the employee) who is a victim of, domestic violence, sexual assault, or stalking. Additional information on contractor requirements and worker protections under the EO is available at

https://www.dol.gov/agencies/whd/government-contracts.

Unlisted classifications needed for work not included within the scope of the classifications listed may be added after award only as provided in the labor standards contract clauses (29CFR 5.5 (a) (1) (iii)).

.....

The body of each wage determination lists the classifications and wage rates that have been found to be prevailing for the type(s) of construction and geographic area covered by the wage determination. The classifications are listed in alphabetical order under rate identifiers indicating whether the particular rate is a union rate (current union negotiated rate), a survey rate, a weighted union average rate, a state adopted rate, or a supplemental classification rate.

Union Rate Identifiers

A four-letter identifier beginning with characters other than ""SU"", ""UAVG"", ?SA?, or ?SC? denotes that a union rate was prevailing for that classification in the survey. Example: PLUM0198-005 07/01/2024. PLUM is an identifier of the union whose collectively bargained rate prevailed in the survey for this classification, which in this example would be Plumbers.

0198 indicates the local union number or district council number where applicable, i.e., Plumbers Local 0198. The next number, 005 in the example, is an internal number used in processing the wage determination. The date, 07/01/2024 in the example, is the effective date of the most current negotiated rate.

Union prevailing wage rates are updated to reflect all changes over time that are reported to WHD in the rates in the collective bargaining agreement (CBA) governing the classification.

Union Average Rate Identifiers

The UAVG identifier indicates that no single rate prevailed for those classifications, but that 100% of the data reported for the classifications reflected union rates. EXAMPLE: UAVG-OH-0010 01/01/2024. UAVG indicates that the rate is a weighted union average rate. OH indicates the State of Ohio. The next number, 0010 in the example, is an internal number used in producing the wage determination. The date, 01/01/2024 in the example, indicates the date the wage determination was updated to reflect the most current union average rate.

A UAVG rate will be updated once a year, usually in January, to reflect a weighted average of the current rates in the collective bargaining agreements on which the rate is based.

Survey Rate Identifiers

The ""SU"" identifier indicates that either a single non-union rate prevailed (as defined in 29 CFR 1.2) for this classification in the survey or that the rate was derived by computing a weighted average rate based on all the rates reported in the survey for that classification. As a weighted average rate includes all rates reported in the survey, it may include both union and non-union rates. Example: SUFL2022-007 6/27/2024. SU indicates the rate is a single non-union prevailing rate or a weighted average of survey data for that classification. FL indicates the State of Florida. 2022 is the year of the survey on which these classifications and rates are based. The next number, 007 in the example, is an internal number used in producing the wage determination. The date, 6/27/2024 in the example, indicates the survey completion date for the classifications and rates under that identifier.

?SU? wage rates typically remain in effect until a new survey is conducted. However, the Wage and Hour Division (WHD) has the discretion to update such rates under 29 CFR 1.6(c)(1).

State Adopted Rate Identifiers

The ""SA"" identifier indicates that the classifications and prevailing wage rates set by a state (or local) government were adopted under 29 C.F.R 1.3(g)-(h). Example: SAME2023-007 01/03/2024. SA reflects that the rates are state adopted. ME refers to the State of Maine. 2023 is the year during which the state completed the survey on which the listed classifications and rates are based. The next number, 007 in the example, is an internal number used in producing the wage determination. The date, 01/03/2024 in the example, reflects the date on which the classifications and rates under the ?SA? identifier took effect under state law in the state from which the rates were adopted.

WAGE DETERMINATION APPEALS PROCESS

1) Has there been an initial decision in the matter? This can be:

- a) a survey underlying a wage determination
- b) an existing published wage determination
- c) an initial WHD letter setting forth a position on a wage determination matter
- d) an initial conformance (additional classification and rate) determination

On survey related matters, initial contact, including requests for summaries of surveys, should be directed to the WHD Branch of Wage Surveys. Requests can be submitted via email to davisbaconinfo@dol.gov or by mail to:

Branch of Wage Surveys Wage and Hour Division U.S. Department of Labor 200 Constitution Avenue, N.W. Washington, DC 20210

Regarding any other wage determination matter such as conformance decisions, requests for initial decisions should be directed to the WHD Branch of Construction Wage Determinations. Requests can be submitted via email to BCWD-Office@dol.gov or by mail to:

Branch of Construction Wage Determinations Wage and Hour Division

U.S. Department of Labor 200 Constitution Avenue, N.W. Washington, DC 20210

2) If an initial decision has been issued, then any interested party (those affected by the action) that disagrees with the decision can request review and reconsideration from the Wage and Hour Administrator (See 29 CFR Part 1.8 and 29 CFR Part 7). Requests for review and reconsideration can be submitted via email to dba.reconsideration@dol.gov or by mail to:

Wage and Hour Administrator U.S. Department of Labor 200 Constitution Avenue, N.W. Washington, DC 20210

The request should be accompanied by a full statement of the interested party's position and any information (wage payment data, project description, area practice material, etc.) that the requestor considers relevant to the issue.

3) If the decision of the Administrator is not favorable, an interested party may appeal directly to the Administrative Review Board (formerly the Wage Appeals Board). Write to:

Administrative Review Board U.S. Department of Labor 200 Constitution Avenue, N.W. Washington, DC 20210.

END OF GENERAL DECISION"

NOTICE TO BIDDERS WAGE RATE DECISION

The wage rate decision of the Department of Labor which has been incorporated in these advertised specifications is incomplete in that the classifications may be omitted from the Department of Labor's decision.


Since the bidder is responsible, independently, for ascertaining area practice with respect to the necessity, or lack of necessity, for the use of these classifications in the prosecution of the work contemplated by this project, no inference may be drawn from the omission of these classifications concerning prevailing area practices relative to their use. Further, this omission will not, per se, be construed as establishing any governmental liability for increased labor cost if it is subsequently determined that such classifications are required.

There may be omissions and/or errors in the federal wage rates. The bidder is responsible for evaluating and determining the correct applicable rate.

If a project includes multiple types of construction (highway, bridge over navigable water, sanitary sewer and water main, building) and there is not a separate wage determination for this type of work included in the proposal, use the wage determination that is in the proposal.

If a project includes multiple types of construction, different wage rate determinations may be inserted into the contract (WI10/Highway = in all WisDOT highway contracts, WI15/Heavy = bridge over navigable water per USDOL and US Coast Guard designation, WI8/Heavy (Sewer & Water Line & Tunnel) = sanitary sewer and water main if the cost is more than 20% of the contract and/or at least \$1,000,000, and Building). If multiple wage rate determinations are inserted into the contract, use the classification in the wage determination for the work being done. Use WI15 wage rates when working on the bridge and/or structure from bank to bank. Use WI8 wage rates when working on any sanitary sewer or water main work. Use Building wage rates for all work done within the footprint of the building. Use WI10 wage rates for all other highway work in the contract and approaches to structures. For example, if a laborer is working within the footprint of a building, use the Laborer rate in the Building wage determination inserted in the contract. If a laborer is working on a bridge/structure within the banks, use the Laborer rate in the WI15/Heavy wage determination if inserted in the contract. If the laborer is working on the highway, use the Laborer rate in the WI10/Highway wage determination.







Page 1 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0002	204.0100 Removing Concrete Pavement	310.000 SY	·	<u> </u>
0004	204.0110 Removing Asphaltic Surface	1,030.000 SY	·	·
0006	204.0115 Removing Asphaltic Surface Butt Joints	520.000 SY		·
8000	204.0120 Removing Asphaltic Surface Milling	208,740.000 SY		·
0010	204.0150 Removing Curb & Gutter	3,550.000 LF	·	
0012	204.0155 Removing Concrete Sidewalk	3,290.000 SY		·
0014	204.0165 Removing Guardrail	1,140.000 LF	·	
0016	204.0195 Removing Concrete Bases	178.000 EACH		
0018	204.0220 Removing Inlets	2.000 EACH		
0020	204.0245 Removing Storm Sewer (size) 01. 12-Inch	45.000 LF	·	
0022	204.9060.S Removing (item description) 01. Traffic Signals STH 181 at Florist Ave	1.000 EACH	<u> </u>	·
0024	204.9060.S Removing (item description) 02. Traffic Signals STH 181 at Mill Rd	1.000 EACH	·	
0026	204.9060.S Removing (item description) 03. Traffic Signals STH 181 at Acacia St	1.000 EACH	<u> </u>	
0028	204.9060.S Removing (item description) 04. Traffic Signals STH 181 at Green Tree Rd	1.000 EACH	·	







Page 2 of 20


Proposal ID: 20251014030 **Project(s):** 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0030	204.9060.S Removing (item description) 05. Traffic Signals STH 181 at Good Hope Rd	1.000 EACH	<u></u>	
0032	204.9060.S Removing (item description) 06. Traffic Signals STH 181 at Calumet Rd	1.000 EACH	.	
0034	204.9060.S Removing (item description) 07. Traffic Signals STH 181 at Bradley Rd	1.000 EACH	<u> </u>	·
0036	204.9060.S Removing (item description) 08. Traffic Signals STH 181 at Tower Rd	1.000 EACH	·	·
0038	204.9060.S Removing (item description) 09. Traffic Signals STH 181 at Servite/Dean Rd	1.000 EACH	.	
0040	204.9060.S Removing (item description) 10. Traffic Signals STH 181 at Northridge Dr	1.000 EACH		·
0042	204.9060.S Removing (item description) 11. Traffic Signals STH 181 at Northridge Lakes Blvd	1.000 EACH		:
0044	204.9060.S Removing (item description) 12. Loop Detector Wire and Lead-In Cable STH 181 at Florist Ave	1.000 EACH		·
0046	204.9060.S Removing (item description) 13. Loop Detector Wire and Lead-In Cable STH 181 at Mill Rd	1.000 EACH	-	·
0048	204.9060.S Removing (item description) 14. Loop Detector Wire and Lead-In Cable STH 181 at Acacia St	1.000 EACH		·
0050	204.9060.S Removing (item description) 15. Loop Detector Wire and Lead-In Cable STH 181 at Green Tree Rd	1.000 EACH	<u>.</u>	







Page 3 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0052	204.9060.S Removing (item description) 16. Loop Detector Wire and Lead-In Cable STH 181 at Good Hope Rd	1.000 EACH	.	·
0054	204.9060.S Removing (item description) 17. Loop Detector Wire and Lead-In Cable STH 181 at Calumet Rd	1.000 EACH	.	
0056	204.9060.S Removing (item description) 18. Loop Detector Wire and Lead-In Cable STH 181 at Bradley Rd	1.000 EACH	.	·
0058	204.9060.S Removing (item description) 19. Loop Detector Wire and Lead-In Cable STH 181 at Tower Ave	1.000 EACH		·
0060	204.9060.S Removing (item description) 20. Loop Detector Wire and Lead-In Cable STH 181 at Servite/Dean Rd	1.000 EACH		
0062	204.9060.S Removing (item description) 21. Loop Detector Wire and Lead-In Cable STH 181 at Northridge Dr	1.000 EACH		
0064	204.9060.S Removing (item description) 22. Loop Detector Wire and Lead-In Cable STH 181 at Northridge Lakes Blvd	1.000 EACH		
0066	204.9060.S Removing (item description) 23. Loop Detector Wire and Lead-In Cable STH 181 at STH 100	1.000 EACH		
0068	205.0100 Excavation Common	1,360.000 CY		
0070	206.5001 Cofferdams (structure) 01. C-40-0053	1.000 EACH		·
0072	208.0100 Borrow	170.000 CY		







Page 4 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0074	208.1100 Select Borrow	90.000 CY		·
0076	213.0100 Finishing Roadway (project) 01. 2140- 14-70	1.000 EACH	.	·
0078	305.0120 Base Aggregate Dense 1 1/4-Inch	1,422.000 TON	<u> </u>	·
0080	390.0405 Base Patching Concrete SHES	85.000 CY		
0082	416.0610 Drilled Tie Bars	350.000 EACH		·
0084	416.0620 Drilled Dowel Bars	408.000 EACH	·	
0086	416.1715 Concrete Pavement Repair SHES	1,025.000 SY	<u> </u>	
0088	450.4000 HMA Cold Weather Paving	3,920.000 TON	·	
0090	455.0605 Tack Coat	29,300.000 GAL	<u> </u>	
0092	460.0105.S HMA Percent Within Limits (PWL) Test Strip Volumetrics	2.000 EACH		·
0094	460.0110.S HMA Percent Within Limits (PWL) Test Strip Density	2.000 EACH		·
0096	460.2005 Incentive Density PWL HMA Pavement	50,230.000 DOL	1.00000	50,230.00
0098	460.2007 Incentive Density HMA Pavement Longitudinal Joints	16,380.000 DOL	1.00000	16,380.00
0100	460.2010 Incentive Air Voids HMA Pavement	25,810.000 DOL	1.00000	25,810.00
0102	460.6223 HMA Pavement 3 MT 58-28 S	28,250.000 TON	.	







Page 5 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0104	460.6224 HMA Pavement 4 MT 58-28 S	21,972.000 TON		
0106	465.0110 Asphaltic Surface Patching	717.000 TON		·
0108	509.1500 Concrete Surface Repair	200.000 SF		
0110	522.0412 Culvert Pipe Reinforced Concrete Class IV 12-Inch	44.000 LF		·
0112	601.0407 Concrete Curb & Gutter 18-Inch Type D	610.000 LF	·	·
0114	601.0409 Concrete Curb & Gutter 30-Inch Type A	147.000 LF	·	
0116	601.0411 Concrete Curb & Gutter 30-Inch Type D	2,143.000 LF		
0118	601.0415 Concrete Curb & Gutter 6-Inch Sloped 30-Inch Type J	640.000 LF	·	·
0120	601.0600 Concrete Curb Pedestrian	467.000 LF		·
0122	602.0410 Concrete Sidewalk 5-Inch	36,153.000 SF	·	·
0124	602.0505 Curb Ramp Detectable Warning Field Yellow	1,232.000 SF	·	
0126	602.0605 Curb Ramp Detectable Warning Field Radial Yellow	150.000 SF	·	
0128	606.0100 Riprap Light	10.000 CY	·	
0130	611.0624 Inlet Covers Type H	2.000 EACH		
0132	611.3004 Inlets 4-FT Diameter	1.000 EACH		







Page 6 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0134	611.3230 Inlets 2x3-FT	1.000 EACH	<u> </u>	<u> </u>
0136	611.8110 Adjusting Manhole Covers	232.000 EACH	<u> </u>	<u> </u>
0138	611.8115 Adjusting Inlet Covers	8.000 EACH	·	
0140	611.8120.S Cover Plates Temporary	417.000 EACH		
0142	611.9710 Salvaged Inlet Covers	2.000 EACH		
0144	614.2300 MGS Guardrail 3	500.000 LF		·
0146	614.2330 MGS Guardrail 3 K	325.000 LF		
0148	614.2500 MGS Thrie Beam Transition	4.000 LF		
0150	614.2610 MGS Guardrail Terminal EAT	3.000 EACH		
0152	614.2620 MGS Guardrail Terminal Type 2	1.000 EACH		
0154	616.0204 Fence Chain Link 4-FT	72.000 LF		·
0156	619.1000 Mobilization	1.000 EACH		
0158	620.0300 Concrete Median Sloped Nose	154.000 SF		·
0160	625.0100 Topsoil	4,437.000 SY		
0162	628.1504 Silt Fence	3,260.000 LF		
0164	628.1520 Silt Fence Maintenance	3,260.000 LF		







Page 7 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0166	628.1905 Mobilizations Erosion Control	11.000 EACH	<u>-</u>	<u> </u>
0168	628.1910 Mobilizations Emergency Erosion Control	8.000 EACH	<u> </u>	
0170	628.7005 Inlet Protection Type A	15.000 EACH	·	
0172	628.7015 Inlet Protection Type C	440.000 EACH	<u> </u>	
0174	628.7504 Temporary Ditch Checks	230.000 LF	<u> </u>	
0176	629.0210 Fertilizer Type B	2.820 CWT		
0178	631.1000 Sod Lawn	4,437.000 SY	<u> </u>	<u> </u>
0180	634.0618 Posts Wood 4x6-Inch X 18-FT	500.000 EACH		
0182	634.0814 Posts Tubular Steel 2x2-Inch X 14-FT	4.000 EACH	<u> </u>	
0184	637.2210 Signs Type II Reflective H	4,458.200 SF		
0186	637.2215 Signs Type II Reflective H Folding	731.080 SF	<u> </u>	
0188	637.2230 Signs Type II Reflective F	1,152.250 SF	<u> </u>	
0190	638.2102 Moving Signs Type II	13.000 EACH	<u> </u>	
0192	638.2602 Removing Signs Type II	627.000 EACH		
0194	638.3000 Removing Small Sign Supports	418.000 EACH		
0196	643.0300 Traffic Control Drums	107,885.000 DAY		<u> </u>







Page 8 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0198	643.0420 Traffic Control Barricades Type III	30,314.000 DAY	<u> </u>	<u> </u>
0200	643.0705 Traffic Control Warning Lights Type A	60,628.000 DAY	<u> </u>	
0202	643.0715 Traffic Control Warning Lights Type C	10,906.000 DAY	<u> </u>	·
0204	643.0810.S Connected Arrow Board	754.000 DAY	·	
0206	643.0900 Traffic Control Signs	43,472.000 DAY	·	
0208	643.0920 Traffic Control Covering Signs Type II	1.000 EACH	·	·
0210	643.1070 Traffic Control Cones 42-Inch	137,971.000 DAY	·	
0212	643.1220.S Connected Work Zone Start and End Location Markers	76.000 DAY	·	·
0214	643.3165 Temporary Marking Line Paint 6-Inch	45,006.000 LF	·	·
0216	643.3180 Temporary Marking Line Removable Tape 6-Inch	62,551.000 LF	·	·
0218	643.3185 Temporary Marking Line Removable Contrast Tape 6-Inch	2,303.000 LF		
0220	643.3265 Temporary Marking Line Paint 10-Inch	2,871.000 LF		·
0222	643.3280 Temporary Marking Line Removable Tape 10-Inch	11,869.000 LF		
0224	643.5000 Traffic Control	1.000 EACH		·
0226	644.1430 Temporary Pedestrian Surface Plate	5,194.000 SF		







Page 9 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0228	644.1601 Temporary Pedestrian Curb Ramp	630.000 DAY	<u> </u>	
0230	644.1605 Temporary Pedestrian Detectable Warning Field	1,651.000 SF		·
0232	644.1810 Temporary Pedestrian Barricade	13,146.000 LF	<u> </u>	
0234	644.1900.S Temporary Audible Message Devices	319.000 DAY		·
0236	645.0130 Geotextile Type R	25.000 SY		
0238	646.2025 Marking Line Grooved Black Epoxy 6- Inch	16,075.000 LF		·
0240	646.2040 Marking Line Grooved Wet Ref Epoxy 6- Inch	111,264.000 LF	·	·
0242	646.4025 Marking Line Grooved Black Epoxy 10- Inch	1,969.000 LF		
0244	646.4040 Marking Line Grooved Wet Ref Epoxy 10-Inch	26,405.000 LF		·
0246	646.5020 Marking Arrow Epoxy	149.000 EACH		
0248	646.5120 Marking Word Epoxy	35.000 EACH		<u> </u>
0250	646.6120 Marking Stop Line Epoxy 18-Inch	1,750.000 LF		
0252	646.6466 Cold Weather Marking Epoxy 6-Inch	27,816.000 LF		<u> </u>
0254	646.6470 Cold Weather Marking Epoxy 10-Inch	6,601.000 LF		
0256	646.7120 Marking Diagonal Epoxy 12-Inch	6,593.000 LF		







Page 10 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0258	646.7220 Marking Chevron Epoxy 24-Inch	178.000 LF		<u> </u>
0260	646.7420 Marking Crosswalk Epoxy Transverse Line 6-Inch	6,288.000 LF	·	
0262	646.8120 Marking Curb Epoxy	2,022.000 LF		
0264	646.8220 Marking Island Nose Epoxy	81.000 EACH		
0266	650.4000 Construction Staking Storm Sewer	2.000 EACH	·	
0268	650.5500 Construction Staking Curb Gutter and Curb & Gutter	3,510.000 LF		
0270	650.8000 Construction Staking Resurfacing Reference	27,544.000 LF		·
0272	650.8501 Construction Staking Electrical Installations (project) 01. 2140-14-70	1.000 EACH		·
0274	650.9000 Construction Staking Curb Ramps	134.000 EACH		
0276	650.9500 Construction Staking Sidewalk (project) 01. 2140-14-70	1.000 EACH		·
0278	650.9911 Construction Staking Supplemental Control (project) 01. 2140-14-70	1.000 EACH		·
0280	652.0225 Conduit Rigid Nonmetallic Schedule 40 2-Inch	7,000.000 LF		
0282	652.0235 Conduit Rigid Nonmetallic Schedule 40 3-Inch	6,205.000 LF		·
0284	652.0605 Conduit Special 2-Inch	5,500.000 LF		







Page 11 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0286	652.0615 Conduit Special 3-Inch	8,515.000 LF	<u> </u>	<u> </u>
0288	652.0800 Conduit Loop Detector	20,708.000 LF		
0290	653.0135 Pull Boxes Steel 24x36-Inch	51.000 EACH		
0292	653.0140 Pull Boxes Steel 24x42-Inch	187.000 EACH		
0294	653.0905 Removing Pull Boxes	230.000 EACH		
0296	654.0101 Concrete Bases Type 1	85.000 EACH		
0298	654.0102 Concrete Bases Type 2	10.000 EACH		
0300	654.0110 Concrete Bases Type 10	40.000 EACH		
0302	654.0120 Concrete Bases Type 10-Special	22.000 EACH		
0304	654.0217 Concrete Control Cabinet Bases Type 9 Special	11.000 EACH	·	
0306	655.0230 Cable Traffic Signal 5-14 AWG	7,930.000 LF	<u></u>	
0308	655.0240 Cable Traffic Signal 7-14 AWG	12,905.000 LF		
0310	655.0260 Cable Traffic Signal 12-14 AWG	21,585.000 LF		
0312	655.0270 Cable Traffic Signal 15-14 AWG	8,890.000 LF		
0314	655.0305 Cable Type UF 2-12 AWG Grounded	9,475.000 LF		
0316	655.0515 Electrical Wire Traffic Signals 10 AWG	27,195.000 LF		







Page 12 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0318	655.0610 Electrical Wire Lighting 12 AWG	10,980.000 LF	<u> </u>	·
0320	655.0700 Loop Detector Lead In Cable	81,626.000 LF	·	
0322	655.0800 Loop Detector Wire	81,151.000 LF	·	·
0324	656.0201 Electrical Service Meter Breaker Pedestal (location) 01. STH 181 at Florist Ave	1.000 EACH	·	
0326	656.0201 Electrical Service Meter Breaker Pedestal (location) 02. STH 181 at Mill Rd	1.000 EACH	<u> </u>	
0328	656.0201 Electrical Service Meter Breaker Pedestal (location) 03. STH 181 at Acacia St	1.000 EACH	<u> </u>	·
0330	656.0201 Electrical Service Meter Breaker Pedestal (location) 04. STH 181 at Green Tree Rd	1.000 EACH	·	·
0332	656.0201 Electrical Service Meter Breaker Pedestal (location) 05. STH 181 at Good Hope Rd	1.000 EACH	·	<u> </u>
0334	656.0201 Electrical Service Meter Breaker Pedestal (location) 06. STH 181 at Calumet Rd	1.000 EACH	<u> </u>	
0336	656.0201 Electrical Service Meter Breaker Pedestal (location) 07. STH 181 at Bradley Rd	1.000 EACH		
0338	656.0201 Electrical Service Meter Breaker Pedestal (location) 08. STH 181 at Tower Ave	1.000 EACH	<u> </u>	







Page 13 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0340	656.0201 Electrical Service Meter Breaker Pedestal (location) 09. STH 181 at Servite/Dean Rd	1.000 EACH		
0342	656.0201 Electrical Service Meter Breaker Pedestal (location) 10. STH 181 at Northridge Dr	1.000 EACH	·	
0344	656.0201 Electrical Service Meter Breaker Pedestal (location) 11. STH 181 at Northridge Lake Blvd	1.000 EACH		
0346	657.0100 Pedestal Bases	85.000 EACH	·	
0348	657.0255 Transformer Bases Breakaway 11 1/2- Inch Bolt Circle	10.000 EACH		<u> </u>
0350	657.0310 Poles Type 3	10.000 EACH		
0352	657.0405 Traffic Signal Standards Aluminum 3.5- FT	8.000 EACH		
0354	657.0420 Traffic Signal Standards Aluminum 13-FT	21.000 EACH		
0356	657.0425 Traffic Signal Standards Aluminum 15-FT	37.000 EACH		
0358	657.0430 Traffic Signal Standards Aluminum 10-FT	19.000 EACH		
0360	657.0609 Luminaire Arms Single Member 4-Inch Clamp 6-FT	18.000 EACH		·
0362	658.0173 Traffic Signal Face 3S 12-Inch	165.000 EACH		
0364	658.0174 Traffic Signal Face 4S 12-Inch	81.000 EACH		
0366	658.0416 Pedestrian Signal Face 16-Inch	92.000 EACH		







Page 14 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0368	658.0500 Pedestrian Push Buttons	119.000 EACH		
0370	658.5070 Signal Mounting Hardware (location) 01. STH 181 at Florist Ave	1.000 EACH	·	·
0372	658.5070 Signal Mounting Hardware (location) 02. STH 181 at Mill Rd	1.000 EACH	.	·
0374	658.5070 Signal Mounting Hardware (location) 03. STH 181 at Acacia St	1.000 EACH		·
0376	658.5070 Signal Mounting Hardware (location) 04. STH 181 at Green Tree Rd	1.000 EACH		·
0378	658.5070 Signal Mounting Hardware (location) 05. STH 181 at Good Hope Rd	1.000 EACH	·	·
0380	658.5070 Signal Mounting Hardware (location) 06. STH 181 at Calumet Rd	1.000 EACH	·	
0382	658.5070 Signal Mounting Hardware (location) 07. STH 181 at Bradley Rd	1.000 EACH		·
0384	658.5070 Signal Mounting Hardware (location) 08. STH 181 at Tower Ave	1.000 EACH		·
0386	658.5070 Signal Mounting Hardware (location) 09. STH 181 at Servite/Dean Rd	1.000 EACH	·	·
0388	658.5070 Signal Mounting Hardware (location) 10. STH 181 at Northridge Dr	1.000 EACH		·
0390	658.5070 Signal Mounting Hardware (location) 11. STH 181 at Northridge Lakes Blvd	1.000 EACH	·	
0392	658.5070 Signal Mounting Hardware (location) 12. STH 181 at STH 100	1.000 EACH		







Page 15 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0394	659.1125 Luminaires Utility LED C	79.000 EACH		
0396	659.5000.S Lamp, Ballast, LED, Switch Disposal by Contractor	361.000 EACH	·	·
0398	661.0201 Temporary Traffic Signals for Intersections (location) 01. STH 181 at Florist Ave	1.000 EACH	<u></u>	·
0400	661.0201 Temporary Traffic Signals for Intersections (location) 02. STH 181 at Mill Rd	1.000 EACH	·	<u> </u>
0402	661.0201 Temporary Traffic Signals for Intersections (location) 03. STH 181 at Acacia St	1.000 EACH	·	·
0404	661.0201 Temporary Traffic Signals for Intersections (location) 04. STH 181 at Green Tree Rd	1.000 EACH	·	·
0406	661.0201 Temporary Traffic Signals for Intersections (location) 05. STH 181 at Good Hope Rd	1.000 EACH	<u></u>	·
0408	661.0201 Temporary Traffic Signals for Intersections (location) 06. STH 181 at Calumet Rd	1.000 EACH		·
0410	661.0201 Temporary Traffic Signals for Intersections (location) 07. STH 181 at Bradley Rd	1.000 EACH	·	·
0412	661.0201 Temporary Traffic Signals for Intersections (location) 09. STH 181 at Servite/Dean Rd	1.000 EACH		
0414	661.0201 Temporary Traffic Signals for Intersections (location) 10. STH 181 at Northridge Dr	1.000 EACH	·	·







Page 16 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0416	661.0201 Temporary Traffic Signals for Intersections (location) 11. STH 181 at Northridge Lakes Blvd	1.000 EACH	<u>. </u>	
0418	690.0150 Sawing Asphalt	20,148.000 LF		·
0420	690.0250 Sawing Concrete	4,805.000 LF		
0422	740.0440 Incentive IRI Ride	47,720.000 DOL	1.00000	47,720.00
0424	ASP.1T0A On-the-Job Training Apprentice at \$5.00/HR	8,400.000 HRS	5.00000	42,000.00
0426	ASP.1T0G On-the-Job Training Graduate at \$5.00/HR	17,280.000 HRS	5.00000	86,400.00
0428	SPV.0060 Special 01. Utility Line Opening (ULO)	35.000 EACH		
0430	SPV.0060 Special 02. Tuck Point Storm Sewer Structure	1.000 EACH		·
0432	SPV.0060 Special 03. Strapping C-40-0053	2.000 EACH		
0434	SPV.0060 Special 04. Install Type 9 Pole	9.000 EACH	<u></u>	<u> </u>
0436	SPV.0060 Special 05. Install Type 9 Special Pole	18.000 EACH		
0438	SPV.0060 Special 06. Install Type 10 Pole	31.000 EACH		<u> </u>
0440	SPV.0060 Special 07. Install Type 10 Special Pole	4.000 EACH	<u></u>	<u> </u>
0442	SPV.0060 Special 08. Install Monotube Arms 15-FT	18.000 EACH		<u> </u>
0444	SPV.0060 Special 09. Install Monotube Arms 20-FT	4.000 EACH		







Page 17 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

0446	Description	Quantity and Units	Unit Price	Bid Amount
	SPV.0060 Special 10. Install Monotube Arms 25-FT	2.000 EACH		
0448	SPV.0060 Special 11. Install Monotube Arms 30-FT	16.000 EACH		
0450	SPV.0060 Special 12. Install Monotube Arms 35-FT Special	19.000 EACH	·	
0452	SPV.0060 Special 13. Install Monotube Arms 40-FT	1.000 EACH		
0454	SPV.0060 Special 14. Install Monotube Arms 45-FT Special	2.000 EACH	·	·
0456	SPV.0060 Special 15. Install Luminaire Arms Steel 15-FT	61.000 EACH	·	
0458	SPV.0060 Special 16. Transport and Install State Furnished Traffic Signal Cabinet Florist Ave	1.000 EACH	·	·
0460	SPV.0060 Special 17. Transport and Install State Furnished Traffic Signal Cabinet Mill Rd	1.000 EACH	·	·
0462	SPV.0060 Special 18. Transport and Install State Furnished Traffic Signal Cabinet Acacia St	1.000 EACH	·	
0464	SPV.0060 Special 19. Transport and Install State Furnished Traffic Signal Cabinet Green Tree Rd	1.000 EACH	·	·
0466	SPV.0060 Special 20. Transport and Install State Furnished Traffic Signal Cabinet Good Hope Rd	1.000 EACH	<u> </u>	·
0468	SPV.0060 Special 21. Transport and Install State Furnished Traffic Signal Cabinet Calumet Rd	1.000 EACH	<u>.</u>	







Page 18 of 20


Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0470	SPV.0060 Special 22. Transport and Install State Furnished Traffic Signal Cabinet Bradley Rd	1.000 EACH	<u></u>	<u></u>
0472	SPV.0060 Special 23. Transport and Install State Furnished Traffic Signal Cabinet Tower Ave	1.000 EACH	<u></u>	<u>-</u>
0474	SPV.0060 Special 24. Transport and Install State Furnished Traffic Signal Cabinet Servite/Dean Rd	1.000 EACH	·	
0476	SPV.0060 Special 25. Transport and Install State Furnished Traffic Signal Cabinet Northridge Dr	1.000 EACH		·
0478	SPV.0060 Special 26. Trnsprt & Install State Frnshd Trffc Sgnl Cabinet Northridge Lakes Blvd	1.000 EACH	·	·
0480	SPV.0060 Special 27. Transport Traffic Signal and Lighting Materials Florist Ave	1.000 EACH	<u></u>	·
0482	SPV.0060 Special 28. Transport Traffic Signal and Lighting Materials Mill Rd	1.000 EACH		<u> </u>
0484	SPV.0060 Special 29. Transport Traffic Signal and Lighting Materials Acacia St	1.000 EACH	<u></u>	·
0486	SPV.0060 Special 30. Transport Traffic Signal and Lighting Materials Green Tree Rd	1.000 EACH	·	·
0488	SPV.0060 Special 31. Transport Traffic Signal and Lighting Materials Good Hope Rd	1.000 EACH		·
0490	SPV.0060 Special 32. Transport Traffic Signal and Lighting Materials Calumet Rd	1.000 EACH		·
0492	SPV.0060 Special 33. Transport Traffic Signal and Lighting Materials Bradley Rd	1.000 EACH		







Page 19 of 20

Proposal ID: 20251014030 **Project(s)**: 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0494	SPV.0060 Special 34. Transport Traffic Signal and Lighting Materials Tower Ave	1.000 EACH		
0496	SPV.0060 Special 35. Transport Traffic Signal and Lighting Materials Servite/Dean Rd	1.000 EACH	·	·
0498	SPV.0060 Special 36. Transport Traffic Signal and Lighting Materials Northridge Dr	1.000 EACH		·
0500	SPV.0060 Special 37. Transport Traffic Signal and Lighting Materials Northridge Lake Blvd	1.000 EACH		·
0502	SPV.0060 Special 38. Modify Traffic Signal STH 181 & STH 100	1.000 EACH	·	·
0504	SPV.0060 Special 39. Inlet Covers Type H-D	1.000 EACH		<u> </u>
0506	SPV.0060 Special 40. Cleaning Storm Sewer	2.000 EACH		
0508	SPV.0060 Special 41. Adjusting Water Valve Boxes	178.000 EACH	·	·
0510	SPV.0060 Special 42. Adjusting Water Manholes	5.000 EACH		
0512	SPV.0060 Special 43. Adjusting Sanitary Manholes	103.000 EACH		
0514	SPV.0060 Special 44. Internal Manhole Seals	4.000 EACH	·	
0516	SPV.0060 Special 45. Manhole Covers Type MS- 58A	4.000 EACH	<u>-</u>	<u></u>
0518	SPV.0060 Special 46. Adjusting CUC Manhole Cover	24.000 EACH	·	·
0520	SPV.0060 Special 47. 4' Diameter "Doghouse" Manhole Type CUC	10.000 EACH	·	·



Page 20 of 20

Proposal ID: 20251014030 Project(s): 2140-14-70

Federal ID(s): WISC 2025601

SECTION: 0001 Contract Items

Alt Set ID: Alt Mbr ID:

Proposal Line Number	Item ID Description	Approximate Quantity and Units	Unit Price	Bid Amount
0522	SPV.0060 Special 48. 5' Diameter "Doghouse" Manhole Type CUC	2.000 EACH		
0524	SPV.0060 Special 49. Removing CUC Manhole	12.000 EACH		
0526	SPV.0060 Special 50. Section Corner Monuments	7.000 EACH		·
0528	SPV.0060 Special 51. Removing Fence, R-40-76	1.000 EACH		
0530	SPV.0060 Special 52. Field Office Facilities Office Space	1.000 EACH		
0532	SPV.0075 Special 01. Street Sweeping	100.000 HRS	·	·
0534	SPV.0090 Special 01. Concrete Curb and Gutter 6- Inch Slope 18-Inch Type J	211.000 LF		
0536	SPV.0090 Special 02. Marking Crosswalk Epoxy Block Style 12-Inch White	6,358.000 LF		
0538	SPV.0195 Special 01. Excavation, Hauling, and Disposal of Lead Contaminated Soil	48.000 TON		
0540	SPV.0195 Special 02. Excavation, Hauling, and Disposal of PAH Contaminated Soil	2.000 TON		
0542	SPV.0195 Special 03. Excavation, Hauling, and Disposal of Petroleum Contaminated Soil	135.000 TON		
0544	SPV.0195 Special 04. Asphaltic Repair	4,667.000 TON		

Section: 0001

ion:	0001	Total:	

ota	Bid:	

PLEASE ATTACH ADDENDA HERE