

JANUARY 2026

## ORDER OF SHEETS

Section No. 1 Title  
 Section No. 2 Typical Sections and Details  
 Section No. 3 Estimate of Quantities  
 Section No. 3 Miscellaneous Quantities  
 Section No. 4 Right of Way Plat  
 Section No. 5 Plan and Profile  
 Section No. 6 Standard Detail Drawings  
 Section No. 7 Sign Plates  
 Section No. 8 Structure Plans  
 Section No. 9 Computer Earthwork Data  
 Section No. 9 Cross Sections

TOTAL SHEETS = 94



N

42

## DESIGN DESIGNATION

A.A.D.T. (2026) = 2900  
 A.A.D.T. (2046) = 3400  
 D.H.V. = ---  
 D.D. = 60/40  
 T. = 25.6%  
 DESIGN SPEED = 60 MPH  
 ESALS = 1,600,000

## CONVENTIONAL SYMBOLS

PLAN	PROFILE
CORPORATE LIMITS	GRADE LINE
PROPERTY LINE	ORIGINAL GROUND
LOT LINE	MARSH OR ROCK PROFILE (To be noted as such)
LIMITED HIGHWAY EASEMENT	SPECIAL DITCH
EXISTING RIGHT OF WAY	GRADE ELEVATION
PROPOSED OR NEW R/W LINE	CULVERT (Profile View)
SLOPE INTERCEPT	UTILITIES
REFERENCE LINE	ELECTRIC
EXISTING CULVERT	FIBER OPTIC
PROPOSED CULVERT (Box or Pipe)	GAS
COMBUSTIBLE FLUIDS	SANITARY SEWER
MARSH AREA	STORM SEWER
WOODED OR SHRUB AREA	TELEPHONE
	WATER
	UTILITY PEDESTAL
	POWER POLE
	TELEPHONE POLE

STATE OF WISCONSIN  
 DEPARTMENT OF TRANSPORTATION


## PLAN OF PROPOSED IMPROVEMENT

## CAMERON - LADYSMITH

LITTLE SOFT MAPLE CREEK BRIDGE, B-54-0131

USH 008  
 RUSK COUNTY

STATE PROJECT	FEDERAL PROJECT	
PROJECT	CONTRACT	
1580-00-70	WISC2026159	1

STATE PROJECT NUMBER  
 1580-00-70

ORIGINAL PLANS PREPARED BY

**AYRES**

WISCONSIN  
 MARK R.  
 PETERSEN  
 E - 36785  
 EAU CLAIRE  
 WI

DATE: 11/19/2025  
 (Professional Engineer Signature)

STATE OF WISCONSIN  
 DEPARTMENT OF TRANSPORTATION

PREPARED BY

Surveyor	AYRES ASSOCIATES, INC
Designer	AYRES ASSOCIATES, INC
Project Manager	ADAM HETRICK
Regional Examiner	REGIONAL EXAMINER
Regional Supervisor	JEFFREY OLSON

APPROVED FOR THE DEPARTMENT

DATE: 11/19/2025  
 Adam Hetrick  
 (Signature)

E

**GENERAL NOTES**

THE LOCATIONS OF EXISTING UTILITY INSTALLATIONS AS SHOWN ON THE PLANS ARE APPROXIMATE. THERE MAY BE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN

NO TREES OR SHRUBS SHALL BE REMOVED WITHOUT APPROVAL BY THE ENGINEER.

THE EROSION CONTROL ITEMS SHOWN ON THE PLANS ARE AT SUGGESTED LOCATIONS. THE ENGINEER MAY MODIFY LOCATIONS AS NEEDED. ALL EROSION CONTROL MEASURES SHALL BE MAINTAINED UNTIL SUCH TIME AS THE ENGINEER DETERMINES THE MEASURE IS NO LONGER NECESSARY.

SHRINKAGE OF EARTHWORK IS VARIABLE. AN AVERAGE FACTOR FOR EXCAVATION COMMON IS 30%.

DO NOT APPLY FERTILIZER WITHIN 20 FEET OF A WATER BODY OR WETLAND.

TEMPORARY STORAGE OF ANY EXCAVATED MATERIAL WILL NOT BE PERMITTED IN WETLANDS, FLOODWAY OR FLOODPLAIN OF ANY WETLANDS.

TRAFFIC CONTROL DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS DIRECTED BY THE ENGINEER.

EXISTING ELEVATIONS SHALL BE VERIFIED IN THE FIELD.

**UTILITY CONTACTS**

SPECTRUM - COMMUNICATIONS  
2016 18 $\frac{3}{4}$  STREET  
RICE LAKE, WI 54868  
ATTN: MICKEY BENIK  
MOBILE: 715-210-3868  
mickey.benik@charter.com

\* DENOTES NOT A DIGGERS HOTLINE MEMBER

**DNR CONTACT**




DNR WEST CENTRAL REGOIN HQ  
1300 WEST CLAIRMONT AVENUE  
EAU CLAIRE, WI 54701  
ATTN: LEAH NICOL  
715-934-9014  
leah.nicol@wisconsin.gov



**DESIGN CONTACT**

AYRES ASSOCIATES INC  
3433 OAKWOOD HILLS PARKWAY  
EAU CLAIRE, WI 54701  
ATTN: MARK PETERSEN  
715-834-3161  
petersenm@ayresassociates.com

**WISDOT DESIGN CONTACT**

DEPARTMENT OF TRANSPORTATION  
1701 NORTH 4TH STREET  
SUPERIOR, WI 54880  
ATTN: PHILIP KEPERS, PE  
715-395-3027  
philip.keppers@dot.wi.gov






## RUNOFF COEFFICIENT TABLE

2

A	HYDROLOGIC SOIL GROUP											
	B			C			D			E		
	SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)		
LAND USE:	0-2	2-6	6 & OVER									
ROW CROPS	.08 .22	.16 .30	.22 .38	.12 .26	.20 .34	.27 .44	.15 .30	.24 .37	.33 .50	.19 .34	.28 .41	.38 .56
MEDIAN STRIP-TURF	.19 .24	.20 .26	.24 .30	.19 .25	.22 .28	.26 .33	.20 .26	.23 .30	.30 .37	.20 .27	.25 .32	.30 .40
SIDE SLOPE: TURF			.25 .32			.27 .34			.28 .36			.30 .38
PAVEMENT:												
ASPHALT							.70 - .95					
CONCRETE							.80 - .95					
BRICK							.70 - .80					
DRIVES, WALKS							.75 - .85					
ROOFS							.75 - .95					
GRAVEL ROADS, SHOULDERS							.40 - .60					

TOTAL PROJECT AREA = 3.255 ACRES

TOTAL AREA EXPECTED TO BE DISTURBED BY CONSTRUCTION ACTIVITIES = 1.826 ACRES



PROJECT NO: 1580-00-70

HWY: USH 8

COUNTY: RUSK


CONSTRUCTION DETAILS

SHEET

E

2

2



PROJECT NO: 1580-00-70

HWY: USH 8

COUNTY: RUSK


CONSTRUCTION DETAIL - TEMP WIDENING LAYOUT

SHEET

E

2

2



PROJECT NO: 1580-00-70

HWY: USH 8

COUNTY: RUSK

EROSION CONTROL - STAGE 1

SHEET

7

FILE NAME: I:\41410764 USH 8 LITTLE SOFT MAPLE CREEK BRIDGE\C3D\SHEETS\PLAN\022001-EC.DWG  
LAYOUT NAME - 022001\_ec


PLOT DATE: 7/15/2025 3:15 PM

PLOT BY: RESHESKE, CARRIE

PLOT NAME:

PLOT SCALE: 1 IN:50 FT


WISDOT/CADDs SHEET 42



\* NOT SHOWN ON PLAN SHEETS. BASED ON CONTRACTORS MEANS AND METHODS FOR STRUCTURE REMOVAL, USE TURBIDITY BARRIER TO ISOLATE WORK ARE FROM STREAM. MAINTAIN CHANNEL FLOW AT ALL TIMES. SEE SDD "TURBIDITY BARRIER" FOR ADDITIONAL INFORMATION.

2

2





- \* NOT SHOWN ON PLAN SHEETS. BASED ON CONTRACTORS MEANS AND METHODS FOR STRUCTURE REMOVAL, USE TURBIDITY BARRIER TO ISOLATE WORK ARE FROM STREAM. MAINTAIN CHANNEL FLOW AT ALL TIMES. SEE SDD "TURBIDITY BARRIER" FOR ADDITIONAL INFORMATION.

PROJECT NO: 1580-00-70	HWY: USH 8	COUNTY: RUSK	EROSION CONTROL - STAGE 3	SHEET 9
------------------------	------------	--------------	---------------------------	---------

2

2



NOTE: NO SIGNS REPLACED WITHIN PROJECT LIMITS

PROJECT NO: 1580-00-70

HWY: USH 8

COUNTY: RUSK

PAVEMENT MARKING

SHEET


E




2

2

SEE SDD "TRAFFIC CONTROL, ONE LANE ROAD WITH TEMPORARY SIGNALS" FOR SIGNS, BARRICADES AND LAYOUT INFORMATION NOT SHOWN HERE.



SEE SDD "TRAFFIC CONTROL, ONE LANE ROAD WITH TEMPORARY SIGNALS" FOR SIGN LAYOUT INFORMATION NOT SHOWN HERE.



#### PROPOSED SIGNAL TIMINGS (SEC.)

PHASE 1 EB USH 8	PHASE 2 WB USH 8	PROGRAM TYPE
10	10	MINIMUM GREEN TIME
5	5	PASSAGE TIME DURING GREEN PHASE
40	40	MAXIMUM GREEN TIME
4	4	YELLOW
36	36	ALL-RED

## Estimate Of Quantities

1580-00-70

Line	Item	Item Description	Unit	Total	Qty
0002	201.0105	Clearing	STA	6.000	6.000
0004	201.0205	Grubbing	STA	6.000	6.000
0006	203.0250	Removing Structure Over Waterway Remove Debris (structure) 01. B-54-408	EACH	1.000	1.000
0008	204.0100	Removing Concrete Pavement	SY	1,444.000	1,444.000
0010	205.0100	Excavation Common	CY	2,027.000	2,027.000
0012	206.1001	Excavation for Structures Bridges (structure) 01. B-54-131	EACH	1.000	1.000
0014	208.0100	Borrow	CY	4,544.000	4,544.000
0016	210.1500	Backfill Structure Type A	TON	338.000	338.000
0018	213.0100	Finishing Roadway (project) 01. 1580-00-70	EACH	1.000	1.000
0020	305.0110	Base Aggregate Dense 3/4-Inch	TON	309.000	309.000
0022	305.0120	Base Aggregate Dense 1 1/4-Inch	TON	4,380.000	4,380.000
0024	312.0110	Select Crushed Material	TON	106.000	106.000
0026	415.0410	Concrete Pavement Approach Slab	SY	80.000	80.000
0028	455.0605	Tack Coat	GAL	241.000	241.000
0030	465.0105	Asphaltic Surface	TON	854.000	854.000
0032	465.0125	Asphaltic Surface Temporary	TON	202.000	202.000
0034	502.0100	Concrete Masonry Bridges	CY	402.000	402.000
0036	502.3200	Protective Surface Treatment	SY	578.000	578.000
0038	502.3210	Pigmented Surface Sealer	SY	112.000	112.000
0040	503.0137	Prestressed Girder Type I 36W-Inch	LF	426.000	426.000
0042	505.0400	Bar Steel Reinforcement HS Structures	LB	7,260.000	7,260.000
0044	505.0600	Bar Steel Reinforcement HS Coated Structures	LB	52,280.000	52,280.000
0046	505.0800.S	Bar Steel Reinforcement HS Stainless Structures	LB	1,640.000	1,640.000
0048	505.0908	Bar Couplers No. 8	EACH	24.000	24.000
0050	506.2605	Bearing Pads Elastomeric Non-Laminated	EACH	12.000	12.000
0052	506.4000	Steel Diaphragms (structure) 01. B-54-131	EACH	5.000	5.000
0054	511.1200	Temporary Shoring (structure) 01. B-54-131	SF	1,700.000	1,700.000
0056	516.0500	Rubberized Membrane Waterproofing	SY	30.000	30.000
0058	550.2106	Piling CIP Concrete 10 3/4 X 0.365-Inch	LF	1,320.000	1,320.000
0060	601.0588	Concrete Curb & Gutter 4-Inch Sloped 36-Inch Type TBT	LF	53.000	53.000
0062	602.3010	Concrete Surface Drains	CY	2.600	2.600
0064	603.8000	Concrete Barrier Temporary Precast Delivered	LF	1,890.000	1,890.000
0066	603.8125	Concrete Barrier Temporary Precast Installed	LF	1,890.000	1,890.000
0068	606.0100	Riprap Light	CY	3.000	3.000
0070	606.0300	Riprap Heavy	CY	545.000	545.000
0072	612.0406	Pipe Underdrain Wrapped 6-Inch	LF	180.000	180.000
0074	614.0150	Anchor Assemblies for Steel Plate Beam Guard	EACH	4.000	4.000
0076	614.0905	Crash Cushions Temporary	EACH	2.000	2.000
0078	614.2300	MGS Guardrail 3	LF	125.000	125.000
0080	614.2500	MGS Thrie Beam Transition	LF	157.600	157.600
0082	614.2610	MGS Guardrail Terminal EAT	EACH	4.000	4.000
0084	618.0100	Maintenance and Repair of Haul Roads (project) 01. 1580-00-70	EACH	1.000	1.000
0086	619.1000	Mobilization	EACH	1.000	1.000
0088	624.0100	Water	MGAL	130.000	130.000
0090	625.0500	Salvaged Topsoil	SY	7,426.000	7,426.000
0092	627.0200	Mulching	SY	9,280.000	9,280.000
0094	628.1504	Silt Fence	LF	1,350.000	1,350.000
0096	628.1520	Silt Fence Maintenance	LF	1,350.000	1,350.000
0098	628.1905	Mobilizations Erosion Control	EACH	8.000	8.000

## Estimate Of Quantities

1580-00-70

Line	Item	Item Description	Unit	Total	Qty
0100	628.1910	Mobilizations Emergency Erosion Control	EACH	5.000	5.000
0102	628.2027	Erosion Mat Class II Type C	SY	2,045.000	2,045.000
0104	628.6005	Turbidity Barriers	SY	200.000	200.000
0106	628.7504	Temporary Ditch Checks	LF	20.000	20.000
0108	629.0210	Fertilizer Type B	CWT	6.000	6.000
0110	630.0120	Seeding Mixture No. 20	LB	420.000	420.000
0112	630.0200	Seeding Temporary	LB	200.000	200.000
0114	630.0500	Seed Water	MGAL	170.000	170.000
0116	633.1100	Delineators Temporary	EACH	80.000	80.000
0118	642.5201	Field Office Type C	EACH	1.000	1.000
0120	643.0300	Traffic Control Drums	DAY	6,700.000	6,700.000
0122	643.0420	Traffic Control Barricades Type III	DAY	125.000	125.000
0124	643.0705	Traffic Control Warning Lights Type A	DAY	225.000	225.000
0126	643.0715	Traffic Control Warning Lights Type C	DAY	3,050.000	3,050.000
0128	643.0900	Traffic Control Signs	DAY	3,150.000	3,150.000
0130	643.3165	Temporary Marking Line Paint 6-Inch	LF	3,748.000	3,748.000
0132	643.3850	Temporary Marking Stop Line Removable Tape 18-Inch	LF	24.000	24.000
0134	643.5000	Traffic Control	EACH	1.000	1.000
0136	645.0111	Geotextile Type DF Schedule A	SY	94.000	94.000
0138	645.0120	Geotextile Type HR	SY	840.000	840.000
0140	645.0130	Geotextile Type R	SY	11.000	11.000
0142	646.2040	Marking Line Grooved Wet Ref Epoxy 6-Inch	LF	4,520.000	4,520.000
0144	646.9000	Marking Removal Line 4-Inch	LF	1,938.000	1,938.000
0146	650.4500	Construction Staking Subgrade	LF	850.000	850.000
0148	650.5000	Construction Staking Base	LF	850.000	850.000
0150	650.6501	Construction Staking Structure Layout (structure) 01. B-54-131	EACH	1.000	1.000
0152	650.9911	Construction Staking Supplemental Control (project) 01. 1580-00-70	EACH	1.000	1.000
0154	650.9920	Construction Staking Slope Stakes	LF	850.000	850.000
0156	661.0101	Temporary Traffic Signals for Bridges (structure) 01. B-54-131	EACH	1.000	1.000
0158	690.0150	Sawing Asphalt	LF	1,260.000	1,260.000
0160	690.0250	Sawing Concrete	LF	698.000	698.000
0162	715.0502	Incentive Strength Concrete Structures	DOL	2,424.000	2,424.000
0164	715.0720	Incentive Compressive Strength Concrete Pavement	DOL	500.000	500.000
0166	ASP.1T0A	On-the-Job Training Apprentice at \$5.00/HR	HRS	300.000	300.000
0168	ASP.1T0G	On-the-Job Training Graduate at \$5.00/HR	HRS	300.000	300.000
0170	SPV.0060	Special 01. Temporary Bypass STA 675+84	EACH	1.000	1.000

**CLEARING AND GRUBBING**

STATION TO STATION	LOCATION	201.0105 CLEARING STA	201.0205 GRUBBING STA
674+00 - 680+00	USH 8	6	6
<b>PROJECT TOTALS</b>		<b>6</b>	<b>6</b>

NOTE: CUTTING TREES BY OTHERS. CLEARING STILL REQUIRED.

**REMOVING CONCRETE PAVEMENT**

STATION TO STATION	LOCATION	204.0100 SY
672+50 - 679+00	USH 8	1444
<b>PROJECT TOTAL</b>		<b>1444</b>

**NOTES:**

(1) COMMON EXCAVATION IS THE SUM OF THE CUT AND EBS EXCAVATION COLUMNS. ITEM NUMBER 205.0100

(2) SALVAGED/UNUSABLE PAVEMENT MATERIAL IS INCLUDED IN CUT.

(4) SALVAGED/UNUSABLE PAVEMENT MATERIAL

(5) AVAILABLE MATERIAL = CUT - SALVAGED/UNUSABLE PAVEMENT MATERIAL

(13) EXPANDED FILL FACTOR = 1.3

EXPANDED FILL = UNEXPANDED FILL \* FILL FACTOR

(14) THE MASS ORDINATE + OR - QTY CALCULATED FOR THE DIVISION. PLUS QUANTITY INDICATES AN EXCESS OF MATERIAL WITHIN THE DIVISION. MINUS INDICATES A SHORTAGE OF MATERIAL WITHIN THE DIVISION.

**CONCRETE PAVEMENT APPROACH SLAB**

FINISHING ROADWAY		415.0410
PROJECT	EACH	STATION TO STATION SY
1580-00-70	1	675+12.82 - 675+27.82 40
<b>PROJECT TOTAL</b>	<b>1</b>	<b>676+40.32 - 676+55.32 40</b>
		<b>PROJECT TOTAL 80</b>

**ASPHALTIC SURFACE ITEMS**

STATION TO STATION	LOCATION	TON	TON	GAL
671+50 - 675+15	SHOULDER, RT	80	---	18
672+50 - 675+15	SHOULDER, LT	44	---	12
672+50 - 675+12.82	MAINLINE	315	---	70
676+55.32 - 679+00	MAINLINE	293	---	66
676+40 - 680+50	SHOULDER, RT	75	---	17
676+50 - 679+50	SHOULDER, LT	47	---	12
671+50 - 680+00	TEMP WIDENING	---	202	46

**BASE AGGREGATE DENSE**

STATION TO STATION	LOCATION	305.0110 3/4-INCH TON	305.0120 1 1/4-INCH TON
671+50 - 675+45	SHOULDER, RT	43	520
672+50 - 675+45	SHOULDER, LT	44	480
672+50 - 675+45	MAINLINE	---	453
676+20 - 179+00	MAINLINE	---	415
676+20 - 680+00	SHOULDER, RT	37	472
676+20 - 679+00	SHOULDER, LT	38	382
671+50 - 680+00	TEMP WIDENING	32	709
	DRIVEWAY	76	---
<b>UNDISTRIBUTED</b>		<b>39</b>	<b>659</b>
<b>PROJECT TOTALS</b>		<b>309</b>	<b>4090</b>

**CONCRETE BARRIER TEMPORARY PRECAST & CRASH CUSHIONS TEMPORARY**

STATION TO STATION	STAGE	603.8000 CONCRETE TEMPORARY DELIVERED LF	603.8125 BARRIER PRECAST INSTALLED LF	614.0905 CRASH CUSHIONS TEMPORARY BACK EACH FT	PROJECT TOTALS	854	202	241
671+27 - 680+54	2	940	940	1	4	OM-3R	TL-3	UNIDIRECTIONAL
671+10 - 680+46	3	950	950	1	4	OM-3R	TL-3	UNIDIRECTIONAL
<b>PROJECT TOTALS</b>		<b>1890</b>	<b>1890</b>	<b>2</b>				

**MGS GUARDRAIL**

614.2500				
614.2300	THRIE BEAM	614.2610		
GUARDRAIL 3		TRANSITION	TERMINAL EAT	
STATION TO STATION	LOCATION	LF	LF	EACH
673+75.07 - 675+28.14	RT	62.5	39.4	1
674+36.87 - 675+28.14	LT	---	39.4	1
676+40 - 677+30.57	RT	---	39.4	1
676+40 - 677+93.77	LT	62.5	39.4	1
<b>PROJECT TOTALS</b>		<b>125.0</b>	<b>157.6</b>	<b>4</b>

**MOBILIZATION**

WATER				
619.1000				
PROJECT	EACH	LOCATION	USE	630.0500
1580-00-70	1	PROJECT LIMITS	SEEDING	---
PROJECT TOTAL	1	PROJECT LIMITS	DUST CONTROL	40
		PROJECT LIMITS	COMPACTON	90
<b>PROJECT TOTALS</b>				<b>130</b>
				<b>170</b>

**SALVAGED TOPSOIL, MULCHING, FERTILIZER, & SEEDING**

630.0120				
625.0500	629.0210	SEEDING	630.0200	
SALVAGED	627.0200	FERTILIZER	MIXTURE	SEEDING
TOPSOIL	MULCHING	TYPE B	NO. 20	TEMPORARY
STATION TO STATION	LOCATION	SY	SY	CWT
672+50 - 679+00	MAINLINE	4586	4586	2.9
671+50 - 680+00	TEMP WIDENING	2840	2840	1.8
UNDISTRIBUTED		1854	1.3	85
				200
<b>PROJECT TOTALS</b>		<b>7426</b>	<b>9280</b>	<b>6.0</b>
				<b>420</b>
				<b>200</b>

**SILT FENCE**

628.1520				
628.1504 MAINTENANCE				
STATION TO STATION	LOCATION	STAGE	LF	LF
671+50 - 672+05	TEMP WIDENING	1	55	55
672+25 - 680+00	TEMP WIDENING	1	725	725
675+91 - 679+00	RT	2	305	305
675+90 - 676+07	LT	3	32	32
UNDISTRIBUTED			233	233
<b>PROJECT TOTALS</b>			<b>1350</b>	<b>1350</b>

**MOBILIZATIONS EROSION CONTROL**

628.1905	
PROJECT	EACH
1580-00-70	8
<b>PROJECT TOTAL</b>	<b>8</b>

**MOBILIZATIONS EMERGENCY EROSION CONTROL**

628.1910	
PROJECT	EACH
1580-00-70	5
<b>PROJECT TOTAL</b>	<b>5</b>

**EROSION MAT CLASS II TYPE C**

628.2027			
STATION TO STATION	LOCATION	STAGE	SY
674+45 - 675+85	TEMP WIDENING	1	365
673+80 - 675+35	RT	2	295
676+35 - 677+55	RT	2	406
674+60 - 675+35	LT	3	273
676+30 - 677+70	LT	3	370
UNDISTRIBUTED			336
<b>PROJECT TOTAL</b>			<b>2045</b>

**TURBIDITY BARRIERS**

PROJECT	SY
1580-00-70	200
<b>PROJECT TOTAL</b>	<b>200</b>

**TEMPORARY DITCH CHECKS**

628.7504			
STATION	LOCATION	STAGE	LF
675+30	RT	2	14
UNDISTRIBUTED			6
<b>PROJECT TOTAL</b>			<b>20</b>

**DELINERATORS TEMPORARY**

633.1100			
STATION TO STATION	LOCATION	STAGE	EACH
671+90 - 679+75	LT	2	64
UNDISTRIBUTED			16
<b>PROJECT TOTAL</b>			<b>80</b>

**TRAFFIC CONTROL ITEMS**

643.0420				
643.0300				
PROJECT	LOCATION	EACH	DAY	EACH
1580-00-70	STAGE 1	20	500	---
1580-00-70	STAGE 2	49	2450	1
1580-00-70	STAGE 3	51	2550	1
ADVANCED WARNING		---	---	---
UNDISTRIBUTED		1200	---	25
<b>PROJECT TOTALS</b>		<b>6700</b>	<b>125</b>	<b>225</b>
				<b>3050</b>
				<b>3150</b>

**FIELD OFFICE TYPE C**

PROJECT	EACH
1580-00-70	1
<b>PROJECT TOTAL</b>	<b>1</b>

**TEMPORARY MARKING LINE**

643.3165 643.3850				
PAINT STOP LINE				
6-INCH REMOVABLE				
WHITE TAPE 18-INCH				
STATION TO STATION	DESCRIPTION	STAGE	LF	LF
671+15 - 680+45	LT & RT EDGELINE			

**TRAFFIC CONTROL**

PROJECT	643.5000
	EACH
1580-00-70	1
<b>PROJECT TOTAL</b>	<b>1</b>

**CONSTRUCTION STAKING**  
**SUPPLEMENTAL CONTROL**

PROJECT	650.9911.01
	EACH
1580-00-70	1

**3****3****MARKING LINE GROOVED WET REFLECTIVE EPOXY 6-INCH**

STATION TO STATION	DESCRIPTION	WHITE LF	YELLOW LF	646.2040
670+20 - 681+50	CENTERLINE	---	2260	
670+20 - 681+50	EDGELINE, RT & LT	2260	---	
<b>SUBTOTALS</b>		<b>2260</b>	<b>2260</b>	
<b>PROJECT TOTAL</b>		<b>4520</b>		

**SAWING**

STATION TO STATION	LOCATION	STAGE	690.0150 ASPHALT	690.0250 CONCRETE
671+50 - 680+00	TEMP WIDENING	1	856	---
671+50 - 672+50	RT	2	102	---
672+50 - 679+00	RT	2	---	674
679+00 - 680+00	RT	2	102	---
671+50 - 672+50	LT	3	100	12
679+00 - 680+00	LT	3	100	12
<b>PROJECT TOTALS</b>			<b>1260</b>	<b>698</b>

**MARKING REMOVAL LINE 4-INCH**

STATION TO STATION	DESCRIPTION	STAGE	646.9000 LF
670+20 - 672+00	DBL CENTERLINE	2	360
671+13 - 680+41	LT, EDGELINE	2	928
679+50 - 681+50	DBL CENTERLINE	2	400
671+25 - 672+50	RT, EDGELINE	3	125
679+00 - 680+25	RT, EDGELINE	3	125
<b>PROJECT TOTAL</b>			<b>1938</b>

**TEMPORARY BYPASS STA 675+84**

STATION	LOCATION	SPV.0060.01 EACH
675+84	USH 8	1
<b>PROJECT TOTAL</b>		<b>1</b>

**TEMPORARY TRAFFIC SIGNALS  
FOR BRIDGES (B-54-131)**

LOCATION	661.0101 EACH
LITTLE SOFT MAPLE CREEK	1
<b>PROJECT TOTAL</b>	<b>1</b>

**CONSTRUCTION STAKING**

STATION TO STATION	SUBGRADE LF	BASE LF	SLOPE LF	STRUCTURE EACH	650.4500 650.5000 650.9920 650.6501 SUBGRADE BASE SLOPE STAKES STRUCTURE LAYOUT
B-54-131	---	---	---	1	
671+50 - 680+00	850	850	850	---	
<b>PROJECT TOTALS</b>	<b>850</b>	<b>850</b>	<b>850</b>	<b>1</b>	

STAKING INCLUDES TEMPORARY AND PERMANENT WORK

PROJECT NO: 1580-00-70

HWY: USH 8

COUNTY: RUSK

MISCELLANEOUS QUANTITIES


SHEET NO: 17

E

PI STA = 678+02.23  
Y = 552220.38  
X = 744880.15  
DELTA = 34°00'02"  
D = 0°45'00"  
T = 1167.82'  
L = 2266.70'  
R = 3819.72'  
PC STA = 666+34.40

Y = 552414.05  
X = 743728.50  
PT STA = 689+01.10  
Y = 552703.83  
X = 745943.21  
BK = S80°27'15"E  
AH = N65°32'43"E  
SE = 3,7%  
LR = 99.00'

BENCHMARKS			
NO.	STATION	ELEV.	DESCRIPTION
1	675+95.0	1116.42	BRASS MONUMENT, 37.9' LT
2	669+71.7	1120.76	RR SPIKE IN PPOL, 40.8' LT



PROJECT NO: 1580-00-70


HWY: USH 8

COUNTY: RUSK

## PLAN AND PROFILE:

SHEET

BENCHMARKS			
NO.	STATION	ELEV.	DESCRIPTION
1	675+95.0	1116.42	BRASS MONUMENT, 37.9' LT
2	669+71.7	1120.76	RR SPIKE IN PPOL, 40.8' LT



## Standard Detail Drawing List

08D02-08A	CONCRETE SURFACE DRAINS FLUME TYPE AT STRUCTURES
08D02-08B	CONCRETE SURFACE DRAINS FLUME TYPE AT STRUCTURES
08D02-08C	CONCRETE SURFACE DRAINS FLUME TYPE AT STRUCTURES
08E09-06	SILT FENCE
08E11-02	TURBIDITY BARRIER
09G02-05A	BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION
09G02-05B	BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION
09G02-05C	BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION
12A03-10	NAME PLATE (STRUCTURES)
13B02-09A	CONCRETE PAVEMENT APPROACH SLAB
13C19-03	HMA LONGITUDINAL JOINTS
14B29-01	SAFETY EDGE
14B42-07A	MI DWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-07B	MI DWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-07C	MI DWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-07D	MI DWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B44-04A	MI DWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B44-04B	MI DWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B44-04C	MI DWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B45-05A	MI DWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05B	MI DWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05C	MI DWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05D	MI DWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05E	MI DWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
15C04-05	TRAFFIC CONTROL, ADVANCE WARNING SIGNS 45 M. P. H. OR GREATER TWO-WAY UNDIVIDED ROAD OPEN TO TRAFFIC
15C08-24A	PERMANENT LONGITUDINAL PAVEMENT MARKINGS
15C08-24B	TEMPORARY LONGITUDINAL PAVEMENT MARKING
15C11-10B	CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS
15C12-09A	TRAFFIC CONTROL FOR LANE CLOSURE WITH FLAGGING OPERATION
15D28-04	TRAFFIC CONTROL, WORK ON SHOULDER OR PARKING LANE, UNDIVIDED ROADWAY
15D33-09	TRAFFIC CONTROL, ONE LANE ROAD WITH TEMPORARY SIGNALS



## GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

ALL STEEL REINFORCEMENT SHALL BE EMBEDDED 2 INCHES CLEAR UNLESS OTHERWISE SHOWN OR NOTED.


- ① USE A JOINT SEALANT CONFORMING TO STANDARD SPECIFICATION 415.2.6.
- ② NO. 4 X 2'-0" TIE BARS SPACED AT 12" C-C TO BE PLACED BY BRIDGE CONTRACTOR OR DRILLED TIE BARS PLACED AS DIRECTED BY THE ENGINEER.
- ③ PAVED CONCRETE SHOULDER (SDD 13A03) OR CONCRETE DRAINAGE SLAB.
- ④ CONCRETE PAVEMENT APPROACH SLAB (SHOWN) OR STRUCTURE APPROACH SLAB AND CONCRETE PAVEMENT APPROACH SLAB. SEE SDD 13B02.
- ⑤ PAVED CONCRETE SHOULDER (SDD 13A03) OR ASPHALT SHOULDER.

- ⑥ CONCRETE CURB AND GUTTER 4-INCH SLOPED 36-INCH TYPE TBT OR TBTT. USE TYPE TBTT CURB WITH NO. 4 X 2'-0" TIE BARS SPACED AT 3'-0" C-C ONLY WHEN ADJACENT TO CONCRETE PAVEMENTS.
- ⑦ PLACE FLUME BEFORE MSG THRIE BEAM TRANSITION POST 1 (SEE SDD 14B45)
- ⑧ CENTER FLUME BETWEEN POSTS. 6-INCH MINIMUM SEPARATION FROM OUTSIDE EDGE OF FLUME TO POSTS.
- ⑨ MINIMUM REINFORCEMENT SHALL BE 4" X 4" - W3.0 X W3.0 OR NO. 3 BARS LONGITUDINAL AND TRANSVERSE SPACING 12" C-C.
- ⑩ SEE ROADWAY PLANS FOR FLUME LOCATION.
- ⑪ START CURB AND GUTTER TRANSITION OR END SECTION.
- ⑫ DEPRESS FLOW LINE (SEE DETAIL)




**CONCRETE SURFACE  
DRAINS FLUME TYPE  
AT STRUCTURES**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




SECTION A - A




SECTION G - G



SECTION H - H



SECTION I - I

PLAN VIEW  
PERPENDICULAR FLUME


## GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

ALL STEEL REINFORCEMENT SHALL BE EMBEDDED 2 INCHES CLEAR UNLESS OTHERWISE SHOWN OR NOTED.


- ① USE A JOINT SEALANT CONFORMING TO STANDARD SPECIFICATION 415.2.6.
- ② NO. 4 X 2' - 0" TIE BARS SPACED AT 12" C-C TO BE PLACED BY BRIDGE CONTRACTOR OR DRILLED TIE BARS PLACED AS DIRECTED BY THE ENGINEER.
- ③ PAVED CONCRETE SHOULDER (SDD 13A03) OR CONCRETE DRAINAGE SLAB.
- ④ CONCRETE PAVEMENT APPROACH SLAB (SHOWN) OR STRUCTURE APPROACH SLAB AND CONCRETE PAVEMENT APPROACH SLAB. SEE SDD 13B02 AND STRUCTURE PLANS.
- ⑤ PAVED CONCRETE SHOULDER (SDD 13A03) OR ASPHALT SHOULDER.
- ⑥ CONCRETE CURB AND GUTTER 4-INCH SLOPED 36-INCH TYPE TBT OR TBTT. USE TYPE TBTT CURB WITH NO. 4 X 2'-0" TIE BARS SPACED AT 3'-0" C-C ONLY WHEN ADJACENT TO CONCRETE PAVEMENTS.

- ⑦ PLACE FLUME BEFORE MSG THRIE BEAM TRANSITION POST 1 (SEE SDD 14B45)
- ⑧ CENTER FLUME BETWEEN POSTS. 6-INCH MINIMUM SEPARATION FROM OUTSIDE EDGE OF FLUME TO POSTS.
- ⑨ MINIMUM REINFORCEMENT SHALL BE 4" X 4" - W3.0 X W3.0 OR NO. 3 BARS LONGITUDINAL AND TRANSVERSE SPACING 12" C-C.
- ⑩ SEE ROADWAY PLANS FOR FLUME LOCATION.
- ⑪ START CURB AND GUTTER TRANSITION OR END SECTION.
- ⑫ DEPRESS FLOW LINE (SEE DETAIL)
- ⑬ MEDIUM RIPRAP UNLESS OTHERWISE SPECIFIED.
- ⑭ LIMITS OF ADDITIONAL RIPRAP WHEN SPECIAL DITCH AS REQUIRED.
- ⑮ GEOTEXTILE TYPE HR.


PLAN VIEW  
SKEWED FLUME

**CONCRETE SURFACE  
DRAINS FLUME TYPE  
AT STRUCTURES**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION





**CURB AND GUTTER TRANSITION SECTION  
CONCRETE CURB AND GUTTER 4-INCH SLOPED  
36 INCH TYPE TBT OR TBTT**




**CURB AND GUTTER END SECTION  
CONCRETE CURB AND GUTTER 4-INCH SLOPED  
36 INCH TYPE TBT OR TBTT**




**CURB AND GUTTER FLOW LINE DEPRESSION  
AT FLUMES CONCRETE CURB AND GUTTER  
4-INCH SLOPED 36 INCH TYPE TBT OR TBTT**




**SECTION C - C  
JOINT DETAIL FOR BRIDGE WITH STRUCTURAL  
APPROACH SLAB AND CONCRETE APPROACH SLAB**




**SECTION C - C  
JOINT DETAIL FOR BRIDGE APPROACH  
WITH CONCRETE SHOULDERS**



**SECTION D - D**



**SECTION E - E**



**SECTION F - F**

## GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.


ALL STEEL REINFORCEMENT SHALL BE EMBEDDED 2 INCHES CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

- ① USE A JOINT SEALANT CONFORMING TO STANDARD SPECIFICATION 415.2.6.
- ② NO. 4 X 2'-0" TIE BARS SPACED AT 12" C-C TO BE PLACED BY BRIDGE CONTRACTOR OR DRILLED TIE BARS PLACED AS DIRECTED BY THE ENGINEER.
- ③ PAVED CONCRETE SHOULDER (SDD 13A03) OR CONCRETE DRAINAGE SLAB.
- ④ CONCRETE PAVEMENT APPROACH SLAB (SHOWN) OR STRUCTURE APPROACH SLAB AND CONCRETE PAVEMENT APPROACH SLAB. SEE SDD 13B02 AND STRUCTURE PLANS.
- ⑤ PAVED CONCRETE SHOULDER (SDD 13A03) OR ASPHALT SHOULDER.
- ⑥ CONCRETE CURB AND GUTTER 4-INCH SLOPED 36-INCH TYPE TBT OR TBTT. USE TYPE TBTT CURB WITH NO. 4 X 2'-0" TIE BARS SPACED AT 3'-0" C-C ONLY WHEN ADJACENT TO CONCRETE PAVEMENTS.
- ⑦ PLACE FLUME BEFORE MSG THRIE BEAM TRANSITION POST 1 (SEE SDD 14B45).
- ⑧ CENTER FLUME BETWEEN POSTS. 6-INCH MINIMUM SEPARATION FROM OUTSIDE EDGE OF FLUME TO POSTS.
- ⑨ MINIMUM REINFORCEMENT SHALL BE 4" X 4" - W3.0 X W3.0 OR NO. 3 BARS LONGITUDINAL AND TRANSVERSE SPACING 12" C-C.
- ⑩ SEE ROADWAY PLANS FOR FLUME LOCATION.
- ⑪ START CURB AND GUTTER TRANSITION OR END SECTION.
- ⑫ DEPRESS FLOW LINE (SEE DETAIL).
- ⑬ MEDIUM RIPRAP UNLESS OTHERWISE SPECIFIED.
- ⑭ LIMITS OF ADDITIONAL RIPRAP WHEN SPECIAL DITCH IS REQUIRED.
- ⑮ GEOTEXTILE TYPE HR.
- ⑯ MINIMUM REINFORCEMENT SHALL BE 6" X 6" - W4.0 X W4.0 OR NO. 3 BARS LONGITUDINAL AND TRANSVERSE SPACING 12" C-C.
- ⑰ MSG THRIE BEAM TRANSITION POST 1. SEE SDD 14B45 FOR ADDITIONAL CONSTRUCTION DETAILS AND ACCEPTABLE MATERIALS.
- ⑱ MAINTAIN WIDTH, THICKNESS AND CROSS SLOPE OF ADJACENT TYPE TBT OR TBTT CURB. SEE NOTE 6 FOR TIE BAR SPACING.
- ⑲ ALIGN FACE OF POST BLOCK WITH FLOW LINE.
- ⑳ MAINTAIN FLOW LINE AT EDGE OF PAVEMENT/FACE OF BEAM GUARD AS APPLICABLE.
- ㉑ DO NOT CONSTRUCT AN EXPANSION JOINT OR INSTALL DOWEL BARS WHEN ABUTTING HMA PAVEMENTS.


## CONCRETE SURFACE DRAINS FLUME TYPE AT STRUCTURES

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2023 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS DEVE  
ENGINEER 23  
FHWA



PLAN VIEW  
TYPICAL APPLICATION OF SILT FENCE




### SILT FENCE AT MEDIAN SURFACE DRAINS


#### GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND APPLICABLE SPECIAL PROVISIONS.


- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1/8" X 1/8" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.




TRENCH DETAIL



SILT FENCE




JOINING TWO LENGTHS OF SILT FENCE<sup>⑤</sup>




SILT FENCE TIE BACK  
(WHEN REQUIRED BY THE ENGINEER)

SILT FENCE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED	/S/ Beth Cannon
4-29-05	DATE
CHIEF ROADWAY DEVELOP 24	
FHWA	



## **SECTION B - B**


**TURBIDITY BARRIER - FLOAT ALTERNATIVE  
CAUTION - SEE NOTE 6**




## **SECTION A - A**

## **TURBIDITY BARRIER - STANDARD POST INSTALLATION**

## **TURBIDITY BARRIER PLACEMENT DETAILS**



## PLAN VIEW




## PLAN VIEW

## **GENERAL NOTES**


DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

TURBIDITY BARRIER MAY BE REMOVED AT THE ENGINEERS DISCRETION, WHEN PERMANENT EROSION CONTROL MEASURES HAVE BEEN ESTABLISHED.

- ① DRIVEN STEEL POSTS, PIPES, OR CHANNELS. LENGTH SHALL BE SUFFICIENT TO SECURELY SUPPORT BARRIER AT HIGH WATER ELEVATIONS.
- ② SAND BAGS TO BE USED AS ADDITIONAL BALLAST WHEN ORDERED BY THE ENGINEER TO MEET ADVERSE FIELD CONDITIONS. SPACE AS APPROPRIATE FOR SITE CONDITIONS.
- ③ WHEN BARRIER HEIGHT "H" EXCEEDS 8 FEET, POST SPACING MAY NEED TO BE DECREASED.
- ④ IN WATERWAYS SUBJECT TO FLUCTUATING WATER ELEVATIONS, PROVISIONS SHOULD BE MADE TO ALLOW THE WATER TO EQUALIZE ON EACH SIDE OF THE BARRIER. THIS MAY BE ACCOMPLISHED BY LEAVING A PORTION OF THE BARRIER OPEN ON THE UPSTREAM END.
- ⑤ ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION PERIOD. MINIMUM BARRIER HEIGHT SHALL BE 2' GREATER THAN EITHER THE Q2 ELEVATION OR THE ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION, WHICHEVER IS GREATER.
- ⑥ FLOAT ALTERNATIVE WILL ONLY BE ALLOWED WITH WRITTEN APPROVAL OF THE ENGINEER, AND IS MEANT FOR LOCATIONS WHERE BEDROCK PREVENTS THE INSTALLATION OF POSTS.
- ⑦ ALLOW SUFFICIENT SLACK VERTICALLY AND HORIZONTALLY SO THAT SEDIMENT BUILD UP WILL NOT SEPARATE OR LOWER THE TURBIDITY BARRIER.
- ⑧ USE AS DIRECTED BY COAST GUARD OR DNR PERMIT WHEN WORKING IN NAVIGABLE WATERWAYS.



## **PLAN VIEW**




## SECTION C - C

## TURBIDITY BARRIER

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED 6/4/02 /S/ Beth Cannestra  
DATE CHIEF ROADWAY DEVELOPMENT ENGINEER 25  
/A



**TYPICAL BRIDGE TEMPORARY TRAFFIC SIGNAL LOCATION**

**LEGEND**

- WOOD POLE (NON-BREAKAWAY)
- WOOD POST (BREAKAWAY)
- - - SIGNAL CABLE
- SIGNAL CABLE W/MESSENGER



DIRECTION OF TRAFFIC

LED TRAFFIC SIGNAL WITH BACKPLATE

3'-12"

**GENERAL NOTES**

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

POLE MOUNTED TRAFFIC SIGNAL CONTROL CABINET MAY BE MOUNTED ON THE SERVICE POLE IF THE ELECTRICAL UTILITY ALLOWS THE INSTALLATION.

WHEN UTILITY POLES ARE USED TO SPAN THE TEMPORARY OVERHEAD CABLE, WRITTEN PERMISSION MUST BE OBTAINED FROM THE OWNER OF THE POLES AND GIVEN TO THE PROJECT MANAGER. ALL PERTINENT UTILITY AND CODE CLEARANCES SHALL BE MAINTAINED.

WOOD POLES (NON-BREAKAWAY) SHALL BE NO CLOSER TO EDGE OF PAVEMENT THAN OFFSET DISTANCE CHART ALLOWS OR 4 FEET BEHIND PROTECTIVE BARRIER (BEAM GUARD, ETC.).

WOOD POSTS (BREAKAWAY) SHALL BE NO CLOSER THAN 2 FEET OUTSIDE OF SHOULDER.

VERTICAL CLEARANCE ETC. PER NEC.


TRAFFIC SIGNAL FACES SHALL BE TYPICALLY PLACED 12 FEET FROM EDGE OF PAVEMENT.

EACH TRAFFIC SIGNAL SHALL HAVE A BACKPLATE.


SIGNING, PAVEMENT MARKING AND LANE CONTROL REQUIREMENTS SHALL CONFORM TO STANDARD DETAIL DRAWING 15D33.

6


6



**TYPICAL DROP TO TRAFFIC SIGNAL FACE**



**POLE MOUNT CABINET INSTALLATION**



**GROUND MOUNT CABINET INSTALLATION**

MINIMUM POLE LENGTHS	CLASS	POLE BURIAL DEPTHS
25'	V	5'
30'	V	6'
35'	IV	7'
40'	IV	8'
45'	IV	9'

OFFSET DISTANCES FOR TEMPORARY NON-BREAKAWAY POLES	
SPEED LIMIT	OFFSET DISTANCE*
GREATER THAN 45 MPH	18 FT
45 MPH OR LESS	12 FT
45 MPH OR LESS W/CURBS	2 FT

\* NOTE: OFFSET MEASURED FROM OUTER EDGE OF OUTSIDE THRU LANE.


**BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
March 2018  
/S/ Ahmet Demirbilek  
DATE  
ROADWAY STANDARDS DEVE  
ENGINEER  
26  
FHWA

SDD09G02 - 05a

SDD09G02 - 05a



SPAN WIRE POLE

GUY POLE


## TYPICAL DEAD-ENDINGS OR GUYING

## GENERAL NOTES


USE  $\frac{3}{4}$ " DRILL IN WOOD POLE TO PROVIDE FOR  $\frac{5}{8}$ " BOLTS.

## BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATIONAPPROVED  
June 2015 /S/ Ahmet Demerbilek  
DATE ROADWAY STANDARDS DEVE 27  
FHWA ENGINEER



**TRAILER MOUNTED TRAFFIC SIGNAL**



**TRAILER MOUNTED TRAFFIC SIGNAL**

**TYPICAL TRAILER MOUNTED TRAFFIC SIGNAL LOCATION**

**GENERAL NOTES**

DETAIL OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

SIGNING, PAVEMENT MARKING AND LANE CONTROL REQUIREMENTS SHALL CONFORM TO STANDARD DETAIL DRAWING 15D33.

**LEGEND**

- POST MOUNTED SIGN
- TEMPORARY PRECAST CONCRETE BARRIER
- TRAILER MOUNTED TRAFFIC SIGNAL
- REMOVE PAVEMENT MARKINGS
- DIRECTION OF TRAFFIC

**BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
June 2015 /S/ Ahmet Demerbilek  
DATE ROADWAY STANDARDS DEVE 28  
FHWA ENGINEER

## GENERAL NOTES

NAME PLATES TO BE INSTALLED ON BRIDGES, CULVERTS, AND RETAINING WALLS SHALL CONFORM TO THE REQUIREMENTS OF SECTION 502.3.11 OF THE STANDARD SPECIFICATIONS.


THE BRIDGE NUMBER AND YEAR BUILT SHOWN ON THIS DRAWING ARE EXAMPLES ONLY. SEE CONSTRUCTION PLANS FOR INDIVIDUAL NUMBERING AND YEAR BUILT.

- ① EPOXY RESIN SHALL BE FROM AN APPROVED MANUFACTURER AND USED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- ② REHABILITATION OF AN EXISTING STRUCTURE SHOULD USE THE DATE OF ORIGINAL STRUCTURE CONSTRUCTION.





**TYPICAL NAME PLATE**  
(BRIDGES, CULVERTS, AND RETAINING WALLS)

6




**NUMBERING DESIGNATION**  
**MULTI-UNIT STRUCTURES**

S.D.D. 12 A 3-10




**ALTERNATE LUG**  
(FOR ATTACHMENT TO PRECAST STRUCTURES)


<b>NAME PLATE (STRUCTURES)</b>	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED	
3/26/10	/S/ Scot Beck
DATE	CHIEF STRUCTURAL DEVELOP 29
FHWA	



**SKEWED APPROACH  
(PAVEMENT MORE THAN TWO LANES)**




**SKEWS > 20°  
(PAVEMENT WIDTH ≤ 30')**




**APPROACH SLAB AND ADJACENT PAVEMENT**


\* (RS) = REINFORCED CONCRETE SLAB  
\* (PS) = PAVED CONCRETE SHOULDER OR CONCRETE DRAINAGE SLAB  
\* (NRS) = NON - REINFORCED CONCRETE SLAB  
\*\*\* STANDARD DOWEL BAR DIAMETER (SEE SDD 13C11 AND SDD 13C13)



**SECTION A - A  
REINFORCEMENT POSITIONING DETAIL**



**SECTION B - B  
BEND DETAIL  
BOTTOM REINFORCEMENT**




**SECTION C - C  
TRANSITION DETAIL  
APPROACH SLAB TO ADJACENT PAVEMENT**

## GENERAL NOTES


THE CONTRACTOR MAY SPLIC NO. 6 BARS IN THE APPROACH SLAB FOR SKEWED STRUCTURES ONLY. STAGGER SPLICES WITH A MAXIMUM OF ONE SPLICE PER BAR. THE LENGTH OF LAP IS 20 INCHES.

TACK WELD DOWEL BARS TO THE BASKETS ON ALTERNATE ENDS.

- ① THE CONTRACTOR MAY USE NO. 4 BARS SPACED AT 2' - 0" C - C IN BOTH THE LONGITUDINAL AND TRANSVERSE DIRECTIONS FOR TOP REINFORCEMENT AS AN ALTERNATIVE TO THE WELDED WIRE FABRIC.
- ② THE CONTRACTOR MAY OMIT THE BARS BETWEEN REINFORCED SLABS WHERE SLAB REINFORCEMENT BARS EXTEND ACROSS THE CENTERLINE OR REFERENCE LINE.
- ③ DO NOT CONSTRUCT AN EXPANSION JOINT OR INSTALL DOWEL BARS WHEN ABUTTING AN HMA PAVEMENT.
- ④ USE A JOINT SEALANT CONFORMING TO STANDARD SPECIFICATION 415.2.6.
- ⑤ PLACE EXPANSION CAP ON THE END OF THE DOWEL THAT IS NOT TACK WELDED TO THE BASKET. DO NOT FORCE DOWEL BAR PAST THE DOWEL STOP.
- ⑥ EXTEND EXPANSION JOINT THROUGH ANY ADJACENT TIED CONCRETE.
- Ⓐ STANDARD CONTRACTION JOINT NORMAL TO C OR R.
- Ⓑ STANDARD LONGITUDINAL JOINT WITH TIE BARS.
- Ⓒ 1 1/2" EXPANSION JOINT WITH DOWEL BARS NORMAL TO C OR R.



**SECTION D - D  
CONTRACTION JOINT**




**EXPANSION JOINT DETAIL**

## CONCRETE PAVEMENT APPROACH SLAB

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
November 2018 /S/ Peter Kemp, P.E.  
DATE  
FHWA  
PAVEMENT SUPERVISOR 30



**TYPICAL PAVEMENT CROSS SECTION  
NOTCHED WEDGE JOINT**

**GENERAL NOTES**


IN ADDITION TO THE DETAILS PROVIDED IN THIS DRAWING, CONFORM TO STANDARD SPECIFICATION 450.3.2.8 FOR WHEN A NOTCHED WEDGE JOINT IS REQUIRED AND FOR GENERAL JOINT CONSTRUCTION REQUIREMENTS.

FOR ALL LONGITUDINAL JOINTS, ENSURE THE PAVER SCREED OVERLAPS THE PREVIOUSLY PLACED PAVEMENT BY  $1'' \pm 0.5''$  AND THE HOT SIDE OF THE JOINT REMAINS HIGHER THAN THE COLD SIDE BY APPROXIMATELY  $0.1''$  AFTER FINAL COMPACTION. (IT WILL BE FLUSH WHEN PAVING IN ECHELON.)


ONLY REMOVE THE LONGITUDINAL NOTCHED WEDGE JOINT FOR SMA PAVEMENT OR AS DIRECTED BY THE ENGINEER TO ADDRESS SPECIFIC LENGTHS OF JOINT DAMAGED BY TRAFFIC.

WHEN MILLING BACK OR REMOVING ANY LONGITUDINAL JOINT, LIMIT THE MATERIAL REMOVED TO  $2''$  FROM THE TOP NOTCH OR FROM THE VERTICAL JOINT EDGE ON THE COLD SIDE OF THE JOINT.


USE LONGITUDINAL MILLED JOINT AS PLANS SHOW OR AS THE ENGINEER DIRECTS.



**TYPICAL PAVEMENT CROSS SECTION  
VERTICAL JOINT**



**OVERLAP DETAIL (TYPICAL)**




**TYPICAL PAVEMENT CROSS SECTION  
VERTICAL JOINT (MILLED)**

**HMA LONGITUDINAL JOINTS**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
November 2020 /S/ Steven Hefel  
DATE  
FHWA

HMA PAVEMENT ENGIN 31



① WOOD OR STEEL POSTS (W6X9 OR W6X8.5) MAY BE USED. DO NOT INTERMIX WOOD AND STEEL POSTS. INSTALL STEEL POSTS WITH HOLES ON APPROACHING TRAFFIC SIDE.

② USE WOOD OR APPROVED PLASTIC BLOCKOUTS. WOOD BLOCKOUTS MAY BE CONSTRUCTED OUT OF TWO OR MORE WOOD BLOCKOUTS. SEE ALTERNATE WOOD BLOCKOUT DETAIL. DIMENSIONS OF APPROVED PLASTIC BLOCKOUTS MAY VARY.


③ IF ROCK IS ENCOUNTERED DURING EXCAVATION, PROVIDE A HOLE 12 INCHES IN DIAMETER EXTENDING 20 INCHES DEEP INTO THE ROCK. PLACE APPROXIMATELY 2 1/2 INCHES OF GRANULAR MATERIAL IN THE BOTTOM OF THE HOLE. CUT THE POSTS TO LENGTH AND INSTALL. BACKFILL WITH EXCAVATED MATERIAL AND COMPACT. BACKFILL IS TO BE FREE OF LARGE ROCKS.

④ WHEN THE DISTANCE FROM BACK OF POST TO SHOULDER HINGE POINT IS LESS THAN 2 FEET INSTALL LONGER POST AT HALF POST SPACING (K).


⑤ FOR NEW MGS INSTALLATION TOP OF W-BEAM RAIL TOLERANCE IS  $\pm 1$ ". FOR EXISTING MGS INSTALLATION TOP OF W-BEAM IS BETWEEN 27  $\frac{3}{4}$ " TO 32".

⑥ WHEN USING STEEL POST AND WOOD BLOCKOUTS INSTALL FOUR 16D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.


⑦ TOTAL POST LENGTH FOR TYPE K IS 7' - 0".  
TOTAL POST LENGTH FOR OTHER MGS TYPES IS 6' - 0".




END VIEW  
LOCATED ALONG A ROADWAY SHOULDER  
STANDARD INSTALLATION




END VIEW  
LOCATED ALONG A CURBED ROADWAY




END VIEW  
MGS LONGER POST AT HALFPOST  
SPACING W BEAM (K)




END VIEW  
SETTING STEEL OR WOOD POST IN ROCK




STEEL POST & HOLE  
PUNCHING DETAIL  
(W 6 X 9) ①




WOOD POST  
(6" X 8") NOMINAL ①



PLAN VIEW  
WOOD POST,  
BLOCKOUT & BEAM




WOOD OR PLASTIC  
BLOCKOUT ②




PLAN VIEW  
STEEL POST,  
PLASTIC BLOCKOUT & BEAM

MIDWEST GUARDRAIL SYSTEM  
(MGS) GUARDRAIL


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**FRONT VIEW  
POST SPACING STANDARD INSTALLATION**




**FRONT VIEW  
HALF POST SPACING (HS) AND  
HALF POST SPACING WITH LONGER POSTS (K)**




**FRONT VIEW  
QUARTER POST SPACING (QS)**




**FRONT VIEW  
MID-SPAN BEAM SPLICE**




**FRONT VIEW AT STEEL POST**



**FRONT VIEW AT WOOD POST**



**SECTION THRU W-BEAM RAIL**



**ONE SIDED REFLECTOR DETAIL  
AND TYPICAL INSTALLATION**

## GENERAL NOTES


- ⑧ DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL.
- ⑨ 25 FEET OF HALF POST SPACING IS REQUIRED ON APPROACH AND DEPARTURE ENDS OF QUARTER POST SPACING.

POST BOLTS ARE A  $\frac{3}{8}$ " DIAMETER ASTM A307 GUARDRAIL BOLT. A POST BOLT REQUIRES  $\frac{3}{8}$ " DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX NUT AND  $\frac{3}{8}$ " DIAMETER F844 FLAT WASHER. POST BOLTS MAY BE LONGER IF MULTIPLE BLOCKOUTS ARE BEING USED.

GUARD RAIL SPLICE BOLTS ARE A  $\frac{3}{8}$ " DIAMETER ASTM A307 GUARDRAIL HEAD BOLT. A GUARDRAIL SPLICE BOLT REQUIRES  $\frac{3}{8}$ " DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX NUT.


**MIDWEST GUARDRAIL SYSTEM  
(MGS) GUARDRAIL**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION



#### DETAIL FOR 16" BLOCKOUT DEPTH

IT IS ACCEPTABLE TO USE BLOCKOUTS UP TO 16" DEEP TO INCREASE THE POST OFFSET TO AVOID UNDERGROUND OBSTACLES. THERE IS NO LIMIT TO THE NUMBER OF POSTS THAT CAN HAVE ADDITIONAL BLOCKOUTS UP TO 16" DEEP.




#### DETAIL FOR 36" BLOCKOUT DEPTH

NOTES: UNDER SPECIAL CIRCUMSTANCES, SUCH AS AVOIDING OBSTACLES THAT ARE NOT RELOCATED, IT IS ACCEPTABLE TO INSTALL ADDITIONAL BLOCKOUTS TO OBTAIN UP TO 36" DEPTH FOR ONE OR TWO POSTS IN A SECTION OF GUARDRAIL.


DO NOT USE 16" OR 36" BLOCKOUTS IF IT CAUSES THE POST TO BE DRIVEN BEYOND SHOULDER HINGE POINT OR CAUSES A FIXED OBJECT TO BE WITHIN THE DEFLECTION DISTANCE OF THE BARRIER.

NOTE:  
1. ALL FILLETS SHALL HAVE A MINIMUM RADIUS OF  $\frac{3}{16}$ ".  
2. IF THE BOLT EXTENDS MORE THAN  $\frac{1}{4}$ " FROM THE NUT THE BOLT SHOULD BE TRIMMED BACK.




#### POST BOLT TABLE


L	T (MIN.)
1 1/4"	1 1/8"
2"	1 3/4"
10"	4"
14"	4 1/16"
18"	4"
21"	4 1/16"
25"	4"




#### ALTERNATE BOLT HEAD




#### POST BOLT, SPLICE BOLT AND RECESS NUT



#### PLAN VIEW BEAM LAPPING DETAIL



#### POST DRIVING FOR CONTINUOUS UNDERGROUND OBSTRUCTION




#### SIDE VIEW

#### PLAN VIEW


#### ALTERNATE WOOD BLOCKOUT DETAIL

**MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**MISSING POST IN MGS GUARDRAIL**




**MISSING POST IN MGS GUARDRAIL NEAR EAT**




**MISSING POST IN MGS GUARDRAIL NEAR AN APPROACH TRANSITION**



**MISSING POST IN MGS GUARDRAIL NEAR FLARED BEAM GUARD**




**MISSING POST IN MGS GUARDRAIL NEAR A TYPE 2 END TERMINAL**




**MISSING POST IN SHORT SPAN MGS GUARDRAIL NEAR CURB (SL)** (407)

400 MAX SPAN 12' - 6"  
 401 2' MIN.  
 402 MGS GUARDRAIL 3  
 403 NESTING BEAM GUARD  
 404 ASYMMETRIC TRANSITION  
 405 SOIL WELL DRAINED AND COMPACTED  
 406 SEE OTHER DRAWINGS IN THIS SDD  
 407 SEE OTHER DRAWINGS FOR MIN. SPACING BETWEEN SPANS  
 408 SEE SDD 14B44  
 409 SEE SDD 14B45  
 410 SEE SDD 14B47  
 411 MINIMUM DISTANCE BETWEEN MISSING POST SPANS.



**SECTION A - A**



**SECTION B - B**

**MIDWEST GUARDRAIL SYSTEM  
(MGS) GUARDRAIL**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2021 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS DEVE  
FHWA UNIT SUPERVISOR 36

## GENERAL NOTES

- (A) THE SLOPE IN THE AREA BOUNDED BY THE GRADELINE, THE HINGE POINT LINE (HPL) AND THE CLEAR ZONE LIMITS (CZL) SHALL BE 4:1 OR FLATTER.
- (B) AFTER FINAL ASSEMBLY, RECHECK CABLE TO BE SURE IT IS TAUT AND HAS NOT RELAXED.
- (C) DIFFERENT MANUFACTURERS REQUIRE DIFFERENT PERFORATED W-BEAM RAIL END PANELS. SEE MANUFACTURER'S INFORMATION.
- (D) ATTACH ALUMINUM SHEET TO E.A.T. HEAD USING 4 STAINLESS STEEL SELF-TAPPING SCREWS. ONE SCREW PER CORNER.
- (E) HARDWARE MAY VARY BETWEEN MANUFACTURER. SEE MANUFACTURER'S DRAWING FOR INFORMATION.

DIMENSIONS MAY VARY, MANUFACTURER'S INFORMATION.


SEE SDD 14B42 FOR MORE INFORMATION.

\* DO NOT ATTACH BLOCKOUTS TO POST 1 AND 2.


DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL.

SEE MANUFACTURER'S DRAWING FOR SPLICE LOCATION, HARDWARE DIMENSIONS AND INSTALLATION INSTRUCTIONS.


THE CENTER OF THE UPPER 3 1/2" DIAMETER HOLE ON POST NUMBER 3 THROUGH POST 9 IS TO BE FLUSH WITH THE GROUND LINE UP TO A MAXIMUM OF 2" ABOVE GROUND LINE. WOOD BLOCKS ON POSTS NUMBERED 3 THROUGH 9 MAY BE ADJUSTED UP TO 3" ABOVE THE TOP OF POST.




DETAIL "A" (E)




SECTION C - C  
TYPICAL AT POST NOS. 3 - 9




PLAN




ELEVATION



SECTION B - B  
TYPICAL AT POST NO. 2\*



SECTION A - A  
TYPICAL AT POST NO. 1\*




DETAIL "B" (E)  
POST NO. 1 \*

MIDWEST GUARDRAIL SYSTEM  
ENERGY ABSORBING TERMINAL  
(MGS)


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

## BILL OF MATERIALS

PART NO.	DESCRIPTION MATERIALS PROVIDED BY MGS EAT MANUFACTURER. SEE MANUFACTURER'S DETAILS FOR MORE INFORMATION.
①	UPPER POST NO. 1 6" X 6" TUBE
②	LOWER POST NO. 1
③	WOOD CRT
④	WOOD BLOCKOUT
⑤	PIPE SLEEVE
⑥	BEARING PLATE
⑦	BCT CABLE ASSEMBLY
⑧	ANCHOR CABLE BOX
⑨	GROUND STRUT
⑩	PERFORATED W-BEAM RAIL END PANEL, 12'-6" LONG.
⑪	STANDARD W-BEAM RAIL. MULTIPLE SECTIONS REQUIRED. SECTIONS VARY IN LENGTH.
⑫	IMPACT HEAD
⑬	EAT MARKER POST - YELLOW (SEE APPROVED PRODUCTS LIST)
⑭	SOIL PLATE
⑮	UPPER POST NO. 2
⑯	LOWER POST NO. 2




GENERIC GROUND STRUT <sup>⑨ (E)</sup>









SECTION A - A


GENERIC ANCHOR CABLE BOX <sup>⑨ (E)</sup>




BEARING PLATE <sup>⑯ (E)</sup>

UPPER POST NO. 1 <sup>①</sup> <sup>(E)</sup>LOWER POST NO. 1 <sup>②</sup> <sup>(E)</sup>WOOD CRT POST  
POSTS NUMBER 3-9 <sup>③</sup> <sup>(E)</sup>UPPER POST NO. 2 <sup>⑯</sup> <sup>(E)</sup>LOWER POST NO. 2 <sup>⑯</sup> <sup>(E)</sup>WOOD BLOCKOUT <sup>④</sup>

REQ'D. AT ALL POSTS EXCEPT POST NO'S 1 &amp; 2

REFLECTIVE SHEETING DETAIL <sup>(E)</sup>


W5 - 59




FRONT VIEW



SIDE VIEW

E.A.T. MARKER POST <sup>⑯</sup>

SIDE VIEW




TOP VIEW

ALTERNATE WOOD  
BLOCKOUT DETAIL

**MIDWEST GUARDRAIL SYSTEM  
ENERGY ABSORBING TERMINAL  
(MGS)**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
7/2018 */S/ Rodney Taylor*  
DATE ROADWAY STANDARDS DEVE  
FHWA UNIT SUPERVISOR 39



**TWO WAY TRAFFIC**

(T) THRIE BEAM CONNECTION

(W) W-BEAM CONNECTION WHEN REQUIRED



**ONE WAY TRAFFIC**

**TYPICAL LOCATIONS OF THRIE BEAM AND W-BEAM CONNECTIONS TO BRIDGE**

**GENERAL NOTES**

IF ROCK IS ENCOUNTERED, REMOVE ROCK TO FULL DEPTH OF POST PLUS 2½", AND 12" DIAMETER AROUND POST. SEE 14B42 FOR MORE DETAILS.

TRANSITION USES STEEL POSTS ONLY.


SEE STANDARD DETAIL DRAWING 14 B 42 FOR MORE INFORMATION.

POST 2 THROUGH 17 USES STEEL POST ONLY


① BRIDGE RAILING TYPE "W" DOES NOT REQUIRE A TERMINAL CONNECTOR.

② OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.

⑬ STEEL OR WOOD POST IS ACCEPTABLE AT POST 1. SEE SDD14B42



**PLAN VIEW**



**ELEVATION VIEW**


**MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION**

**MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


## GENERAL NOTES

- (2) OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- (3) WHEN USING STEEL POSTS AND WOOD BLOCKOUTS INSTALL FOUR 10D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.
- (4) TOLERANCE FOR TOP OF W-BEAM RAIL IS  $\pm 1"$ .
- (13) STEEL OR WOOD POST IS ACCEPTABLE AT POST 1. SEE SDD 14B42




**SECTION A-A**  
**POSTS 1-5**

6





**SECTION D-D**  
**POSTS 12-17**

S.D.D. 14 B 45-5b




**SPICE DETAIL**


**SECTION B-B**  
**POST 6**




**SECTION C-C**  
**POSTS 7-11**



**PLATE WASHER DETAIL**



**THRIE BEAM  
TERMINAL CONNECTOR**



**SECTION THRU THRIE  
BEAM RAIL ELEMENT**


MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


S.D.D. 14 B 45-5b

6


41





## W-BEAM TO THRIE BEAM TRANSITION SECTION





## 6'-3" THRIE BEAM SECTION



## 12'-6" THRIE BEAM SECTION



SIDE VIEW  
TOP VIEW  
ALTERNATE WOOD BLOCKOUT DETAIL



## GENERAL NOTES



STEEL POSTS ARE W6X9 OR W6X8.5.

BOLT HOLES FOR POST ARE ON FRONT AND SIDE OF POST.

(3) WHEN USING STEEL POSTS AND WOOD BLOCKOUTS INSTALL FOUR 16D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.


(5) WOOD BLOCKS MAY BE CONSTRUCTED OUT OF 2 WOOD BLOCKS. SEE ALTERNATE WOOD BLOCK DETAIL.

(13) STEEL OR WOOD POST IS ACCEPTABLE AT POST 1. SEE SDD 14B42.



MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)



STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION



FRONT VIEW

### THRIE BEAM CONNECTION TO BRIDGE PARAPET WITH SQUARE ENDS

SECTION E-E





FRONT VIEW

### W BEAM TRANSITION AND CONNECTION TO BRIDGE PARAPETS WITH SQUARE ENDS

(USE ONLY ON THE TRAFFIC EXIT END OF ONE WAY BRIDGES)

SECTION F-F



DRILL HOLE LOCATION


#### MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATIONAPPROVED  
07/2018 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS UNIT SUPERVISOR  
FHWA 43

## GENERAL NOTES

THESE ARE TYPICAL CONNECTION DETAILS. ADJUST THE POSITION OF CONNECTIONS TO EXISTING BRIDGES TO FIT THE ACTUAL BRIDGE AND SITE DIMENSIONS.


- ② OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- ④ TOLERANCE FOR TOP OF BEAM IS  $\pm 1"$ .
- ⑥ DRILLING BOLT HOLES THROUGH THE PARAPET, BOLTS, NUTS, WASHERS AND REPAIRING DAMAGED CONCRETE ARE INCIDENTAL TO THE CONTRACT.
- ⑦ BOLTS MAY BE A325 BOLTS OR A449 BOLTS. BOLT LENGTH AND THREADING LENGTH ARE TO ALLOW FOR A TIGHT CONNECTION BETWEEN RIGID BARRIER AND THRIE BEAM CONNECTION PLATE. CONTRACTOR IS TO FIELD VERIFY BOLT LENGTH AND THREAD LENGTH. ONE ROUND WASHER REQUIRED BETWEEN BOLT HEAD AND THRIE BEAM CONNECTOR PLATE. BOLTS THAT EXTEND THROUGH THE PARAPET AND OUT THE BACK FACE REQUIRE A HARDENED ROUND STEEL WASHER THAT IS 2" O.D. X 5/32" THICK AND ONE PLATE WASHER. REPAIR ANY DAMAGED CONCRETE FROM BOLT INSTALLATION.
- ⑧ THE RECESS FOR A W-BEAM CONNECTION, WHICH EXISTS ON SOME PARAPETS OF THIS TYPE, SHALL BE FILLED WITH A TREATED TIMBER BLOCKOUT. BLOCKOUT SIZE IS 1'-6" X 2'-0" X 3 1/2".
- ⑨ BOLT, NUT AND WASHERS NOT REQUIRED FOR THIS LOCATION WHEN RETROFITTING AN EXISTING PARAPET AND THE HOLE IS EITHER ABOVE PARAPET OR WITHIN 4 INCHES OF THE EDGE OF PARAPET.



SECTION G-G

⑥ ⑦  $\frac{7}{8}$ " DIA. HEX HEAD CAP SCREWS INTO THREADED INSERTS (FURNISHED WITH THE BRIDGE) WHEN RETROFITTING INTO AN EXISTING RIGID BARRIER  $\frac{7}{8}$ " DIA. H.S. HEX BOLT AND WASHERS REQUIRED  
1" DIA. HOLES DRILLED THRU PARAPET (4 REQ'D.)



## THRIE BEAM CONNECTION TO VERTICAL FACED PARAPETS



FRONT VIEW

## W BEAM CONNECTION TO VERTICAL FACE PARAPET

(USE ONLY ON THE TRAFFIC EXIT END OF ONE WAY BRIDGES)



SECTION H-H


MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
07/2018 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS UNIT SUPERVISOR  
FHWA 44


## GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS.  
 THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A MINIMUM OF 200 FEET (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.  
 ALL SIGNS ARE 48" X 48" UNLESS OTHERWISE NOTED.  
 SIGNS THAT WILL BE IN PLACE LESS THAN SEVEN CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.  
 IF A "STOP" SIGN MUST BE REMOVED FOR A WORK OPERATION, A TEMPORARY "STOP" SIGN SHALL BE PLACED PRIOR TO THE SIGN REMOVAL, OR A FLAGGER SHALL BE PROVIDED UNTIL THE SIGN IS REESTABLISHED.  
 \* OMIT G20-1 SIGNS IF LENGTH OF WORK AREA IS 2 MILES OR LESS  
 \*\* PLACE AN ADDITIONAL W20-1A "ROAD WORK AHEAD" SIGN IF WORK AREA WITHIN THE PROJECT IS SEPARATED BY MORE THAN 2 MILES FROM PREVIOUS WORK AREA.



## LEGEND

- Ⓐ SIGN ON PERMANENT SUPPORT
- DIRECTION OF TRAFFIC
- ▨ WORK AREA




## TRAFFIC CONTROL, ADVANCE WARNING SIGNS 45MPH OR GREATER

**TRAFFIC CONTROL, ADVANCE WARNING SIGNS 45 MPH OR GREATER TWO-WAY UNDIVIDED ROAD OPEN TO TRAFFIC**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
July 2018 /S/ Andrew Heidke  
DATE  
FHWA

WORK ZONE ENGINEER 45



PERMANENT PAVEMENT MARKING

**GENERAL NOTES**

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.


\* CONFIRM MARKING LINE WIDTH WITH THE MISCELLANEOUS QUANTITIES

- ① LOCATE THE NO PASSING ZONE W14-3 SIGN WITHIN 50 FEET OF THE "T" MARKING
- ② MEASURE FROM EDGE OF MARKING TO JOINT LINE. THIS DOES NOT INCLUDE SPACE NEEDED FOR GROOVING OPERATIONS.


**LEGEND**

- "T" MARKING
- SIGN ON PERMANENT SUPPORT
- DIRECTION OF TRAFFIC


<b>PERMANENT LONGITUDINAL PAVEMENT MARKINGS</b>	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED December 2024 /S/ Jeannie Silver DATE Statewide Pavement Marking Engineer FHWA	




TEMPORARY BARRIER OFFSET FROM EDGE LINE



TWO WAY TRAFFIC



ONE WAY TRAFFIC



FREEWAYS AND EXPRESSWAYS

## TEMPORARY PAVEMENT MARKING

## GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.

## LEGEND


→ DIRECTION OF TRAFFIC

\* CONFIRM MARKING LINE WIDTH WITH THE MISCELLANEOUS QUANTITIES


## TEMPORARY LONGITUDINAL PAVEMENT MARKING

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
December 2024 /S/ Jeannie Silver  
DATE Statewide Pavement Marking Engineer  
FHWA

**DRUM**


BALLAST WIDTHS  
RANGE FROM 24"-36"

**42" CONE**


DO NOT USE IN TAPERS  
 $\frac{1}{2}$  SPACING OF DRUMS  
 BALLAST WIDTHS  
RANGE FROM 14"-20"

**VERTICAL PANEL**

THE STRIPES SHALL SLOPE DOWNWARD TO  
THE TRAFFIC SIDE FOR CHANNELIZATION.

**TYPE II BARRICADE**

FOR RAILS LESS THAN 36" LONG, 4" WIDE STRIPES  
MAY BE USED. ALL STRIPES SHALL SLOPE DOWNWARD  
TO THE TRAFFIC SIDE FOR CHANNELIZATION.

**TYPE III BARRICADE**

IF SIGN MOUNTED, DO NOT COVER MORE THAN 50% OF THE TOP  
TWO RAILS OR 33% OF THE TOTAL AREA OF THE THREE RAILS.

\* IF USED FOR A PERMANENT APPLICATION USE RED SHEETING.


## GENERAL NOTES

- ① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.
- ② LOCATION OF WARNING LIGHTS WHEN SHOWN ON THE PLAN.

### CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
November 2022 /S/ Andrew Heidtke  
DATE FHWA  
WORK ZONE ENGINEER 48

**LEGEND****GENERAL NOTES**

DETAILS OF TRAFFIC CONTROL DEVICES AND INSTALLATION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.


ALL SIGNS ARE 48" X 48" UNLESS OTHERWISE NOTED.

"WO" SIGNS ARE THE SAME AS "W" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

THE EXACT NUMBER, LOCATION AND SPACING OF ALL SIGNS, DEVICES, AND LOCATION OF ALL FLAGGERS SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

THE FIRST ADVANCE WARNING SIGN SHOULD TYPICALLY BE LOCATED IN ADVANCE OF THE ANTICIPATED TRAFFIC BACKUP OR QUEUE.

WHEN A SIDE ROAD OR RAMP INTERSECTS THE FACILITY ON WHICH THE WORK IS BEING PERFORMED, ADDITIONAL TRAFFIC CONTROLS SHALL BE PROVIDED AS SPECIFIED IN THE PLANS AND/OR THE SPECIAL PROVISIONS OR AS APPROVED BY THE ENGINEER.




**STOP/SLOW PADDLE  
ON SUPPORT STAFF**

**SIGN AND TEMPORARY RUMBLE STRIP ARRAY SPACING TABLE**

SPEED LIMIT	SPACING "A"
25-30 MPH	200'
35-40 MPH	350'
45-55 MPH	500'



USE OF WO3-4 SIGN IS OPTIONAL. WHEN USED, THIS SIGN SHALL BE LOCATED BETWEEN THE W20-7A AND W20-4A SIGNS, USING SPACING "A".

**FLAGGING**

FLAGGERS SHALL BE IN SIGHT OF EACH OTHER OR IN DIRECT COMMUNICATION AT ALL TIMES. THEY SHALL BE EQUIPPED WITH STOP/SLOW PADDLES FASTENED ON SUPPORT STAFFS. WHEN THE FLAGGING OPERATION IS NOT IN EFFECT REMOVE TEMPORARY PORTABLE RUMBLE STRIPS PRIOR TO COVERING OR REMOVING ALL ADVANCE SIGNING.

- (1) FOR MOVING WORK OPERATIONS, POST ADDITIONAL W20-7A FLAGGER SIGNS AT APPROXIMATELY 3,500' INTERVALS IN THE MOVING WORK OPERATION OR AS APPROVED BY THE ENGINEER.
- (2) SIGN NOT REQUIRED IF FLAGGING OPERATION OCCURS WITHIN A SIGNED ROAD WORK ZONE AREA.

WHEN THE DISTANCE BETWEEN FLAGGERS EXCEEDS 2 MILES, A PILOT CAR IS REQUIRED. WHEN CURVES REDUCE SIGHT DISTANCE BELOW 400', A PILOT CAR IS REQUIRED.

**TEMPORARY PORTABLE RUMBLE STRIPS**

UTILIZE TEMPORARY PORTABLE RUMBLE STRIPS ON ALL FLAGGING OPERATIONS.


- (3) EACH TEMPORARY PORTABLE RUMBLE STRIP ARRAY CONSISTS OF THREE RUMBLE STRIPS PLACED TRANSVERSE ACROSS THE LANE AT THE LOCATIONS SHOWN. WITHIN EACH ARRAY, SPACING BETWEEN RUMBLE STRIPS SHALL BE 15 FEET ON CENTER.

ONLY USE TEMPORARY PORTABLE RUMBLE STRIPS FROM THE APPROVED PRODUCTS LIST.

INSTALL TEMPORARY RUMBLE STRIPS PER MANUFACTURER'S RECOMMENDATIONS.

PLACE ADVANCE SIGNING PRIOR TO INSTALLING TEMPORARY RUMBLE STRIPS.

DO NOT INSTALL TEMPORARY PORTABLE RUMBLE STRIPS ON GRAVEL, MILLED SURFACES, OR ASPHALT THAT HAS BEEN PAVED LESS THAN 12 HOURS.



**TRAFFIC CONTROL FOR  
LANE CLOSURE WITH  
FLAGGING OPERATION**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2022 /S/ Andrew Heidke  
DATE  
FHWA

WORK ZONE ENGINEER 49

**LEGEND**

- SIGN ON PERMANENT SUPPORT
- TRAFFIC CONTROL DRUM
- DIRECTION OF TRAFFIC
- WORK ZONE

**GENERAL NOTES**

ALL SIGNS ARE 48"X48" UNLESS OTHERWISE NOTED. IF NECESSARY DUE TO SPACE CONSTRAINTS IN URBAN AREAS, 36" X 36" SIGNS MAY BE USED IF APPROVED BY THE REGIONAL TRAFFIC UNIT.

"WO" SIGN IS THE SAME AS "W" SIGN EXCEPT THE BACKGROUND IS ORANGE.


ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH THE TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

CHANNELIZING DEVICES PLACED ADJACENT TO WORK AREA SHALL BE PULLED BACK FROM THE TRAVEL LANE WHEN WORK IS NOT IN PROGRESS.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

W20-1A AND G20-2A SIGNS ARE NOT REQUIRED IF THE WORK AREA IS WITHIN A LARGER WORK ZONE WHERE THESE SIGNS ARE ALREADY PRESENT. G20-2A SIGNS MAY ALSO BE OMITTED IF DURATION OF WORK IS LESS THAN 7 CONTINUOUS DAYS AND NIGHTS.



POSTED SPEED LIMIT PRIOR TO WORK STARTING (MPH)	ADVANCE WARNING SIGN SPACING (A) FEET	SHOULDER TAPER L / 3 W, LATERAL OFFSET (FT)						BUFFER SPACE (B) FEET
		3	4	5	6	7	8	
25	200'	10	14	17	21	24	28	55
30	200'	15	20	25	30	35	40	85
35	350'	20	27	34	40	47	54	120
40	350'	26	35	44	53	62	70	170
45	500'	45	59	74	89	104	119	220
50	500'	50	66	83	99	116	132	280
55	500'	54	73	91	109	127	145	335'

**TRAFFIC CONTROL, WORK ON  
SHOULDER OR PARKING LANE,  
UNDIVIDED ROADWAY**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2020 /S/ Andrew Heidke  
DATE STATEWIDE WORK ZONE T  
FHWA SAFETY ENGINEER 50

## LEGEND

|| TYPE III BARRICADE WITH ATTACHED SIGN

◎ SIGN ON PERMANENT SUPPORT

◐ TRAFFIC CONTROL DRUM WITH TYPE "C" STEADY BURN LIGHT

● TRAFFIC CONTROL DRUM

  FLAGS, 16" X 16" MIN. (ORANGE)

—X—X— REMOVING PAVEMENT MARKING


 DIRECTION OF TRAFFIC

 ASPHALTIC PAVEMENT WIDENING

 CONCRETE BARRIER TEMPORARY PRECAST

 TEMPORARY SIGNAL. SEE SDD 09G02 FOR EXACT PLACEMENT

WIDTH ON SIGN TO BE APPROX. 1-Foot  
LESS THAN AVAILABLE WIDTH. (OMIT IF  
AVAILABLE WIDTH IS MORE THAN 16 FEET)



## GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND TO PROVIDE A MINIMUM OF 200 FEET (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE..

THIS LANE CLOSURE IS TYPICAL FOR CLOSING RIGHT LANE - REVERSE FOR CLOSING LEFT LANE.

"WOLIS THE SAME AS "WILEXCEPT THE BACKGROUND IS ORANGE.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED OR AS APPROVED BY THE ENGINEER.

REMOVE PAVEMENT MARKING AND PLACE TEMPORARY PAVEMENT MARKING LINES IF THE CLOSURE IS TO BE IN PLACE FOR 4 OR MORE CONTINUOUS DAYS AND NIGHTS.

INSTALL OVERHEAD TEMPORARY SIGNAL HEADS ABOVE THE MIDDLE OF THE TRAVEL LANE THEY ARE CONTROLLING.

- ① 500 FOOT SPACING SHOWN IS FOR ROADWAYS WITH A PRE-CONSTRUCTION REGULATORY SPEED LIMIT OF 45 MPH OR MORE. FOR 35 - 40 MPH, USE 350 FOOT TYPICAL SPACING. FOR 25 - 30 MPH, USE 200 FOOT TYPICAL SPACING.
- ② USE 300 FOOT SPACING IF THE PRE - CONSTRUCTION REGULATORY SPEED IS 35 MPH OR LESS.
- ③ DIMENSION DETERMINED BY CBTP TAPER FROM EDGE LINE TO TANGENT SECTION OF THE ROAD.
- ④ TEMPORARY PAVEMENT MARKING LINE, 18 INCH WHITE STOP LINE.
- ⑤ 700 FOOT TEMPORARY PAVEMENT MARKING LINE, 6 INCH DOUBLE YELLOW . WHEN THE DISTANCE FOR THE PRECEDING NO - PASSING ZONE IS LESS THAN THE MINIMUM DISTANCE BETWEEN ZONES AS INDICATED IN THE SPECIFICATIONS, THE TWO ZONES SHALL BE CONNECTED.
- ⑥ SEE SDD 15C02 - SHEET "F" FOR ADVANCED WIDTH RESTRICTION SIGNING.

WIDTH ON SIGN TO BE APPROX. 1-FOOT  
LESS THAN AVAILABLE WIDTH. (OMIT IF  
AVAILABLE WIDTH IS MORE THAN 16 FEET)

A triangular road sign with a black border and the words "ROAD WORK" in black capital letters inside.

A graphic of a road signpost pointing downwards, with the text 'W20-1A' written on it.


## **TRAFFIC CONTROL, ONE LANE ROAD TEMPORARY SIGNALS**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION



---

/S/ Andrew Heidtke  
WORK ZONE ENGINEER 51

## URBAN AREA



## RURAL AREA (See Note 2)



\*\* The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

## GENERAL NOTES

1. Signs wider than 4 feet or 20 sq.ft or larger, shall be mounted on multiple posts. Refer to plate A4-4.
2. If signs are mounted on or behind barrier wall, see A4-10 sign plate. The Double Arrow sign (W12-1D) shall be mounted at a height of 2'-3" (±) 3". The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Enhanced Reference Markers, Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4'-3" (±) 3".
3. For expressways and freeways, mounting height is 7'-3" (±) 3" or 6'-3" (±) 3" depending upon existence of a sub-sign.
4. Minimum mounting height for signs mounted on traffic signal poles is 5'-3" (±) 3".
5. Offset distance shall be consistent with existing signs or consistent throughout length of project.
6. Folding signs shall be mounted at a height of 5'-3" (±) 3" or as directed by the Engineer.

## POST EMBEDMENT DEPTH

Area of Sign Installation (Sq. Ft.)	D (Min)
20 or Less	4'
Greater than 20	5'


\* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

TYPICAL INSTALLATION  
OF PERMANENT TYPE II  
SIGNS ON SINGLE POSTS

WISCONSIN DEPT OF TRANSPORTATION


APPROVED *Matthew P. Rauch*  
for State Traffic Engineer

DATE 12/6/23 PLATE NO. A4-3.23




ELEVATION VIEW

DETAIL OF WOOD 4 X 6 SIGN POST IN BOX-OUT



ELEVATION VIEW

DETAIL OF STEEL 2 X 2 SIGN POST IN BOX-OUT



PLAN VIEW

FOR NEW CONCRETE/ASPHALT INSTALLATIONS

SIGN POST  
BOX-OUTS  
A4-3B

WISCONSIN DEPT OF TRANSPORTATION

APPROVED  
*Matthew P. Rauch*  
for State Traffic Engineer  
DATE 1/27/14 PLATF 53

PROJECT NO:

HWY:



COUNTY:

SHEET NO:




E

### GENERAL NOTES

- For 3 or 4 post installations, individual post spacing shall be greater than 3'-6".
- See tables below for required number of posts.
- For expressways and freeways, mounting height is 7'-3" ( $\pm$  3") or 6'-3" ( $\pm$  3") depending upon existence of sub-sign.
- The ( $\pm$ ) tolerance for mounting height is 3 inches.
- J-Assemblies are considered to be one sign for mounting height.
- Offset distance shall be consistent with existing signs or consistent throughout length of project.
- Folding signs shall be mounted at a height of 5'-3" ( $\pm$  3") or as directed by the engineer.
- The Double Arrow sign (W12-1) shall be mounted at a height of 2'-3" ( $\pm$  3"). The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4"-3" ( $\pm$  3").



### RURAL AREA (See Note 3)



\* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

\*\* The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

\*\*\* See A4-3 sign plate for signs 4' or less in width and less than 20 S.F. in area.

**SIGN SHAPE OTHER THAN DIAMOND (TWO POSTS REQUIRED)**

L	E
Greater than 48"	12"
Less than 60"	
60" to 108"	L/5

**SIGN SHAPE OTHER THAN DIAMOND (THREE POSTS REQUIRED)**

L	E
Greater than 108" to 144"	12"

### POST EMBEDMENT DEPTH

Area of Sign Installation ( Sq. Ft. )	D ( Min )
20 or Less	4'
Greater than 20	5'

### TYPICAL INSTALLATION OF TYPE II SIGNS ON MULTIPLE POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

*Matthew R. Rauch*  
for State Traffic Engineer

DATE 12/6/23 PLATE NO. A4-4.16


PROJECT NO:

HWY:


COUNTY:

SHEET NO: 54

**E**



SIGN SHALL BE MOUNTED TO PROJECT  
ABOVE THE TOP OF THE POST



Nuts, bolts and lags used for mounting signs shall have hexagonal heads and shall be either :

- a. Hot dip galvanized in accordance with ASTM Designation: A 153, Class D, or SC 3
- b. Electro-galvanized in accordance with ASTM Designation :B 633, TYPE III, SC 3.

Threads on bolts and nuts shall be manufactured with sufficient allowance for the cadmium plate or galvanized coating to permit the nuts to run freely on the bolts.

#### STRINGER BOLTING TO ALUMINUM SIGNS (SEE SIGN PLATE A4-18)

MACHINE BOLTS -  $\frac{5}{16}$ " X 1-3/4" Length w/ lock nuts

#### WOOD POSTS (4" x 6")

LAG SCREWS -  $\frac{3}{8}$ " X 3" (NO STRINGERS ON BACK OF SIGN)  
 $\frac{3}{8}$ " X 4" (STRINGERS ON BACK OF SIGN)

#### SQUARE STEEL POSTS (2" x 2")

MACHINE BOLTS -  $\frac{3}{8}$ " X 3-1/4" Length w/ nuts (NO STRINGER ON BACK OF SIGN)  
 $\frac{3}{8}$ " X 5" Length w/ nuts (STRINGERS ON BACK OF SIGN)

RIVETS -  $\frac{9}{32}$ " (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM BODY/MANDREL

O.D. FLANGE .720-.765 INCH, GRIP RANGE .042-.375 INCH

#### WASHERS (ALL POSTS) -

1-1/4" O.D. X  $\frac{3}{8}$ " I.D. X  $\frac{1}{16}$ " STEEL

1-1/4" O.D. X  $\frac{3}{8}$ " I.D. X .080 NYLON

\* Two different fastening systems are shown for illustration purposes. On any individual sign, either one or the other system shall be used. Actual number of fasteners per sign varies with the sign area, but normally there are two. For a single post installation, all signs greater than 9 sq. ft. require the use of 3 fasteners.


#### ATTACHMENT OF SIGNS TO POSTS

WISCONSIN DEPT OF TRANSPORTATION


APPROVED *Matthew R Rauch*  
for State Traffic Engineer

DATE 4/1/2020 PLATE NO. A4-8.9



**TELESCOPIC TUBING ANCHORS  
TWO PIECE SYSTEM**



**DETAIL OF TUBULAR STEEL SIGN POST  
(IN Poured CONCRETE OR ASPHALT)**



**DETAIL OF TUBULAR STEEL SIGN POST  
(IN LOCATIONS OTHER THAN Poured CONCRETE OR ASPHALT)**



Area of Sign Installation (Sq. Ft.)	Number of Required Posts
9 or less	1
Greater than 9 less than or equal to 18	2
Greater than 18 less than or equal to 27	3

Signs wider than 3 feet or larger than 9 sq. ft shall be mounted on multiple posts (see above table).

**TUBULAR STEEL  
SIGN POST  
A4-9**

WISCONSIN DEPT OF TRANSPORTATION

APPROVED  
Matthew P. Rauch

for State Traffic Engineer

DATE 2/05/15 PLATI 56 14-9.9



PROJECT NO:

HWY:

COUNTY:

SHEET NO:

E



GENERAL NOTES

1. All 4 x 6 Wood Posts shall be modified by having two  $1\frac{1}{2}$ " diameter holes drilled perpendicular to the roadway centerline.

4 X 6 WOOD POST  
MODIFICATIONS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

*Cheska J. Spangler*  
for State Traffic Engineer

DATE 3/27/97 PLATE NO. A4-11.2

PROJECT NO:

HWY:




COUNTY:

# BANDING


## GENERAL NOTES

1. Any sign over 3 feet in width shall use the V-Block banding method. See A5-10 standard plate.
2. Signs 3 feet or greater in height shall have three bracket bands installed. Signs less than 3 feet in height shall have two bracket bands installed.
3. Banding and assembly bracket shall be stainless steel. All bands shall be  $\frac{3}{4}$ " in width and 0.025" thickness.
4. ALL SIGN MOUNTING BOLTS AND WASHERS SHALL BE EITHER:
  - a. Hot dip or mechanically galvanized in accordance with ASTM Designation: A 153, Class D
  - b. Electro-galvanized in accordance with ASTM designation: B 633, Type III, SC 3

## SINGLE SIGN




## WASHER PLACEMENT



WASHERS (ALL POSTS) -  
 1-1/4" O.D. X  $\frac{3}{8}$ " I.D. X  $\frac{1}{16}$ " STEEL  
 1-1/4" O.D. X  $\frac{3}{8}$ " I.D. X .080 NYLON  
 FOR ALL TYPE H SIGNS



## "J" ASSEMBLY



## STANDARD SIGN SIGN BANDING DETAILS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED  
  
 for State Traffic Engineer  
 DATE 6/10/19 PLATE NO. A5-9.4



### GENERAL NOTES

1. WOOD 4"X6" POST MATERIAL SHALL CONFORM TO 507.2.2 OF THE WisDOT STANDARD SPECIFICATIONS
2. BLOCK BANDING AND CLIPS SHALL BE STAINLESS STEEL,  $3/4$ " WIDTH AND 0.025" THICKNESS
3. SIGNS 3' OR GREATER IN HEIGHT SHALL UTILIZE 3 BLOCK BANDS. SIGNS UNDER 3' IN HEIGHT SHALL UTILIZE 2 BLOCK BANDS
4. ACTUAL NUMBER OF FASTENERS PER SIGN VARIES WITH THE SIGN AREA, BUT NORMALLY THERE ARE TWO. FOR SIGNS GREATER THAN 9 S.F. 3 FASTENERS SHALL BE USED.
5. ALL SIGN MOUNTING BOLTS AND WASHERS SHALL BE EITHER:
  - a. Hot dip or mechanically galvanized in accordance with ASTM Designation: A 153, Class D
  - b. Electro-galvanized in accordance with ASTM Designation : B 633, TYPE III, SC 3
6. ALL BOLTS SHALL HAVE HEXAGONAL HEADS.
7. STEEL WASHERS SHALL BE  $1\frac{1}{4}$ " O.D. X  $3\frac{3}{8}$ " I.D. X  $\frac{1}{16}$ "
8. NYLON WASHERS SHALL BE  $1\frac{1}{4}$ " O.D. X  $3\frac{3}{8}$ " I.D. X .080 FOR TYPE H OR TYPE F FACE SIGN

＊ LAG BOLTS SHALL BE  $3/8$ " X  $2\frac{1}{2}$ "

7


7

BLOCK BANDING DETAIL  
( V-BLOCK OPTION )

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R Rauch*  
for State Traffic Engineer  
DATE 4/19/2022 PLATE NO. A5-10.3

7



### NOTES

1. Sign is Type II - Type F Reflective
2. Color:  
Background - Orange  
Message - Black
3. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
4. W01-4L is the same as W01-4R except the arrow is reversed along the vertical centerline.

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	36		$2\frac{1}{4}$	$\frac{5}{8}$	$\frac{3}{4}$	$5\frac{1}{4}$	4	$12\frac{3}{8}$	$7\frac{7}{8}$	$16\frac{7}{8}$	$10\frac{1}{2}$	$1\frac{5}{8}$	6	$4\frac{1}{2}$	1	$\frac{1}{2}$	$2\frac{1}{4}$	$7\frac{1}{2}$								9.0	
2S	48		3	$\frac{3}{4}$	1	7	$5\frac{1}{4}$	$16\frac{1}{2}$	$10\frac{1}{2}$	$22\frac{1}{2}$	14	$2\frac{1}{4}$	8	6	$1\frac{1}{4}$	$\frac{5}{8}$	3	10							16.0		
2M	48		3	$\frac{3}{4}$	1	7	$5\frac{1}{4}$	$16\frac{1}{2}$	$10\frac{1}{2}$	$22\frac{1}{2}$	14	$2\frac{1}{4}$	8	6	$1\frac{1}{4}$	$\frac{5}{8}$	3	10							16.0		
3	48		3	$\frac{3}{4}$	1	7	$5\frac{1}{4}$	$16\frac{1}{2}$	$10\frac{1}{2}$	$22\frac{1}{2}$	14	$2\frac{1}{4}$	8	6	$1\frac{1}{4}$	$\frac{5}{8}$	3	10							16.0		
4	48		3	$\frac{3}{4}$	1	7	$5\frac{1}{4}$	$16\frac{1}{2}$	$10\frac{1}{2}$	$22\frac{1}{2}$	14	$2\frac{1}{4}$	8	6	$1\frac{1}{4}$	$\frac{5}{8}$	3	10							16.0		
5	48		3	$\frac{3}{4}$	1	7	$5\frac{1}{4}$	$16\frac{1}{2}$	$10\frac{1}{2}$	$22\frac{1}{2}$	14	$2\frac{1}{4}$	8	6	$1\frac{1}{4}$	$\frac{5}{8}$	3	10							16.0		

PROJECT NO:

HWY:

COUNTY:

### STANDARD SIGN

W01-4

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

Matthew R Rauch

for State Traffic Engineer


DATE 1/24/2024 PLATE NO. W01-4.2

SHEET NO: 60

E

NOTES

1. Sign is Type II - Type F Reflective
2. Color:  
Background - Orange  
Message - Black
3. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.



W01-6

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	48	24	1 7/8	1/2	5/8		12	13 1/4	1	7 1/2	6 1/2	3 1/4	19 1/2	39												8.0	
2M	48	24	1 7/8	1/2	5/8		12	13 1/4	1	7 1/2	6 1/2	3 1/4	19 1/2	39												8.0	
3	60	30	1 7/8	1/2	5/8		15	16 1/4	1 1/4	9 1/4	8	4	24 3/8	48 3/4												12.5	
4	60	30	1 7/8	1/2	5/8		15	16 1/4	1 1/4	9 1/4	8	4	24 3/8	48 3/4												12.5	
5	60	30	1 7/8	1/2	5/8		15	16 1/4	1 1/4	9 1/4	8	4	24 3/8	48 3/4												12.5	

PROJECT NO:

HWY:

COUNTY:

STANDARD SIGN

W01-6

WISCONSIN DEPT OF TRANSPORTATION

APPROVED


*Matthew R. Rauch*  
for State Traffic Engineer

DATE 1/24/2024 PLATE NO. W01-6.2

SHEET NO:

E

7




W05-52L

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4															3.0	
2M	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4															3.0	
3	18	54	1 1/2			6	5 1/2	8 1/2	45°	6	6 9/16															6.75	
4																											
5																											

PROJECT NO:

HWY:

COUNTY:



W05-52R

## NOTES


1. Sign is Type II - Type F Reflective
2. Color:  
Background - Orange  
Message - Black
4. Alternate colors of stripes as shown.

STANDARD SIGN	
W05-52L & W05-52R	
WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<i>Matthew R Rauch</i> for State Traffic Engineer
DATE 3/13/2024 PLATE NO. W05-52.2	

SHEET NO. 62

E






PROFILE GRADE LINE - R USH 8

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	SUPER.	W. STRUCT. APP.	WEST ABUT.	EAST ABUT.	E. STRUCT. APP.	TOTALS
203.0250	REMOVING STRUCTURE OVER WATERWAY REMOVE DEBRIS B-54-408	EACH	—	—	—	—	—	1
206.1001	EXCAVATION FOR STRUCTURES BRIDGES B-54-131	EACH	—	—	—	—	—	1
210.1500	BACKFILL STRUCTURE TYPE A	TON	—	—	169	169	—	338
305.0120	BASE AGGREGATE DENSE 1 1/4-INCH	TON	—	145	—	—	145	290
312.0110	SELECT CRUSHED MATERIAL	TON	106	—	—	—	—	106
502.0100	CONCRETE MASONRY BRIDGES	CY	157.5	64.8	57.3	57.2	64.8	402
502.3200	PROTECTIVE SURFACE TREATMENT	SY	356	111	—	—	111	578
502.3210	PIGMENTED SURFACE SEALER	SY	72	20	—	—	20	112
503.0137	PRESTRESSED GIRDERS TYPE I 36W-INCH	LF	426	—	—	—	—	426
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB	—	—	3630	3630	—	7260
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	26800	11000	1740	1740	11000	52280
505.0800.S	BAR STEEL REINFORCEMENT HS STAINLESS STRUCTURES	LB	1640	—	—	—	—	1640
505.0908	BAR COUPLERS NO.8	EACH	—	12	—	—	12	24
506.2605	BEARING PADS ELASTOMERIC NON-LAMINATED	EACH	—	—	6	6	—	12
506.4000	STEEL DIAPHRAGMS B-54-131	EACH	5	—	—	—	—	5
511.200	TEMPORARY SHORING B-54-131	SF	—	—	—	—	—	1700
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	—	—	15	15	—	30
550.2106	PILING CIP CONCRETE 10 3/4 X 0.365-IN	LF	—	—	660	660	—	1320
606.0300	RIPRAP HEAVY	CY	—	—	265	280	—	545
612.0406	PIPE UNDERDRAIN WRAPPED 6-INCH	LF	—	—	90	90	—	180
614.0150	ANCHOR ASSEMBLIES FOR STEEL PLATE BEAM GUARD	EACH	—	2	—	—	2	4
645.0111	GEOTEXTILE TYPE DF SCHEDULE A	SY	—	—	47	47	—	94
645.0120	GEOTEXTILE TYPE HR	SY	—	—	405	435	—	840
	NON-BID ITEMS	SIZE	—	—	—	—	—	1/2", 3/4", 1/2"
	FILLER	SIZE	—	—	—	—	—	1/2", 3/4", 1/2"

MEASURED PERPENDICULAR TO TANGENT LINE




STATE PROJECT NUMBER  
1580-00-70  
SECTION  
PLAN

**RODENT SHIELD DETAIL**

\* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SHIELD, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".

THE RODENT SHIELD SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALLY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SHIELD TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SHIELD SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH STAINLESS STEEL SHEET METAL SCREWS.



**TYPICAL SECTION THRU ABUTMENT**

▲ BACKFILL PAY LIMITS. BACKFILL BEYOND BACKFILL PAY LIMITS SHALL BE INCIDENTAL TO EXCAVATION FOR STRUCTURES. LIMITS OF EXCAVATION SHALL BE DETERMINED BY THE CONTRACTOR.

PIPE UNDERDRAIN WRAPPED (6 INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN.

**GENERAL NOTES**

DRAWINGS SHALL NOT BE SCALED.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BEVEL EXPOSED EDGES OF CONCRETE 3/4" UNLESS OTHERWISE NOTED.

THE UPPER LIMITS OF "EXCAVATION FOR STRUCTURES B-54-131" SHALL BE THE EXISTING GROUNDLINE.

AT THE BACK FACE OF ABUTMENT ALL VOLUME WHICH CANNOT BE PLACED BEFORE ABUTMENT CONSTRUCTION AND IS NOT OCCUPIED BY THE NEW STRUCTURE SHALL BE BACKFILLED WITH STRUCTURE BACKFILL TYPE A. ALSO EXCLUDED IS THE "BASE AGGREGATE DENSE 1 1/4-INCH" AS DETAILED ON THE STRUCTURAL APPROACH SLAB SHEETS.

EXCAVATION BELOW THE ABUTMENT AND ABUTMENT BEDDING MATERIALS REQUIRES ENGINEER APPROVAL. GEOTEXTILE SHALL BE SET AT THE BOTTOM OF EXCAVATION AND EXTEND 2'-0" ABOVE BOTTOM OF ABUTMENT.

THE QUANTITY FOR BACKFILL STRUCTURE IS CALCULATED BASED ON THE DETAIL SHOWN IN THE PLANS.

ELASTOMERIC BEARING PADS NEED NOT BE INDIVIDUALLY MOLDED PROVIDED THE CUT EDGES ARE SMOOTH AND TRUE.

PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO THE ENTIRE EXPOSED TOP OF DECK AND APPROACH SLAB SURFACES AND TO THE VERTICAL AND HORIZONTAL SURFACES OF THE PAVING NOTCHES AT ABUTMENT DIAPHRAGMS.


PIGMENTED SURFACE SEALER TO BE APPLIED TO THE FRONT FACE AND THE TOP OF THE PARAPETS, INCLUDING PARAPETS ON APPROACH SLABS.

THE SLOPE OF THE FILL IN FRONT OF THE ABUTMENTS SHALL BE COVERED WITH HEAVY RIPRAP AND GEOTEXTILE TYPE "HR" TO THE EXTENT SHOWN ON SHEET 1 AND THE ABUTMENT DETAILS.


THE HAUNCH CONCRETE QUANTITY IS BASED ON THE AVERAGE HAUNCH SHOWN ON THE "36W PRESTRESSED GIRDERS DETAILS 2" SHEET.

EXCAVATION REQUIRED TO REMOVE EXISTING STRUCTURE AND SHAPE STREAMBED IS INCLUDED IN THE BID ITEM "EXCAVATION FOR STRUCTURES B-54-131".

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-54-131			
DRAWN BY	PLANS CK'D.	DBM	
CROSS SECTION & QUANTITIES		SHEET 2	
		64	

**STAGE 1 REMOVAL**


LOOKING EAST

**NOTE**

STAGE 2 REMOVAL NOT DEPICTED. REMOVAL CONSISTS OF EXCAVATING AND REMOVING REMAINDER OF EXISTING STRUCTURE PRIOR TO STAGE 2 CONSTRUCTION

**STAGE 1 CONSTRUCTION**

LOOKING EAST



■ = MEASURED PERPENDICULAR TO TANGENT LINE

● = TEMPORARY TRAFFIC BARRIER PAID FOR UNDER ROADWAY BID ITEMS, SEE ROADWAY PLANS FOR MORE INFORMATION

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-54-131			
DRAWN BY	EJV	PLANS CK'D.	DMB
CONSTRUCTION STAGING		SHEET 3	
		65	


STATE PROJECT NUMBER

1580-00-70

MATERIAL SYMBOLS

ASPHALT	TOPSOIL	PEAT
CONCRETE	FILL	GRAVEL
SAND	CLAY	SILT
BOULDERS OR COBBLES	LIMESTONE	BEDROCK (UNKNOWN)
SHALE	SANDSTONE	IGNEOUS/META

LEGEND OF BORING



(1) UNCONFINED STRENGTH, AS DETERMINED BY A POCKET PENETROMETER (TSF)

(2) UNLESS OTHERWISE SPECIFIED, THE SPT 'N' VALUE IS BASED ON AASHTO T-206, STANDARD PENETRATION TEST. THE SPT 'N' VALUE PRESENTED HAS NOT BEEN CORRECTED FOR OVERBURDEN PRESSURE OR HAMMER EFFICIENCY.

GROUND WATER ELEVATION

▽ AT TIME OF DRILLING

▼ END OF DRILLING

■ AFTER DRILLING

## ABBREVIATIONS

F-FINE M-MEDIUM C-COARSE ST-SHELBY TUBE

SUBSURFACE EXPLORATION FOR FOUNDATION DESIGN AND BIDDERS INFORMATION

BORINGS WERE COMPLETED AT POINTS APPROXIMATELY AS INDICATED ON THIS DRAWING TO OBTAIN INFORMATION CONCERNING THE CHARACTER OF SUBSURFACE MATERIALS FOUND AT THE SITE. BECAUSE THE INVESTIGATED DEPTHS ARE LIMITED AND THE AREA OF THE BORINGS IS VERY SMALL IN RELATION TO THE ENTIRE SITE, THE WISCONSIN DEPARTMENT OF TRANSPORTATION DOES NOT WARRANT SIMILAR SUBSURFACE CONDITIONS BELOW, BETWEEN, OR BEYOND THESE BORINGS. VARIATIONS IN SOIL CONDITIONS SHOULD BE EXPECTED AND FLUCTUATIONS IN GROUNDWATER LEVELS MAY OCCUR.

NO. DATE REVISION BY


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION  
STRUCTURES DESIGN SECTION

STRUCTURE B-54-131

DRAWN BY TLP PLANS C.R.D. DMB

SUBSURFACE EXPLORATION SHEET 4  
66

BORING #	DATE COMPLETED	NORTHING (Y)	EASTING (X)
1	7/31/2019	552403	744703
2	8/6/2019	552414	744844
BORINGS COMPLETED BY: WISDOT			
REPORT COMPLETED BY: WISDOT			
ALL COORDINATES REFERENCED TO WCCS NAD 83(91) RUSK COUNTY			
COORDINATES COLLECTED USING NON-SURVEY GRADE EQUIPMENT			



8

8


SCALE 15.00'




STATE PROJECT NUMBER

1580-00-70


NOTE: THE FIRST OR FIRST TWO DIGITS OF THE  
BAR MARK SIGNIFIES THE BAR SIZE



## WING 1 ELEVATION




WING 1 SECTION A-A




A509, A412, A519, A520, A528


BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
A501		61	15'-8"	X		BODY - STIRRUPS
A402		10	28'-0"	X		PILES - 1 PER BODY PILE
A403		20	2'-3"			PILES - 2 PER BODY PILE
A704		7	15'-0"			BODY - HORIZONTAL - B.F. - STAGE 2
A605		7	12'-5"			BODY - HORIZONTAL - B.F. - STAGE 2
A806		7	28'-5"	X		BODY - HORIZONTAL - B.F. - STAGE 1
A607		12	24'-7"			BODY - HORIZONTAL - F.F. - STAGE 2
A608		12	27'-5"			BODY - HORIZONTAL - F.F. - STAGE 1
A509		35	7'-11"	X		BODY - VERT. - OVER GIRDS. 3-6
A410		5	10'-2"			BODY - HORIZ. - OVER GIRDS. 3, STAGE 2
A411		10	26'-5"			BODY - HORIZ. - OVER GIRDS. 4-6, STAGE 1
A412		20	4'-5"	X		BODY - VERTICAL - BTWN BEAM SEATS
A413		10	6'-6"			BODY - HORIZONTAL - BTWN BEAM SEATS
A515	X	10	18'-6"	X		WING 1 - STIRRUPS - LOWER WING
A716	X	9	12'-1"			WING 1 - HORIZONTAL - B.F. - LOWER WING
A517	X	7	12'-8"			WING 1 - HORIZONTAL - F.F. - LOWER WING
A418	X	4	6'-0"			WING 1 - BODY VERTICAL ENDS
A519	X	9	11'-4"	X		WING 1 - VERTICAL - UPPER WING
A520	X	13	12'-8"	X		WING 1 - VERTICAL - UPPER WING
A421	X	4	7'-9"			WING 1 - HORIZONTAL - UPPER WING
A422	X	9	15'-8"			WING 1 - HORIZONTAL - UPPER WING
A623	X	2	15'-8"			WING 1 - HORIZONTAL - UPPER WING TOP
A524	X	13	15'-8"	X		WING 2 - STIRRUPS - LOWER WING
A525	X	9	13'-7"			WING 2 - HORIZONTAL - B.F. - LOWER WING
A526	X	6	15'-1"			WING 2 - HORIZONTAL - F.F. - LOWER WING
A427	X	4	4'-7"			WING 2 - BODY - VERTICAL ENDS
A528	X	17	12'-4"	X		WING 2 - VERTICAL - UPPER WING
A429	X	9	11'-8"			WING 2 - HORIZONTAL - UPPER WING
A630	X	2	11'-8"			WING 2 - HORIZONTAL - UPPER WING TOP




8




## WING 2 ELEVATION



WING 2 SECTION B-B



## PILE DETAILS



## **END PLATE DETAIL**

(A03) OPTIONAL CONST. JOINT: KEYWAY FORMED BY BEVELED 2 x 6. (18" RMW @ B.F. & 3/4" "V" GROOVE @ F.F. IF JOINT IS USED).

(A09) SUPPORT ABUTMENT ON 10 3/4" DIA. X 0.365"  
CIP CONCRETE PILING, ESTIMATED 55'-0"  
LONG WITH A REQUIRED DRIVING RESISTANCE  
OF 150 TONS PER PILE


OF 150 TONS PER PILE.

(A15) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.



(A17) 1/2" FILLER (INCLUDED IN WING LENGTH): SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW CUTTER LINE AT INSIDE FACE

**A19** 18" (RMW) RUBBERIZED MEMBRANE WATERPROOFING



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION <b>STRUCTURES DESIGN SECTION</b>			
<b>STRUCTURE B-54-131</b>			
DRAWN BY		PLANS EJV	CK'D. <b>DMB</b>
<b>WEST ABUTMENT DETAILS</b>		SHEET 6	
		68	



**ELEVATION**  
LOOKING EAST @ F.F.  
ADJUST STIRRUP SPACING TO MISS PILES

**PLAN****PILE PLAN**

STEEL TROWEL TOP SURFACE OF ABUTMENT. PLACE MULTIPLE LAYERS OF POLYETHYLENE SHEETS OVER ENTIRE ABUTMENT TOP BEFORE PLACING BEARING PADS. TOTAL THICKNESS OF SHEETS SHALL BE AT LEAST 0.03".

**SECTION THRU BODY****SECTION****RODENT SHIELD DETAIL**

\* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SHIELD, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".

THE RODENT SHIELD SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALLY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SHIELD TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SHIELD SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH STAINLESS STEEL SHEET METAL SCREWS.

▲ DIMENSIONS MEASURED ALONG C BEARING.

○ INDICATES GIRDER NUMBER.

★ MEASURED AT F.F. ABUT.

A04 VERT. CONST. JOINT: KEYWAY FORMED BY A BEVELED 2 X 8, 3/4" "V" GROOVE @ THE FRONT FACE AND 18" RMW @ BACKFACE.

A09 SUPPORT ABUTMENT ON 10 3/4" DIA. X 0.365" CIP CONCRETE PILING, ESTIMATED 55'-0" LONG WITH A REQUIRED DRIVING RESISTANCE OF 150 TONS PER PILE.

A15 PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.

A17 1/2" FILLER (INCLUDED IN WING LENGTH): SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER, (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

A18 3/4" CORK FILLER UP VERT. BEAM SEAT FACES THAT RUN PARALLEL WITH GIRDER.


A19 18" (RMW) RUBBERIZED MEMBRANE WATERPROOFING SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-54-131			
DRAWN BY	EJV	PLANS CK'D.	DMB
EAST ABUTMENT		SHEET 7	


NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE

## BILL OF BARS



BAR MARK	COA/	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
B501		61	15'-8"	X		BODY - STIRRUPS
B402		10	28'-0"	X		PILES - 1 PER BODY PILE
B403		20	2'-3"			PILES - 2 PER BODY PILE
B704		7	15'-0"			BODY - HORIZONTAL - B.F. - STAGE 2
B605		7	12'-6"			BODY - HORIZONTAL - B.F. - STAGE 2
B806		7	28'-5"	X		BODY - HORIZONTAL - B.F. - STAGE 1
B607		12	24'-7"			BODY - HORIZONTAL - F.F. - STAGE 2
B608		12	27'-5"			BODY - HORIZONTAL - F.F. - STAGE 1
B509		35	7'-11"	X		BODY - VERT. - OVER GIRDS. 3-6
B410		5	10'-3"			BODY - HORIZ. - OVER GIRDS. 3, STAGE 2
B411		10	26'-5"			BODY - HORIZ. - OVER GIRDS. 4-6, STAGE 1
B412		20	4'-5"	X		BODY - VERTICAL - BTWN BEAM SEATS
B413		10	6'-6"			BODY - HORIZONTAL - BTWN BEAM SEATS
B515	X	10	18'-6"	X		WING 4 - STIRRUPS - LOWER WING
B716	X	9	12'-1"			WING 4 - HORIZONTAL - B.F. - LOWER WING
B517	X	7	12'-8"			WING 4 - HORIZONTAL F.F. - LOWER WING
B418	X	4	6'-0"			WING 4 - BODY VERTICAL ENDS
B519	X	9	11'-4"	X		WING 4 - VERTICAL - UPPER WING
B520	X	13	12'-8"	X		WING 4 - VERTICAL - UPPER WING
B421	X	4	7'-9"			WING 4 - HORIZONTAL - UPPER WING
B422	X	9	15'-8"			WING 4 - HORIZONTAL - UPPER WING
B623	X	2	15'-8"			WING 4 - HORIZONTAL - UPPER WING TOP
B524	X	13	15'-8"	X		WING 3 - STIRRUPS - LOWER WING
B525	X	9	13'-7"			WING 3 - HORIZONTAL - B.F. - LOWER WING
B526	X	6	15'-1"			WING 3 - HORIZONTAL - F.F. - LOWER WING
B427	X	4	4'-7"			WING 3 - BODY - VERTICAL ENDS
B528	X	17	12'-4"	X		WING 3 - VERTICAL - UPPER WING
B429	X	9	11'-8"			WING 3 - HORIZONTAL - UPPER WING
B630	X	2	11'-8"			WING 3 - HORIZONTAL - UPPER WING TOP




WING 4 ELEVATION




WING 4 SECTION A-A




B509, B412, B519, B520, B528




WING 3 ELEVATION




WING 3 SECTION B-B



C.I.P. PIPE PILE DETAIL



PILE DETAILS



END PLATE DETAIL

(A03) OPTIONAL CONST. JOINT: KEYWAY FORMED BY BEVELED 2 x 6. (18" RMW @ B.F. & 3/4" "V" GROOVE @ F.F. IF JOINT IS USED).

(A09) SUPPORT ABUTMENT ON 10 3/4" DIA. X 0.365" CIP CONCRETE PILING, ESTIMATED 55'-0" LONG WITH A REQUIRED DRIVING RESISTANCE OF 150 TONS PER PILE.

(A15) PIPE UNDERDRAIN WRAPPED (6-INCH), SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.

(A17) 1/2" FILLER (INCLUDED IN WING LENGTH): SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE), EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

(A19) 18" (RMW) RUBBERIZED MEMBRANE WATERPROOFING SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			

STRUCTURE B-54-131			
DRAWN BY	EJV	PLANS CK'D.	DMB

EAST ABUTMENT DETAILS		SHEET 8
		70

## NOTES

TOP OF GIRDER TO BE ROUGH FLOATED AND BROOMED TRANSVERSELY, EXCEPT THE OUTSIDE 8" OF GIRDER, WHICH SHALL RECEIVE A SMOOTH FINISH. AN APPROVED CONCRETE SEALER SHALL BE APPLIED TO ALL SMOOTH SURFACES INCLUDING THE OUTSIDE 8" OF THE TOP FLANGE.

DO NOT APPLY CONCRETE SEALER OR EPOXY TO SURFACES RECEIVING APPLICATION OF CONCRETE STAINING.

THE GIRDER SHALL BE PROVIDED WITH A SUITABLE LIFTING DEVICE FOR HANDLING AND ERECTING THE GIRDER. SEE SECT. 503.3.3 OF STANDARD SPECIFICATIONS FOR GUIDANCE.

STRANDS SHALL BE FLUSH WITH END OF GIRDER. FOR GIRDER ENDS EMBEDDED COMPLETELY IN CONCRETE, END OF STRANDS SHALL BE COATED WITH NON-BITUMINOUS JOINT SEALER. FOR GIRDER ENDS THAT ARE FINALLY EXPOSED, COAT THE GIRDER ENDS, EXPOSED STRAND ENDS AND ALL NON-BONDING SURFACES WITHIN 2 FEET OF THE GIRDER ENDS WITH A NON-PIGMENTED EPOXY CONFORMING TO AASHTO M-235 TYPE III, GRADE 2, CLASS B OR C. THE EPOXY SHALL BE APPLIED AT LEAST 3 DAYS AFTER MOIST CURING HAS CEASED AND PRIOR TO THE APPLICATION OF THE SEALER.


ALL GIRDER SHALL BE CAST FULL LENGTH AS SHOWN.

SPACING SHOWN FOR #4 STIRRUPS IS FOR GRADE 60 REINFORCEMENT.

AN EQUIVALENT OF WELDED WIRE FABRIC (WWF) ASTM A1064 MAY BE SUBSTITUTED FOR THE STIRRUP REINFORCEMENT SHOWN. UPON ACCEPTANCE OF THE STRUCTURES MAINTENANCE SECTION, IF USED, WWF SUBSTITUTION DETAILS SHALL BE SUBMITTED ELECTRONICALLY TO THE WISDOT FABRICATION LIBRARY AND ACCEPTED PRIOR TO SHOP DRAWING SUBMITTAL.

PRESTRESSING STRANDS SHALL BE (0.6" DIA.)-7 WIRE LOW-RELAXATION STRANDS WITH AN ULTIMATE STRENGTH OF 270,000 PSI.

FOR DIAPHRAGM INSERT & CONNECTION DETAILS SEE "STEEL DIAPHRAGM" SHEET.




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-54-131			
	DRAWN BY EJV	PLANS CK'D. DMB	
36W" PRESTRESSED GIRDER DETAILS 1		SHEET 9	
			71

\* MINIMUM CYLINDER STRENGTH OF CONCRETE @ TIME OF TRANSFER OF PRESTRESS FORCE.


## GIRDER DATA

SPAN	GIRDER	GIRDER LENGTH "L" (FEET)	DEAD LOAD DEFL. (IN.)									CONC. STRGTH. $f'_c$ (P.S.I.)	DRAPE PATTERN				UNDRAPE PATTERN							
			1/10	2/10	3/10	4/10	5/10	6/10	7/10	8/10	9/10		1ST 1/3 OF GIRDER	MID 1/3 OF GIRDER	END 1/3 OF GIRDER	DIA. OF STRAND (IN.)	TOTAL NO. OF STRANDS	$f'_ci$ (P.S.I.) *	"A" MIN.	"B" MAX.	"C"	TOTAL NO. OF STRANDS	$f'_ci$ (P.S.I.) *	
1	1-6	71'-0"	0.3	0.5	0.7	0.8	0.8	0.8	0.7	0.5	0.3	8,000	7	7	7	0.6	22	6,400	32	11	14	4	--	--




STANDARD ARRANGEMENTS TO RAISE CENTER OF GRAVITY  
TO AVOID DRAPING OF STRANDS

0.6" DIA. STRANDS



ARRANGEMENT AT  $\frac{1}{4}$  SPAN - FOR GIRDERS WITH DRAPED STRANDS


0.6" DIA. STRANDS



\* THE THEORETICAL INITIAL CAMBER VALUE AT THE TIME OF STRAND RELEASE AT MIDSPAN MULTIPLIED BY A FACTOR OF 1.4 TO ACCOUNT FOR CAMBER GROWTH FROM THE TIME OF STRAND RELEASE TO JOBSITE PLACEMENT.

SPAN	CAMBER (IN.) *
1	1.9"

THESE VALUES ARE NOT TO BE USED IN DETERMINING 'T'.  
USE ACTUAL GIRDER SHOTS.  
THESE VALUES ARE FOR INFORMATIONAL PURPOSES ONLY.




DECK HAUNCH DETAIL

IF  $1\frac{1}{4}$ " MINIMUM HAUNCH HEIGHT AT EDGE OF GIRDER CANNOT BE MAINTAINED, THE GRADE LINE MAY BE REVISED BY THE ENGINEER AT THE OPTION OF THE CONTRACTOR. THE PLAN DECK THICKNESS SHALL BE HELD. NOTIFY THE STRUCTURES SECTION IF THE GRADE LINE IS RAISED FROM THE PLAN PROFILE BY MORE THAN  $\frac{1}{2}$ " OR, \*\* IF 3" MINIMUM DECK EMBEDMENT OF TIE BAR CANNOT BE OBTAINED.


TO DETERMINE 'T', ELEV. OF TOP OF GIR.'S. AT  $\frac{1}{4}$  OF SUBSTRUCTURE UNITS & AT 1/10 POINTS OF EACH SPAN SHALL BE TAKEN. THEN FOLLOW THIS PROCESS:

TOP OF DECK ELEV. AT FINAL GRADE  
- TOP OF GIRDER ELEVATION  
+ DEAD LOAD DEFLECTION  
- DECK THICKNESS  
= HAUNCH HEIGHT 'T'

NOTE: AN AVERAGE HAUNCH ('T') OF 3.1 INCHES WAS USED IN THE QUANTITY "CONCRETE MASONRY BRIDGES".




TYP. STRAND PATTERN



DEAD LOAD DEFLECTION DIAGRAM


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-54-131			
DRAWN BY EJV PLANS CK'D. DMB			
36W" PRESTRESSED GIRDERS DETAILS 2	SHEET 10		
	72		



EXTERIOR GIRDER

INTERIOR GIRDER


## PART TRANSVERSE SECTION AT DIAPHRAGM



DETAIL C



DETAIL B

8




SECTION A-A

(FOR EXTERIOR ATTACHMENT)



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
STRUCTURE B-54-131			
DRAWN BY	EJV	PLANS CK'D.	DMB
STEEL DIAPHRAGM	SHEET 11		
	73		



NOTE: THE FIRST OR FIRST TWO DIGITS OF THE  
BAR MARK SIGNIFIES THE BAR SIZE


## BILL OF BARS

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
S501	X	108	23'-3"		DECK TRANS. - BOTTOM	- STAGE 2
S502	X	108	26'-0"		DECK TRANS. - BOTTOM	- STAGE 1
S503	X	109	23'-3"		DECK TRANS. - TOP	- STAGE 2
S504	X	109	26'-0"		DECK TRANS. - TOP	- STAGE 1
S405	X	142	37'-3"		DECK LONG. BOTTOM	
S406	X	140	37'-3"		DECK LONG. TOP	
S507	X	202	5'-3"	X	DECK TRANS. - TOP EDGE	
S508	X	218	4'-5"	X	42SS PARAPET	- VERT.
S509	X	218	6'-8"	X	42SS PARAPET	- VERT.
S510	X	32	37'-7"		42SS PARAPET	- HORIZ.
S411	X	50	3'-3"	X	ABUT. DIAPH. - VERT.	- BTWN GIR.
S512	X	24	10'-0"	X	ABUT. DIAPH. AT GIRDS	- STIRRUPS
S513	X	92	11'-6"	X	ABUT. DIAPH. - STIRRUP	
S514	X	92	6'-3"	X	ABUT. DIAPH. - VERT.	- BTWN GIR.
S619	X	4	5'-6"		ABUT. DIAPH. - BTWN GIR.	HORIZ. STAGE 1
S620	X	4	3'-5"		ABUT. DIAPH. - BTWN GIR.	HORIZ. STAGE 2
S421	X	20	4'-2"		ABUT. DIAPH. - BTWN GIR.	HORIZONTAL
S622	X	10	5'-2"		ABUT. DIAPH. - BTWN GIR.	HORIZONTAL
S623	X	32	4'-7"		ABUT. DIAPH. - BTWN GIR.	HORIZONTAL
S624	X	10	26'-7"		ABUT. DIAPH. - HORIZ.	STAGE 1
S625	X	10	24'-6"		ABUT. DIAPH. - HORIZ.	STAGE 2
S526	X	24	6'-0"		ABUT. DIAPH. - HORIZ.	- THRU GIR.
S427	X	8	3'-8"		ABUT. DIAPH. - VERT.	- EXTERIOR WING
S528	X	8	14'-4"	X	ABUT. DIAPH. STIRRUP	- EXTERIOR WING
S629	X	4	8'-10"	X	ABUT. DIAPH. - EXTERIOR WING	HORIZ. - BOT.
S630	X	8	10'-4"	X	ABUT. DIAPH. - EXTERIOR WING	HORIZ.
S631	X	4	7'-1"	X	ABUT. DIAPH. - EXTERIOR WING	HORIZ. - TOP


SS901		96	5'-0"	X	ABUT.DIAPH./APPROACH SLAB TIE
					STAINLESS STEEL

## ABUTMENT DIAPHRAGM PLAN DETAIL


EAST ABUTMENT SHOWN. WEST  
ABUTMENT SIMILAR




S411, S514, S629, S630




S509



08




S507




## BEARING PAD DETAIL

## TOP OF DECK ELEVATIONS




	CL	BRG. W. ABUT.	1/10	2/10	3/10	4/10	5/10	6/10	7/10	8/10	9/10	CL	BRG. E. ABUT.
N. EOD/GUTTER LINE	1122.75	1122.71	1122.67	1122.63	1122.59	1122.55	1122.51	1122.47	1122.43	1122.40	1122.36		
GIRDER 1	1122.82	1122.78	1122.74	1122.70	1122.66	1122.63	1122.59	1122.55	1122.51	1122.47	1122.44		
GIRDER 2	1123.12	1123.08	1123.04	1123.00	1122.96	1122.92	1122.88	1122.84	1122.81	1122.77	1122.73		
GIRDER 3	1123.42	1123.37	1123.33	1123.30	1123.26	1123.22	1123.18	1123.14	1123.10	1123.07	1123.03		
TANGENT/CONST. JT.	1123.57	1123.53	1123.49	1123.45	1123.41	1123.37	1123.33	1123.29	1123.25	1123.22	1123.18		
GIRDER 4	1123.71	1123.67	1123.63	1123.59	1123.55	1123.51	1123.47	1123.44	1123.40	1123.36	1123.33		
GIRDER 5	1124.01	1123.97	1123.93	1123.89	1123.85	1123.81	1123.77	1123.73	1123.70	1123.66	1123.62		
GIRDER 6	1124.30	1124.26	1124.22	1124.18	1124.14	1124.11	1124.07	1124.03	1123.99	1123.96	1123.92		
S. EOD/GUTTER LINE	1124.37	1124.34	1124.30	1124.26	1124.22	1124.18	1124.14	1124.11	1124.07	1124.03	1123.99		




## PART LONGIT. SECTION



S512, S513, S528




NOTE: THE FIRST OR FIRST TWO DIGITS OF THE  
BAR MARK SIGNIFIES THE BAR SIZE



## PLAN


## BAR COUPLER DETAIL

BAR LENGTH HAS BEEN COMPUTED TO C OF CONSTRUCTION JOINT AND SHALL BE MODIFIED TO BAR COUPLER MANUFACTURER RECOMMENDATIONS. BAR COUPLERS REQUIRED ON STAGE 1 SIDE OF CONSTRUCTION JOINT.




## BILL OF BARS

BAR MARK	COAT	NO. REQ'D.		LENGTH	BENT	BAR SERIES	LOCATION
		WEST	EAST				
T501	X	46	46	12'-2"	X		APPROACH SLAB FOOTING - STIRRUP
T502	X	4	4	8'-8"	X		APPROACH SLAB FOOTING - STIRRUP - END
T803	X	4	4	21'-5"			APPROACH SLAB FOOTING - TRANS. - END - STAGE 1
T804	X	4	4	22'-3"			APPROACH SLAB FOOTING - TRANS. - END - STAGE 2
T805	X	8	8	22'-8"			APPROACH SLAB FOOTING - TRANS. STAGE 1
T806	X	8	8	23'-6"			APPROACH SLAB FOOTING - TRANS. STAGE 2
T507	X	40	40	4'-1"	X		APPROACH SLAB - TRANS. - TOP - WING
T508	X	42	42	26'-1"			APPROACH SLAB - TRANS. STAGE 1
T509	X	42	42	23'-6"			APPROACH SLAB - TRANS. STAGE 2
T810	X	78	78	21'-4"	X		APPROACH SLAB - LONG. - BOTTOM
T511	X	48	48	19'-8"			APPROACH SLAB - LONG. - TOP



## SECTION C-C

(LOOKING EAST)



SECTION THRU APPROACH SLAB

- APPLY PROTECTIVE SURFACE TREATMENT TO PAVING NOTCH SURFACES PRIOR TO POURING STRUCTURAL APPROACH SLAB.
- MEASURED NORMAL TO ABUTMENT
- ▲ SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NONSUSTAINING GRAY NON-BITUMINOUS JOINT SEALER (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE)
- SLOPE TO DRAIN

(TC2) STEEL TROWEL TOP SURFACE OF FOOTING AND PLACE MULTIPLE LAYERS (0.03" MIN. TOTAL THK.) OF POLYETHYLENE SHEETS OVER THE ENTIRE LENGTH OF THE FOOTING.

(TC3) PLACE MULTIPLE LAYERS (0.03" MIN. TOTAL THK.) OF POLYETHYLENE SHEETS OVER THE ENTIRE TOP OF SUBGRADE BENEATH SLAB

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DESIGN SECTION			
<b>STRUCTURE B-54-131</b>			
		DRAWN BY	PLANS CKD. <b>DMB</b>
<b>STRUCTURAL APPROACH SLAB</b>		SHEET 14  76	

BILL OF BARS

## FOR ABUTMENT PARAPETS


BAR MARK	COAT	WEST ABUT.	EAST ABUT.	LENGTH	BENT	BAR SERIES	LOCATION
R501	X	34	34	4'-5"	X		PARAPET VERT.
R502	X	34	34	6'-8"	X		PARAPET VERT.
R503	X	24	24	2'-9"	X		PARAPET VERT.
R504	X	34	34	4'-4"	X		PARAPET VERT.
R505	X	10	10	6'-5"	X		PARAPET VERT.
R506	X	12	12	6'-6"	X		PARAPET VERT.
R507	X	2	2	19'-6"	X		PARAPET HORIZ.
R508	X	10	10	19'-6"			PARAPET HORIZ.
R509	X	12	12	5'-5"	X	▲	PARAPET VERT.
R510	X	4	4	19'-6"	X		PARAPET HORIZ.

⚠ LENGTH SHOWN FOR BAR IS AN AVERAGE LENGTH AND SHOULD ONLY BE USED FOR BAR WEIGHT CALCULATIONS. SEE BAR SERIES TABLE FOR ACTUAL LENGTHS.


## PARAPET END TREATMENT DETAIL

LOOKING AT INSIDE FACE OF PARAPET



**SECTION A-A**





**SECTION B-B**



## SECTION C-C



**SECTION THRU PARAPET ON DECK**




## INSIDE ELEVATION

NW CORNER SHOWN, OTHERS SIMILAR  
WING & STRUCTURAL APPROACH SLAB FOOTING NOT SHOWN FOR CLARITY




✓ THREADED INSERTS FOR  $\frac{7}{8}$ " DIA. X 2" LONG GALVANIZED HEX HEAD CAP SCREWS CAP SCREWS TO BE THREADED A MIN



#### DETAIL OF ANCHOR ASSEMBLY

NOTE: HEX HEAD CAP SCREWS & WASHERS TO BE GALVANIZED  
IN ACCORDANCE WITH AASHTO M232 CLASS C.

ASSEMBLY SHALL BE BID ITEM "ANCHOR ASSEMBLIES FOR STEEL PLATE BEAM GUARD", EACH.



USH 8

STATION	AREA (SF)		INCREMENTAL VOL (CY) (UNADJUSTED)		CUMULATIVE VOL (CY)		
	CUT	FILL	CUT	FILL	CUT 1.00	EXPANDED FILL 1.30	MASS ORDINATE
672+50	68.42	11.05	0.00	0.00	0.00	0.00	0.00
673+00	115.04	14.31	170.00	23.00	170.00	29.90	140.10
673+16.87	128.69	14.48	76.00	9.00	246.00	41.60	204.40
673+50	89.38	18.49	134.00	20.00	380.00	67.60	312.40
673+75.07	126.23	22.04	100.00	19.00	480.00	92.30	387.70
674+00.07	123.87	21.74	116.00	20.00	596.00	118.30	477.70
674+25.07	77.36	21.77	93.00	20.00	689.00	144.30	544.70
674+36.87	76.06	57.31	34.00	17.00	723.00	166.40	556.60
674+61.87	74.15	114.96	70.00	80.00	793.00	270.40	522.60
674+86.87	75.89	67.82	69.00	85.00	862.00	380.90	481.10
675+00	71.45	65.78	36.00	32.00	898.00	422.50	475.50
675+27.82	66.58	0.00	71.00	34.00	969.00	466.70	502.30
675+83.87	0.00	0.00	69.00	0.00	1038.00	466.70	571.30
STRUCTURE							
676+40.32	62.27	0.00	0.00	1335.00	466.70	571.30	
676+50	67.30	9.07	23.00	2.00	1061.00	469.30	591.70
676+80.57	64.26	29.92	74.00	22.00	1135.00	497.90	637.10
677+00	60.78	131.37	45.00	58.00	1180.00	573.30	606.70
677+05.57	60.23	181.15	12.00	32.00	1192.00	614.90	577.10
677+30.57	61.42	293.93	56.00	220.00	1248.00	900.90	347.10
677+43.77	61.50	276.44	30.00	139.00	1278.00	1081.60	196.40
677+50	61.50	256.79	14.00	62.00	1292.00	1162.20	129.80
677+68.77	61.33	233.04	43.00	170.00	1335.00	1383.20	-48.20
677+93.77	61.02	334.21	57.00	263.00	1392.00	1725.10	-333.10
678+00	61.00	327.36	14.00	76.00	1406.00	1823.90	-417.90
678+50.57	60.51	253.20	114.00	544.00	1520.00	2531.10	-1011.10
679+00	59.45	205.89	110.00	420.00	1630.00	3077.10	-1447.10


USH 8 TEMPORARY


STATION	AREA (SF)		INCREMENTAL VOL (CY) (UNADJUSTED)		CUMULATIVE VOL (CY)		
	CUT	FILL	CUT	FILL	CUT 1.00	EXPANDED FILL 1.30	MASS ORDINATE
672+00	14.26	0.45	0.00	0.00	0.00	0.00	0.00
672+50	13.32	4.20	26.00	4.00	26.00	5.20	20.80
673+00	11.86	6.10	23.00	10.00	49.00	18.20	30.80
673+50	12.39	7.09	22.00	12.00	71.00	33.80	37.20
674+00	13.93	3.06	24.00	9.00	95.00	45.50	49.50
674+50	15.60	0.89	27.00	4.00	122.00	50.70	71.30
675+00	13.88	50.44	27.00	48.00	149.00	113.10	35.90
675+50	13.47	36.92	25.00	81.00	174.00	218.40	-44.40
675+83.87	13.06	9.35	17.00	29.00	191.00	256.10	-65.10
676+00	13.07	12.51	8.00	7.00	199.00	265.20	-66.20
676+50	12.36	13.91	24.00	24.00	223.00	296.40	-73.40
677+00	10.42	35.36	21.00	46.00	244.00	356.20	-112.20
677+50	11.26	53.54	20.00	82.00	264.00	462.80	-198.80
678+00	11.37	58.34	21.00	104.00	285.00	598.00	-313.00
678+50	10.71	57.35	20.00	107.00	305.00	737.10	-432.10
679+00	10.46	59.57	20.00	108.00	325.00	877.50	-552.50
679+50	9.99	56.44	19.00	107.00	344.00	1016.60	-672.60
680+00	9.13	50.04	18.00	99.00	362.00	1145.30	-783.30
680+50	7.63	60.90	16.00	103.00	378.00	1279.20	-901.20


USH 8 DRWY


STATION	AREA (SF)		INCREMENTAL VOL (CY) (UNADJUSTED)		CUMULATIVE VOL (CY)		
	CUT	FILL	CUT	FILL	CUT 1.00	EXPANDED FILL 1.30	MASS ORDINATE
18+50	9.22	8.10	0.00	0.00	0.00	0.00	0.00
18+75	12.22	30.71	10.00	18.00	10.00	23.40	-13.40
19+00	3.45	135.36	7.00	77.00	17.00	123.50	-106.50
19+25	0.00	461.67	2.00	276.00	19.00	482.30	-463.30
19+50	0.00	556.94	0.00	472.00	19.00	1095.90	-1076.90
19+75	0.00	88.99	0.00	299.00	19.00	1484.60	-1465.60


NOTE:  
MASS ORDINATE DOES NOT INCLUDE  
FILL MATERIAL REQUIRED FOR  
UNUSABLE PAVEMENT MATERIAL.  
SEE EARTHWORK SUMMARY.























9

9

PROJECT NO: 1580-00-70

HWY: USH 8

COUNTY: RUSK

CROSS SECTIONS: DRWY

SHEET

E

FILE NAME : V:\TRANS-EC\410764 USH 8 LITTLE SOFT MAPLE CREEK BRIDGE\C3D\DESIGN\CORRIDORS\CORRIDOR-USH8-DRWY.DWG  
LAYOUT NAME - 0901-(1)

PLOT DATE : 2/27/2020 4:08 PM



PLOT BY : RESHESKE, CARRIE

PLOT NAME :

PLOT SCALE : 1 IN:20 FT HORZ. / 1 IN:20 FT VERT.

WISDOT/CADD'S SHEET 49

86



9

9

PROJECT NO: 1580-00-70

HWY: USH 8

COUNTY: RUSK

CROSS SECTIONS: DRWY

SHEET

E

FILE NAME : V:\TRANS-EC\410764 USH 8 LITTLE SOFT MAPLE CREEK BRIDGE\C3D\DESIGN\CORRIDORS\CORRIDOR-USH8-DRWY.DWG  
LAYOUT NAME - 0901-(2)

PLOT DATE : 2/27/2020 4:08 PM


PLOT BY : RESHESKE, CARRIE

PLOT NAME :

PLOT SCALE : 1 IN:20 FT HORZ. / 1 IN:20 FT VERT.

WISDOT/CADD'S SHEET 49

87



PROJECT NO: 1580-00-70


HWY: USH 8

COUNTY: RUSK

CROSS SECTIONS: TEMP WIDENING

SHEET

E



9

9

PROJECT NO: 1580-00-70

HWY: USH 8

COUNTY: RUSK

CROSS SECTIONS: TEMP WIDENING

SHEET

E

FILE NAME: V:\TRANS-EC\410764 USH 8 LITTLE SOFT MAPLE CREEK BRIDGE\C3D\DESIGN\CORRIDORS\CORRIDOR-USH8-TEMP.DWG  
LAYOUT NAME - 0902-(2)


PLOT DATE: 2/27/2020 4:08 PM


PLOT BY: RESHESKE, CARRIE

PLOT NAME:

PLOT SCALE: 1 IN:20 FT HORZ. / 1 IN:20 FT VERT.

WISDOT/CADD'S SHEET 49





PROJECT NO: 1580-00-70

HWY: USH 8

COUNTY: RUSK

## CROSS SECTIONS: TEMP WIDENING

## SHEET

E

FILE NAME : V:\TRANS-EC\410764 USH 8 LITTLE SOFT MAPLE CREEK BRIDGE\C3D\DESIGN\CORRIDORS\CORRIDOR-USH8-TEMP.DWG  
LAYOUT NAME - 0902-(4)


PLOT DATE : 2/27/2020 4:08 PM

PLOT BY : RESHESKE, CARRIE

PLOT NAME :

LOT SCALE : 1 IN:20 FT HORZ. / 1 IN:20 FT VERT.

1/ISDOT/CADD\$ SHEET 49



PROJECT NO: 1580-00-70

HWY: USH 8

COUNTY: RUSK

## CROSS SECTIONS: TEMP WIDENING

SHEET

E

FILE NAME : V:\TRANS-EC\410764 USH 8 LITTLE SOFT MAPLE CREEK BRIDGE\C3D\DESIGN\CORRIDORS\CORRIDOR-USH8-TEMP.DWG  
LAYOUT NAME - 0902-(5)

PLOT DATE : 2/27/2020 4:08 PM

PLOT BY : RESHESKE, CARRIE


PLOT NAME :

1 IN:20 FT HORZ. / 1 IN:20 FT VERT.

VIEDOT/CAD

WISDOT/CADD3 SHEET 49

# Notes



## ***Wisconsin Department of Transportation***

Dedicated people creating transportation solutions  
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>