

WKE

WITH: N/A


3846-00-74

COUNTY: WALWORTH

FEBRUARY  
ORDER OF SHEETS

Section No. 1 Title  
 Section No. 2 Typical Sections and Details  
 Section No. 3 Estimate of Quantities  
 Section No. 3 Miscellaneous Quantities  
 Section No. 4 Right of Way Plat  
 Section No. 5 Plan and Profile  
 Section No. 6 Standard Detail Drawings  
 Section No. 7 Sign Plates  
 Section No. 8 Structure Plans  
 Section No. 9 Computer Earthwork Data  
 Section No. 9 Cross Sections

TOTAL SHEETS = 94



N

PROJECT LOCATION

DESIGN DESIGNATION 3846-00-04

A.A.D.T. 2026 = 109  
 A.A.D.T. 2046 = 126  
 D.H.V. = 17  
 D.D. = 62/38  
 T. = 7.7%  
 DESIGN SPEED = 30 MPH  
 ESALS = 15,000

## CONVENTIONAL SYMBOLS

PLAN	PROFILE
CORPORATE LIMITS	GRADE LINE
PROPERTY LINE	ORIGINAL GROUND
LOT LINE	MARSH OR ROCK PROFILE (To be noted as such)
LIMITED HIGHWAY EASEMENT	SPECIAL DITCH
EXISTING RIGHT OF WAY	GRADE ELEVATION
PROPOSED OR NEW R/W LINE	CULVERT (Profile View)
SLOPE INTERCEPT	UTILITIES
REFERENCE LINE	ELECTRIC
EXISTING CULVERT	FIBER OPTIC
PROPOSED CULVERT (Box or Pipe)	GAS
COMBUSTIBLE FLUIDS	SANITARY SEWER
MARSH AREA	STORM SEWER
WOODED OR SHRUB AREA	TELEPHONE
	WATER
	UTILITY PEDESTAL
	POWER POLE
	TELEPHONE POLE

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

## PLAN OF PROPOSED IMPROVEMENT


## T LINN - HILLSIDE ROAD

BRIDGE OVER CMSTPP RAILROAD P64-101

LOC STR  
WALWORTH COUNTYSTATE PROJECT NUMBER  
3846-00-74

R-17-E ← R-18-E

T-1-N

BEGIN PROJECT  
STA. 12+85  
Y = 304 482.520  
X = 784 458.982END PROJECT  
STA. 18+75STRUCTURE  
B-64-0215SCALE 0 1 MI  
TOTAL NET LENGTH OF CENTERLINE = 0.112 MI

HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COORDINATE REFERENCE SYSTEM (WISCRS), WALWORTH COUNTY, NAD83 (2011), IN U.S. SURVEY FEET. POSITIONS SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES ARE THE SAME AS GROUND DISTANCES.

ELEVATIONS ARE REFERENCED TO NAVD 88 (2012). GPS DERIVED ELEVATIONS ARE BASED ON GEOID 18.

STATE PROJECT	FEDERAL PROJECT	
	PROJECT	CONTRACT
3846-00-74	—	—

ACCEPTED FOR

TOWN OF LINN  
10/16/25  
Date  
(Signature and Title of Official)

ORIGINAL PLANS PREPARED BY

WESTBROOK  
Associated Engineers, Inc.

619 EAST HOXIE STREET  
P.O. BOX 429  
SPRING GREEN, WISCONSIN 53588  
PHONE (608) 588-7866  
FAX (608) 588-7954

WISCONSIN  
PROFESSIONAL ENGINEER  
AARON B.  
PALMER  
E-35695  
RICHLAND CENTER,  
WI  
DATE: 10/13/25  
Signature  
(Professional Engineer Signature)

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

PREPARED BY  
 Surveyor WESTBROOK ASSOCIATED ENGINEERS, INC.  
 Designer WESTBROOK ASSOCIATED ENGINEERS, INC.  
 Project Manager JOSEPH JELACIC, P.E.  
 Regional Examiner SE REGION  
 Regional Supervisor AMY TAETSCH, P.E.

APPROVED FOR THE DEPARTMENT  
Joseph C Jelacic  
DATE: 10/21/25  
(Signature)

Digitally signed by Joseph C Jelacic  
Date: 2025.10.21 10:49:24-05'00'  
E-mail: E-Jelacic@dot.wisconsin.gov  
Organization: WisDOT PPM  
City: Madison, WI  
State: WI  
Country: US

## GENERAL NOTES

2

THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS AS SHOWN ON THE PLANS ARE APPROXIMATE. THERE MAY BE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.

THE CONTRACTOR SHALL PREPARE AN EROSION CONTROL IMPLEMENTATION PLAN (ECIP) AND SUBMIT THE PLAN TO WISDOT AND WDNR FOR REVIEW AT LEAST 14 DAYS PRIOR TO THE PRECONSTRUCTION CONFERENCES.

THE CONTRACTOR WILL BE RESPONSIBLE FOR RESHAPING AND SEEDING ANY PREVIOUSLY GRASSED AREAS WHICH ARE DISTURBED BY OPERATIONS, OUTSIDE OF THE NORMAL CONSTRUCTION LIMITS.

HMA PAVEMENT WEIGHT CALCULATIONS ARE BASED ON 112 LBS/SY/IN.

APPLY TACK COAT BETWEEN LAYERS OF HMA PAVEMENT AT A RATE OF 0.05 GAL/SY.

NO TREES OR SHRUBS ARE TO BE REMOVED WITHOUT THE APPROVAL OF THE ENGINEER.

RIGHT OF WAY INFORMATION SHOWN ON THE PLANS IS APPROXIMATE.

WHEN THE QUANTITY OF THE ITEMS OF BASE AGGREGATE, SUBBASE OR HMA PAVEMENT IS MEASURED FOR PAYMENT BY THE TON OR CUBIC YARD, THE DEPTH OR THICKNESS OF THE LAYERS SHOWN ON THE PLAN IS APPROXIMATE AND THE ACTUAL THICKNESS WILL DEPEND ON THE DISTRIBUTION OF THE MATERIAL AS DIRECTED BY THE ENGINEER.

EROSION CONTROL FEATURES AS SHOWN IN THE PLANS ARE AT APPROXIMATE LOCATIONS. EXACT LOCATIONS WILL BE DETERMINED BY THE CONTRACTOR'S ECIP AND APPROVED BY THE ENGINEER. MAINTAIN EROSION CONTROL MEASURES UNTIL SUCH A TIME AS THE ENGINEER DETERMINES THE MEASURE IS NO LONGER NECESSARY.

ANY AND ALL GRADED OR DISTURBED AREAS THAT WILL NOT BE FINISHED AND PERMANENTLY RESTORED WITHIN 7 CALENDAR DAYS SHALL BE SEEDED WITH TEMPORARY SEEDING AND MULCHED WITHIN 48 HOURS OF DISTURBANCE.

SLOPES STEEPER THAN 3:1 REQUIRE EROSION MAT.

SAWCUTS, AS SHOWN ON THE PLANS, ARE SUGGESTED LOCATIONS AND MAY BE ADJUSTED AT THE DISCRETION OF THE ENGINEER TO BETTER SUIT FIELD CONDITIONS.

REMOVAL OF ASPHALTIC SURFACES WHERE AN ABUTTING ASPHALTIC SURFACE IS TO REMAIN IN PLACE SHALL REQUIRE A SAW CUT MEETING THE APPROVAL OF THE ENGINEER IN THE FIELD.

THE CONTRACTOR'S PAVING OPERATION SHALL BE CONSISTENT WITH THE TYPICAL SECTIONS AND CONSTRUCTED TO PREVENT LONGITUDINAL JOINTS FROM BEING LOCATED WITHIN A DRIVING, TURNING, PASSING, OR PARKING LANE.

THE 6-INCH ASPHALTIC SURFACE SHALL BE CONSTRUCTED USING ONE (1) 4-INCH LOWER LAYER WITH 19 MM AGGREGATE AND ONE (1) 2-INCH UPPER LAYER WITH 12.5 MM AGGREGATE. THE PREFERRED LOWER LAYER IS 4-INCHES OF 3 LT 58-28 S. THE PREFERRED UPPER LAYER IS 2-INCHES OF 4 LT 58-28 S.

TRAFFIC CONTROL DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS DIRECTED BY THE ENGINEER.

DO NOT DRIVE OR STORE EQUIPMENT, OR STORE CONSTRUCTION MATERIALS IN ENVIRONMENTALLY SENSITIVE AREAS, WETLANDS OR WATERWAYS.

## RUNOFF COEFFICIENT TABLE

LAND USE:	HYDROLOGIC SOIL GROUP											
	A			B			C			D		
	SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)	
0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	
ROW CROPS:	.08	.16	.22	.12	.20	.27	.15	.24	.33	.19	.28	.38
	.22	.30	.38	.26	.34	.44	.30	.37	.50	.34	.41	.56
MEDIAN STRIPTURF:	.19	.20	.24	.19	.22	.26	.20	.23	.30	.20	.25	.30
	.24	.26	.30	.25	.28	.33	.26	.30	.37	.27	.32	.40
SIDE SLOPETURF:			.25			.27			.28			.30
			.32			.34			.36			.38
PAVEMENT:												
ASPHALT:												.70 - .95
CONCRETE:												.80 - .95
BRICK:												.70 - .80
DRIVES, WALKS:												.75 - .85
ROOFS:												.75 - .95
GRAVEL ROADS, SHOULDERS:												.40 - .60

TOTAL PROJECT AREA = 1.141 ACRES

TOTAL AREA EXPECTED TO BE DISTURBED BY CONSTRUCTION ACTIVITIES = 0.561 ACRES

PROJECT NO: 3846-00-74

HWY: HILLSIDE RD

COUNTY: WALWORTH

GENERAL NOTES

SHEET

E

## WISCONSIN DNR LIAISON

CRAIG WEBSTER  
SOUTH WEST REGION  
141 NW BARSTOW ST  
WAUKESHA, WI 53188  
PHONE: (262) 574-2850  
EMAIL: craig.webster@wisconsin.gov

## CONSULTANT LIAISON

AARON PALMER, P.E.  
WESTBROOK ASSOCIATED ENGINEERS, INC.  
619 EAST HOXIE ST  
SPRING GREEN, WI 53588  
PHONE: (608) 588-7866  
EMAIL: apalmer@westbrookeng.com

## COUNTY DIRECTOR PUBLIC WORKS

RICHARD HOUGH  
WALWORTH COUNTY  
W4097 COUNTY ROAD NN  
ELKHORN, WI 53121  
PHONE: (262) 903-8486  
EMAIL: rrough@co.walworth.wi.us

## TOWN OF LINN

JIM HURLEY  
ADMINISTRATOR/TREASURER  
W3728 FRANKLIN WALSH ST  
ZENDA, WI 53195  
PHONE: (262) 275-6300  
EMAIL: admin@townoflinn.wi.gov

## UTILITIES CONTACTS

ALLIANT ENERGY  
ELECTRIC  
AUSTIN KROHN  
400B KOOPMAN LANE  
ELKHORN, WI 53121  
PHONE: (262) 741-0905  
EMAIL: austinkrohn@alliantenergy.com

FRONTIER COMMUNICATIONS  
COMMUNICATIONS  
CHRISTOPHER POLLACK  
521 N 4TH ST  
WAUSAU, WI 54403  
PHONE: (715) 847-1240  
EMAIL: christopher.pollack@ftr.com

CHARTER COMMUNICATIONS  
COMMUNICATIONS  
DOMINIC KATCHA  
1320 N DR MARTIN LUTHER KING JR DR  
MILWAUKEE, WI 53212  
PHONE: (414) 277-4020  
EMAIL: Dominic.Katcha@charter.com

## STANDARD ABBREVIATIONS

AC	ACRE	LT	LEFT
AGG	AGGREGATE	LHF	LEFT HAND FORWARD
AH	AHEAD	L	LENGTH OF CURVE
∠	ANGLE	LF	LINEAR FOOT
AADT	ANNUAL AVERAGE DAILY TRAFFIC	LC	LONG CHORD OF CURVE
AEW	APRON ENDWALL	LS	LUMP SUM
ASPH	ASPHALTIC	MGAL	ONE THOUSAND GALLONS
BK	BACK	ML OR M/L	MATCH LINE
BAD	BASE AGGREGATE DENSE	NOM	NOMINAL
BL OR B/L	BASE LINE	NC	NORMAL CROWN
BM	BENCH MARK	NB	NORTHBOUND
CL OR C/L	CENTER LINE	NO	NUMBER
Δ	CENTRAL ANGLE OR DELTA	OD	OUTSIDE DIAMETER
CE	COMMERCIAL ENTRANCE	PAVT	PAVEMENT
CONC	CONCRETE	PLE	PERMANENT LIMITED EASEMENT
CONST	CONSTRUCTION	PC	POINT OF CURVATURE
CP	CONTROL POINT	PI	POINT OF INTERSECTION
CO	COUNTY	PT	POINT OF TANGENCY
CTH	COUNTY TRUCK HIGHWAY	PCC	PORTLAND CEMENT CONCRETE
CY	CUBIC YARD	LB	POUND
CP	CULVERT PIPE	PSI	POUNDS PER SQUARE INCH
CPCA	CULVERT PIPE CORRUGATED ALUMINUM	PE	PRIVATE ENTRANCE
CPCPE	CULVERT PIPE CORRUGATED POLYETHYLENE	PROJ	PROJECT
CPCPP	CULVERT PIPE CORRUGATED POLYPROPYLENE	PL	PROPERTY LINE
CPCSAC	CULVERT PIPE CORRUGATED STEEL ALUMINUM COATED	PRW	PROPOSED RIGHT OF WAY
CPCSPC	CULVERT PIPE CORRUGATED STEEL POLYMER COATED	R	RADIUS
CPRC	CULVERT PIPE REINFORCED CONCRETE	RL OR R/L	REFERENCE LINE
CPRCHE	CULVERT PIPE REINFORCED CONCRETE HORIZONTAL ELLIPTICAL	REQD	REQUIRED
CPS	CULVERT PIPE SALVAGED	RT	RIGHT
CPT	CULVERT PIPE TEMPORARY	RHF	RIGHT HAND FORWARD
D	DEGREE OF CURVE	R/W	RIGHT OF WAY
DHV	DESIGN HOUR VOLUME	RD	ROAD
DIA	DIAMETER	RDWY	ROADWAY
DD	DIRECTIONAL DISTRIBUTION	SHLDR	SHOULDER
DE	DRAINAGE EASEMENT	SW	SIDEWALK
DWY	DRIVEWAY	SB	SOUTHBOUND
EA	EACH	SF	SQUARE FEET
EB	EASTBOUND	SY	SQUARE YARD
EL OR ELEV	ELEVATION	SDD	STANDARD DETAIL DRAWINGS
EMB	EMBANKMENT	STH	STATE TRUNK HIGHWAY
EW	ENDWALL	STA	STATION
ESALS	EQUIVALENT SINGLE AXLE LOADS	SE	SUPERELEVATION
EXC	EXCAVATION	SL OR S/L	SURVEY LINE
EBS	EXCAVATION BELOW SUBGRADE	TEMP	TEMPORARY
EXIST	EXISTING	TI	TEMPORARY INTEREST
FERT	FERTILIZER	TLE	TEMPORARY LIMITED EASEMENT
FE	FIELD ENTRANCE	TL OR T/L	TRANSIT LINE
FL OR F/L	FLOW LINE	T	TRUCKS (PERCENT OF)
FT	FOOT	TYP	TYPICAL
HE	HIGHWAY EASEMENT	USH	UNITED STATES HIGHWAY
CWT	HUNDRED WEIGHT	VAR	VARIABLE
IN DIA	INCH DIAMETER	VC	VERTICAL CURVE
ID	INSIDE DIAMETER	VPC	VERTICAL POINT OF CURVATURE
INTERS	INTERSECTION	VPI	VERTICAL POINT OF INTERSECTION
IH	INTERSTATE HIGHWAY	VPT	VERTICAL POINT OF TANGENCY
INV	INVERT	W	WEST
JT	JOINT	WB	WESTBOUND

**DIGGERS HOTLINE**  
Dial 811 or (800)242-8511  
www.DiggersHotline.com




## ORDER OF SECTION 2 DETAIL SHEETS

GENERAL NOTES  
TYPICAL SECTIONS  
DRIVEWAY DETAILS  
PAVEMENT MARKING AND PERMANENT SIGNING  
ALIGNMENT DETAILS AND CONTROL POINTS

2

2

2



**EXISTING TYPICAL SECTION - RAILROAD**

PROJECT NO: 3846-00-74




HWY: HILLSIDE RD

COUNTY: WALWORTH

EXISTING TYPICAL SECTIONS


SHEET

E



## NOTES

- ① VARIES. 1' TYP.
- ② VARIES. GRADE FOR POSITIVE DITCH DRAINAGE
- ③ LIMITS OF SEEDING, TEMPORARY SEEDING, FERTILIZER, SALVAGED TOPSOIL, MULCH & E-MAT




LEGEND: PERMANENT SIGNING	
	EXISTING SIGN
	PROPOSED SIGN
	DENOTES SIGN NUMBER
	WORK CODE: R=REMOVE SIGN COUNT SEQUENCE

2


Z

2



2


2




#### CONTROL POINTS

NO.	STATION	DESCRIPTION	Y	X
CP 1	12+74.50	3/4" REBAR W/ CAP SET, 16.0' LT	304 471.660	784 443.197
CP 2	13+10.74	GIN SPIKE SET, 0.1' LT	304 508.251	784 458.299
CP 3	15+16.50	60D NAIL SET, 57.5' RT	304 715.274	784 511.205
CP 4	15+94.53	60D NAIL SET, 71.5' LT	304 790.330	784 380.410
CP 5	17+90.17	3/4" REBAR W/ CAP SET, 21.9' RT	304 988.063	784 469.338
CP 6	17+91.48	GIN SPIKE SET, 0.3' LT	304 988.855	784 447.063


#### TIES TO CP 1




#### TIES TO CP 2




#### TIES TO CP 3




#### TIES TO CP 4



#### TIES TO CP 5



#### TIES TO CP 6



PROJECT NO: 3846-00-74

HWY: HILLSIDE RD

COUNTY: WALWORTH

ALIGNMENT DETAILS AND CONTROL POINTS

SHEET

7

## Estimate Of Quantities

3846-00-74

Line	Item	Item Description	Unit	Total	Qty
0002	201.0205	Grubbing	STA	5.000	5.000
0004	203.0100	Removing Small Pipe Culverts	EACH	3.000	3.000
0006	203.0220	Removing Structure (structure) 01. P-64-101	EACH	1.000	1.000
0008	203.0330	Debris Containment (structure) 01. P-64-101	EACH	1.000	1.000
0010	205.0100	Excavation Common	CY	455.000	455.000
0012	206.1001	Excavation for Structures Bridges (structure) 01. B-64-215	EACH	1.000	1.000
0014	208.0100	Borrow	CY	609.000	609.000
0016	210.1500	Backfill Structure Type A	TON	370.000	370.000
0018	213.0100	Finishing Roadway (project) 01. 3846-00-74	EACH	1.000	1.000
0020	305.0110	Base Aggregate Dense 3/4-Inch	TON	100.000	100.000
0022	305.0120	Base Aggregate Dense 1 1/4-Inch	TON	460.000	460.000
0024	415.0410	Concrete Pavement Approach Slab	SY	132.000	132.000
0026	455.0605	Tack Coat	GAL	46.000	46.000
0028	465.0105	Asphaltic Surface	TON	307.000	307.000
0030	465.0120	Asphaltic Surface Driveways and Field Entrances	TON	34.000	34.000
0032	502.0100	Concrete Masonry Bridges	CY	417.000	417.000
0034	502.3200	Protective Surface Treatment	SY	648.000	648.000
0036	503.0128	Prestressed Girder Type I 28-Inch	LF	863.000	863.000
0038	505.0400	Bar Steel Reinforcement HS Structures	LB	36,800.000	36,800.000
0040	505.0600	Bar Steel Reinforcement HS Coated Structures	LB	38,870.000	38,870.000
0042	506.2605	Bearing Pads Elastomeric Non-Laminated	EACH	30.000	30.000
0044	506.4000	Steel Diaphragms (structure) 01. B-64-215	EACH	12.000	12.000
0046	511.1200	Temporary Shoring (structure) 01. B-64-215	SF	1,590.000	1,590.000
0048	513.4061	Railing Tubular Type M	LF	358.000	358.000
0050	516.0500	Rubberized Membrane Waterproofing	SY	14.000	14.000
0052	520.1024	Apron Endwalls for Culvert Pipe 24-Inch	EACH	2.000	2.000
0054	520.3524	Culvert Pipe Class III-B 24-Inch	LF	62.000	62.000
0056	550.1100	Piling Steel HP 10-Inch X 42 Lb	LF	1,730.000	1,730.000
0058	604.0500	Slope Paving Crushed Aggregate	SY	379.000	379.000
0060	612.0406	Pipe Underdrain Wrapped 6-Inch	LF	170.000	170.000
0062	618.0100	Maintenance and Repair of Haul Roads (project) 01. 3846-00-74	EACH	1.000	1.000
0064	619.1000	Mobilization	EACH	1.000	1.000
0066	624.0100	Water	MGAL	5.000	5.000
0068	625.0500	Salvaged Topsoil	SY	2,700.000	2,700.000
0070	627.0200	Mulching	SY	1,650.000	1,650.000
0072	628.1504	Silt Fence	LF	800.000	800.000
0074	628.1520	Silt Fence Maintenance	LF	1,290.000	1,290.000
0076	628.1905	Mobilizations Erosion Control	EACH	4.000	4.000
0078	628.1910	Mobilizations Emergency Erosion Control	EACH	3.000	3.000
0080	628.2008	Erosion Mat Urban Class I Type B	SY	1,050.000	1,050.000
0082	628.7504	Temporary Ditch Checks	LF	100.000	100.000
0084	628.7555	Culvert Pipe Checks	EACH	13.000	13.000
0086	629.0210	Fertilizer Type B	CWT	2.500	2.500
0088	630.0130	Seeding Mixture No. 30	LB	200.000	200.000
0090	630.0200	Seeding Temporary	LB	130.000	130.000
0092	630.0500	Seed Water	MGAL	92.000	92.000
0094	633.5200	Markers Culvert End	EACH	2.000	2.000
0096	634.0612	Posts Wood 4x6-Inch X 12-FT	EACH	4.000	4.000
0098	637.2230	Signs Type II Reflective F	SF	12.000	12.000

## Estimate Of Quantities

3846-00-74

Line	Item	Item Description	Unit	Total	Qty
0100	638.2602	Removing Signs Type II	EACH	9.000	9.000
0102	638.3000	Removing Small Sign Supports	EACH	10.000	10.000
0104	642.5001	Field Office Type B	EACH	1.000	1.000
0106	643.0300	Traffic Control Drums	DAY	70.000	70.000
0108	643.0420	Traffic Control Barricades Type III	DAY	3,151.000	3,151.000
0110	643.0705	Traffic Control Warning Lights Type A	DAY	6,302.000	6,302.000
0112	643.0900	Traffic Control Signs	DAY	2,466.000	2,466.000
0114	643.1050	Traffic Control Signs PCMS	DAY	14.000	14.000
0116	643.5000	Traffic Control	EACH	1.000	1.000
0118	645.0111	Geotextile Type DF Schedule A	SY	70.000	70.000
0120	646.1005	Marking Line Paint 4-Inch	LF	1,180.000	1,180.000
0122	650.4500	Construction Staking Subgrade	LF	414.000	414.000
0124	650.5000	Construction Staking Base	LF	494.000	494.000
0126	650.6000	Construction Staking Pipe Culverts	EACH	1.000	1.000
0128	650.6501	Construction Staking Structure Layout (structure) 01. B-64-215	EACH	1.000	1.000
0130	650.9911	Construction Staking Supplemental Control (project) 01. 3846-00-74	EACH	1.000	1.000
0132	650.9920	Construction Staking Slope Stakes	LF	537.000	537.000
0134	690.0150	Sawing Asphalt	LF	62.000	62.000
0136	715.0502	Incentive Strength Concrete Structures	DOL	2,502.000	2,502.000
0138	715.0720	Incentive Compressive Strength Concrete Pavement	DOL	40.000	40.000
0140	801.0117	Railroad Flagging Reimbursement	DOL	31,200.000	31,200.000
0142	999.2000.S	Installing and Maintaining Bird Deterrent System (station) 01. 13+50	EACH	1.000	1.000
0144	SPV.0165	Special 01. Temporary Shoring Railroad	SF	560.000	560.000

ALL ITEMS CATEGORY 0010 UNLESS NOTED OTHERWISE.

## GRUBBING

201.0205  
 STATION TO STATION LOCATION STA  
 12+00 - 17+00 LT/RT 5  
 TOTAL 5

## EXCAVATION SUMMARY

DIVISION	FROM/TO STATION	205.0100 EXCAVATION COMMON (CY) (1)	CUT (2)	SALVAGED/UNUSABLE PAVEMENT MATERIAL (CY) (3)	AVAILABLE MATERIAL (CY) (4)	UNEXPANDED FILL (CY)	EXPANDED FILL (CY) (5)	MASS ORDINATE +/- (CY) (6)	WASTE (CY) (7)	BORROW (CY)
SOUTH APPROACH	12+85 / 14+54.41	207		63	144	214	268	-124	0	124
NORTH APPROACH	16+29.62 / 18+75	203		91	112	316	397	-283	0	283
RAILROAD DITCH	50+06 / 51+29	43		0	43	0	0	43	43	0
DRIVEWAY	0+14 / 0+90	2		0	2	163	205	-202	0	202
GRAND TOTAL		455		154	301	693	870	-566	43	609

## REMOVING SMALL PIPE CULVERTS

203.0100  
 STATION LOCATION EACH REMARKS  
 15+39 RAILROAD DITCH, LT/RT 1 SALVAGE FOR WSOR  
 15+61 RAILROAD DITCH, LT/RT 1 SALVAGE FOR WSOR  
 16+94 HILLSIDE RD, LT/RT 1  
 TOTAL 3

NOTES:  
 (1) EXCAVATION COMMON IS THE SUM OF THE CUT COLUMN. ITEM NUMBER 205.0100  
 (2) SALVAGED/UNUSABLE PAVEMENT MATERIAL IS INCLUDED IN CUT.  
 (3) SALVAGED/UNUSABLE PAVEMENT MATERIAL INCLUDES EXISTING ASPHALT.  
 (4) AVAILABLE MATERIAL = CUT - SALVAGED/UNUSABLE PAVEMENT MATERIAL  
 (5) EXPANDED FILL FACTOR = 1.25  
 EXPANDED FILL = (UNEXPANDED FILL) \* FILL FACTOR  
 (6) THE MASS ORDINATE + OR - QTY CALCULATED FOR THE DIVISION. PLUS QUANTITY INDICATES AN EXCESS OF MATERIAL WITHIN THE DIVISION. MINUS INDICATES A SHORTAGE OF MATERIAL WITHIN THE DIVISION.  
 (7) FACTORS USED TO COMPUTE ANTICIPATED WASTE AND THE COMPUTED WASTE VOLUME IDENTIFIED ARE FOR GENERAL INFORMATION ONLY.

## BASE AGGREGATE DENSE

305.0110 BASE AGGREGATE DENSE 3/4-INCH TON \* 305.0120 BASE AGGREGATE DENSE 1 1/4-INCH TON 624.0100 WATER MGAL

STATION	TO	STATION	LOCATION	TON	TON	TON
12+85	-	14+54	SOUTH APPROACH	45	160	2.1
16+30	-	18+75	NORTH APPROACH	55	230	2.9
TOTAL				100	390	5.0

\* ADDITIONAL QUANTITIES FOUND ELSEWHERE IN PLANS

## CONCRETE PAVEMENT APPROACH SLAB

415.0410  
 STATION TO STATION LOCATION SY  
 14+29.74 - 14+53.55 SOUTH APPROACH 66  
 16+30.47 - 16+54.29 NORTH APPROACH 66  
 TOTAL 132

## ASPHALTIC PAVEMENT

STATION	TO	STATION	LOCATION	TACK COAT GAL	ASPHALTIC SURFACE TON
12+85	-	14+54	SOUTH APPROACH	18	120
16+30	-	18+75	NORTH APPROACH	28	187
TOTAL				46	307

## DRIVEWAY

*	305.0120 BASE AGGREGATE DENSE 1 1/4-INCH TON	465.0120 ASPHALTIC SURFACE DRIVEWAYS AND FIELD ENTRANCES
STATION	LOCATION	TON
16+38	RT	70
TOTAL		70
		34

## CULVERT PIPES SUMMARY

520.1024 APRON ENDWALLS FOR CULVERT PIPE 24-INCH EACH	520.3524 CULVERT PIPE CLASS III-B 24-INCH LF	650.6000 CONSTRUCTION STAKING PIPE CULVERTS EACH	*	JOINT TIES EACH	STEEL THICKNESS INCHES	** INLET ELEVATION	** OUTLET ELEVATION
16+93.57 HILLSIDE RD, LT/RT	2	62	1	6	0.064	976.17	975.12
TOTAL		2	62	1			

\* ADDITIONAL QUANTITIES FOUND ELSEWHERE IN PLANS  
 \*\* NON-BID ITEM. FOR INFORMATION ONLY  
 \*\* PIPE INVERT AT END OF PIPE. FOR INFORMATION ONLY. FIELD VERIFY.

## TEMPORARY DITCH CHECKS

628.7504  
 STATION LOCATION LF  
 13+00 LT 14  
 14+75 LT 7  
 15+04 LT 7  
 16+24 RT 16  
 15+01 "RR" LT 8  
 15+29 "RR" RT 8  
 15+64 "RR" LT 6  
 15+93 "RR" RT 6  
 UNDISTRIBUTED 28  
 TOTAL 100

## CULVERT PIPE CHECKS

STATION	LOCATION	EACH
16+94	RT	6
1+00 "PE"	LT	4
UNDISTRIBUTED		3
TOTAL		13

## MOBILIZATIONS EROSION CONTROL

628.1905 MOBILIZATIONS EROSION CONTROL EACH	628.1910 MOBILIZATIONS EMERGENCY EROSION CONTROL EACH
LOCATION	
PROJECT	
TOTAL	4 3

## SILT FENCE

STATION	TO	STATION	LOCATION	LF
12+82	-	14+52	SOUTH APPROACH, RT	180
16+45	-	18+80	NORTH APPROACH, LT	245
16+68	-	18+80	NORTH APPROACH, RT	220
UNDISTRIBUTED				155
TOTAL				800
				1,290

ALL ITEMS CATEGORY 0010 UNLESS NOTED OTHERWISE.

3

3

## FINISHING ITEMS

STATION	TO	STATION	LOCATION	625.0500 SALVAGED TOPSOIL SY	627.0200 MULCHING SY	628.2008 EROSION MAT URBAN CLASS I TYPE B SY	629.0210 FERTILIZER CWT	630.0130 SEEDING MIXTURE NO. 30 LB	630.0200 SEEDING TEMPORARY LB	630.0500 SEED WATER MGAL
12+85	-	14+54	SOUTH APPROACH, LT	370	370	---	0.4	30	20	14
12+85	-	14+54	SOUTH APPROACH, RT	330	330	---	0.3	25	15	12
14+54	-	15+44	SOUTH RAILROAD GRADING	540	---	540	0.4	30	20	14
15+57	-	16+30	NORTH RAILROAD GRADING	300	---	300	0.2	15	10	7
16+30	-	18+75	NORTH APPROACH, LT	250	250	---	0.3	25	15	12
16+30	-	18+75	NORTH APPROACH, RT	170	170	---	0.2	20	15	9
0+14 "PE"	-	0+94 "PE"	DRIVEWAY, LT/RT	190	190	---	0.2	15	10	6
			UNDISTRIBUTED	550	340	210	0.5	40	25	18
			TOTAL	2,700	1,650	1,050	2.5	200	130	92

## MARKERS CULVERT END

STATION	LOCATION	EACH
16+94	LT/RT	2
TOTAL		2

## SIGNING SUMMARY

STATION	LOCATION	SIGN NUMBER	SIGN CODE	EACH	SF	EACH	EACH	SIGN DESCRIPTION
---	SOUTH APPROACH, RT	1R	---	---		1	1	ONE LANE BRIDGE AHEAD .2 MILE, 40 TON LIMIT
14+35	SOUTH APPROACH, RT	2R	W5-3, W54-56	---		1	1	ONE LANE BRIDGE, SLOW
14+41	SOUTH APPROACH, RT	3	W5-52R	1	3	---	---	BRIDGE HASH MARKS
14+73	SOUTH APPROACH, RT	3R	W5-52R	---		1	1	40 TON LIMIT, BRIDGE HASH MARKS
14+62	SOUTH APPROACH, LT	4	W5-52L	1	3	---	---	BRIDGE HASH MARKS
14+71	SOUTH APPROACH, LT	4R	W5-52L	---		1	1	BRIDGE HASH MARKS
16+21	NORTH APPROACH, RT	5R	W5-52L	---		1	1	BRIDGE HASH MARKS
16+22	NORTH APPROACH, RT	5	W5-52L	1	3	---	---	BRIDGE HASH MARKS
16+21	NORTH APPROACH, LT	6R	W5-52R	---		1	1	40 TON LIMIT, BRIDGE HASH MARKS
16+43	NORTH APPROACH, LT	6	W5-52R	1	3	---	---	BRIDGE HASH MARKS
16+46	NORTH APPROACH, LT	7R	W5-52	---		1	2	ROTATED BRIDGE HASH MARKS
16+74	NORTH APPROACH, LT	8R	W5-3, W54-56	---		1	1	ONE LANE BRIDGE, SLOW
---	NORTH APPROACH, LT	9R	---	---		1	1	ONE LANE BRIDGE AHEAD .7 MILE, 40 TON LIMIT
		TOTAL		4	12	9	10	

## TRAFFIC CONTROL

LOCATION	DURATION	643.0300	643.0420	643.0705	643.0900	643.1050	643.5000
		TRAFFIC CONTROL	BARRICADES DRUMS	TRAFFIC CONTROL	TRAFFIC CONTROL	TRAFFIC CONTROL	TRAFFIC CONTROL
SOUTH APPROACH	137	---	---	9	1,233	18	2,466
NORTH APPROACH	137	---	---	9	1,233	18	2,466
UNDISTRIBUTED	137	---	---	5	685	10	1,370
PROJECT	7	10	70	---	---	4	548
TOTAL	10	70	23	3,151	46	6,302	18
							2,466
						2	14
							1

## MARKING LINE PAINT 4-INCH

STATION	TO	STATION	LOCATION	646.1005 LF	REMARKS
12+85	-	18+75	CENTERLINE	1,180	DOUBLE YELLOW
			TOTAL	1,180	

## CONSTRUCTION STAKING

STATION	TO	STATION	LOCATION	CONSTRUCTION STAKING SUBGRADE LF	CONSTRUCTION STAKING BASE LF	CONSTRUCTION STAKING STRUCTURE LAYOUT 01. B-64-0215 EACH	CONSTRUCTION STAKING SUPPLEMENTAL CONTROL 01. 3864-00-74 EACH	CONSTRUCTION STAKING SLOPE STAKES LF
12+85	-	14+54	SOUTH APPROACH	169	169	---	---	169
16+30	-	18+75	NORTH APPROACH	245	245	---	---	245
50+06 "RR"	-	51+29 "RR"	RAILROAD	---	---	---	---	123
0+14 "PE"	-	0+94 "PE"	DRIVEWAY	---	80	---	---	---
			PROJECT	---	---	1	1	---
			TOTAL	414	494	1	1	537

## SAWING ASPHALT

STATION	LOCATION	LF
12+85	SOUTH APPROACH	22
18+75	NORTH APPROACH	22
0+94 "PE"	DRIVEWAY	18
TOTAL		62

\* CATEGORY 0020

PROJECT NO: 3846-00-74

HWY: HILLSIDE RD

COUNTY: WALWORTH


MISCELLANEOUS QUANTITIES

SHEET 11

E


CONVENTIONAL SYMBOLS		NOTES:		R/W PROJECT NUMBER 3846-00-04		SHEET NUMBER 4.01	TOTAL SHEETS 2	
SECTION LINE		SECTION CORNER SYMBOL		R/W MONUMENT (TO BE SET)	●			
QUARTER LINE		NON-MONUMENTED R/W POINT	○					
SIXTEENTH LINE		FOUND IRON PIN (1-INCH UNLESS NOTED)	IP					
NEW REFERENCE LINE								
NEW R/W LINE								
EXISTING R/W OR HE LINE								
PROPERTY LINE								
LOT, TIE & OTHER MINOR LINES								
SLOPE INTERCEPT								
CORPORATE LIMITS								
UNDERGROUND FACILITY (COMMUNICATIONS, ELECTRIC, ETC)								
NEW R/W (FEE OR HE) (HATCHING VARIES BY OWNER)								
TEMPORARY LIMITED EASEMENT AREA								
EASEMENT AREA (PERMANENT LIMITED OR RESTRICTED DEVELOPMENT)								
TRANSMISSION STRUCTURES								
BUILDING		TO BE REMOVED						
BRIDGE		CULVERT						
CONVENTIONAL UTILITY SYMBOLS								
WATER								
GAS								
TELEPHONE								
OVERHEAD TRANSMISSION LINES								
ELECTRIC								
CABLE TELEVISION								
FIBER OPTIC								
SANITARY SEWER								
STORM SEWER								
ELECTRIC TOWER								
CONVENTIONAL ABBREVIATIONS								
ACCESS RIGHTS	AR	POINT OF COMPOUND CURVE	PCC					
ACRES	AC	POINT OF INTERSECTION	PI					
AHEAD	AH	PROPERTY LINE	PL					
ALUMINUM	ALUM	RECORDED AS	(100')					
AND OTHERS	ET AL	REEL / IMAGE	R/I					
BACK	BK	REFERENCE LINE	R/L					
BLOCK	BLK	REMAINING	REM					
CENTERLINE	C/L	RESTRICTIVE DEVELOPMENT	RDE					
CERTIFIED SURVEY MAP	CSM	EASEMENT	RT					
CONCRETE	CONC	RIGHT	R/W					
COUNTY	CO	RIGHT OF WAY	SEC					
COUNTY TRUNK HIGHWAY	CTH	SECTION	SEPV					
DISTANCE	DIST	SEPTIC VENT	SF					
CORNER	COR	SQUARE FEET	STH					
DOCUMENT NUMBER	DOC	STATE TRUNK HIGHWAY	STA					
EASEMENT	EASE	STATION	TP					
EXISTING	EX	TELEPHONE PEDESTAL	TLE					
GAS VALVE	GV	TEMPORARY LIMITED						
GRID NORTH	GN	EASEMENT						
HIGHWAY EASEMENT	HE	TRANSPORTATION PROJECT PLAT	TPP					
IDENTIFICATION	ID	UNITED STATES HIGHWAY	USH					
LAND CONTRACT	LC	VOLUME	V					
LEFT	LT							
MONUMENT	MON							
NATIONAL GEODETIC SURVEY	NGS							
NUMBER	NO	LONG CHORD	LCH					
OUTLOT	OL	LONG CHORD BEARING	LCB					
PAGE	P	RADIUS	R					
POINT OF TANGENCY	PT	DEGREE OF CURVE	D					
PERMANENT LIMITED EASEMENT	PLE	CENTRAL ANGLE	Δ/DELTA					
POINT OF BEGINNING	POB	LENGTH OF CURVE	L					
POINT OF CURVATURE	PC	TANGENT	T					
		DIRECTION AHEAD	DA					
		DIRECTION BACK	DB					
CURVE DATA ABBREVIATIONS								
NOTES:								
POSITIONS SHOWN ON THIS PLAT ARE WISCONSIN COORDINATE REFERENCE SYSTEM COORDINATES (WISCRS), WALWORTH COUNTY, NAD83 (2011) IN US SURVEY FEET. VALUES SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES MAY BE USED AS GROUND DISTANCES.								
ALL NEW RIGHT-OF-WAY AND PERMANENT EASEMENT MONUMENTS WILL BE TYPE 2 (TYPICALLY $\frac{3}{4}$ " X 24" IRON REBARS), UNLESS OTHERWISE NOTED, AND WILL BE PLACED PRIOR TO THE COMPLETION OF THE PROJECT.								
DIMENSIONING FOR THE NEW RIGHT-OF-WAY IS MEASURED ALONG AND PERPENDICULAR TO THE NEW REFERENCE LINES.								
RIGHT-OF-WAY BOUNDARIES ARE DEFINED WITH COURSES OF THE PERIMETER OF THE HIGHWAY LANDS REFERENCED TO THE U.S. PUBLIC LAND SURVEY SYSTEM OR OTHER "SURVEYS" OF PUBLIC RECORD.								
FOR THE CURRENT ACCESS/DRIVEWAY INFORMATION, CONTACT THE PLANNING UNIT OF THE TOWN OF LINN.								
PARCEL AND UTILITY IDENTIFICATION NUMBERS MAY NOT POINT TO ALL AREAS OF ACQUISITION, AS NOTED ON THE DETAIL PAGES.								
INFORMATION FOR THE BASIS OF EXISTING HIGHWAY RIGHT-OF-WAY POINTS OF REFERENCE AND ACCESS CONTROL ARE LISTED ON THE DETAIL PAGES.								
NOTES CONT'D:								
A TEMPORARY LIMITED EASEMENT (TLE) IS A RIGHT FOR CONSTRUCTION PURPOSES, AS DEFINED HEREIN, INCLUDING THE RIGHT TO OPERATE NECESSARY EQUIPMENT THEREON, THE RIGHT OF INGRESS AND EGRESS, AS LONG AS REQUIRED FOR SUCH PUBLIC PURPOSE, INCLUDING THE RIGHT TO PRESERVE, PROTECT, REMOVE, OR PLANT THEREON ANY VEGETATION THAT THE HIGHWAY AUTHORITIES MAY DEEM DESIRABLE. ALL (TLES) ON THIS PLAT EXPIRE AT THE COMPLETION OF THE CONSTRUCTION PROJECT FOR WHICH THIS INSTRUMENT IS GIVEN.								
A PERMANENT LIMITED EASEMENT (PLE) IS A RIGHT FOR CONSTRUCTION AND MAINTENANCE PURPOSES, AS DEFINED HEREIN, INCLUDING THE RIGHT TO OPERATE NECESSARY EQUIPMENT THEREON AND THE RIGHT OF INGRESS AND EGRESS, AS LONG AS REQUIRED FOR SUCH PUBLIC PURPOSE, INCLUDING THE RIGHT TO PRESERVE, PROTECT, REMOVE, OR PLANT THEREON ANY VEGETATION THAT THE HIGHWAY AUTHORITIES MAY DEEM DESIRABLE, BUT WITHOUT PREJUDICE TO THE OWNER'S RIGHTS TO MAKE OR CONSTRUCT IMPROVEMENTS ON SAID LANDS OR TO FLATTEN THE SLOPES, PROVIDING SAID ACTIVITIES WILL NOT IMPAIR OR OTHERWISE ADVERSELY AFFECT THE HIGHWAY FACILITIES.								
AN EASEMENT FOR HIGHWAY PURPOSES (HE), AS LONG AS SO USED, INCLUDING THE RIGHT TO PRESERVE, PROTECT, REMOVE, OR PLANT THEREON ANY VEGETATION THAT THE HIGHWAY AUTHORITIES MAY DEEM DESIRABLE.								
R-17-E								
ACCEPTED FOR TOWN OF LINN								
4/3/2025								
Signed by:  (Signature and Title of Official)								
ORIGINAL PLANS PREPARED BY								
<p>WESTBROOK Associated Engineers, Inc. 619 East Hoxie St.   P.O. Box 429   Spring Green, WI 53588 p: (608) 588-7866   f: (608) 588-7954   www.westbrookeng.com</p>								
<p>WISCONSIN NICHOLAS J. BREY S-3145 LA VALLE WI LAND SURVEYOR</p>								
DATE: 03/28/2025								
(Professional Land Surveyor Signature)								





## Standard Detail Drawing List

08A05-22A	INLET COVERS TYPE A, H, A-S, H-S & Z
08A05-22E	INLET COVER TYPE BW, MANHOLE COVERS, TYPE K, J, J-S, L & M
08B09-04	MANHOLES 3-FT, 4-FT, 5-FT, 6-FT, 7-FT, 8-FT, 9-FT, 10-FT DIAMETER
08C06-03	INLETS 3-FT AND 4-FT DIAMETER
08C07-03	INLETS 2X2-FT, 2X2.5-FT, 2X3-FT, 2.5X3-FT & 2X3.5-FT
08D01-24A	CONCRETE CURB & GUTTER
08D01-24B	CONCRETE CURB, TIES AND CURB AND GUTTER APPLICATIONS
08D05-22E	CURB RAMPS TYPES 5, 6, 7A, 7B & 8
08D05-22G	CURB RAMPS RECTANGULAR AND RADIAL DETECTABLE WARNING PLATES
08D16-11	CONCRETE GUTTER, CURB AND GUTTER AND PAVEMENT TIES
08D17-06	MANHOLES, MANHOLE & INLET COVERS
08D18-05	DRIVEWAY AND SIDEWALK RAMPS TYPES X & Y
08E09-06	SILT FENCE
08E10-02	INLET PROTECTION TYPE A, B, C AND D
09C02-09	CONCRETE BASES, TYPES 1, 2, 5, & 6
12A03-10	NAME PLATE (STRUCTURES)
12A04-03	STRUCTURE IDENTIFICATION PLAQUES, RAMP GATES, SIGN BRIDGES & OVERHEAD SIGN SUPPORTS & TRAFFIC SIGNALS
13A03-07	CONCRETE PAVEMENT SHOULDERS
13B02-09A	CONCRETE PAVEMENT APPROACH SLAB
13C01-19	CONCRETE PAVEMENT LONGITUDINAL JOINTS AND TIES
13C19-03	HMA LONGITUDINAL JOINTS
15C02-09A	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C02-09B	BARRICADES AND SIGNS FOR VARIOUS CLOSURES
15C02-09C	DETOUR SIGNING FOR MAINLINE CLOSURES
15C02-09H	MODIFIED ROUTE ASSEMBLY FOR DETOUR SIGNING
15C05-05	TRAFFIC CONTROL, ADVANCE WARNING SIGNS 40 M.P.H. OR LESS TWO-WAY UNDIVIDED ROAD OPEN TO TRAFFIC
15C06-12	SIGNING & MARKING FOR TWO LANE BRIDGES
15C08-24A	PERMANENT LONGITUDINAL PAVEMENT MARKINGS
15C08-24B	TEMPORARY LONGITUDINAL PAVEMENT MARKING
15C11-10B	CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS
15D30-11A	TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION
15D30-11C	TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION
15D30-11F	TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION
15D30-11G	TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION
15D30-11K	TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION
15D30-11L	TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION
15D32-07	TRAFFIC CONTROL, ONE LANE ROAD STOP CONDITION





NOTE: EITHER CASTING IS ACCEPTABLE

TYPE "C" CHECKERED  
TOP DESIGN (OPTIONAL)

SEE LOGO DETAIL

NOTE: CURB BOX HEIGHT ADJUSTABLE 6" - 9"



**TYPE "H"**

NOTE: EITHER CASTING IS ACCEPTABLE

**SPECIAL GRATE FOR  
TYPE "H" COVER**



(MEASURES 35" X 17 3/4" X 2")

(NOTED AS TYPE H-S ON DRAINAGE TABLE)

**LOGO DETAIL**




NOTE: CURB BOX HEIGHT ADJUSTABLE 6" - 9"

NOTE: EITHER CASTING IS ACCEPTABLE



**GENERAL NOTES**

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

DETAIL DRAWINGS FOR PROPOSED ALTERNATE DESIGNS FOR CATCH BASIN, MANHOLE AND INLET COVERS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL PROVIDING THAT SUCH ALTERNATE DESIGNS MAKE PROVISION FOR EQUIVALENT CAPACITY AND STRENGTH. ROUND FRAMES AND COVERS SHALL HAVE CONTINUOUSLY MACHINED BEARING SURFACES TO PREVENT ROCKING AND RATTLING.

**SPECIAL GRATE FOR  
TYPE "A" COVER**

(MEASURES 19 3/4" X 17" X 1 7/8")  
(NOTED AS TYPE A-S ON DRAINAGE  
TABLE)

**TYPE "A"****TYPE "Z"****INLET COVERS  
TYPES A, H, A-S, H-S AND Z**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION



















APPROVED  
February 2025 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS DEVELOPMENT  
FHWA UNIT SUPERVISOR

## GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

DETAIL DRAWINGS FOR PROPOSED ALTERNATE DESIGNS FOR MANHOLE COVERS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL PROVIDING THAT SUCH ALTERNATE DESIGNS MAKE PROVISION FOR EQUIVALENT CAPACITY AND STRENGTH.

ROUND FRAMES AND COVERS SHALL HAVE CONTINUOUSLY MACHINED BEARING SURFACES TO PREVENT ROCKING AND RATTLING.



**TYPE "J"**

NOTE: EITHER CASTING IS ACCEPTABLE

**TYPE "J" SPECIAL**

TYPE "B" NON-ROCKING SELF-SEAL LID  
(NOTED AS TYPE J-S ON THE DRAINAGE TABLE)

NOTE: EITHER CASTING IS ACCEPTABLE


**TYPE "L"**

**TYPE "M"**


**INLET COVERS TYPES BW  
MANHOLE COVERS TYPES K,  
J, J-S, L, AND M**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
February 2025 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS DEVELOPMENT  
FHWA UNIT SUPERVISOR



**PLAN VIEW  
CIRCULAR OPENING**



**OPTIONAL PRECAST  
REINFORCED CONCRETE  
ECCENTRIC TOP**

**MANHOLE COVER OPENING MATRIX**

MANHOLE COVER OPENING SIZE (FT.)	C	ALL J'S	K	L	M
2 DIA.	X	X		X	
3 DIA.			X		X

**GENERAL NOTES**

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

UNLESS OTHERWISE AUTHORIZED IN WRITING BY THE ENGINEER, THE CONTRACTOR SHALL NOT ORDER AND DELIVER PRECAST MANHOLE UNITS REQUIRED FOR THE PROJECT UNTIL A LIST OF SIZES IS FURNISHED BY THE ENGINEER.

DETAILED DRAWINGS FOR PROPOSED ALTERNATE DESIGNS FOR UNDERGROUND DRAINAGE STRUCTURES SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL PROVIDING THAT SUCH ALTERNATE DESIGNS MAKE PROVISION FOR EQUIVALENT CAPACITY AND STRENGTH.

ALL DRAINAGE STRUCTURES ARE DESIGNATED ON THE PLANS AS "MANHOLES 3X3-L", "CATCH BASINS 4-B", "INLETS 2X3-H", ETC. THE FIRST NUMBERS DESIGNATE THE SIZE OF THE STRUCTURE, AND THE FOLLOWING LETTER DESIGNATES THE TYPE OF COVER TO BE USED TO COMprise THE COMPLETE UNIT.

BASES SHALL BE PLACED ON A BED OF MATERIAL AT LEAST 6 INCHES IN DEPTH, WHICH MEETS THE REQUIREMENTS OF FOUNDATION BACKFILL. THIS BEDDING SHALL BE COMPAKTED AND PROVIDE UNIFORM SUPPORT FOR THE ENTIRE AREA OF THE BASE.

PRECAST REINFORCED CONCRETE CONE TOPS (ECCENTRIC OR CONCENTRIC) OR PRECAST REINFORCED CONCRETE FLAT SLAB TOPS MAY BE USED ON CONCRETE BLOCK STRUCTURES.

ECCENTRIC CONE TOPS MAY BE USED ON ALL STRUCTURES. CONCENTRIC CONE TOPS SHALL BE USED ONLY ON STRUCTURES 5 FEET OR LESS IN DEPTH UNLESS OTHERWISE DIRECTED BY THE ENGINEER.

STEPS MEETING AASHTO M199 AND THE FOLLOWING REQUIREMENTS SHALL BE INSTALLED IN ALL STRUCTURES OVER 5 FEET IN DEPTH: 16 INCH C-C MAXIMUM SPACING; PROJECT A MINIMUM CLEAR DISTANCE OF 4 INCHES FROM THE WALL AT THE POINT OF EMBEDMENT; MINIMUM LENGTH OF 10 INCHES; MINIMUM WALL EMBEDMENT OF 3 INCHES. FERROUS METAL STEPS NOT PAINTED OR TREATED TO RESIST CORROSION SHALL HAVE A MINIMUM CROSS SECTIONAL IMENSION OF 1 INCH.

STEPS OF APPROVED POLYPROPYLENE PLASTIC COATED REINFORCEMENT BAR ARE ACCEPTABLE. REINFORCING BAR MUST BE A MINIMUM OF  $\frac{1}{2}$  INCH AND MEET THE REQUIREMENTS OF ASTM A615.

CERTIFICATION SHALL BE PROVIDED THAT INSTALLED STEPS WHEN TESTED IN ACCORDANCE WITH SECTION 10 OF AASHTO T280 CAN WITHSTAND A VERTICAL LOAD OF 800 LBS. AND A HORIZONTAL LOAD OF 400 LBS.

ALL BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2 INCHES CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

ALL PRECAST MANHOLE UNITS SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF AASHTO DESIGNATION M199.

PRECAST REINFORCED RISERS SHALL HAVE A TONGUE AND GROOVE JOINT WITH TONGUE UP OR DOWN.

CONCRETE BLOCK WILL NOT BE PERMITTED FOR STRUCTURES GREATER THAN 4 FEET IN DIAMETER.

4" OVERHANGING BASES ARE REQUIRED FOR ALL CONCRETE BLOCK INSTALLATIONS. 4" OVERHANG IS REQUIRED WHEN SEPARATE PRECAST BASE IS PROVIDED. OVERHANG IS NOT REQUIRED ON PRECAST STRUCTURES WITH AN INTEGRAL OR MONOLITHIC BASE.

FOR ADDITIONAL CONFIGURATIONS, MAINTAIN A MINIMUM OF 12 INCHES AS MEASURED FROM THE INSIDE OF THE STRUCTURE WALL BETWEEN THE OUTSIDE PIPE WALLS OF ADJACENT PIPES. SEE DETAIL "D".


① FOR PRECAST MANHOLES AND REINFORCED CONCRETE BASES PROVIDE REINFORCING STEEL IN ACCORDANCE TO AASHTO M199.

② SEE PIPE MATRIX TABLE FOR MINIMUM WALL THICKNESS FOR PRECAST MANHOLES

③ SEE PIPE MATRIX TABLE FOR MINIMUM THICKNESS OF PRECAST FLAT SLAB TOPS AND BASES.

④ JOINTS TO BE SEALED WITH A BUTYL RUBBER SEAL PER SEALANT MANUFACTURERS RECOMMENDATIONS CONFORMING TO ASTM C 990 OR RUBBER GASKETS CONFORMING TO ASTM C443.


⑤ SEE MANHOLE COVER OPENING MATRIX.




**PRECAST REINFORCED  
CONCRETE WITH  
MONOLITHIC BASE**

**CONCRETE BLOCK WITH  
CAST IN PLACE OR  
PRECAST REINFORCED  
CONCRETE BASE** ①

**OPTIONAL PRECAST  
REINFORCED CONCRETE  
CONCENTRIC TOP**




**SEPARATE PRECAST REINFORCED  
CONCRETE BASE OPTION**




**PRECAST REINFORCED CONCRETE  
WITH INTEGRAL BASE OPTION**


**DETAIL "A"**




**DETAIL "B"**



**DETAIL "C"**



**DETAIL "C"**




**MINIMUM HORIZONTAL  
PIPE SEPARATION**

**DETAIL "D"**


**MANHOLES, 3-FT, 4-FT  
5-FT, 6-FT, 7-FT, 8-FT, 9-FT  
AND 10-FT DIAMETER**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
December 2023 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS DEVELOPMENT UNIT SUPERVISOR  
FHWA



PLAN VIEW CIRCULAR OPENING



PLAN VIEW RECTANGULAR OPENING



PRECAST REINFORCED CONCRETE WITH MONOLITHIC BASE

CONCRETE BLOCK WITH CAST IN PLACE OR PRECAST REINFORCED CONCRETE BASE

CIRCULAR INLETS WITH FLAT TOP

## CATCH BASIN COVER OPENING MATRIX

INLET SIZE	INLET COVER TYPE	ALL A'S	ALL B'S	BW	C	F	ALL H'S	S	T	V	V-B	WM	Z
	OPENING SIZE (FT.)												
3-FT	2 DIA.						X						X
	2 X 2	X	X						X	X			
4-FT	2 DIA.						X						X
	2 X 2	X	X						X	X			
4-FT	2 X 2.5			X					X	X	X	X	
	2 X 3							X					
4-FT	2.5 X 3						X						

## GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

UNLESS OTHERWISE AUTHORIZED IN WRITING BY THE ENGINEER, THE CONTRACTOR SHALL NOT ORDER AND DELIVER PRECAST INLET UNITS REQUIRED FOR THE PROJECT UNTIL A LIST OF SIZES IS FURNISHED BY THE ENGINEER.

DETAILED DRAWINGS FOR PROPOSED ALTERNATE DESIGNS FOR UNDERGROUND DRAINAGE STRUCTURES SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL PROVIDING THAT SUCH ALTERNATE DESIGNS MAKE PROVISION FOR EQUIVALENT CAPACITY AND STRENGTH.

ALL DRAINAGE STRUCTURES ARE DESIGNATED ON THE PLANS AS "MANHOLES 3X3-L", "CATCH BASINS 4-B", "INLETS 2X3-H", ETC. THE FIRST NUMBERS DESIGNATE THE SIZE OF THE STRUCTURE, AND THE FOLLOWING LETTER DESIGNATES THE TYPE OF COVER TO BE USED TO COMprise THE COMPLETE UNIT.

BASES SHALL BE PLACED ON A BED OF MATERIAL AT LEAST 6 INCHES IN DEPTH, WHICH MEETS THE REQUIREMENTS OF FOUNDATION BACKFILL. THIS BEDDING SHALL BE COMPAKTED AND PROVIDE UNIFORM SUPPORT FOR THE ENTIRE AREA OF THE BASE.

ALL BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2 INCHES CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

ALL PRECAST INLET UNITS SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF AASHTO DESIGNATION M199.

PRECAST REINFORCED RISERS SHALL HAVE A TONGUE AND GROOVE JOINT WITH TONGUE UP OR DOWN.

4" OVERHANGING BASES ARE REQUIRED FOR ALL CONCRETE BLOCK INSTALLATIONS. 4" OVERHANG IS REQUIRED WHEN SEPARATE PRECAST BASE IS PROVIDED. OVERHANG IS NOT REQUIRED ON PRECAST STRUCTURES WITH AN INTEGRAL OR MONOLITHIC BASE.

FOR ADDITIONAL CONFIGURATIONS, MAINTAIN A MINIMUM OF 12 INCHES AS MEASURED FROM THE INSIDE OF THE STRUCTURE WALL BETWEEN THE OUTSIDE PIPE WALLS OF ADJACENT PIPES. SEE DETAIL "D".


① MINIMUM WALL THICKNESS SHALL BE 4 INCHES FOR 3-FT DIAMETER AND 5 INCHES FOR 4-FT DIAMETER PRECAST INLETS.

② FOR PRECAST INLETS AND REINFORCED CONCRETE BASES PROVIDE REINFORCING STEEL IN ACCORDANCE TO AASHTO M199.

③ JOINTS TO BE SEALED WITH A BUTYL RUBBER SEAL PER SEALANT MANUFACTURERS RECOMMENDATIONS CONFORMING TO ASTM C 990 OR RUBBER GASKETS CONFORMING TO ASTM C443.

## PIPE MATRIX


INLET SIZE	MAXIMUM INSIDE PIPE DIAMETER FOR TWO PIPES	
	180° SEPARATION (IN)	90° SEPARATION (IN)
3-FT	15	12
4-FT	24	18




SEPARATE PRECAST REINFORCED CONCRETE BASE OPTION

PRECAST REINFORCED CONCRETE WITH INTEGRAL BASE OPTION


DETAIL "A"




TOP WITH PLAIN END JOINT



TOP WITH TONGUE AND GROOVE JOINT




RISER WITH TONGUE AND GROOVE JOINT

MINIMUM HORIZONTAL PIPE SEPARATION  
DETAIL "D"


## INLETS 3-FT AND 4-FT DIAMETER

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
December 2023 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS DEVELOPMENT  
FHWA UNIT SUPERVISOR




PLAN VIEW




**PRECAST REINFORCED CONCRETE WITH MONOLITHIC BASE**    **PRECAST REINFORCED CONCRETE WITH INTEGRAL BASE**


































































SECTION A - A


**SEPARATE PRECAST REINFORCED CONCRETE BASE OPTION**

DETAIL "B"


**INLETS 2 X 2-FT, 2 X 2.5-FT, 2 X 3-FT, 2.5 X 3-FT AND 2X3.5-FT**

DETAIL "A"








TYPES A (1) &amp; D



6" SLOPED CURB TYPES G (1) &amp; J




4" SLOPED CURB TYPES G (1) &amp; J

TYPES K (1) & L  
(OPTIONAL CURB SHAPE)


TYPES K (1) &amp; L

CONCRETE CURB AND GUTTER 30"




TYPES A (1) &amp; D

CONCRETE CURB AND GUTTER 18"




6" SLOPED CURB TYPES A (1) &amp; D




4" SLOPED CURB TYPES A (1) &amp; D

CONCRETE CURB AND GUTTER 36"

4" SLOPED CURB TYPES R (1) & T  
CONCRETE CURB AND GUTTER 30"

TBT & TBTT	X
30"	22"
36"	28"




TYPES TBT &amp; TBTT (1)



CONCRETE CURB AND GUTTER

PAVEMENT THICKNESS  
AND MAXIMUM CONCRETE  
PANEL WIDTH TABLE

PAVEMENT THICKNESS	MAXIMUM PANEL WIDTH
LESS THAN 10"	12'
10" & ABOVE	15'

PARTIAL SECTION OF PAVEMENT  
WITH INTEGRAL CURB AND GUTTER

\* BIKE LANE IS NOT SHOWN

REVERSE SLOPE GUTTER  
(TYPICAL FOR ALL CURB & GUTTER TYPES)

3" SLOPED CURB TYPES R (1) &amp; T

CONCRETE CURB AND GUTTER

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

## GENERAL NOTES



DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

PAVEMENT TIES AND TIE BARS SHALL BE EPOXY COATED IN CONFORMANCE WITH SUBSECTION 505.2.6.2 OF THE STANDARD SPECIFICATIONS.

INTEGRAL CURB AND GUTTER SHALL CONFORM TO THE DETAILS SHOWN FOR CONCRETE CURB AND GUTTER INCLUDING THE TRANSVERSE GUTTER SLOPE.

UNLESS OTHERWISE SHOWN ON THE TYPICAL CROSS SECTIONS, THE BASE AGGREGATE AND COMMON EXCAVATION LIMITS ARE 2' - 0" BEHIND THE BACK OF CURBS.

- ① TIE BARS ARE REQUIRED FOR CURB AND GUTTERS TYPES A, G, K, R, AND TBTT.
- ② THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE AGGREGATE PROVIDED A 6" MINIMUM GUTTER THICKNESS IS MAINTAINED.
- ③ USE 8" MINIMUM GUTTER THICKNESS WHEN USED WITH AN ADJACENT CONCRETE TRUCK APRON PLACED BEHIND BACK OF CURB.
- ④ THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE AGGREGATE PROVIDED A 8" MINIMUM GUTTER THICKNESS IS MAINTAINED.
- ⑤ UNLESS OTHERWISE NOTED, FOR STAKING PURPOSES THE FACE OF CURB IS 6" FROM THE BACK OF CURB.
- ⑥ WHEN REVERSE SLOPE GUTTER IS REQUIRED, THE LOCATION(S) WILL BE SHOWN ELSEWHERE IN THE PLAN.
- ⑦ USE 4% GUTTER CROSS SLOPE UNLESS OTHERWISE NOTED IN THE PLANS.
- ⑧ INCLUDE LONGITUDINAL JOINT AND TIE BARS ALONG LANE EDGE WHEN CONCRETE PANEL WIDTH EXCEEDS THE MAXIMUM WIDTH PER TABLE BELOW. LONGITUDINAL JOINT(S) ARE NOT ALLOWED WITHIN TRAFFIC LANES AND BIKE LANES. LONGITUDINAL JOINT MAY BE SAWED.
- ⑨ SLOPE TO BE REVERSE SLOPE MATCHING THE SLOPE OF THE PAVEMENT AND THE CIRCULATORY ROADWAY








**END SECTION CURB AND GUTTER****GENERAL NOTES**

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

PAVEMENT TIES AND TIE BARS SHALL BE EPOXY COATED IN CONFORMANCE WITH SUBSECTION 505.2.6.2 OF THE STANDARD SPECIFICATIONS.

UNLESS OTHERWISE SHOWN ON THE TYPICAL CROSS SECTIONS, THE BASE AGGREGATE AND COMMON EXCAVATION LIMITS ARE 2'-0" BEHIND THE BACK OF CURBS.


- ① TIE BARS ARE REQUIRED FOR CURB AND GUTTERS TYPES A, G, K, R, AND TBTT.
- ② THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE AGGREGATE PROVIDED A 6" MINIMUM GUTTER THICKNESS IS MAINTAINED.
- ⑩ REFER TO SDD 08D18 AND 08D19 FOR ADDITIONAL DRIVEWAY ENTRANCE CURB DETAILS.
- ⑪ PLACE 1" THICK EXPANSION JOINT MATERIAL BETWEEN VERTICAL FACE CURB TYPES EXTENDING FROM THE TOP OF CURB TO 1 INCH BELOW THE ADJOINING CONCRETE SURFACE. RIGID CONCRETE STRUCTURES INCLUDE RAISED CONCRETE MEDIANIS, CONCRETE SAFETY ISLANDS, SPLITTER ISLANDS, OR LOCATIONS IDENTIFIED ON THE PLANS.

**TYPES A ① & D****CONCRETE CURB****EXPANSION JOINT DETAIL FOR VERTICAL CURB ABUTTING A RIGID STRUCTURE ⑪****PLAN VIEW****SECTION A - A**  
**TIE BARS DRILLED INTO EXISTING PAVEMENT****TYPICAL TIE BAR LOCATION****DRIVEWAY ENTRANCE CURB**


(WHEN DIRECTED BY THE ENGINEER)

⑩

**CONCRETE CURB, TIES AND CURB AND GUTTER APPLICATIONS**STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATIONAPPROVED  
February 2025  
/S/ Rodney Taylor  
DATE  
ROADWAY STANDARDS DEVELOPMENT  
UNIT SUPERVISOR  
FHWA




**CURB RAMP TYPE 8  
DETECTABLE WARNINGS  
FOR SIDEWALKS OR SHARED USE PATHS  
AT RAILROAD CROSSINGS**




## **CURB RAMP TYPE 6 DETECTABLE WARNING AT ISLANDS**


REFER TO GENERAL NOTES (2) AND (3)  
FOR ALL ISLAND CURB RAMPS



**CURB RAMP TYPE 5  
MEDIAN ISLAND  
NON-ELEVATED PEDESTRIAN CROSSING**



## **CURB RAMP TYPE 7A FOR INTERSECTIONS AND MID BLOCK CROSSINGS**



## **CURB RAMP TYPE 7B FOR INTERSECTIONS AND MID BLOCK CROSSINGS**


## **GENERAL NOTES**

AVOID PLACING DRAINAGE STRUCTURES, JUNCTION BOXES OR OTHER OBSTRUCTIONS IN FRONT OF CURB RAMP ACCESS AREAS.  
DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO  
THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.  
SIDEWALK CROSS SLOPE SHALL NOT EXCEED 2.1%.  
DETECTABLE WARNING FIELDS THAT ARE INSTALLED AS A GROUP OR SIDE BY SIDE, SHALL BE FROM THE SAME MANUFACTURER.

- ② GRADE CHANGE BETWEEN GUTTER COUNTER SLOPE AND THE CURB RAMP SLOPE IS DESIRABLY 11% OR LESS AND SHALL NOT EXCEED 13.3%. TYPICAL GUTTER COUNTER SLOPE IS 4% BUT MAY BE MODIFIED TO FIT FIELD CONDITIONS. PROVIDE LONGITUDINAL DRAINAGE AROUND CURB AND AWAY FROM CURB RAMP. NO VERTICAL LIPS OR DISCONTINUITIES ARE ALLOWED. SLOPE OF CURB HEAD OPENING SHALL MATCH THE RAMP SLOPE, MINIMALLY 1.5%, DESIRABLY 7% OR LESS, AND SHALL NOT EXCEED A MAXIMUM OF 8.3%. WHEN ADJACENT TO 1.5% LANDING, CONSTRUCT CURB HEAD OPENING AT 1.5% IN THE DIRECTION OF PEDESTRIAN TRAVEL.
- ③ MAXIMUM 8.3% CURB RAMP SLOPE IS ALLOWABLE WITH GUTTER COUNTER SLOPE OF 5% MAXIMUM AND A 13.3% MAXIMUM GRADE CHANGE.
- ④  $\pm 0.5\%$  CONSTRUCTION TOLERANCE IN SIDEWALK CROSS SLOPE. THE SIDEWALK CROSS SLOPE SHALL NOT EXCEED 2.1% WITHOUT PRIOR APPROVAL FROM THE ENGINEER.
- ⑥ PROVIDE A 5 FOOT BY 5 FOOT LANDING. SLOPE PERPENDICULAR TO CURB SHALL BE 2.1% MAXIMUM. SLOPE PARALLEL TO CURB SHALL MATCH THE CURB AND GUTTER LONGITUDINAL SLOPE.
- ⑩ INSTALL TRANSITION NOSE (INCIDENTAL TO OTHER PAY ITEMS). DO NOT MARK TRANSITION NOSE.
- ⑪ SLOPE SIDEWALK TOWARD LANDING AS SHOWN WHERE THERE IS NO TERRACE OR WHERE THE TERRACE WIDTH IS LESS THAN 6 FEET WIDE.
- ⑫ THE EDGE OF THE DETECTABLE WARNING FIELD NEAREST TO A RAILROAD CROSSING SHALL BE 1.5 FEET  $\pm 0.1'$  FROM THE FACE OF THE GATE ARM IF THE GATE ARM EXTENDS ACROSS THE SIDEWALK/PATH. WHERE THERE IS NO PEDESTRIAN GATE, THE EDGE OF THE DETECTABLE WARNING FIELD NEAREST TO THE RAILROAD TRACK IS 15 FEET MAXIMUM AND 12 FEET MINIMUM, 15 FEET TYPICAL FROM THE NEAREST RAIL.
- ⑯ DO NOT INSTALL DETECTABLE WARNING FIELDS AT THE EDGES OF STREET-LEVEL PEDESTRIAN REFUGE ISLANDS IF A MINIMUM 2 FOOT CONCRETE SURFACE WITHOUT DETECTABLE WARNINGS (MEASURED IN THE DIRECTION OF PEDESTRIAN TRAVEL) CANNOT BE ACHIEVED.
- ⑰ A MAXIMUM 2-INCH CONCRETE BORDER IS PERMITTED ALONG ALL SIDES OF THE DETECTABLE WARNING FIELD SURFACE.
- ⑱ WHEN THE DISTANCE BETWEEN THE BACK OF CURBS IS LESS THAN 6 FEET BUT THE FACE OF CURB TO FACE OF CURB DISTANCE IS 6 FEET OR GREATER THEN THE DETECTABLE WARNING FIELDS MAY BE MOVED SO THAT THE EDGE OF THE WARNING FIELD IS PLACED AT THE GUTTER FLOWLINE. MAINTAIN A MINIMUM OF TWO FEET BETWEEN DETECTABLE WARNING FIELD PANELS.
- ㉑ THE ENTIRE RAMP SHALL BE A PLANAR SURFACE. DO NOT WARP THE RUNNING SLOPE OR CROSS SLOPE OF THE RAMP. WARPING OF THE SIDEWALK CROSS SLOPE SHALL TAKE PLACE BETWEEN THE LANDING AND MATCH POINT.

## LEGEND

- ===== **1/2" EXPANSION JOINT SIDEWALK**
- - - - - **CONTRACTION JOINT FIELD LOCATED**
- ||||||||||| **PAVEMENT MARKING CROSSWALK (WHITE)**
- \*** **MAXIMUM 8.3%**
- \*\*** **1% MINIMUM (PROVIDE DRAINAGE)**
- \*\*\*** **DETAILS TO BE DETERMINED BY ENGINEER**
- \*\*\*\*** **FOR SHARED USE PATHS, WIDTH MUST BE AS WIDE AS THE CROSSWALK**
  - 6' - 0" MIN.
  - LANDING




**SECTION B - B FOR TYPE 7A**

## **CURB RAMPS TYPE 5, 6, 7A, 7B & 8**



STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

	MIN.	MAX.
<b>A</b>	1.6"	2.4"
<b>B</b>	0.65"	1.5"
<b>C</b>	*	*
<b>D</b>	0.9"	1.4"


\* THE C DIMENSION IS 50% TO 65% OF THE D DIMENSION.



PLAN VIEW



DETECTABLE WARNING FIELD  
PLANAR INSTALLATION

### TRUNCATED DOMES DETECTABLE WARNING PATTERN DETAIL

RECTANGULAR  
PLATES

PLAN VIEW

## DETECTABLE WARNING FIELDS (TYPICAL)


PLAN VIEW  
RADIAL DETECTABLE  
WARNING FIELD ATTRIBUTESPLAN VIEW  
RADIAL WEDGE PLATE  
CONNECTION DETAIL

### CURB RAMPS RECTANGULAR AND RADIAL DETECTABLE WARNING PLATES


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
February 2025  
DATE  
FHWA


/S/ Rodney Taylor  
<position>




**CONCRETE CURB AND GUTTER 31"** <sup>①</sup>




**CONCRETE CURB AND GUTTER 22"** <sup>①</sup>




**CONCRETE CURB AND GUTTER 19"** <sup>①</sup>




**CONCRETE GUTTER 24"** <sup>①</sup>




**END SECTION CURB AND GUTTER**



**PARTIAL SECTION OF PAVEMENT WITH INTEGRAL CURB AND GUTTER**



**TYPICAL TIE BAR LOCATION** <sup>①</sup>



**HIGH SIDE SECTION** <sup>③</sup>  
(TYPICAL FOR ALL CURB & GUTTER TYPES)

## GENERAL NOTES


DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

PAVEMENT TIES AND TIE BARS SHALL BE EPOXY COATED IN CONFORMANCE WITH SUBSECTION 505.2.6.2 OF THE STANDARD SPECIFICATIONS.


INTEGRAL CURB AND GUTTER SHALL CONFORM TO THE DETAILS SHOWN FOR CONCRETE CURB AND GUTTER INCLUDING THE TRANSVERSE GUTTER SLOPE. A LONGITUDINAL CONSTRUCTION JOINT IS NOT REQUIRED WITH INTEGRAL CURB AND GUTTER.

UNLESS OTHERWISE SHOWN ON THE TYPICAL CROSS SECTIONS, THE BASE COURSE AND UNCLASSIFIED EXCAVATION LIMITS ARE 2' - 0" BEHIND THE BACK OF CURBS.

- ① WHEN PLACED ADJACENT TO NEW CONCRETE, TIE BARS ARE REQUIRED FOR CURB AND GUTTER 31", 22", 19" AND CONCRETE GUTTER 24".
- ② THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE COURSE PROVIDED A 7" MINIMUM GUTTER THICKNESS IS MAINTAINED.
- ③ WHEN HIGH SIDE CURB SECTION IS REQUIRED, THE LOCATION(S) WILL BE NOTED ON THE PLANS



**PLAN VIEW**



**SECTION A - A**

## PAVEMENT TIES


## CONCRETE GUTTER, CURB AND GUTTER AND PAVEMENT TIES

(For Optional use in Milwaukee Co. Only)


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
February 2020 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS DEVE  
FHWA ENGINEER 25





**TYPE X**  
**SIDEWALK ABUTS CURB AND GUTTER**  
**TERRACE VARIES 0 TO 3 FEET**



**TYPE Y**  
**SIDEWALK WITH NARROWER TERRACE**  
**TERRACE VARIES 4 TO 6 FEET**

#### GENERAL NOTES

PROVIDE CONSTRUCTION JOINTS ALONG THE CENTER OF THE CONCRETE FOR DRIVEWAYS UNDER 20 FEET IN WIDTH AND AT THE THIRD POINTS OVER 20 FEET IN WIDTH.

(W) IS SHOWN ON PLAN AND PROFILE SHEETS.

OFFSETS, ELEVATIONS, AND PERCENT GRADE ARE SHOWN ON THE CROSS SECTIONS.

(1) CONSTRUCTION TOLERANCE OF  $0.5\% \pm$  FOR SIDEWALK CROSS SLOPE. THE SIDEWALK CROSS SLOPE SHALL NOT EXCEED 2.1%.

(2) THE SIDEWALK RAMP MAXIMUM RUNNING SLOPE SHALL NOT REQUIRE THE RAMP LENGTH TO EXCEED 15 FEET TO AVOID CHASING THE SLOPE INDEFINITELY WHEN CONNECTING TO STEEP GRADES. WHEN APPLYING THE 15 FOOT MAXIMUM LENGTH, THE RUNNING SLOPE OF THE SIDEWALK SHALL BE AS FLAT AS FEASIBLE AND NOT EXCEED THE LONGITUDINAL GRADE OF THE ROADWAY. SLOPE SIDEWALK RAMP TOWARD APRON AS SHOWN WHERE THERE IS NO TERRACE OR WHERE THE TERRACE WIDTH IS LESS THAN 6 FEET WIDE.



(3) DRIVEWAY SLOPES: DESIRABLE MAXIMUM 10.5% UP AWAY FROM SIDEWALK (SAG)  
8.5% DOWN AWAY FROM SIDEWALK (CREST)  
ABSOLUTE MAXIMUM 15% FOR BOTH CREST AND SAG

(4) DRIVEWAY TYPES  
\* 6-INCH CONCRETE DRIVEWAY PAVEMENT OVER 6-INCH BASE AGGREGATE  
\* 2-INCH TO 3-INCH ASPHALTIC SURFACE OVER 6-INCH BASE AGGREGATE  
\* 6-INCH BASE AGGREGATE (MAY BE INCREASED FOR CLAY SUBGRADES.)

(5) 1/2" EXPANSION JOINT FILLER

DETECABLE WARNING FIELDS ARE REQUIRED WHEN A PEDESTRIAN CIRCULATION ROUTE CROSSES A DRIVEWAY THAT IS TRAFFIC SIGNAL, STOP, OR YIELD SIGN CONTROLLED. DETECTABLE WARNING FIELDS TO BE 2 FT DEEP AND EXTEND THE WIDTH OF THE PEDESTRIAN CIRCULATION ROUTE.

(6) DETECTABLE WARNING FIELDS ARE REQUIRED WHEN A PEDESTRIAN CIRCULATION ROUTE CROSSES A DRIVEWAY THAT IS TRAFFIC SIGNAL, STOP, OR YIELD SIGN CONTROLLED. DETECTABLE WARNING FIELDS TO BE 2 FT DEEP AND EXTEND THE WIDTH OF THE PEDESTRIAN CIRCULATION ROUTE.




**SECTION X - X**  
**4% GUTTER SLOPE**

(W): 12' MIN. - 24' MAX. RESIDENTIAL AND NON-COMMERCIAL (PE & FE)  
16' MIN. - 35' MAX. COMMERCIAL (CE)


**TABLE Y**

(A) FEET	(C) FEET
3.5'	2.0'
4.5'	3.0'
5.5'	3.5'



NOTE: SIDEWALK MAY BE DEPRESSED IN DRIVEWAY AREAS


**SECTION Y - Y**  
**DRIVEWAY DETAIL WITH CONCRETE CURB AND GUTTER**  
**(URBAN AND SUBURBAN)**




**DRIVEWAY AND SIDEWALK RAMPS**  
**TYPES X AND Y**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
February 2025 /S/ Rodney Taylor  
DATE  
FHWA



PLAN VIEW  
TYPICAL APPLICATION OF SILT FENCE




### SILT FENCE AT MEDIAN SURFACE DRAINS


#### GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND APPLICABLE SPECIAL PROVISIONS.


- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1/8" X 1/8" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.




TRENCH DETAIL



SILT FENCE




JOINING TWO LENGTHS OF SILT FENCE<sup>⑤</sup>



SILT FENCE TIE BACK  
(WHEN REQUIRED BY THE ENGINEER)

SILT FENCE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED	/S/ Beth Cannon
4-29-05	DATE
CHIEF ROADWAY DEVELOP 28	
FHWA	



### INLET PROTECTION, TYPE A

#### GENERAL NOTES

INLET PROTECTION DEVICES SHALL BE MAINTAINED OR REPLACED AT THE DIRECTION OF THE ENGINEER.


MANUFACTURED ALTERNATIVES APPROVED AND LISTED ON THE DEPARTMENT'S EROSION CONTROL PRODUCT ACCEPTABILITY LIST MAY BE SUBSTITUTED.

WHEN REMOVING OR MAINTAINING INLET PROTECTION, CARE SHALL BE TAKEN SO THAT THE SEDIMENT TRAPPED ON THE GEOTEXTILE FABRIC DOES NOT FALL INTO THE INLET. ANY MATERIAL FALLING INTO THE INLET SHALL BE REMOVED IMMEDIATELY.

① FINISHED SIZE, INCLUDING FLAP POCKETS WHERE REQUIRED, SHALL EXTEND A MINIMUM OF 10" AROUND THE PERIMETER TO FACILITATE MAINTENANCE OR REMOVAL.


② FOR INLET PROTECTION, TYPE C (WITH CURB BOX), AN ADDITIONAL 18" OF FABRIC IS WRAPPED AROUND THE WOOD AND SECURED WITH STAPLES. THE WOOD SHALL NOT BLOCK THE ENTIRE HEIGHT OF THE CURB BOX OPENING.

③ FLAP POCKETS SHALL BE LARGE ENOUGH TO ACCEPT WOOD 2x4.



### INLET PROTECTION, TYPE B (WITHOUT CURB BOX)

(CAN BE INSTALLED IN ANY INLET WITHOUT A CURB BOX)



### INLET PROTECTION, TYPE C (WITH CURB BOX)

#### INSTALLATION NOTES

##### TYPE B & C

TRIM EXCESS FABRIC IN THE FLOW LINE TO WITHIN 3" OF THE GRATE.


THE CONTRACTOR SHALL DEMONSTRATE A METHOD OF MAINTENANCE, USING A SEWN FLAP, HAND HOLDS OR OTHER METHOD TO PREVENT ACCUMULATED SEDIMENT FROM ENTERING THE INLET.

##### TYPE D

DO NOT INSTALL INLET PROTECTION TYPE D IN INLETS SHALLOWER THAN 30", MEASURED FROM THE BOTTOM OF THE INLET TO THE TOP OF THE GRATE.

TRIM EXCESS FABRIC IN THE FLOW LINE TO WITHIN 3" OF THE GRATE.

THE INSTALLED BAG SHALL HAVE A MINIMUM SIDE CLEARANCE, BETWEEN THE INLET WALLS AND THE BAG, MEASURED AT THE BOTTOM OF THE OVERFLOW HOLES, OF 3". WHERE NECESSARY THE CONTRACTOR SHALL CINCH THE BAG, USING PLASTIC ZIP TIES, TO ACHIEVE THE 3" CLEARANCE. THE TIES SHALL BE PLACED AT A MAXIMUM OF 4" FROM THE BOTTOM OF THE BAG.



### INLET PROTECTION, TYPE D

(CAN BE INSTALLED IN ANY INLET TYPE WITH OR WITHOUT A CURB BOX AS PER NOTE ②)

#### INLET PROTECTION TYPE A, B, C, AND D

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
10/16/02 /S/ Beth Conner  
DATE 29  
FHWA CHEF ROADWAY DEVELOPMENT ENGINEER

FORM DEPTH SHALL BE NO MORE THAN 6" BELOW GRADE ON THE LOWER SIDE OF BASE

QUANTITY REQUIREMENTS	CONCRETE BASE TYPE		
	1	2	5 & 6
APPROX. CUBIC YARDS OF CONCRETE	0.40	0.57	0.40
LBS. OF HOOP BAR STEEL	NONE	23	16
LBS. OF VERTICAL BAR STEEL	NONE	60	18

**FORMING DETAIL**

**TYPE 1**

**TYPE 2**

**CONCRETE BASES**

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

BASES SHALL BE EXCAVATED BY USE OF A CIRCULAR AUGER.

TOP SURFACES OF CONCRETE BASES SHALL BE TROWEL FINISHED SMOOTH AND LEVEL.

CONDUIT SIZES AND LOCATIONS SHALL BE SHOWN ON THE PLANS.

THE FINAL OR TERMINATING CONCRETE BASE IN A CONDUIT RUN SHALL HAVE A 6" EXIT STUB INSTALLED FOR FUTURE CABLING USE. THE EXIT STUB SHALL BE SIZED AS USED THROUGHOUT THE CONDUIT RUN AS SHOWN AT THE ENTRANCE OF THE BASE.

ENDS OF CONDUIT INSTALLED BELOW GRADE FOR FUTURE USE SHALL BE CAPPED IF METALLIC OR PLUGGED IF NON-METALLIC.

MINIMUM BENDING RADIUS OF CONDUIT IS EQUAL TO 6X THE DIAMETER.

CONDUIT HEIGHT ABOVE CONCRETE BASES SHALL BE 1 INCH. ALL METALLIC CONDUIT ENDS SHALL BE REAMED AND THREADED.

ALL CONDUIT ENDS AT THE TOP OF CONCRETE BASES SHALL BE CAPPED IF METALLIC OR PLUGGED IF NON-METALLIC IMMEDIATELY AFTER PLACEMENT AND BEFORE CONCRETE IS POURED. CONDUITS IN WHICH WIRE OR CABLE IS NOT INSTALLED SHALL REMAIN CAPPED OR PLUGGED.

BELL ENDS SHALL BE INSTALLED ON ALL PVC CONDUIT EXPOSED AT THE TOP OF CONCRETE BASES BEFORE INSTALLATION.

WHEN REQUIRED TO CONNECT NON-METALLIC CONDUIT TO METALLIC CONDUIT, ONLY ADAPTER FITTINGS, U.L. LISTED FOR ELECTRICAL USE, SHALL BE USED.

IF A BASE REQUIRES A DEEP FORM BECAUSE OF LOOSE DIRT OR FILL, THE FORM SHALL BE REMOVED BEFORE BACKFILLING AROUND THE BASE. BACKFILL SHALL BE TAMPED TIGHT AGAINST THE BARE CONCRETE BASE IN LAYERS OF 1 FOOT OR LESS.

A NO. 4 AWG STRANDED COPPER EQUIPMENT GROUNDING CONDUCTOR SHALL BE EXOTHERMICALLY WELDED TO THE EQUIPMENT GROUNDING ELECTRODE (GROUND ROD) FOR TYPE 2, TYPE 5 AND TYPE 6 BASES.

THE EQUIPMENT GROUNDING CONDUCTOR SHALL BE FURNISHED AND INSTALLED TO ENTER ALL BASE TYPES THROUGH A 1 INCH CONDUIT INSTALLED FOR GROUNDING PURPOSES, LEAVING A 4 FOOT COIL OF WIRE ABOVE THE CONCRETE BASE. THE EQUIPMENT GROUNDING CONDUCTOR SHALL BE NEATLY COILED AND THE COILS TIED TOGETHER.

ANCHOR RODS SHALL BE THREADED 12" IN LENGTH ON EACH END OF THE ROD. ANCHOR RODS SHALL BE MANUFACTURED IN ACCORDANCE WITH SECTION 654.2.1 OF THE STANDARD SPECIFICATIONS.

WASHERS AND LOCK WASHERS ARE REQUIRED ON ALL ANCHOR RODS.

WHEN ANCHOR RODS USING THE ALTERNATE "L" BEND ARE FURNISHED, THE 4 INCH "L" BEND SHALL BE IN ADDITION TO THE SPECIFIED ANCHOR ROD BAR LENGTH. THE "L" BEND SHALL NOT BE THREADED.

ANCHOR RODS SHALL BE INSTALLED WITH MISALIGNMENTS OF LESS THAN 1:40 FROM VERTICAL.

WELDING OF THE ANCHOR RODS TO THE CAGE IS UNACCEPTABLE. TIE WIRES SHALL BE USED.

BAR STEEL REINFORCEMENT SHALL BE COATED WITH POWDERED EPOXY RESIN IN ACCORDANCE WITH SECTION 505 OF THE STANDARD SPECIFICATIONS (LATEST EDITION).

**TYPE 5 & 6**

**CONCRETE BASES TYPES 1, 2, 5, & 6**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2019  
/S/ Ahmet Demirbilek  
DATE  
FHWA


STATE ELECTRICAL ENGI 30

## GENERAL NOTES

NAME PLATES TO BE INSTALLED ON BRIDGES, CULVERTS, AND RETAINING WALLS SHALL CONFORM TO THE REQUIREMENTS OF SECTION 502.3.11 OF THE STANDARD SPECIFICATIONS.


THE BRIDGE NUMBER AND YEAR BUILT SHOWN ON THIS DRAWING ARE EXAMPLES ONLY. SEE CONSTRUCTION PLANS FOR INDIVIDUAL NUMBERING AND YEAR BUILT.

- ① EPOXY RESIN SHALL BE FROM AN APPROVED MANUFACTURER AND USED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- ② REHABILITATION OF AN EXISTING STRUCTURE SHOULD USE THE DATE OF ORIGINAL STRUCTURE CONSTRUCTION.





**TYPICAL NAME PLATE**  
(BRIDGES, CULVERTS, AND RETAINING WALLS)

6




**NUMBERING DESIGNATION**  
**MULTI-UNIT STRUCTURES**

S.D.D. 12 A 3-10



**ALTERNATE LUG**  
(FOR ATTACHMENT TO PRECAST STRUCTURES)

<b>NAME PLATE (STRUCTURES)</b>
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION
APPROVED 3/26/10      /S/ Scot Beck DATE      CHIEF STRUCTURAL DEVELOP 31 FHWA



RAMP GATE, SIGN BRIDGE, OVERHEAD SIGN SUPPORT AND TRAFFIC SIGNAL  
STRUCTURE PLAQUE FOR SIGN BRIDGES AND OVERHEAD SIGN  
SUPPORT WHICH ARE NOT STRUCTURE MOUNTED

## GENERAL NOTES

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN IN THIS DRAWING  
SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

PLAQUES SHALL BE INCIDENTAL TO ALL NEW INSTALLATIONS.

IF THE PROPOSED SIGN BRIDGE OR OVERHEAD SIGN SUPPORT IS REPLACING AN EXISTING SIGN BRIDGE OR OVERHEAD SIGN SUPPORT, A NEW IDENTIFICATION PLAQUE WILL BE REQUIRED.

FASTEN TOP, CENTER AND BOTTOM OF PLAQUE TO POLE OR OTHER LOCATION AS FOLLOWS:

**GALVANIZED STEEL SHAFT - 3 STAINLESS STEEL POP RIVETS**

A588 STEEL SHAFT - SHIM FOR DRAINAGE WITH STAINLESS WASHERS;  
FASTEN WITH STAINLESS SELF-TAPPING SCREWS

ALUMINUM SHAFTS - 3 ALUMINUM POP RIVETS

MOUNTING HEIGHT SHALL BE APPROXIMATELY 5.0' ABOVE CURB OR SHOULDER. ADJUST IF IT IS KNOWN THAT REQUIRED TRAFFIC SIGNS WILL OBSTRUCT.

## PLAQUE MATERIALS:

BASE - SHEET ALUMINUM, 0.060" THICK.


FACE - WHITE, SELF-ADHESIVE VINYL SHEETING, NON-RETROREFLECTIVE

LINES - BLACK,  $\frac{1}{2}$ " WIDE, SELF-ADHESIVE

CHARACTERS:- BLACK, SELF ADHESIVE, SERIES "D", SIZE AS SHOWN.

FOR SIGN BRIDGES, STRUCTURE MOUNTED, THE STRUCTURE PLAQUE SHALL BE MOUNTED HORIZONTALLY AS SHOWN ON THE DRAWING. THE STRUCTURE PLAQUE SHALL BE MOUNTED HORIZONTALLY TO THE BACK OF THE SIGN, BETWEEN THE ALUMINUM EXTRUSIONS, NEAR THE TOP LEFT HAND CORNER OF THE SIGN. THE BASE MATERIAL SHALL BE OMITTED AND THE FACE ADHERED DIRECTLY TO THE ALUMINUM SURFACE. PRIOR TO ADHERING THE MATERIAL, THE ALUMINUM SURFACE SHALL BE SMOOTH, CLEAN AND DRY.


WHERE SIGN BRIDGE ILLUMINATION IS PROVIDED, THE STRUCTURE MUST ALSO HAVE A SIGN BRIDGE CIRCUIT PLAQUE AS SHOWN IN THE ELECTRICAL DETAILS.



**IDENTIFICATION PLAQUE FOR SIGN BRIDGE,  
STRUCTURE MOUNTED**

\*\* LETTER "G" UTILIZED FOR RAMP GATES.  
LETTER "S" UTILIZED FOR SIGN BRIDGES,  
OVERHEAD SIGN SUPPORTS, AND TRAFFIC  
SIGNALS.

<p style="text-align: center;"><b>STRUCTURE IDENTIFICATION PLAQUES, RAMP GATES, SIGN BRIDGES, OVERHEAD SIGN SUPPORTS, &amp; TRAFFIC SIGNALS</b></p>	
<p style="text-align: center;"><b>STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION</b></p>	
<p><b>APPROVED</b></p>	
<u>12/4/2012</u>	<u>/S/</u> <i>Travis Feltes</i> STATE TRAFFIC ENGINEER <u>32</u>
SIGN	



**PLAN VIEW  
CONCRETE PAVEMENT SHOULDER**

**TIE BAR TABLE**

PAVEMENT DEPTH (D)	TIE BAR SIZE	TIE BAR LENGTH (L)	MAX. TIE BAR SPACING
<10 1/2"	NO. 4	30"	36"
>10 1/2"	NO. 5	36"	36"
>10 1/2"	NO. 4*	30"	24" **

\* SUBSTITUTE BENT BATS AT LONGITUDINAL JOINTS WHEN EQUIPMENT LIMITATIONS DURING CONSTRUCTION WARRANT (e.g. AUXILIARY LANES OR TURN LANES).

\*\* CONFORM TO 15" MINIMUM SPACING FROM TRANSVERSE JOINTS; SPACING BETWEEN TIE BARS WILL BE 30" AT TRANSVERSE JOINTS.

**PAVEMENT DEPTH, DOWEL BAR SIZE  
AND JOINT SPACING TABLE**

PAVEMENT DEPTH (D)	DOWEL BAR DIAMETER ***	CONTRACTION JOINT SPACING
6", 6 1/2"	NONE	12"
7", 7 1/2"	1"	14"
8" & ABOVE	1 1/4"	15"

\*\*\*

FOR DOWELED CONCRETE SHOULDERS WITH TRAPEZOIDAL CROSS SECTIONS, CHOOSE THE APPROPRIATE DOWEL BAR DIAMETER BASED ON THE SMALLER PAVEMENT DEPTH (LIKELY THE OUTSIDE EDGE OF THE SHOULDER). IF USING BASKETS, USE BASKETS FROM THE AVERAGE THICKNESS OF THE CROSS SECTION.


## GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.

TRANSVERSE JOINT DETAILS ARE SHOWN ELSEWHERE IN THE PLAN.

FINISH THE SHOULDER PAVEMENT CONFORMING TO SUBSECTION 415.3.8 OF THE STANDARD SPECIFICATIONS.

TIE BARS SHALL CONFORM TO SUBSECTION 505.2.4 OF THE STANDARD SPECIFICATIONS.




**SECTION A - A  
LONGITUDINAL CONSTRUCTION JOINT**


**CONCRETE PAVEMENT  
SHOULDERS**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
November 2022 /S/ Peter Kemp  
DATE  
FHWA  
PAVEMENT SUPERVISOR 33



## SKEWED APPROACH (PAVEMENT MORE THAN TWO LANES)




**SKEWS > 20°  
(PAVEMENT WIDTH ≤ 30')**




**SKEWS  $\leq 20^\circ$   
(PAVEMENT WIDTH  $\leq 30'$ )**


## APPROACH SLAB AND ADJACENT PAVEMENT



**SECTION A - A**  
**REINFORCEMENT POSITIONING DETAIL**



**SECTION B - B  
BEND DETAIL  
BOTTOM REINFORCEMENT**



**SECTION C - C  
TRANSITION DETAIL  
APPROACH SLAB TO ADJACENT PAVEMENT**

## GENERAL NOTES

THE CONTRACTOR MAY SPLIC NO. 6 BARS IN THE APPROACH SLAB FOR SKEWED STRUCTURES ONLY. STAGGER SPLICES WITH A MAXIMUM OF ONE SPLIC PER BAR. THE LENGTH OF LAP IS 20 INCHES.


TACK WELD DOWEL BARS TO THE BASKETS ON ALTERNATE ENDS.

- ① THE CONTRACTOR MAY USE NO. 4 BARS SPACED AT 2' - 0" C - C IN BOTH THE LONGITUDINAL AND TRANSVERSE DIRECTIONS FOR TOP REINFORCEMENT AS AN ALTERNATIVE TO THE WELDED WIRE FABRIC.
- ② THE CONTRACTOR MAY OMIT THE BARS BETWEEN REINFORCED SLABS WHERE SLAB REINFORCEMENT BARS EXTEND ACROSS THE CENTERLINE OR REFERENCE LINE.
- ③ DO NOT CONSTRUCT AN EXPANSION JOINT OR INSTALL DOWEL BARS WHEN ABUTTING AN HMA PAVEMENT.
- ④ USE A JOINT SEALANT CONFORMING TO STANDARD SPECIFICATION 4152.6.
- ⑤ PLACE EXPANSION CAP ON THE END OF THE DOWEL THAT IS NOT TACK WELDED TO THE BASKET. DO NOT FORCE DOWEL BAR PAST THE DOWEL STOP.
- ⑥ EXTEND EXPANSION JOINT THROUGH ANY ADJACENT TIED CONCRETE.

(A) STANDARD CONTRACTION JOINT NORMAL TO C OR R.


(B) STANDARD LONGITUDINAL JOINT WITH TIE BARS.

(C) 1 1/2" EXPANSION JOINT WITH DOWEL BARS NORMAL TO C OR R.



## SECTION D - D

### CONTRACTION JOINT




#### EXPANSION JOINT DETAIL


## **CONCRETE PAVEMENT APPROACH SLAB**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
ember 2018 \_\_\_\_\_ /S/ Peter Kemp, P.E.  
DATE PAVEMENT SUPERVIS 34



CONSTRUCTION JOINT




SAWED JOINT




PLAN VIEW


NO. 6 TIE BARS SPACED 30" C-C,  
INSTALLED PERPENDICULAR  
TO THE LONGITUDINAL JOINT. ①




DETAIL "A"



DETAIL "B"



DETAIL "C"




SECTION A-A  
LONGITUDINAL CONSTRUCTION JOINT  
TIE BARS ANCHORED  
INTO EXISTING PAVEMENT

PAVEMENT DEPTH (D)	TIE BAR SIZE	TIE BAR LENGTH (L)	MAX. TIE BAR SPACING
< 10 1/2"	NO. 4	30"	36"
≥ 10 1/2"	NO. 5	36"	36"
	NO. 4 *	30"	24" **

\* SUBSTITUTE BENT BARS AT LONGITUDINAL JOINTS WHEN EQUIPMENT LIMITATIONS DURING CONSTRUCTION WARRANT (e.g. AUXILIARY LANES OR TURN LANES)

\*\* CONFORM TO 15" MINIMUM SPACING FROM TRANSVERSE JOINTS; SPACING BETWEEN TIE BARS WILL BE 30" AT TRANSVERSE JOINTS.



PLAN VIEW  
SHOWING LOCATION OF TIE BARS

CONCRETE PAVEMENT  
LONGITUDINAL JOINTS AND TIES

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
March 2018 /S/ Peter Kern  
DATE PAVEMENT SUPER 35  
FHWA

GENERAL NOTES

CREATE A LONGITUDINAL JOINT FOR PAVEMENT WIDTHS GREATER THAN 15 FEET.

CORRELATE LONGITUDINAL JOINTS WITH LANE LINES WHEN POSSIBLE.

- ① ANCHOR TIE BARS INTO DRILLED HOLES WITH AN EPOXY.
- ② PAVEMENT THAT WAS IN PLACE PRIOR TO THE CONTRACT.



**TYPICAL PAVEMENT CROSS SECTION  
NOTCHED WEDGE JOINT**

**GENERAL NOTES**


IN ADDITION TO THE DETAILS PROVIDED IN THIS DRAWING, CONFORM TO STANDARD SPECIFICATION 450.3.2.8 FOR WHEN A NOTCHED WEDGE JOINT IS REQUIRED AND FOR GENERAL JOINT CONSTRUCTION REQUIREMENTS.

FOR ALL LONGITUDINAL JOINTS, ENSURE THE PAVER SCREED OVERLAPS THE PREVIOUSLY PLACED PAVEMENT BY  $1'' \pm 0.5''$  AND THE HOT SIDE OF THE JOINT REMAINS HIGHER THAN THE COLD SIDE BY APPROXIMATELY  $0.1''$  AFTER FINAL COMPACTION. (IT WILL BE FLUSH WHEN PAVING IN ECHELON.)


ONLY REMOVE THE LONGITUDINAL NOTCHED WEDGE JOINT FOR SMA PAVEMENT OR AS DIRECTED BY THE ENGINEER TO ADDRESS SPECIFIC LENGTHS OF JOINT DAMAGED BY TRAFFIC.

WHEN MILLING BACK OR REMOVING ANY LONGITUDINAL JOINT, LIMIT THE MATERIAL REMOVED TO  $2''$  FROM THE TOP NOTCH OR FROM THE VERTICAL JOINT EDGE ON THE COLD SIDE OF THE JOINT.


USE LONGITUDINAL MILLED JOINT AS PLANS SHOW OR AS THE ENGINEER DIRECTS.



**TYPICAL PAVEMENT CROSS SECTION  
VERTICAL JOINT**



**OVERLAP DETAIL (TYPICAL)**




**TYPICAL PAVEMENT CROSS SECTION  
VERTICAL JOINT (MILLED)**

**HMA LONGITUDINAL JOINTS**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
November 2020 /S/ Steven Hefel  
DATE  
FHWA

HMA PAVEMENT ENGIN 36



**DETAIL B**  
**MAINLINE CLOSURE WITH POSTED DETOUR**

WORK ZONE LESS THAN  $\frac{1}{2}$  MILE FROM DETOUR ROUTE (1000 FEET IF URBAN)

**LEGEND**

- SIGN ON PERMANENT SUPPORT
- + TYPE III BARRICADE
- || TYPE III BARRICADE WITH ATTACHED SIGN
- TYPE "A" WARNING LIGHT (FLASHING)



WORK AREA




FLAGS, 16" X 16" MIN. (ORANGE)

- DETOUR M4 - 8
- EAST M3 - X
- XX M1 - 4 OR XX M1 - 6 OR COUNTY X M1 - 5A
- OR M05 - 1 OR M06 - 1

SPEED LIMIT (MPH)	"STOP AHEAD" ADVANCE WARNING DISTANCE (FT)
25	200
30	200
35	350
40	350
45	500
50	550
55	750

SEE SDD 15C2-SHEET "b" FOR GENERAL NOTES AND FOOTNOTES ① THROUGH ⑦



**BARRICADES AND SIGNS FOR MAINLINE CLOSURES**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2023 /S/ Andrew Heidke  
DATE  
WORK ZONE ENGINEER 37  
FHWA

## GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE", SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION, OR FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL "D" FOR FULL ROAD CLOSURES.

TYPE "A" LOW - INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11 - 2, R11 - 3, M4 - 9, R11 - 4, AND R10 - 61 SIGNS PLACED ON THE BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE RAIL OR BOTTOM RAILS.

"WO" AND "MO" SIGNS ARE THE SAME AS "W" AND "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

R11 - 2 SHALL BE 48" X 30"

R11 - 3 SHALL, R11 - 4 AND R10 - 61 SHALL BE 60" X 30"

M4 - 9 SHALL BE 30" X 24"

M3 - X SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)


M4 - 8 SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)

M1 - 4, M1 - 5A AND M1 - 6 SHALL BE 24" X 24" (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS)

M05 - 1 AND M06 - 1 SHALL BE 21" X 21" (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS)


D1 - X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.

R1 - 1 SHALL BE 36" X 36"



**DETAIL D**  
**ROAD CLOSURE BARRICADE DETAIL**  
**APPROACH VIEW**

6



**DETAIL E**  
**LANE CLOSURE BARRICADE DETAIL**  
**APPROACH VIEW**

6

- ① TWO WARNING LIGHTS SHALL BE PROVIDED ON THE CENTER BARRICADE AND A MINIMUM OF ONE WARNING LIGHT SHALL BE PROVIDED ON EACH OF THE OTHER BARRICADES WITHIN THE ROADWAY LIMITS. SPACING OF THE WARNING LIGHTS SHALL BE UNIFORM TO THE EDGE OF ROADWAY AS SHOWN (APPROX. 8 FOOT LIGHT SPACING).
- ② THESE SIGNS AND BARRICADES ARE NOT REQUIRED IF ROAD CLOSURE BEGINS AT AN INTERSECTION.
- ③ FOR ROAD CLOSURE WITHOUT LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "D".
- ④ FOR ROAD CLOSURE WITH LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "E".
- ⑤ FOR BRIDGE OR CULVERT REPLACEMENTS, SUBSTITUTE "BRIDGE OUT" INSTEAD OF "ROAD CLOSED" ON R11 - 2 AND R11 - 3 SIGNS.
- ⑥ INSTALL DETOUR AND COMMUNITY GUIDE SIGNS AND ARROWS ONLY IF SPECIFIED IN THE CONTRACT. IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. MODIFY EXISTING SIGNS WHERE POSSIBLE. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. IF DETOUR SIGNS ARE BEING INSTALLED BY OTHERS, PLACE THE CONTRACTED TRAFFIC CONTROL SIGNS TO ALLOW FOR PLACEMENT OF ALL WARNING, DETOUR AND GUIDE SIGNS AS SHOWN.
- ⑦ "EAST" CARDINAL DIRECTION MARKERS AND RIGHT TURN ARROWS ARE SHOWN. USE OTHER CARDINAL DIRECTIONS AND ARROWS AS APPROPRIATE.

SEE SDD 15C2 - SHEET "a" FOR LEGEND

SDD 15C02 - 09b


## BARRICADES AND SIGNS FOR VARIOUS CLOSURES

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2023  
DATE  
FHWA

/S/ Andrew Heidke  
WORK ZONE ENGINEER 38


SDD 15C02 - 09b



SEE SPECIFIC PROJECT DETOUR  
SIGNING DETAIL SHEETS AND  
DETAIL A OR B ON SSD SHEET 15C02 - SHEET "a"

## **DETAIL F DETOUR SIGNING**

## LEGEND



## **GENERAL NOTES**

THE EXACT NUMBER, LOCATION AND SPACING OF ALL SIGNS SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. MODIFY EXISTING SIGNS WHERE POSSIBLE.

THE SPACING BETWEEN TRAFFIC CONTROL AND DETOUR SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND TO PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.


SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY

"MO" SIGNS ARE THE SAME AS "M" S

M3-X SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)  
M4-8 SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)  
M1-4, M1-5A AND M1-6 SHALL BE 24" X 24" (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS)  
M05-1 AND M06-1 SHALL BE 21" X 21" (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS)  
M4-9 AND M4-59 SHALL BE 30" X 24"  
M4-8a SHALL BE 24" X 18"  
G20-51 SHALL BE 60" X 24"  
W20-2A SHALL BE 48" X 48"  
D1-X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS

\* OPTIONAL SIGNS SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS


\*\* FOR A TOWN ROAD OR LOCAL STREET DETOURED ONTO A STATE TRUNK HIGHWAY, PLACE A ROAD NAME PLAQUE ABOVE THE M4-9 SIGN AS SPECIFIED IN THE CONTRACT.



## **DETOUR SIGNING FOR MAINLINE CLOSURES**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED \_\_\_\_\_ /S/ Andrew Heidtke  
May 2023 \_\_\_\_\_ DATE WORK ZONE ENGINEER 39



## GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS.


THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A MINIMUM OF 200 FEET (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

ALL SIGNS ARE 48" X 48" UNLESS OTHERWISE NOTED. IF NECESSARY DUE TO SPACE CONSTRAINTS, 36"X36" SIGNS MAY BE USED INSTEAD OF 48" X 48" SIGNS.

SIGNS THAT WILL BE IN PLACE LESS THAN SEVEN CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.


IF A "STOP" SIGN MUST BE REMOVED FOR A WORK OPERATION, A TEMPORARY "STOP" SIGN SHALL BE PLACED PRIOR TO THE SIGN REMOVAL, OR A FLAGGER SHALL BE PROVIDED UNTIL THE SIGN IS REESTABLISHED.

\* THE THIRD W20-1 SIGN IS REQUIRED ONLY IF THERE IS AN INTERSECTION BETWEEN THE "ROAD WORK 500 FEET" SIGN AND THE WORK ZONE. ADJUST THE PLACEMENT OF THIS SIGN BASED ON INTERSECTION LOCATION AND OTHER FIELD CONDITIONS.



## LEGEND

- Ⓐ SIGN ON PERMANENT SUPPORT
- DIRECTION OF TRAFFIC
- ▨ WORK AREA




TRAFFIC CONTROL, ADVANCE WARNING SIGNS 40MPH OR LESS

**TRAFFIC CONTROL, ADVANCE WARNING SIGNS 40 MPH OR LESS TWO-WAY UNDIVIDED ROAD OPEN TO TRAFFIC**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
July 2018 /S/ Andrew Heidke  
DATE  
FHWA

WORK ZONE ENGINEER 41



### SITUATION 1

WARRANTING CRITERIA:  
BRIDGE WIDTH IS AT LEAST 16 FEET BUT LESS THAN 24 FEET.



### SITUATION 2

WARRANTING CRITERIA:  
1. BRIDGE WIDTH IS AT LEAST 24 FEET AND  
2. BRIDGE SHOULDER WIDTH IS LESS THAN 6 FEET

### GENERAL NOTES

DETAILS OF TRAFFIC CONTROL DEVICES AND INSTALLATION NOT SHOWN ON THE DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

LOCATE W5-52 SIGN POST(S) BEHIND GUARDRAIL WHEN PRESENT.

PLACE THE EDGE OF THE W-52 SIGN IN LINE WITH FACE OF CURB OR PARAPET.

ON BRIDGE ONLY PROJECTS, PLACE 300 FEET OF EDGELINE.

OMIT EDGELINES ON ROADWAYS WITHOUT EXISTING EDGELINES.

① OMIT ON ONE-WAY TRAVELED WAYS.

### LEGEND

Ⓐ SIGN ON PERMANENT SUPPORT

→ DIRECTION OF TRAFFIC


### DISTANCE TABLE

POSTED OR 85TH PERCENTILE SPEED	DISTANCE "A"
25	150'
30	200'
35	250'
40	300'
45	400'
50	550'
55	700'

### SIGNING AND MARKING FOR TWO LANE BRIDGES


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2023 /S/ Jeannie Silver  
DATE  
Statewide Pavement Marking Engineer  
FHWA



TWO WAY TRAFFIC

## PERMANENT PAVEMENT MARKING



ONE WAY TRAFFIC

## GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.


\* CONFIRM MARKING LINE WIDTH WITH THE MISCELLANEOUS QUANTITIES

- ① LOCATE THE NO PASSING ZONE W14-3 SIGN WITHIN 50 FEET OF THE "T" MARKING
- ② MEASURE FROM EDGE OF MARKING TO JOINT LINE. THIS DOES NOT INCLUDE SPACE NEEDED FOR GROOVING OPERATIONS.


## LEGEND

- "T" MARKING
- SIGN ON PERMANENT SUPPORT
- DIRECTION OF TRAFFIC


PERMANENT LONGITUDINAL PAVEMENT MARKINGS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED December 2024 /S/ Jeannie Silver DATE Statewide Pavement Marking Engineer FHWA	




TEMPORARY BARRIER OFFSET FROM EDGELINE



TWO WAY TRAFFIC



ONE WAY TRAFFIC



FREEWAYS AND EXPRESSWAYS

## TEMPORARY PAVEMENT MARKING

## TEMPORARY LONGITUDINAL PAVEMENT MARKING

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
December 2024 /S/ Jeannie Silver  
DATE  
FHWA  
Statewide Pavement Marking Engineer


## GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.


## LEGEND

→ DIRECTION OF TRAFFIC

\* CONFIRM MARKING LINE WIDTH WITH THE MISCELLANEOUS QUANTITIES


**DRUM**

BALLAST WIDTHS  
RANGE FROM 24"-36"


**42" CONE**

DO NOT USE IN TAPERS  
 $\frac{1}{2}$  SPACING OF DRUMS


BALLAST WIDTHS  
RANGE FROM 14"-20"

**VERTICAL PANEL**

THE STRIPES SHALL SLOPE DOWNWARD TO  
THE TRAFFIC SIDE FOR CHANNELIZATION.

**TYPE II BARRICADE**

FOR RAILS LESS THAN 36" LONG, 4" WIDE STRIPES  
MAY BE USED. ALL STRIPES SHALL SLOPE DOWNWARD  
TO THE TRAFFIC SIDE FOR CHANNELIZATION.

**TYPE III BARRICADE**

IF SIGN MOUNTED, DO NOT COVER MORE THAN 50% OF THE TOP  
TWO RAILS OR 33% OF THE TOTAL AREA OF THE THREE RAILS.

\* IF USED FOR A PERMANENT APPLICATION USE RED SHEETING.


## GENERAL NOTES

- ① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.
- ② LOCATION OF WARNING LIGHTS WHEN SHOWN ON THE PLAN.

### CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
November 2022 /S/ Andrew Heidtke  
DATE FHWA  
WORK ZONE ENGINEER 45



## **NARROW SIDEWALK PASSING DETAIL**

## **JOINT ALLOWANCES**

A diagram of a rectangular frame. The left side shows a vertical line with a bracket above it labeled "1/2" with a double quote symbol, indicating the width of the frame.

## MAXIMUM VERTICAL GAP

#### MAXIMUM HORIZONTAL GAP

The diagram illustrates a temporary pedestrian surface setup. It features a grey base layer labeled '4-INCH BASE AGGREGATE DENSE 1 1/4-INCH'. A 'TEMPORARY PEDESTRIAN SURFACE' is placed on top, with a '2" MAX.' thickness indicator. The surface has a '2.1% MAX. SLOPE' with a circled '4' indicating the radius of curvature. On either side of the surface are vertical 'PEDESTRIAN BARRICADE' units. A dimension line indicates a '4' MINIMUM' distance between the barricades, and a '5' DESIRABLE' distance is also shown. Text on the left and right sides of the barricades reads: 'INSTALL PEDESTRIAN BARRICADE PER MANUFACTURERS RECOMMENDATIONS' and 'THE TOP OF THE TO BE A SMOOTH SURFACE FREE OF ROUGH EDGES' respectively.

## **TEMPORARY PEDESTRIAN ACCESS**

## LEGEND


## TEMPORARY PEDESTRIAN BARRICADE

#### AUDIBLE MESSAGE DEVICE

TEMPORARY SIGN SUPPORT

## WORK AREA

#### **TEMPORARY PEDESTRIAN BARRICADE**




TEMPORARY AUDIBLE MESSAGE DEVICE  
(TAMD) MESSAGE: "SIDEWALK CLOSED WAIT  
FOR ASSISTANCE"


## **TEMPORARY PEDESTRIAN FLAGGING**

## TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION



**WITH SIDE APRON**



**WITH PROTECTIVE EDGE**

**TEMPORARY CURB RAMP PERPENDICULAR TO CURB**

**GENERAL NOTES**

CURB RAMPS SHALL BE 48" MINIMUM WIDTH WITH A FIRM, STABLE AND SLIP RESISTANT SURFACE.

ALTERNATE SIDEWALK WORK BETWEEN LEFT AND RIGHT SIDE OF ROADWAY TO MAINTAIN PEDESTRIAN ACCESS.

CURB RAMPS AND LANDINGS SHALL HAVE A 1:48 (2.1%) MAX. CROSS-SLOPE.

CLEAR SPACE OF 48" X 48" SHALL BE PROVIDED ABOVE AND BELOW THE CURB RAMP.

LATERAL JOINTS OR GAPS BETWEEN SURFACES SHALL BE LESS THAN  $\frac{1}{2}$ " WIDTH.

CHANGES BETWEEN SURFACE HEIGHTS SHALL NOT EXCEED  $\frac{1}{2}$ ". LATERAL EDGES MAY BE VERTICAL UP TO  $\frac{1}{4}$ " HIGH AND SHALL BE BEVELED AT 1:2 BETWEEN  $\frac{1}{4}$ " AND  $\frac{1}{2}$ ".

- ① INSTALL CONTRASTING TEMPORARY DETECTABLE WARNING FIELD AT PEDESTRIAN STREET CROSSINGS, AS SHOWN IN THE PLANS
- ② PROTECTIVE EDGING WITH A 2" MIN. HEIGHT SHALL BE INSTALLED WHEN A CURB RAMP OR LANDING PLATFORM HAS A VERTICAL DROP OF 6" OR GREATER OR HAS A SIDE APRON SLOPE STEEPER THAN 1:3 (33%). PROTECTIVE EDGING SHOULD BE CONSIDERED WHEN CURB RAMPS OR LANDING PLATFORMS HAVE A VERTICAL DROP OF 3" OR MORE.
- ③ DETECTABLE EDGING WITH 6" MIN. HEIGHT AND CONTRASTING COLOR SHALL BE INSTALLED ON ALL CURB RAMP LANDINGS WHERE THE WALKWAY CHANGES DIRECTION (TURNS).
- ④ DO NOT RESTRICT WATER FLOW IN THE GUTTER SYSTEM.
- ⑤ CAN ONLY BE USED FOR RAMPS WITH 6" OR LESS OF VERTICAL CHANGE.

## LEGEND

- Ⓐ SIGN ON PERMANENT SUPPORT
- Ⓑ SIGN ON TEMPORARY SUPPORT
- Ⓒ UNDER PEDESTRIAN TRAFFIC
- Ⓓ WORK AREA
- Ⓔ TEMPORARY PEDESTRIAN BARRICADE
- Ⓕ DIRECTION OF TRAFFIC
- Ⓖ TEMPORARY AUDIBLE MESSAGE DEVICE (EXACT PLACEMENT BASED UPON FIELD CONDITIONS)


## GENERAL NOTES

WHERE TEMPORARY BARRICADE RUNS PARALLEL ALONG SIDEWALK, PLACE THE FACE OF THE BARRICADE AT THE EDGE OF THE SIDEWALK.

SIGNS THAT REMAIN IN PLACE LESS THAN SEVEN CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

PLACE TEMPORARY PEDESTRIAN BARRICADE TO FIT FIELD CONDITIONS, AVOIDING CONFLICTS WITH DRIVEWAYS AND OTHER EXISTING FEATURES.

- ① IF TERRACE IS LESS THAN 6 FEET WIDE, OMIT TEMPORARY PEDESTRIAN BARRICADE FROM THE SIDEWALK TO THE CURB.
- ② PLACE BARRICADE CLOSURE SO THAT THE TEMPORARY PEDESTRIAN BARRICADE END IS AT THE LAST OPEN SIDEWALK ACCESS TO RESIDENCES OR BUSINESSES BEFORE THE SIDEWALK CLOSURE.
- ③ IF TEMPORARY PEDESTRIAN BARRICADE PANEL IS WIDER THAN THE SIDEWALK WIDTH, THE PORTION OF EXCESS PANEL SHOULD EXTEND INTO THE TERRACE.
- ④ MOUNTING HEIGHT OF 5 FEET FROM THE SURFACE TO THE BOTTOM OF SIGN.



**SIDEWALK DETOUR, SIDEWALK ONLY ON ONE SIDE**

## LEGEND

-  SIGN ON TEMPORARY SUPPORT
-  WORK AREA
-  UNDER PEDESTRIAN TRAFFIC
-  TEMPORARY PEDESTRIAN SURFACE
-  TEMPORARY PEDESTRIAN BARRICADE
-  OPTIONAL TEMPORARY PEDESTRIAN BARRICADE
-  DIRECTION OF TRAFFIC


## GENERAL NOTES

TYPICAL TEMPORARY PEDESTRIAN BARRICADE PANEL IS 6 FEET LONG.

WHERE TEMPORARY BARRICADE RUNS PARALLEL ALONG SIDEWALK, PLACE THE FACE OF THE BARRICADE AT THE EDGE OF THE SIDEWALK.

SIGNS THAT REMAIN IN PLACE LESS THAN SEVEN CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.


- ① USE TEMPORARY PEDESTRIAN BARRICADE TO SEPARATE PEDESTRIANS FROM DROP OFFS OR FOR ADDITIONAL PEDESTRIAN CHANNELIZATION.
- ② IF TEMPORARY PEDESTRIAN BARRICADE PANEL IS WIDER THAN THE SIDEWALK WIDTH, THE PORTION OF EXCESS PANEL SHOULD EXTEND INTO THE TERRACE.
- ③ MOUNTING HEIGHT OF 5 FEET FROM THE SURFACE TO THE BOTTOM OF SIGN.



**SIDEWALK BYPASS  
SINGLE SIDE**

**LEGEND**

- Ⓐ SIGN ON PERMANENT SUPPORT
- Ⓑ SIGN ON TEMPORARY SUPPORT
- Ⓒ UNDER PEDESTRIAN TRAFFIC
- Ⓓ WORK AREA
- Ⓔ TEMPORARY PEDESTRIAN BARRICADE
- Ⓕ DIRECTION OF TRAFFIC
- Ⓖ TEMPORARY AUDIBLE MESSAGE DEVICE (EXACT PLACEMENT BASED UPON FIELD CONDITIONS)

**SIDEWALK DETOUR, SIDEWALK ON BOTH SIDES****GENERAL NOTES**

WHERE TEMPORARY BARRICADE RUNS PARALLEL ALONG SIDEWALK, PLACE THE FACE OF THE BARRICADE AT THE EDGE OF THE SIDEWALK.


SIGNS THAT REMAIN IN PLACE LESS THAN SEVEN CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

PLACE TEMPORARY PEDESTRIAN BARRICADE TO FIT FIELD CONDITIONS, AVOIDING CONFLICT WITH DRIVEWAYS AND OTHER EXISTING FEATURES.

- ① IF TERRACE IS LESS THAN 6 FEET WIDE, OMIT TEMPORARY PEDESTRIAN BARRICADE FROM THE SIDEWALK TO THE CURB.
- ② PLACE BARRICADE CLOSURE SO THAT THE TEMPORARY PEDESTRIAN BARRICADE END IS AT THE LAST OPEN SIDEWALK ACCESS TO RESIDENCES OR BUSINESSES BEFORE THE SIDEWALK CLOSURE.
- ③ IF TEMPORARY PEDESTRIAN BARRICADE PANEL IS WIDER THAN THE SIDEWALK WIDTH, THE PORTION OF EXCESS PANEL SHOULD EXTEND INTO THE TERRACE.
- ④ MOUNTING HEIGHT OF 5 FEET FROM THE SURFACE TO THE BOTTOM OF SIGN.

**TRAFFIC CONTROL,  
PEDESTRIAN ACCOMMODATION**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION



## **TEMPORARY PEDESTRIAN CROSSING**

## GENERAL NOTES

TYPICAL TEMPORARY PEDESTRIAN BARRICADE PANEL IS 6 FEET LONG.  
SEE OTHER PEDESTRIAN ACCOMMODATION DETAILS FOR SIGNING AND DEVICES FOR DIFFERENT PEDESTRIAN FACILITIES CLOSURES.

WHEN THE TEMPORARY PEDESTRIAN ACCESS ROUTE RUNS PARALLEL ON THE ROADWAY SURFACE, THE MAXIMUM CROSS SLOPE WILL MATCH THE EXISTING ROADWAY CROSS SLOPE.

- ① SHOULDER OR LANE CLOSURE ADVANCED WARNING AND PROPER BUFFER SPACE REQUIRED.
- ② 4 FEET MINIMUM, 5 FEET DESIRABLE.
- ③ WHITE 6" TEMPORARY PAVEMENT MARKING.
- ④ IF MINIMUM LANE WIDTHS CAN'T BE ATTAINED, PERPENDICULAR CURB RAMPS MAY NEED TO BE UTILIZED.
- ⑤ IF MINIMUM 100' SPACING FROM THE MID-BLOCK CROSSING CANNOT BE ATTAINED BEFORE THE INTERSECTION, REMOVE THIS SIGN ASSEMBLY.
- ⑥ IF TERRACE IS LESS THAN 6 FEET WIDE, OMIT TEMPORARY PEDESTRIAN BARRICADE FROM THE SIDEWALK TO THE CURB.
- ⑦ PLACE BARRICADE CLOSURE SO THAT THE TEMPORARY PEDESTRIAN BARRICADE END IS AT THE LAST OPEN SIDEWALK ACCESS TO RESIDENCES OR BUSINESSES BEFORE THE SIDEWALK CLOSURE.
- ⑧ IF TEMPORARY PEDESTRIAN BARRICADE PANEL IS WIDER THAN THE SIDEWALK WIDTH, THE PORTION OF THE EXCESS PANEL SHOULD EXTEND INTO THE TERRACE.
- ⑨ MOUNTING HEIGHT OF 5 FEET FROM THE SURFACE TO THE BOTTOM OF THE SIGN.

## LEGEND

	TRAFFIC CONTROL DRUM
	SIGN ON TEMPORARY SUPPORT
	TEMPORARY CURB RAMP
	TEMPORARY DETECTABLE WARNING FIELD
	TEMPORARY PEDESTRIAN SURFACE "A"
	TEMPORARY PEDESTRIAN SURFACE "B"
	WORK AREA
	TEMPORARY PEDESTRIAN BARRICADE
	DIRECTION OF TRAFFIC
	TEMPORARY AUDIBLE MESSAGE DEVICE (EXACT PLACEMENT BASED UPON FIELD CONDITIONS)

## TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
November 2025 \_\_\_\_\_ /S/ Andrew Heidtke  
DATE \_\_\_\_\_ WORK ZONE ENGINEER

## LEGEND

-  TYPE III BARRICADE WITH ATTACHED SIGN
-  SIGN ON PERMANENT SUPPORT
-  TRAFFIC CONTROL DRUM WITH TYPE "C" STEADY BURN LIGHT
-  TRAFFIC CONTROL DRUM
-  FLAGS, 16" X 16" MIN. (ORANGE)
-  REMOVING PAVEMENT MARKING
-  DIRECTION OF TRAFFIC
-  ASPHALTIC PAVEMENT WIDENING
-  CONCRETE BARRIER TEMPORARY PRECAST

WIDTH ON SIGN TO BE APPROX. 1-FOOT LESS THAN AVAILABLE WIDTH. (OMIT IF AVAILABLE WIDTH IS MORE THAN 16 FEET)



## GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND TO PROVIDE A MINIMUM OF 200 FEET (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE..

THIS LANE CLOSURE IS TYPICAL FOR CLOSING RIGHT LANE - REVERSE FOR CLOSING LEFT LANE.  
ALL SIGNS ARE 48" x 48" UNLESS OTHERWISE NOTED.

"WO" IS THE SAME AS "W" EXCEPT THE BACKGROUND IS ORANGE.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED OR AS APPROVED BY THE ENGINEER.

REMOVE PAVEMENT MARKINGS AND PLACE TEMPORARY PAVEMENT MARKING LINES IF LANE CLOSURE IS TO BE IN PLACE FOR 4 OR MORE CONTINUOUS DAYS AND NIGHTS.

- ① 500 FOOT SPACING SHOWN IS FOR ROADWAYS WITH A PRE-CONSTRUCTION REGULATORY SPEED LIMIT OF 45 MPH OR MORE. FOR 35 - 40 MPH, USE 350 FOOT TYPICAL SPACING. FOR 25 - 30 MPH, USE 200 FOOT TYPICAL SPACING.
- ② DIMENSION DETERMINED BY CBTP TAPER FROM EDGE LINE TO TANGENT SECTION OF THE ROAD.
- ③ TEMPORARY PAVEMENT MARKING LINE, 18 INCH WHITE STOP LINE.
- ④ 700 FOOT TEMPORARY PAVEMENT MARKING LINE, 6 INCH DOUBLE YELLOW. WHEN THE DISTANCE FOR THE PRECEDING NO - PASSING ZONE IS LESS THAN THE MINIMUM DISTANCE BETWEEN ZONES AS INDICATED IN THE SPECIFICATIONS, THE TWO ZONES SHALL BE CONNECTED.
- ⑤ SEE SDD 15C02 - SHEET "F" FOR ADVANCED WIDTH RESTRICTION SIGNING.

WIDTH ON SIGN TO BE APPROX. 1-FOOT  
LESS THAN AVAILABLE WIDTH. (OMIT IF  
AVAILABLE WIDTH IS MORE THAN 16 FEET)

## **TRAFFIC CONTROL, ONE LANE ROAD STOP CONDITION**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2023


/S/ Andrew Heidtke

WORK ZONE ENGINEER 52

## URBAN AREA




## RURAL AREA (See Note 2)




### GENERAL NOTES

1. Signs wider than 4 feet or 20 sq.ft or larger, shall be mounted on multiple posts. Refer to plate A4-4.
2. If signs are mounted on or behind barrier wall, see A4-10 sign plate.
3. The Double Arrow sign (W12-1D) shall be mounted at a height of 2'-3" (\pm) 3". The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Enhanced Reference Markers, Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4'-3" (\pm) 3".
4. For expressways and freeways, mounting height is 7'-3" (\pm) 3" or 6'-3" (\pm) 3" depending upon existence of a sub-sign.
5. Minimum mounting height for signs mounted on traffic signal poles is 5'-3" (\pm) 3".
6. Offset distance shall be consistent with existing signs or consistent throughout length of project.
7. Folding signs shall be mounted at a height of 5'-3" (\pm) 3" or as directed by the Engineer.

2' Min - 4' Max (See Note 5)



White Edgeline Location



\*\* The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

### POST EMBEDMENT DEPTH

Area of Sign Installation (Sq. Ft.)	D (Min)
20 or Less	4'
Greater than 20	5'

\* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

TYPICAL INSTALLATION  
OF PERMANENT TYPE II  
SIGNS ON SINGLE POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew P. Rauch*  
for State Traffic Engineer

DATE 12/6/23 PLATE NO. A4-3.23


PROJECT NO:

HWY:

COUNTY:

SHEET NO: 53

E




ELEVATION VIEW

DETAIL OF WOOD 4 X 6 SIGN POST IN BOX-OUT


NOTES:

1. ALL MATERIAL TO BE APPROVED BY ENGINEER PRIOR TO INSTALLATION
2. SEE SIGN PLATE A4-8 FOR SIGN HARDWARE REQUIREMENTS
3. 18 INCH X 18 INCH SQUARE BOX-OUTS MAY BE USED FOR INSTALLATIONS IN EXISTING CONCRETE OR ASPHALT LOCATIONS.



ELEVATION VIEW

DETAIL OF STEEL 2 X 2 SIGN POST IN BOX-OUT



PLAN VIEW

FOR NEW CONCRETE/ASPHALT INSTALLATIONS

SIGN POST  
BOX-OUTS  
A4-3B

WISCONSIN DEPT OF TRANSPORTATION

APPROVED  
*Matthew P. Rauch*  
for State Traffic Engineer  
DATE 1/27/14 PLATF 54 A4-3B.1

PROJECT NO:

HWY:



COUNTY:

SHEET NO:




E

GENERAL NOTES

1. For 3 or 4 post installations, individual post spacing shall be greater than 3'-6".
2. See tables below for required number of posts.
3. For expressways and freeways, mounting height is 7'-3" ( $\pm$  3") or 6'-3" ( $\pm$  3") depending upon existence of sub-sign.
4. The ( $\pm$ ) tolerance for mounting height is 3 inches.
5. J-Assemblies are considered to be one sign for mounting height.
6. Offset distance shall be consistent with existing signs or consistent throughout length of project.
7. Folding signs shall be mounted at a height of 5'-3" ( $\pm$  3") or as directed by the engineer.
8. The Double Arrow sign (W12-1) shall be mounted at a height of 2'-3" ( $\pm$  3"). The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4"-3" ( $\pm$  3").



**RURAL AREA (See Note 3)**



\* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

\*\* The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

\*\*\* See A4-3 sign plate for signs 4' or less in width and less than 20 S.F. in area.

**SIGN SHAPE OTHER THAN DIAMOND (TWO POSTS REQUIRED)**

L	E
Greater than 48"	12"
Less than 60"	
60" to 108"	L/5

**SIGN SHAPE OTHER THAN DIAMOND (THREE POSTS REQUIRED)**

L	E
Greater than 108" to 144"	12"

**POST EMBEDMENT DEPTH**

Area of Sign Installation ( Sq. Ft. )	D ( Min )
20 or Less	4'
Greater than 20	5'

**TYPICAL INSTALLATION OF TYPE II SIGNS ON MULTIPLE POSTS**

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

*Matthew R. Rauch*  
for State Traffic Engineer

DATE 12/6/23 PLATE NO. A4-4.16


PROJECT NO:

HWY:


COUNTY:

SHEET NO: 55

**E**



SIGN SHALL BE MOUNTED TO PROJECT  
ABOVE THE TOP OF THE POST



Nuts, bolts and lags used for mounting signs shall have hexagonal heads and shall be either :

- a. Hot dip galvanized in accordance with ASTM Designation: A 153, Class D, or SC 3
- b. Electro-galvanized in accordance with ASTM Designation :B 633, TYPE III, SC 3.

Threads on bolts and nuts shall be manufactured with sufficient allowance for the cadmium plate or galvanized coating to permit the nuts to run freely on the bolts.

#### STRINGER BOLTING TO ALUMINUM SIGNS (SEE SIGN PLATE A4-18)

MACHINE BOLTS -  $\frac{5}{16}$ " X 1-3/4" Length w/ lock nuts

#### WOOD POSTS (4" x 6")

LAG SCREWS -  $\frac{3}{8}$ " X 3" (NO STRINGERS ON BACK OF SIGN)  
 $\frac{3}{8}$ " X 4" (STRINGERS ON BACK OF SIGN)

#### SQUARE STEEL POSTS (2" x 2")

MACHINE BOLTS -  $\frac{3}{8}$ " X 3-1/4" Length w/ nuts (NO STRINGER ON BACK OF SIGN)  
 $\frac{3}{8}$ " X 5" Length w/ nuts (STRINGERS ON BACK OF SIGN)

RIVETS -  $\frac{9}{32}$ " (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM BODY/MANDREL

O.D. FLANGE .720-.765 INCH, GRIP RANGE .042-.375 INCH

#### WASHERS (ALL POSTS) -

1-1/4" O.D. X  $\frac{3}{8}$ " I.D. X  $\frac{1}{16}$ " STEEL

1-1/4" O.D. X  $\frac{3}{8}$ " I.D. X .080 NYLON

\* Two different fastening systems are shown for illustration purposes. On any individual sign, either one or the other system shall be used. Actual number of fasteners per sign varies with the sign area, but normally there are two. For a single post installation, all signs greater than 9 sq. ft. require the use of 3 fasteners.


#### ATTACHMENT OF SIGNS TO POSTS

WISCONSIN DEPT OF TRANSPORTATION


APPROVED *Matthew R Rauch*  
for State Traffic Engineer

DATE 4/1/2020 PLATE NO. A4-8.9



### TELESCOPIC TUBING ANCHORS TWO PIECE SYSTEM



### DETAIL OF TUBULAR STEEL SIGN POST (IN POURED CONCRETE OR ASPHALT)



### DETAIL OF TUBULAR STEEL SIGN POST (IN LOCATIONS OTHER THAN POURED CONCRETE OR ASPHALT)



Area of Sign Installation (Sq. Ft.)	Number of Required Posts
9 or less	1
Greater than 9 less than or equal to 18	2
Greater than 18 less than or equal to 27	3

Signs wider than 3 feet or larger than 9 sq. ft shall be mounted on multiple posts (see above table).

**TUBULAR STEEL  
SIGN POST  
A4-9**

WISCONSIN DEPT OF TRANSPORTATION

APPROVED  
*Matthew P. Rauch*

for State Traffic Engineer

DATE 2/05/15 PLATI 57 14-9.9



PROJECT NO:

HWY:

COUNTY:

SHEET NO:

E



SIDE VIEW

GENERAL NOTES

1. All 4 x 6 Wood Posts shall be modified by having two  $1\frac{1}{2}$ " diameter holes drilled perpendicular to the roadway centerline.

4 X 6 WOOD POST  
MODIFICATIONS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

*Cheska J. Spangler*  
for State Traffic Engineer

DATE 3/27/97

PLATE NO. A4-11.2

PROJECT NO:


HWY:

COUNTY:


SHEET NO: 58

E

7



W5-52L



W5-52R

NOTES

1. Sign is Type II - Type F Reflective
2. Color:  
Background - Yellow  
Message - Black
3. Alternate colors of stripes as shown.

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4															3.0	
2M	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4															3.0	
3	18	54	1 1/2			6	5 1/2	8 1/2	45°	6	6 9/16															6.75	
4																											
5																											

PROJECT NO:

HWY:

COUNTY:

SHEET NO: 59 E

## STANDARD SIGN

W5-52L &amp; W5-52R

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R Rauch*  
for State Traffic Engineer

DATE 3/4/2024 PLATE NO. W5-52.10

## DESIGN DATA

## LIVE LOAD:

DESIGN LOADING — HL-93  
 INVENTORY RATING FACTOR — RF=1.10  
 OPERATING RATING FACTOR — RF=1.43  
 WISCONSIN STANDARD PERMIT  
 VEHICLE RATING (WIS.-SPV): — 250 KIPS

STRUCTURE IS DESIGNED FOR A FUTURE WEARING SURFACE OF 20 POUNDS PER SQUARE FOOT.

## MATERIAL PROPERTIES:

CONCRETE MASONRY, DECK —  $f_c' = 4,000$  P.S.I.  
 ALL OTHER —  $f_c' = 3,500$  P.S.I.  
 HIGH-STRENGTH BAR STEEL  
 REINFORCEMENT —  $f_y = 60,000$  P.S.I.  
 28-INCH PRESTRESSED GIRDERS  
 CONCRETE MASONRY —  $f_c' = 8,000$  P.S.I.  
 STRANDS — 0.6" DIAMETER  
 WITH AN ULTIMATE TENSILE  
 STRENGTH OF —  $f_u = 270,000$  P.S.I.

## FOUNDATION DATA:

ABUTMENTS TO BE SUPPORTED ON HP 10 X 42 PILING  
 DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 150  
 TONS PER PILE\*\* AT S. ABUT. AND N. ABUT. AS  
 DETERMINED BY THE MODIFIED GATES DYNAMIC  
 FORMULA. ESTIMATED 45 FT PILE LENGTHS AT S.  
 ABUT. AND N. ABUT.

PIERS TO BE SUPPORTED ON HP 10 X 42 PILING  
 DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 170  
 TONS PER PILE\*\* AT PIER 1 AND PIER 2 AS  
 DETERMINED BY THE MODIFIED GATES DYNAMIC  
 FORMULA. ESTIMATED 45 FT PILE LENGTHS AT PIER 1  
 AND 35 FT PILE LENGTHS AT PIER 2.

\*\*THE FACTORED AXIAL RESISTANCE OF PILES IN  
 COMPRESSION USED FOR DESIGN IS THE REQUIRED  
 DRIVING RESISTANCE MULTIPLIED BY A RESISTANCE  
 FACTOR OF 0.5 USING MODIFIED GATES DYNAMIC  
 FORMULA TO DETERMINE DRIVEN PILE CAPACITY.


## BENCH MARKS

NO.	STATION/OFFSET	DESCRIPTION	ELEVATION
BM 1	12+12.91, 27.86' RT.	RAILROAD SPIKE IN POWER POLE	979.67
BM 2	16+83.65, 26.71' RT.	RAILROAD SPIKE IN POWER POLE	977.65

HORIZONTAL DATUM AND ADJUSTMENT: NAD 83 (2011)

VERTICAL DATUM AND ADJUSTMENT: NAVD 88 (2012)

COORDINATE REFERENCE SYSTEM: WISCRS WALWORTH CO.



## NOTES

EXCAVATION AS INDICATED IN THE HATCH AREAS, TO BE INCLUDED IN THE BID ITEM "EXCAVATION FOR STRUCTURES BRIDGES B-64-215".

(G01) BACKFILL PAY LIMITS. BACKFILL BEYOND BACKFILL PAY LIMITS SHALL BE INCLUDED WITH BID ITEM "EXCAVATION FOR STRUCTURES BRIDGES B-64-215". LIMITS OF EXCAVATION SHALL BE DETERMINED BY THE CONTRACTOR.

(G02) "GEOTEXTILE TYPE OF SCHEDULE A" LIMITS. EXTEND 2'-0" ABOVE BOTTOM OF ABUTMENT FOR THE ENTIRE ABUTMENT BODY LENGTH.

(G03) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN AS DETAILED IN "NORTH ABUTMENT" SHEET.

(G04) NAME PLATE REQUIRED AND BENCH MARK CAP (WHEN SUPPLIED). FOR LOCATION SEE "SOUTH ABUTMENT" SHEET.


(G05) EXISTING 18" CMP CULVERTS ON NORTH AND SOUTH TRACKSIDE DITCHES, SHALL BE REMOVED SALVAGED AND STORED ON RAILROAD PROPERTY ADJACENT TO THE PROJECT SITE FOR RECLAIM BY WSR. SEE ROADWAY PLANS FOR DETAILS, BID ITEM AND SIDE DITCH LAYOUT.

(G06) EXISTING TIMBER WALL NEAR S. ABUT. & PIER 1 TO BE REMOVED. COSTS ASSOCIATED WITH THE REMOVAL OF THE EXISTING TIMBER WALL SHALL BE INCLUDED IN THE BID ITEM "REMOVING STRUCTURE P-64-101".

□ INDICATES WING NUMBER

## LIST OF DRAWINGS

- GENERAL PLAN
- CROSS SECTION, GENERAL NOTES AND QUANTITIES
- SUBSURFACE EXPLORATION
- SOUTH ABUTMENT
- NORTH ABUTMENT DETAILS
- NORTH ABUTMENT
- NORTH ABUTMENT DETAILS
- PIER 1
- PIER 1 DETAILS
- PIER 2
- PIER 2 DETAILS
- BEAM SEAT DETAIL
- 28-INCH PRESTRESSED GIRDERS
- 28-INCH PRESTRESSED GIRDERS DETAILS
- INTERMEDIATE STEEL DIAPHRAGM
- SUPERSTRUCTURE
- SUPERSTRUCTURE DETAILS
- ABUTMENT DIAPHRAGM REINFORCEMENT
- PIER DIAPHRAGM REINFORCEMENT
- SUPERSTRUCTURE REINFORCEMENT
- RAILING TUBULAR TYPE M
- SLOPE PAVING CRUSHED AGGREGATE



ABUTMENT BACKFILL DETAIL  
(TYPICAL AT BOTH ABUTMENTS)

## TRAFFIC DATA:

HILLSIDE ROAD  
 A.A.D.T. (2026) — 109  
 A.A.D.T. (2046) — 126  
 DESIGN SPEED — 30 M.P.H.

CONSULTANT CONTACT  
 ANDREW C. KNUTSON, P.E.  
 SPRING GREEN, WI  
 12-2-25

BRIDGE OFFICE CONTACT  
 AARON BONK, P.E.  
 (608) 588-7866

NO. DATE REVISION BY  
 619 EAST HOXIE STREET  
 P.O. BOX 429  
 SPRING GREEN, WI 53588  
 PHONE (608) 588-7866  
 FAX (608) 588-7954

STATE OF WISCONSIN  
 DEPARTMENT OF TRANSPORTATION  
 ACCEPTED — 12/04/25  
 CHIEF STRUCTURES DESIGN ENGINEER  
 DATE


STRUCTURE B-64-215

HILLSIDE ROAD OVER WSR RAILROAD  
 COUNTY WALWORTH TOWN/CITY/VILLAGE LINN

DESIGN SPEC.  
 AASHTO LRFD DESIGN SPEC.

DESIGNED BY CDS DESIGN JDO DRAWN BY CDS PLANS ck'd. ACK

SHEET 1 OF 22  
 GENERAL PLAN  
 60



## LEGEND

(G07)  $\frac{3}{4}$ " V-GROOVE. EXTEND V-GROOVE TO 6" FROM FRONT FACE OF ABUTMENT DIAPHRAGM. V-GROOVES ARE REQUIRED.

(G08) COAT WITH "PROTECTIVE SURFACE TREATMENT" AS PER THE STANDARD SPECIFICATIONS. PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO ENTIRE EXPOSED TOP OF DECK, INCLUDING THE DECK EDGES AND 1'-0" UNDER THE DECK, THE TOP AND EXTERIOR EXPOSED FACE OF WINGS, THE FRONT FACE OF THE ABUTMENTS AND CONCRETE DIAPHRAGMS TO 1'-0" PAST THE EDGE OF DECK, THE PIER CAP EXTERIOR FACE AND THE TOP/SIDES OF THE PIER CAP TO 1'-0" PAST THE EDGE OF DECK.

(#) INDICATES GIRDER LINE DESIGNATION

## TOTAL ESTIMATED QUANTITIES

ITEM NO.	BID ITEMS	UNIT	S. ABUT.	PIER 1	PIER 2	N. ABUT.	SUPER.	TOTALS
203.0220	REMOVING STRUCTURE P-64-101	EACH	---	---	---	---	---	1
203.0330	DEBRIS CONTAINMENT P-64-101	EACH	---	---	---	---	---	1
206.1001	EXCAVATION FOR STRUCTURES BRIDGES B-64-215	EACH	---	---	---	---	---	1
210.1500	BACKFILL STRUCTURE TYPE A	TON	190	---	---	180	---	370
502.0100	CONCRETE MASONRY BRIDGES	CY	37.6	75.0	106.1	36.1	162.4	417
502.3200	PROTECTIVE SURFACE TREATMENT	SY	22	3	3	21	599	648
503.0128	PRESTRESSED GIRDERS TYPE I 28-INCH	LF	---	---	---	---	863	863
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB	2200	14730	17800	2070	---	36800
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	1260	0	0	1040	36570	38870
506.2605	BEARING PADS ELASTOMERIC NON-LAMINATED	EACH	5	10	10	5	---	30
506.4000	STEEL DIAPHRAGMS B-64-215	EACH	---	---	---	12	12	
511.1200	TEMPORARY SHORING B-64-215	SF	---	640	950	---	1590	
513.4061	RAILING TUBULAR TYPE M	LF	---	---	---	358	358	
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	7	---	---	7	---	14
550.1100	PILING STEEL HP 10-INCH X 42 LB	LF	225	720	560	225	---	1730
604.0500	SLOPE PAVING CRUSHED AGGREGATE	SY	183	---	---	196	---	379
612.0406	PIPE UNDERDRAIN WRAPPED 6-INCH	LF	85	---	---	85	---	170
645.0111	GEOTEXTILE TYPE DF SCHEDULE A	SY	35	---	---	35	---	70
SPV.0165	TEMPORARY SHORING RAILROAD	SF	---	---	560	---	560	
(NON-BID ITEM)	FILLER	SIZE	---	---	---	---	---	1/2"

## GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BEVEL EXPOSED EDGES OF CONCRETE  $\frac{3}{4}$ " UNLESS OTHERWISE NOTED.

AT THE BACK FACE OF THE ABUTMENT ALL VOLUME WHICH CANNOT BE PLACED BEFORE ABUTMENT CONSTRUCTION AND IS NOT OCCUPIED BY THE NEW STRUCTURE SHALL BE BACKFILLED WITH BACKFILL STRUCTURE TYPE A.

THE BACKFILL QUANTITIES ARE BASED ON THE PAY LIMITS SHOWN ON THE PLANS AND MAY NOT REFLECT ACTUAL PLACED QUANTITIES. "BACKFILL STRUCTURE TYPE A" REQUIRED DIRECTLY BEHIND ABUTMENTS AND ABUTMENT WINGS FOR 3 FEET. BACKFILL PLACED BEYOND PAY LIMITS OR EXCEEDING PLAN QUANTITIES SHALL BE INCLUDED WITH BID ITEM "EXCAVATION FOR STRUCTURES BRIDGES B-64-215".

EXCAVATION BELOW THE ABUTMENT AND ABUTMENT BEDDING MATERIALS REQUIRES ENGINEER APPROVAL. GEOTEXTILE SHALL BE SET AT THE BOTTOM OF EXCAVATION AND EXTEND 2'-0" ABOVE BOTTOM OF ABUTMENT.

DO NOT PLACE FILL ABOVE 3'-0" FROM BOTTOM OF ABUTMENT UNTIL SUPERSTRUCTURE IS IN PLACE.


THE EXISTING GROUND LINE SHALL BE USED AS THE UPPER LIMITS OF EXCAVATION AT THE ABUTMENTS AND PIERS.

THE SLOPE OF THE FILL IN FRONT OF THE ABUTMENTS SHALL BE COVERED WITH SLOPE PAVING MATERIAL TO THE EXTENT SHOWN ON THE "GENERAL PLAN" SHEET AND THE "SLOPE PAVING CRUSHED AGGREGATE" SHEET.

THE HAUNCH CONCRETE QUANTITY IS BASED ON THE AVERAGE HAUNCH SHOWN ON THE "28-INCH PRESTRESSED GIRDER DETAILS" SHEET.


ELASTOMERIC BEARING PADS NEED NOT BE INDIVIDUALLY MOLDED PROVIDED THE CUT EDGES ARE SMOOTH AND TRUE.

THE EXISTING STRUCTURE P-64-101 IS A NINE SPAN TIMBER DECK GIRDERS WITH AN OVERALL LENGTH OF 136.0-FT AND A TOTAL DECK WIDTH OF 20.4-FT. SUPERSTRUCTURE, TIMBER PIERS, TIMBER ABUTMENTS, AND ADJACENT TIMBER WALLS NEAR S. ABUT. & PIER 1 SHALL BE REMOVED IN ACCORDANCE WITH THE BID ITEM "REMOVING STRUCTURE P-64-101".





PROFILE GRADE LINE,  
C HILLSIDE ROAD


(ELEVATIONS BASED ON TOP OF RAIL FIELD SURVEY)



## ABUTMENT BACKFILL DIAGRAM





PROFILE GRADE LINE, C HILLSIDE ROAD




HP WELD DETAIL  
(FLANGE SHOWN, WEB SIMILAR)

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-64-215			
DRAWN BY	CDS	PLANS CK'D	ACK
CROSS SECTION, GENERAL NOTES AND QUANTITIES			
SHEET 2 OF 22			
61			







**ELEVATION**  
(S. ABUT. LOOKING SOUTH)



## PLAN



## PILE PLAN



TYPICAL SECTION THRU  
SOUTH ABUTMENT

## NOTES

DO NOT PLACE FILL ABOVE 3'-0" FROM THE BOTTOM OF THE ABUTMENT UNTIL SUPERSTRUCTURE IS IN PLACE

SOUTH ABUTMENT TO BE SUPPORTED ON HP 10 X 42 PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 150 TONS PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA. ESTIMATED 45 FT PILE LENGTHS AT THE SOUTH ABUTMENT.

SEE "CROSS SECTION, GENERAL NOTES & QUANTITIES" SHEET FOR  
FILE SPLICE DETAILS

2'-0"

A01 PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO  
 SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE  
 UNDERDRAIN AS DETAILED ON "NORTH ABUTMENT" SHEET.  
 RODENT SHIELD SHALL BE INCLUDED WITH THE BID ITEM "PIPE  
 UNDERDRAIN WRAPPED 6-INCH".

A02 SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES  
 OF  $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS  
 JOINT SEALER. (1" DEEP AND HOLD  $\frac{1}{8}$ " BELOW SURFACE OF  
 CONCRETE).  $\frac{1}{2}$ " FILLER TO EXTEND FROM BEAM SEAT TO TOP  
 OF WING.

A03 18" RUBBERIZED MEMBRANE WATERPROOFING (R.M.W.), SEAL  
 ALL HORIZONTAL AND VERTICAL JOINTS ON BACK FACE.

A04  $\frac{1}{2}$ " X 8" X 1'-10" NON-LAMINATED ELASTOMERIC BEARING PAD,  
 TYP. SEE "BEAM SEAT DETAILS" SHEET.

A05  $\frac{3}{4}$ " CORK FILLER ON VERTICAL BEAM SEAT FACES THAT RUN  
 PARALLEL WITH GIRDER, TYP.

A06  $\frac{1}{2}$ " PREFORMED FILLER, TYP. SEE "BEAM SEAT DETAILS" SHEET.

A07 NAME PLATE REQUIRED AND BENCH MARK CAP (WHEN  
 SUPPLIED). SEE "NAME PLATE DETAILS", THIS SHEET.


A08 A410, A511 REQUIRED WHERE DIMENSION EXCEEDS 4"

A09 SLOPING BEAM SEAT REQ. SEE "BEAM SEAT DETAILS" SHEET.

 INDICATES WING NUMBER


 INDICATES GIRDER LINE DESIGNATION

F.F. - FRONT FACE
B.F. - BACK FACE








### NAME PLATE DETAIL

STEEL TROWEL TOP SURFACE OF ABUTMENT. PLACE -  
MULTIPLE LAYERS OF POLYETHYLENE SHEETS OVER  
ENTIRE ABUTMENT TOP AND BEFORE PLACING  
BEARING PADS AND SUPERSTRUCTURE. TOTAL  
THICKNESS OF SHEETS SHALL BE AT LEAST 0.03".





**DETAIL A**

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-64-215</b>			
	DRAWN BY	ZDM	PLANS CK'D
			ACK
			SHEET 4 OF 22
<b>SOUTH ABUTMENT</b>			
<i>63</i>			

COATED = 1,260 LBS.  
UNCOATED = 2,200 LBS.**BAR BEND DIMENSIONS**

MARK	"A"	"B"	"C"
A418	12'-9"	2'-11"	159'
A420	12'-9"	1'-9"	159'
A429	14'-10"	1'-9"	159'
A431	14'-10"	2'-11"	159'

**BILL OF BARS  
SOUTH ABUTMENT**

MARK	NUMBER	COATED	UNCOATED	LENGTH	BENT	BAR SERIES		LOCATION
						VERT.	HORIZ.	
A601	10	36'-3"						
A802	10	16'-0"						
A603	5	10'-1"						
A504	46	15'-0"						
A405	10	2'-3"						
A406	5	28'-0"						
A607	10	3'-7"						
A408	8	5'-8"						
A409	12	3'-11"						
A410	4	22'-6"						
A511	23	5'-11"						
A512	4	14'-8"						
A513	1	12'-9"						
A814	4	16'-7"						
A815	1	14'-8"						
A816	2	13'-7"						
A417	3	8'-3"						
A418	1	15'-8"						
A419	3	7'-0"						
A420	1	14'-6"						
A421	24	8'-0"						
A422	4	10'-3"						
A523	4	17'-7"						
A524	1	15'-7"						
A825	4	19'-6"						
A826	1	17'-6"						
A827	2	14'-10"						
A428	3	7'-3"						
A429	1	16'-7"						
A430	3	8'-5"						
A431	1	17'-9"						
A432	28	8'-4"						
A433	4	10'-11"						
A434	8	3'-9"	X					

THE FIRST DIGIT OF A BAR MARK SIGNIFIES THE BAR SIZE.

F.F. - FRONT FACE  
B.F. - BACK FACE

ALL BAR BEND DIMENSIONS ARE OUT TO OUT OF BAR.

▲ LENGTH SHOWN FOR BAR IS AN AVERAGE LENGTH AND SHOULD ONLY BE USED FOR BAR WEIGHT CALCULATIONS. SEE "BAR SERIES TABLE" FOR ACTUAL LENGTHS.

**NOTES**

DO NOT PLACE FILL ABOVE 3'-0" FROM THE BOTTOM OF THE ABUTMENT UNTIL SUPERSTRUCTURE IS IN PLACE.

SOUTH ABUTMENT TO BE SUPPORTED ON HP 10 X 42 PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 150 TONS PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA. ESTIMATED 45 FT PILE LENGTHS AT THE SOUTH ABUTMENT.

SEE "CROSS SECTION, GENERAL NOTES &amp; QUANTITIES" SHEET FOR PILE SPLICE DETAILS.



(A01) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN AS DETAILED ON "NORTH ABUTMENT" SHEET. RODENT SHIELD SHALL BE INCLUDED WITH THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".

(A02) SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF  $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD  $\frac{1}{8}$ " BELOW SURFACE OF CONCRETE.)  $\frac{1}{2}$ " FILLER TO EXTEND FROM BRIDGE SEAT TO TOP OF WING.**BAR SERIES TABLE**

MARK	NO. REQ'D	LENGTH
A417	1 SERIES OF 3	5'-8" TO 10'-9"
A419	1 SERIES OF 3	4'-5" TO 9'-6"
A421	2 SERIES OF 12	5'-11" TO 10'-0"
A428	1 SERIES OF 3	4'-8" TO 9'-9"
A430	1 SERIES OF 3	5'-10" TO 10'-11"
A432	2 SERIES OF 14	5'-11" TO 10'-8"

BUNDLE AND TAG EACH SERIES SEPARATELY.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-64-215			
DRAWN BY	ZDM	PLANS CK'D	ACK
SOUTH ABUTMENT DETAILS			
SHEET 5 OF 22			



TYPICAL SECTION THRU  
NORTH ABUTMENT

## NOTES

DO NOT PLACE FILL ABOVE 3'-0" FROM THE BOTTOM OF THE ABUTMENT UNTIL SUPERSTRUCTURE IS IN PLACE


NORTH ABUTMENT TO BE SUPPORTED ON HP 10 X 42 PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 150 TONS PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA. ESTIMATED 15 FT PILE LENGTHS AT THE NORTH ABUTMENT.

SEE "CROSS SECTION, GENERAL NOTES & QUANTITIES" SHEET FOR  
PILE SPLICE DETAILS

- (B01) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN AS DETAILED ON THIS SHEET. RODENT SHIELD SHALL BE INCLUDED WITH THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".
- (B02) SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF  $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD  $\frac{1}{6}$ " BELOW SURFACE OF CONCRETE).  $\frac{1}{2}$ " FILLER TO EXTEND FROM BEAM SEAT TO TOP OF WING.
- (B03) 18" RUBBERIZED MEMBRANE WATERPROOFING (R.M.W.), SEAL ALL HORIZONTAL AND VERTICAL JOINTS ON BACK FACE.
- (B04)  $\frac{1}{2}$ " X 8" X 1'-10" NON-LAMINATED ELASTOMERIC BEARING PAD, TYP. SEE "BEAM SEAT DETAILS" SHEET.
- (B05)  $\frac{3}{4}$ " CORK FILLER ON VERTICAL BEAM SEAT FACES THAT RUN PARALLEL WITH GIRDER, TYP.
- (B06)  $\frac{1}{2}$ " PREFORMED FILLER, TYP. SEE "BEAM SEAT. DETAILS" SHEET.
- (B07) B410, B511 REQUIRED WHERE DIMENSION EXCEEDS 4"
- (B08) SLOPING BEAM SEAT REQUIRED. SEE "BEAM SEAT DETAILS" SHEET.

 INDICATES WING NUMBER

 INDICATES GIRDER LINE DESIGNATION



#### RODENT SHIELD DETAIL

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-64-215</b>			
DRAWN BY		ZDM	PLANS CK'D
<b>NORTH ABUTMENT</b>		SHEET 6 OF 22	
		65	
E: B640215_06-07_Nabut.dwg DT SCALE:			

INDICATES GIRDER LINE DESIGNATION

F.F. - FRONT FACE  
B.F. - BACK FACE

COATED = 1,040 LBS.  
UNCOATED = 2,070 LBS.BILL OF BARS  
NORTH ABUTMENT

MARK	NUMBER		LENGTH	BENT	BAR SERIES	LOCATION
	COATED	UNCOATED				
B601	10	36'-3"				BODY - F.F., TOP, & BOT.
B802	5	14'-0"				BODY - B.F. NEAR WING 4
B603	5	25'-2"				BODY - B.F. CENTER - NEAR WING 3
B504	46	15'-0"	X			BODY - STIRRUP
B405	10	2'-3"				BODY - BOTTOM AT PILES
B406	5	28'-0"	X			BODY - BOTTOM AT PILES
B607	10	3'-7"	X			BODY - END L-BAR NEAR WINGS
B408	8	5'-8"				BODY - TOP BTWN BEAM SEATS
B409	12	3'-11"	X			BODY - TOP BTWN BEAM SEATS
B410	4	22'-6"				BODY - TOP
B511	23	5'-11"	X			BODY - TOP
B512	5	12'-8"				WING 3 - F.F. - BODY
B613	5	13'-0"				WING 3 - B.F. - BODY
B714	2	12'-9"				WING 3 - F.F. & B.F. - BODY
B415	3	8'-5"	▲			WING 3 - F.F.
B416	1	13'-6"	X			WING 3 - F.F. - TOP
B417	3	7'-2"	▲			WING 3 - B.F.
B418	1	12'-4"	X			WING 3 - B.F. - TOP
B419	20	8'-5"	▲			WING 3 - STIRRUP
B420	4	10'-3"	X			WING 3 - STIRRUP
B521	4	15'-7"				WING 4 - F.F. - BODY
B522	1	15'-4"				WING 4 - F.F. - BODY
B823	4	17'-6"				WING 4 - B.F. - BODY
B824	1	17'-3"				WING 4 - B.F. - BODY
B825	2	14'-7"	▲			WING 4 - F.F. & B.F. - BODY
B426	3	7'-1"	▲			WING 4 - F.F.
B427	1	14'-6"	X			WING 4 - F.F. - TOP
B428	3	8'-3"	▲			WING 4 - B.F.
B429	1	15'-8"	X			WING 4 - B.F. - TOP
B430	24	8'-7"	▲			WING 4 - STIRRUP
B431	4	10'-10"	X			WING 4 - STIRRUP
B432	8	3'-9"	X			WINGS 3 & 4 TOP STIRRUP

THE FIRST DIGIT OF A BAR MARK SIGNIFIES THE BAR SIZE.

F.F. - FRONT FACE  
B.F. - BACK FACE

ALL BAR BEND DIMENSIONS ARE OUT TO OUT OF BAR.

▲ LENGTH SHOWN FOR BAR IS AN AVERAGE LENGTH AND SHOULD ONLY BE USED FOR BAR WEIGHT CALCULATIONS. SEE "BAR SERIES TABLE" FOR ACTUAL LENGTHS.

## NOTES

DO NOT PLACE FILL ABOVE 3'-0" FROM THE BOTTOM OF THE ABUTMENT UNTIL SUPERSTRUCTURE IS IN PLACE.

NORTH ABUTMENT TO BE SUPPORTED ON HP 10 X 42 PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 150 TONS PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA. ESTIMATED 45 FT PILE LENGTHS AT THE NORTH ABUTMENT.

SEE "CROSS SECTION, GENERAL NOTES &amp; QUANTITIES" SHEET FOR PILE SPLICE DETAILS.

(B01) PIPE UNDERDRAIN WRAPPED (6-INCH), SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN AS DETAILED ON "NORTH ABUTMENT" SHEET. RODENT SHIELD SHALL BE INCLUDED WITH THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".

(B02) SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF  $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD  $\frac{1}{8}$ " BELOW SURFACE OF CONCRETE.)  $\frac{1}{2}$ " FILLER TO EXTEND FROM BRIDGE SEAT TO TOP OF WING.

## BAR SERIES TABLE

MARK	NO. REQ'D	LENGTH
B415	1 SERIES OF 3	5'-11" TO 10'-10"
B417	1 SERIES OF 3	4'-8" TO 9'-7"
B419	2 SERIES OF 10	6'-9" TO 10'-0"
B426	1 SERIES OF 3	4'-7" TO 9'-6"
B428	1 SERIES OF 3	5'-9" TO 10'-8"
B430	2 SERIES OF 12	6'-7" TO 10'-7"


BUNDLE AND TAG EACH SERIES SEPARATELY.


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

STRUCTURE B-64-215


DRAWN BY ZDM PLANS CK'D ACK

NORTH ABUTMENT DETAILS SHEET 7 OF 22







**ELEVATION**  
(LOOKING NORTH)



## PLAN



END VIEW  
(LOOKING WEST)



## SLOPING BEAM SEAT AT PIER 1

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-64-215</b>			
DRAWN BY		PLANS CK'D	ACK
PIER 1		SHEET 8 OF 22	
67			
E: B640215_08-09_pier 1.dwg DT SCALE:			

BILL OF BARS  
PIER 1

UNCOATED = 14,730 LBS.

MARK	NUMBER		LENGTH	BENT	LOCATION
	COATED	UNCOATED			
C801	12	35'-8"	FOOTING	- BOT.	HORIZ.
C802	48	8'-8"	FOOTING	- BOT.	HORIZ.
C703	12	35'-8"	FOOTING	- TOP	HORIZ.
C504	36	8'-8"	FOOTING	- TOP	HORIZ.
C805	72	7'-6"	X	FOOTING - DOWELS	VERT.
C806	72	26'-1"		COLUMN	VERT.
C507	288	10'-6"	X	COLUMN - STIRRUP	HORIZ.
C708	8	31'-1"		PIER CAP - BOTTOM LONGIT. REIN.	HORIZ.
C509	4	31'-1"		PIER CAP - SKIN REIN.	HORIZ.
C710	8	32'-11"	X	PIER CAP - TOP LONGIT. REIN.	HORIZ.
C411	40	10'-2"	X	PIER CAP - STIRRUP	VERT.
C512	6	5'-7"	X	PIER CAP - END STIRRUP	HORIZ.
C413	4	18'-6"		PIER CAP - TOP	HORIZ.
C514	19	5'-8"	X	PIER CAP - TOP STIRRUP	VERT.
C515	8	2'-0"		PIER CAP - DOWEL BAR	VERT.

THE FIRST DIGIT OF A BAR MARK SIGNIFIES THE BAR SIZE.

ALL BAR BEND DIMENSIONS ARE OUT TO OUT OF BAR.

## NOTES

PIER 1 TO BE SUPPORTED ON HP 10 X 42 STEEL PILING DRIVEN TO A REQUIRED DRIVING DISTANCE OF 170 TONS PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA. ESTIMATED 45 FT PILE LENGTHS AT PIER.

FOR PILE SPLICING DETAILS SEE "CROSS SECTION, GENERAL NOTES AND QUANTITIES" SHEET

(C01) KEYED CONSTRUCTION JOINT FOR ALL COLUMNS AND FOOTINGS FORMED BY BEVELED 1'-3" X 2'-0" X 4".

(C02) KEYED CONSTRUCTION JOINT BETWEEN BEAM SEATS FORMED BY BEVELED 2" x 6".

(C03) C515 BARS MAY BE PLACED AFTER CONCRETE IS POURED, BUT BEFORE INITIAL SET HAS TAKEN PLACE. EMBED BAR 1'-0".

### TYPICAL SECTION THRU PIER CAP

## TYPICAL SECTION THRU COLUMN

30°-11"

## TYPICAL FOOTING REINFORCEMENT AND PILE PLAN

NO.	DATE	REVISION
-----	------	----------

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

STRUCTURE B-64-215


DRAWN BY ZDM PLANS CK'D ACK'D

SHEET 9 OF 10


## PIER 1 DETAILS

68






TYPICAL SECTION THRU PIER CAP



## TYPICAL SECTION THRU COLUMN



**BILL OF BARS  
PIER 2**

UNCOATED = 17,800 LBS.

MARK	NUMBER		LENGTH	BENT	LOCATION
	COATED	UNCOATED			
D801	12	35'-8"	FOOTING	- BOT.	HORIZ.
D802	48	8'-8"	FOOTING	- BOT.	HORIZ.
D703	12	35'-8"	FOOTING	- TOP	HORIZ.
D504	36	8'-8"	FOOTING	- TOP	HORIZ.
D805	72	7'-6"	X	FOOTING - DOWELS	VERT.
D806	72	29'-4"	COLUMN		VERT.
D507	324	10'-6"	X	COLUMN - STIRRUP	HORIZ.
D608	26	22'-8"	CRASH WALL	- SIDES	HORIZ.
D609	26	17'-6"	X	CRASH WALL - ENDS	HORIZ.
D410	20	29'-6"	X	CRASH WALL - STIRRUP	VERT.
D411	18	12'-5"	CRASH WALL - COL. FACES & ENDS		VERT.
D712	8	31'-1"	PIER CAP - BOT. LONGIT. REIN.		HORIZ.
D513	4	31'-1"	PIER CAP - SKIN REINFORCEMENT		HORIZ.
D714	8	32'-11"	X	PIER CAP - TOP LONGIT. REIN.	HORIZ.
D415	40	10'-2"	X	PIER CAP - STIRRUP	VERT.
D516	6	5'-7"	X	PIER CAP - END STIRRUP	HORIZ.
D417	4	14'-0"	PIER CAP - TOP		HORIZ.
D518	14	5'-8"	X	PIER CAP - TOP	VERT.
D519	8	2'-0"	PIER CAP - DOWEL BAR		VERT.

THE FIRST DIGIT OF A BAR MARK SIGNIFIES THE BAR SIZE.

ALL BAR BEND DIMENSIONS ARE OUT TO OUT OF BAR.

## NOTES


PIER 2 TO BE SUPPORTED ON HP 10 X 42 STEEL PILING DRIVEN TO A REQUIRED DRIVING DISTANCE OF 170 TONS PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA. ESTIMATED 35 FT PILE LENGTHS AT PIER 2.

FOR PILE SPLICING DETAILS SEE "CROSS SECTION, GENERAL NOTES AND QUANTITIES" SHEET

(D01) KEYED CONSTRUCTION JOINT FOR ALL COLUMNS AND FOOTINGS FORMED BY BEVELED 1'-3" X 2'-0" X 4".

(D02) KEYED CONSTRUCTION JOINT BETWEEN BEAM SEATS FORMED BY BEVELED 2" x 6".

(D03) D519 BARS MAY BE PLACED AFTER CONCRETE IS POURED, BUT BEFORE INITIAL SET HAS TAKEN PLACE. EMBED BAR 1'-0".




## TYPICAL FOOTING REINFORCEMENT AND PILE PLAN

## PIER 2 DETAILS

7


PLOT DATE: Aug 25, 2025



## ABUTMENT BEAM SEAT DETAIL

## NOTES


- (E01)  $\frac{1}{2}$ " X 8" X 1'-10" NON-LAMINATED ELASTOMERIC BEARING PAD, TYP.
- (E02) C515, D518 BETWEEN PIER BEAM SEATS, TYP. SEE SHEETS "PIER 1" & "PIER 2", RESPECTIVELY, FOR PLACEMENT.
- (E03)  $\frac{3}{4}$ " CORK FILLER ON VERTICAL BEAM SEAT FACES THAT RUN PARALLEL WITH GIRDER



## PIER BEAM SEAT DETAIL

(SLOPING BEAM SEATS AT PIERS ARE SHOWN ON PIER SHEETS)

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-64-215</b>			
DRAWN BY	ZDM	PLANS CK'D	ACK
<b>BEAM SEAT DETAIL</b>		SHEET 12 OF 22	
		71	
FILE: B640215_12_beam seat.dwg PLOT SCALE:			



PLAN VIEW OF GIRDER ENDS

STIRRUP SPACING TABLE									
SPAN	GIRDER	GIRDER LENGTH "L"	"A"	"B"		"C"		"D"	
1	1-5	52'-4 1/2"	3 3/4"	11 SPA. AT 1'-0" = 11'-0"		---		16 SPA. AT 1'-3" = 20'-0"	
2	1-5	67'-9"	6 1/2"	14 SPA. AT 8" = 9'-4"		6 SPA. AT 1'-0" = 6'-0"		21 SPA. AT 1'-3" = 26'-3"	
3	1-5	52'-4 1/2"	3 3/4"	11 SPA. AT 1'-0" = 11'-0"		---		16 SPA. AT 1'-3" = 20'-0"	

## GIRDER NOTES

TOP OF GIRDER TO BE ROUGH FLOATED AND BROOMED TRANSVERSELY, EXCEPT THE OUTSIDE 2" OF GIRDER, WHICH SHALL RECEIVE A SMOOTH FINISH. AN APPROVED CONCRETE SEALER SHALL BE APPLIED TO ALL SMOOTH SURFACES INCLUDING THE OUTSIDE 2" OF THE TOP FLANGE.

DO NOT APPLY CONCRETE SEALER TO SURFACES RECEIVING APPLICATION OF CONCRETE STAINING.

THE GIRDER SHALL BE PROVIDED WITH A SUITABLE LIFTING DEVICE FOR HANDLING AND ERECTING THE GIRDER. SEE SECTION 503.3.4 OF STANDARD SPECIFICATIONS FOR GUIDANCE.

STRANDS SHALL BE FLUSH WITH THE END OF GIRDER. FOR GIRDER ENDS EMBEDDED COMPLETELY IN CONCRETE, ENDS OF STRANDS SHALL BE COATED WITH NON-BITUMINOUS JOINT SEALER. FOR GIRDER ENDS THAT ARE FINALLY EXPOSED, COAT THE GIRDER ENDS, EXPOSED STRAND ENDS AND ALL NON-BONDING SURFACES WITHIN 2 FEET OF THE GIRDER ENDS WITH A NON-PIGMENTED EPOXY CONFORMING TO AASHTO M-235 TYPE III, GRADE 2, CLASS B OR C. THE EPOXY SHALL BE APPLIED AT LEAST 3 DAYS AFTER MOIST CURING HAS CEASED AND PRIOR TO APPLICATION OF THE SEALER.


ALL GIRDERS SHALL BE CAST FULL LENGTH AS SHOWN.

FOR DIAPHRAGM INSERT & CONNECTION DETAILS, SEE "INTERMEDIATE STEEL DIAPHRAGM" SHEET.

SPACING SHOWN FOR #4 STIRRUPS IS FOR GRADE 60 REINFORCEMENT.

AN ALTERNATE EQUIVALENT OF WELDED WIRE FABRIC (WWF) ASTM A1064 MAY BE SUBSTITUTED FOR THE STIRRUP REINFORCEMENT SHOWN, UPON APPROVAL OF THE STRUCTURES DESIGN SECTION. IF USED, WWF SUBSTITUTION DETAILS SHALL BE SUBMITTED ELECTRONICALLY TO THE WISDOT FABRICATION LIBRARY AND ACCEPTED PRIOR TO SHOP DRAWING SUBMITTAL.

PRESTRESSING STRANDS SHALL BE 0.6" DIA. - 7 - WIRE LOW-RELAXATION STRANDS WITH AN ULTIMATE STRENGTH OF 270,000 PSI.



SECTION THRU GIRDER  
SHOWING WELDED WIRE FABRIC (WWF) STIRRUPS  
ASTM A1064 (FY = 70 KSI)

## SPAN 1 STIRRUP PROJECTION TABLE

	"P" 1st 1/3 OF GIRDER	"P" MID 1/3 OF GIRDER	"P" END 1/3 OF GIRDER
GIRDER 1	7.00"	7.50"	7.00"
GIRDER 2	6.50"	6.50"	6.50"
GIRDER 3	6.50"	7.00"	7.00"
GIRDER 4	7.00"	7.00"	7.00"
GIRDER 5	7.50"	7.50"	7.50"

## SPAN 2 STIRRUP PROJECTION TABLE

	"P" 1st 1/5 OF GIRDER	"P" 2nd 1/5 OF GIRDER	"P" MID 1/5 OF GIRDER	"P" 4th 1/5 OF GIRDER	"P" END 1/5 OF GIRDER
GIRDER 1	7.75"	9.50"	10.00"	9.50"	8.00"
GIRDER 2	7.25"	8.50"	9.00"	8.50"	7.25"
GIRDER 3	7.25"	8.50"	9.00"	8.50"	7.25"
GIRDER 4	7.50"	8.50"	9.00"	8.50"	7.50"
GIRDER 5	8.50"	9.25"	9.50"	9.25"	7.75"


## SPAN 3 STIRRUP PROJECTION TABLE

	"P" 1st 1/3 OF GIRDER	"P" MID 1/3 OF GIRDER	"P" END 1/3 OF GIRDER
GIRDER 1	7.50"	7.50"	7.00"
GIRDER 2	7.00"	7.00"	6.50"
GIRDER 3	7.00"	7.00"	6.50"
GIRDER 4	7.00"	7.00"	6.50"
GIRDER 5	7.50"	8.00"	7.25"

SPAN	GIRDER	GIRDER LENGTH "L"	DEAD LOAD DEFLECTION (IN.)									CONC. STRGTH. $f'_c$ (psi)	DIA. OF STRAND (IN.)	DRAPE PATTERN (IN.)				UNDRAPE PATTERN	
			1/10	2/10	3/10	4/10	5/10	6/10	7/10	8/10	9/10			"A"	"B"	"B"	"C"	TOTAL NO. OF STRANDS	$f'_ci$ (psi) *
1	1-5	52'-4 1/2"	0.2	0.3	0.4	0.5	0.5	0.5	0.4	0.3	0.2	8,000	0.6	---	---	---	---	8	6,800
2	1-5	67'-9"	0.5	0.9	1.3	1.5	1.5	1.5	1.3	0.9	0.5	8,000	0.6	---	---	---	---	16	6,800
3	1-5	52'-4 1/2"	0.2	0.3	0.4	0.5	0.5	0.5	0.4	0.3	0.2	8,000	0.6	---	---	---	---	8	6,800


\* MINIMUM CYLINDER STRENGTH OF CONCRETE @ TIME OF TRANSFER OF PRESTRESS FORCE

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-64-215			
DRAWN BY JDO PLANS CK'D ACK			
28-INCH PRESTRESSED GIRDER	SHEET 13 OF 22		
			72



STANDARD ARRANGEMENTS TO RAISE CENTER OF GRAVITY TO AVOID DRAPING OF 0.6" DIA. STRANDS


(0.5" DIA. STRANDS MAY ALSO BE USED)



\* THE THEORETICAL INITIAL CANTER VALUE AT THE TIME OF STRAND RELEASE AT MIDSPAN MULTIPLIED BY A FACTOR OF 1.4 TO ACCOUNT FOR CANTER GROWTH FROM THE TIME OF STRAND RELEASE TO JOBSITE PLACEMENT.


SPAN	CANTER (IN.)*
1	1.2
2	2.8
3	1.2

THESE VALUES ARE NOT TO BE USED IN DETERMINING 'T', USE ACTUAL GIRDER SHOTS.  
THESE VALUES ARE FOR INFORMATIONAL PURPOSES ONLY.



TYPICAL STRAND PATTERN

3/4" V-GROOVE. EXTEND V-GROOVE TO 6" FROM FRONT FACE OF ABUTMENT DIAPHRAGMS




IF 1 1/4" MINIMUM HAUNCH HEIGHT AT EDGE OF GIRDER CANNOT BE MAINTAINED, THE GRADE LINE MAY BE REVISED BY THE ENGINEER AT THE OPTION OF THE CONTRACTOR. THE PLAN DECK THICKNESS SHALL BE HELD. NOTIFY THE STRUCTURES SECTION IF THE GRADE LINE IS RAISED FROM THE PLAN PROFILE BY MORE THAN 1/8" OR, \*\*IF 3" MINIMUM DECK EMBEDMENT OF TIE BAR CANNOT BE OBTAINED.

TO DETERMINE 'T', ELEVATIONS OF TOP OF GIRDERS AT C OF SUBSTRUCTURE UNITS & AT 1/10 POINTS OF EACH SPAN SHALL BE TAKEN. THEN FOLLOW THIS PROCESS:

TOP OF DECK ELEVATION AT FINAL GRADE (SEE "SUPERSTRUCTURE DETAILS" SHEET)  
- TOP OF GIRDER ELEVATION  
+ DEAD LOAD DEFLECTION  
- SLAB THICKNESS  
= HAUNCH HEIGHT 'T'


NOTE: AN AVERAGE HAUNCH ('T') OF 3.4" WAS USED IN THE QUANTITY "CONCRETE MASONRY BRIDGES".



DEAD LOAD DEFLECTION AND CAMBER DIAGRAM


(SEE GIRDER DATA TABLE ON "28-INCH PRESTRESSED GIRDER" SHEET)

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-64-215			
DRAWN BY	JDO	PLANS CK'D	ACK
28-INCH PRESTRESSED GIRDER DETAILS			SHEET 14 OF 22
73			




DIAPHRAGM SUPPORT

● DIMENSION CHANGES TO 2 1/2" WHEN ALTERNATE PLATE DIAPHRAGM IS USED.




SECTION THROUGH ALTERNATE DIAPHRAGM

SEE "28-INCH PRESTRESSED GIRDER DETAILS" SHEET FOR BOTTOM OF DECK AT EXT. GIRDER INFORMATION.




PART TRANSVERSE SECTION AT DIAPHRAGM




SECTION A-A

(FOR EXTERIOR ATTACHMENT)



DETAIL A

DETAIL B



STEEL DIAPHRAGM LAYOUT PLAN

## NOTES

ALL DIAPHRAGM MATERIAL NOT EMBEDDED IN THE CONCRETE GIRDER SHALL BE PAID FOR AT THE UNIT PRICE BID FOR "STEEL DIAPHRAGMS B-64-215", EACH.




EACH DIAPHRAGM BETWEEN GIRDER SHALL CONSTITUTE ONE UNIT.

ALL DIAPHRAGM STRUCTURAL STEEL SHALL BE ASTM A709 GRADE 36.

ALL DIAPHRAGM MATERIAL INCLUDING BOLTS, NUTS, AND WASHERS SHALL BE GALVANIZED AFTER FABRICATION.

STEEL DIAPHRAGM TO CONCRETE WEB CONNECTION SHALL BE SNUG-TIGHT PLUS 1/4 TURN, UNLESS NOTED OTHERWISE. HIGH STRENGTH BOLTS FOR WEB CONNECTION SHALL MEET THE REQUIREMENTS FOR ASTM A325 OR ASTM A449.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-64-215			
DRAWN BY	ZDM	PLANS CK'D	ACK
INTERMEDIATE STEEL DIAPHRAGM			
SHEET 15 OF 22			
74			



END POST DETAIL  
(WING 1 & 3 POST SHOWN, 2 & 4 SIMILAR)  
(ONLY RAIL POST REINFORCEMENT SHOWN FOR CLARITY)

8 8

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-64-215	DRAWN BY ZDM	PLANS CK'D	ACK
SUPERSTRUCTURE			
75	SHEET 16 OF 22		

**NOTES**

(S03)  $\frac{3}{4}$ " V-GROOVE. EXTEND V-GROOVE TO 6" FROM FRONT FACE OF ABUTMENT DIAPHRAGMS.

( ) INDICATES GIRDER LINE DESIGNATION

**SPAN 1 - TOP OF DECK ELEVATIONS**

	S. ABUT.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	PIER 1
W. DECK EDGE	983.81	983.98	984.14	984.31	984.48	984.64	984.79	984.93	985.05	985.15	985.25
GIRDER 1	983.79	983.96	984.13	984.29	984.46	984.63	984.78	984.92	985.05	985.16	985.26
GIRDER 2	983.75	983.92	984.09	984.25	984.42	984.59	984.75	984.91	985.05	985.17	985.28
GIRDER 3 / CROWN POINT	983.73	983.89	984.06	984.23	984.39	984.56	984.73	984.89	985.04	985.18	985.30
GIRDER 4	983.48	983.65	983.81	983.98	984.15	984.31	984.48	984.65	984.81	984.96	985.09
GIRDER 5	983.24	983.41	983.57	983.74	983.91	984.07	984.24	984.41	984.58	984.74	984.88
E. DECK EDGE	983.12	983.29	983.46	983.62	983.79	983.96	984.12	984.29	984.46	984.62	984.77


**SPAN 2 - TOP OF DECK ELEVATIONS**

	PIER 1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	PIER 2
W. DECK EDGE	985.25	985.35	985.42	985.50	985.51	985.49	985.44	985.37	985.28	985.16	
GIRDER 1	985.26	985.37	985.45	985.51	985.55	985.56	985.51	985.45	985.36	985.25	
GIRDER 2	985.28	985.41	985.50	985.58	985.63	985.66	985.63	985.59	985.52	985.42	
GIRDER 3 / CROWN POINT	985.30	985.44	985.55	985.64	985.71	985.75	985.77	985.76	985.73	985.67	985.59
GIRDER 4	985.09	985.25	985.37	985.48	985.56	985.62	985.65	985.66	985.64	985.60	985.54
GIRDER 5	984.88	985.05	985.20	985.32	985.41	985.48	985.53	985.56	985.53	985.48	
E. DECK EDGE	984.77	984.95	985.10	985.23	985.34	985.42	985.47	985.50	985.51	985.49	985.45

**SPAN 3 - TOP OF DECK ELEVATIONS**


	PIER 2	2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	N. ABUT.
W. DECK EDGE	985.16	985.05	984.93	984.80	984.65	984.49	984.34	984.18	984.03	983.87	983.73
GIRDER 1	985.25	985.15	985.03	984.90	984.76	984.60	984.45	984.29	984.14	983.98	983.83
GIRDER 2	985.42	985.33	985.23	985.11	984.98	984.83	984.68	984.52	984.37	984.21	984.06
GIRDER 3 / CROWN POINT	985.59	985.52	985.42	985.32	985.20	985.06	984.91	984.76	984.60	984.45	984.29
GIRDER 4	985.54	985.47	985.39	985.30	985.19	985.07	984.93	984.78	984.62	984.47	984.31
GIRDER 5	985.48	985.43	985.36	985.28	985.18	985.07	984.94	984.80	984.65	984.50	984.34
E. DECK EDGE	985.45	985.40	985.34	985.26	985.17	985.06	984.94	984.81	984.66	984.51	984.35

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-64-215			
	DRAWN BY	JDO	PLANS CK'D ACK
SUPERSTRUCTURE DETAILS			SHEET 17 OF 22
			76



#### DIAPHRAGM REINFORCEMENT AT ABUTMENT


(SOUTH ABUTMENT SHOWN LOOKING SOUTH, NORTH ABUTMENT SIMILAR)



#### NOTES

- (S04) DIMENSION IS TAKEN NORMAL TO  $\frac{1}{2}$  OF GIRDERS.
- (S05) DIMENSION IS TAKEN NORMAL TO  $\frac{1}{2}$  OF SUBSTRUCTURE UNITS (ABUTMENTS & PIERS).
- (S06)  $\frac{1}{2}$ " DIA. HOLE IN WEB FOR TWO S516 BARS TO BE PLACED SYM. ABOUT  $\frac{1}{2}$  OF GIRDERS. FIELD BEND BARS ALONG SKEW.
- (S07)  $\frac{1}{2}$ " PREFORMED FILLER, TYP. SEE "BEAM SEAT DETAILS" SHEET.
- (S08)  $\frac{1}{2}$ " X 8" X 1'-10" NON-LAMINATED ELASTOMERIC BEARING PAD, TYP. SEE "BEAM SEAT DETAILS" SHEET.
- (S09) 18" RUBBERIZED MEMBRANE WATERPROOFING (R.M.W.), SEAL ALL HORIZONTAL AND VERTICAL JOINTS ON BACK FACE.
- (S10) SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF  $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD  $\frac{1}{8}$ " BELOW SURFACE OF CONCRETE).  $\frac{1}{2}$ " FILLER TO EXTEND FROM BRIDGE SEAT TO TOP OF WING.
- (S11) OPTIONAL CONSTRUCTION JOINT. IF USED, DECK POUR MUST BE WITHIN 2 WEEKS FROM THE TIME OF THE DIAPHRAGM POUR.
- (S12) APPLY PROTECTIVE SURFACE TREATMENT TO PAVING NOTCH


□ INDICATES WING NUMBER




#### PLAN VIEW OF DIAPHRAGM AT WINGS

(SOUTH ABUTMENT SHOWN, NORTH ABUTMENT SIMILAR)


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-64-215			
DRAWN BY	ZDM	PLANS CK'D	ACK
ABUTMENT DIAPHRAGM REINFORCEMENT		SHEET 18 OF 22	
		77	

**DIAPHRAGM REINFORCEMENT AT PIER**

(PIER 1 SHOWN LOOKING NORTH, PIER 2 SIMILAR)

**SECTION THRU DIAPHRAGM AT PIER**

(PIER 1 SHOWN LOOKING WEST, PIER 2 SIMILAR)

**PLAN VIEW OF DIAPHRAGM AT PIER**(PIER 1 SHOWN, PIER 2 SIMILAR)  
(DECK REINFORCEMENT NOT SHOWN FOR CLARITY)**NOTES**

CONCRETE DIAPHRAGM TO EXTEND BETWEEN OUTSIDE FACES OF EXTERIOR GIRDERS.

(S04) DIMENSION IS TAKEN NORMAL TO  $\mathbb{Q}$  OF GIRDERS.(S05) DIMENSION IS TAKEN NORMAL TO  $\mathbb{Q}$  OF SUBSTRUCTURE UNITS (ABUTMENTS & PIERS).(S07)  $\frac{1}{2}$ " PREFORMED FILLER, TYP. SEE "BEAM SEAT DETAILS" SHEET.(S08)  $\frac{1}{2}$ " X 8" X 1'-10" NON-LAMINATED ELASTOMERIC BEARING PAD, TYP. SEE "BEAM SEAT DETAILS" SHEET.

(S11) OPTIONAL CONSTRUCTION JOINT. IF USED, DECK POUR MUST BE WITHIN 2 WEEKS FROM THE TIME OF THE DIAPHRAGM POUR.

(S13) DIMENSION IS TAKEN PARALLEL TO  $\mathbb{Q}$  GIRDERS

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-64-215</b>			
DRAWN BY	JDO	PLANS CK'D	ACK
<b>PIER DIAPHRAGM REINFORCEMENT</b> SHEET 19 OF 22			
78			

BILL OF BARS  
SUPERSTRUCTURE

COATED = 36,570 LBS.

MARK	NUMBER		LENGTH	BENT	BAR SERIES	LOCATION
	COATED	UNCOATED				
S401	144		45'-0"			DECK - BOTTOM - ALL SPANS LONGIT.
S402	70		37'-0"			DECK - TOP - SPAN 1 & 3 LONGIT.
S903	70		36'-0"			DECK - TOP - CONTINUITY AT PIERS LONGIT.
S904	70		14'-0"			DECK - TOP - CONTINUITY AT PIERS LONGIT.
S405	35		35'-4"			DECK - TOP - SPAN 2 LONGIT.
S406	70		13'-7"	▲		DECK - BOT. - ENDS TRANS.
S407	68		12'-10"	▲		DECK - TOP - ENDS TRANS.
S408	533		26'-2"			DECK - TOP & BOT. TRANS.
S609	224		6'-0"			DECK - TOP AT INTERIOR RAIL POSTS LONGIT.
S610	120		11'-6"	X		DECK - TOP AT RAIL POSTS TRANS.
S611	16		4'-8"	X		DECK - TOP AT END RAIL POSTS LONGIT.
S412	24		4'-5"	X		ABUT. - DIAPHRAGM BTWN. SEATS VERT.
S413	16		3'-2"			ABUT. - DIAPHRAGM BTWN. SEATS HORIZ.
S514	52		11'-6"	X		ABUT. - DIAPHRAGM VERT.
S615	48		4'-0"			ABUT. - DIAPHRAGM AT F.F. HORIZ.
S516	20		6'-0"			ABUT. - DIAPHRAGM - THRU GIRDER HORIZ.
S517	44		6'-10"	X		ABUT. - DIAPHRAGM VERT.
S518	8		7'-8"	X		ABUT. - DIAPHRAGM AT WINGS VERT.
S619	8		7'-4"	X		ABUT. - DIAPHRAGM AT WINGS HORIZ.
S620	4		7'-11"	X		ABUT. - DIAPHRAGM AT WINGS HORIZ.
S621	10		33'-6"			ABUT. - DIAPHRAGM AT B.F. & TOP HORIZ.
S522	32		8'-7"	X		PIER - DIAPHRAGM VERT.
S423	64		3'-8"			PIER - DIAPHRAGM - F.F. & B.F. - BOT. HORIZ.
S424	12		33'-6"			PIER - DIAPHRAGM - TOP HORIZ.
S425	32		8'-0"	X		PIER - DIAPHRAGM INTO DECK LONGIT.

THE FIRST DIGIT OF A BAR MARK SIGNIFIES THE BAR SIZE.


ALL BAR BEND DIMENSIONS ARE OUT TO OUT OF BAR.

▲ LENGTH SHOWN FOR BAR IS AN AVERAGE LENGTH AND SHOULD ONLY BE USED FOR BAR WEIGHT CALCULATIONS. SEE "BAR SERIES TABLE" FOR ACTUAL LENGTHS.


## BAR SERIES TABLE

MARK	NO. REQ'D	LENGTH
S406	2 SERIES OF 35	1'-3" TO 25'-11"
S407	2 SERIES OF 34	1'-2" TO 24'-5"


BUNDLE AND TAG EACH SERIES SEPARATELY.




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-64-215			
DRAWN BY	ZDM	PLANS CK'D	ACK
SUPERSTRUCTURE REINFORCEMENT		SHEET 20 OF 22	
		79	



SECTION THRU RAILING ON DECK



FIELD ERECTION JOINT DETAIL





SECTION THRU POST WEB

## LEGEND



- ① W6 x 25 WITH 1 1/8" x 1 1/2" HORIZ. SLOTS ON EACH SIDE OF POST FOR BOLT NO. 6. CUT BOTTOM OF POST TO MATCH "CROSS" SLOPE OF ROADWAY. PLACE POST VERTICAL. PLACE POSTS NORMAL TO GRADE LINE.
- ② PLATE 1 1/4" x 11 3/4" x 1'-8" WITH 1 1/16" DIA. OVERSIZED HOLES FOR ANCHOR BOLTS NO. 3. WELD TO NO. 1 AS SHOWN.
- ③ ASTM A449 - 1 1/8" DIA. ANCHOR BOLTS WITH NUT AND HARDENED WASHER (ALL GALVANIZED). 5 REQ'D. PER POST. THREAD 3" AND PLACE NORMAL TO PLATE NO. 2. CHAMFER TOP OF BOLTS BEFORE THREADING. USE 1'-9" LONG IN ABUTMENT PLATE. AT POSTS ON CONCRETE SLAB SUPERSTRUCTURES WHERE THE SLAB THICKNESS IS > 16" USE 1'-3" LONG. USE 10 3/4" LONG AT ALL OTHER LOCATIONS. (AN EQUIVALENT THREADED ROD WITH NUTS AND HARDENED WASHERS MAY BE SUBSTITUTED FOR ANCHOR BOLTS IN WINGS IF REQ'D. FOR CONSTRUCTABILITY.)
- ④ 5/8" x 11" x 1'-8" ANCHOR PLATE (GALVANIZED) WITH 1 1/16" DIA. HOLES FOR ANCHOR BOLTS NO. 3
- ⑤ TS 5 x 4 x 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- ⑤A TS 5 x 5 x 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- ⑥ 7/8" DIA. A325 SLOTTED ROUND HEAD BOLT WITH NUT, 3/16" x 1 1/8" x 1 1/8" MIN. WASHER, AND LOCK WASHER (2 REQ'D. AT EACH RAIL TO POST LOCATION.)
- ⑨ SPLICE SLEEVE FABRICATED FROM 1/4" PLATE. PROVIDE "SLIDING FIT".
- ⑩ 3/8" x 3 5/8" x 2'-4" PLATE. 2 PER RAIL. USED IN NO. 5 & 5A.
- ⑩A 3/8" x 2 5/8" x 2'-4" PLATE USED IN NO. 5. 3/8" x 3 5/8" x 2'-4" PLATE USED IN NO. 5A. 2 PER RAIL.
- ⑪ 7/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER AND LOCK WASHER. USE 15 1/16" x 1 1/4" LONG. SLOTTED HOLES IN PLATE NO. 10A. AT FIELD JOINTS AND 15 1/16" x 2 1/4" MIN. LONGIT. SLOTTED HOLES AT EXP. JOINTS IN PLATE NO. 10A. PROVIDE 1 1/16" DIA. ROUND HOLES IN TUBES NO. 5 AND NO. 5A.

## NOTES

1. BID ITEM SHALL BE "RAILING TUBULAR TYPE M" WHICH INCLUDES ALL ITEMS SHOWN.
2. RAIL POST AND BASE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 50. HOLLOW RAILING STRUCTURAL TUBING SHALL CONFORM TO THE REQUIREMENTS OF ASTM A500 GRADE B OR C WITH A CERTIFIED FY = 50 KSI. ANCHOR PLATES, AND SPLICE TUBE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 36.
3. THE NUT SECURING THE POST BASE PLATE TO THE CONCRETE SHALL BE TIGHTENED TO A SNUG FIT AND GIVEN AN ADDITIONAL 1/8 TURN.
4. RAILS SHALL BE CONTINUOUS OVER A MINIMUM OF THREE (3) POSTS WITHOUT SPLICES WHERE POSSIBLE. RAILS SHALL BE SPLINED IN A PANEL OVER EXPANSION JOINTS.
5. ENDS OF TUBE SECTIONS SHALL BE SAWED. GRIND SMOOTH EXPOSED EDGES. ALL CUT ENDS SHALL BE TRUE AND SMOOTH.
6. WELD IS THE SAME ON BOTH FLANGES. FLANGE WELD DOES NOT REQUIRE MAGNETIC PARTICLE TESTING.
7. FILL BOLT SLOT OPENINGS IN POST SHIMS AND PLATE NO. 2 AND CAULK AROUND PERIMETER OF PLATE NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. STEEL POST SHIMS MAY BE USED UNDER POSTS WHERE REQ'D. FOR ALIGNMENT.
8. POST BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.
9. ALL MATERIAL SHALL BE GALVANIZED AFTER FABRICATION. PRIOR TO GALVANIZING, ALL STEEL RAILING POSTS & STEEL TUBING SHALL BE GIVEN A NO. 6 BLAST CLEANING BY S.S.P.C. SPECIFICATIONS.




SHOP RAIL SPLICE DETAIL  
(LOCATION MUST BE SHOWN ON SHOP DRAWINGS)SECTION THRU RAIL  
NOTE: CONNECTIONS AT LOWER RAILS SHOWN. CONNECTIONS AT TOP RAIL SIMILAR.

TYPICAL RAIL TO POST CONNECTIONS

ANCHOR BOLTS  
\* ANCHOR BOLT ASSEMBLY MAY BE TACK WELDED, EITHER IN THE SHOP, OR IN THE FIELD AFTER THE ANCHOR PLATE IS PLACED.


SECTION A-A

(R01) TIE TO TOP MAT OF STEEL.

ANCHOR PLATE  
AT RAIL TO DECK CONNECTIONPOST SHIM  
DETAIL

PART ELEVATION OF RAILING

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-64-215			
DRAWN BY	ZDM	PLANS CK'D	ACK
RAILING TUBULAR TYPE M			
SHEET 21 OF 22			
FILE: B640215_21_mraill.dwg			
PLOT SCALE: 80			



PLAN VIEW SHOWING LIMITS OF SLOPE PAVING CRUSHED AGGREGATE


## NOTES

BID ITEM SHALL BE "SLOPE PAVING CRUSHED AGGREGATE".

WOOD FORMS MAY BE LEFT IN PLACE WHEN OF A QUALITY  
ACCEPTABLE TO THE ENGINEER.

 INDICATES WING NUMBER

F.F. - FRONT FACE  
B.F. - BACK FACE



TYPICAL SECTION THRU SLOPE  
PAVING CRUSHED AGGREGATE

(ROUND STONE WILL NOT BE ACCEPTED)  
(S. ABUT. SHOWN IN ABUT. SIMILAR)

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-64-215</b>			
DRAWN BY		PLANS CK'D	ACK
<b>SLOPE PAVING</b> <b>CRUSHED</b> <b>AGGREGATE</b>		SHEET 22 OF 22	
		81	
FILE: B640215-22_slope pav.dwg			


STATION	DISTANCE	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)		
		CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	EXPANDED FILL	MASS ORDINATE
12+85.00	0.00	54.57	10.00	8.14	0	0	0	0	0	0
13+00.00	15.00	55.07	10.00	8.60	30	6	5	30	6	18
13+50.00	50.00	40.19	10.00	21.15	88	19	28	30	41	52
14+00.00	50.00	22.06	10.00	38.58	58	19	55	30	110	22
14+30.00	30.00	8.32	10.00	79.08	17	11	65	30	191	-53
14+36.84	6.84	11.43	10.00	92.19	3	3	22	30	219	-81
14+54.41	17.57	22.77	5.00	27.94	11	5	39	30	268	-124
STRUCTURE B-64-0215										
		SOUTH APPROACH TOTAL			207	63	214			


STATION	DISTANCE	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)		
		CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	EXPANDED FILL	MASS ORDINATE
STRUCTURE B-64-0215										
16+29.62	0.00	5.00	5.00	21.47	0	0	0	0	0	0
16+37.72	8.10	10.00	10.00	31.56	2	2	8	2	10	-10
16+47.18	9.46	10.00	10.00	57.69	4	4	16	6	30	-30
16+54.29	7.11	10.00	10.00	113.60	3	3	23	9	59	-59
16+71.52	17.23	10.00	10.00	78.48	6	6	61	15	135	-135
16+72.00	0.48	10.00	10.00	104.80	0	0	2	15	138	-138
16+94.00	22.00	10.00	10.00	76.95	8	8	74	23	231	-230
17+00.00	6.00	10.00	10.00	67.56	2	2	16	25	251	-250
17+50.00	50.00	12.66	10.00	26.76	21	19	87	46	360	-357
18+00.00	50.00	31.22	10.00	2.19	41	19	27	87	394	-369
18+50.00	50.00	46.08	10.00	0.00	72	19	2	159	397	-318
18+75.00	25.00	49.17	10.00	0.00	44	9	0	203	397	-283
		NORTH APPROACH TOTAL			203	91	316			


STATION	DISTANCE	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)		
		CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	EXPANDED FILL	MASS ORDINATE
50+06.00	0.00	0.71	0.00	0.23	0	0	0	0	0	0
50+25.00	19.00	1.45	0.00	1.18	1	0	0	1	0	1
50+30.00	5.00	3.38	0.00	0.99	0	0	0	1	0	1
50+50.00	20.00	9.56	0.00	0.10	5	0	0	6	0	6
50+75.00	25.00	12.50	0.00	0.07	10	0	0	16	0	16
51+00.00	25.00	21.59	0.00	0.04	16	0	0	32	0	32
51+04.00	4.00	18.17	0.00	0.04	3	0	0	35	0	35
51+25.00	21.00	2.93	0.00	0.29	8	0	0	43	0	43
51+29.00	4.00	0.80	0.00	0.17	0	0	0	43	0	43
		RAILROAD DITCH GRADING TOTAL			43	0	0			


STATION	DISTANCE	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)		
		CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	SALVAGED/UNUSABLE PAVEMENT MATERIAL	FILL	CUT	EXPANDED FILL	MASS ORDINATE
0+14.03	0.00	0.00	0.00	81.25	0	0	0	0	0	0
0+20.00	5.97	0.00	0.00	96.84	0	0	20	0	25	-25
0+30.00	10.00	0.00	0.00	119.29	0	0	40	0	75	-75
0+40.00	10.00	0.00	0.00	96.41	0	0	40	0	125	-125
0+50.00	10.00	0.00	0.00	66.60	0	0	30	0	163	-163
0+60.00	10.00	0.00	0.00	40.18	0	0	20	0	188	-188
0+70.00	10.00	0.00	0.00	15.88	0	0	10	0	201	-200
0+80.00	10.00	0.52	0.00	2.09	0	0	3	0	205	-204
0+90.00	10.00	9.90	0.00	0.17	2	0	0	2	205	-202
		DRIVEWAY TOTAL			2	0	163			
		PROJECT TOTAL			455	154	693			


NOTES:	
1 - CUT	CUT INCLUDES SALVAGED/UNUSABLE PAVEMENT MATERIAL
2 - SALVAGED/UNUSABLE PAVEMENT MATERIAL	THIS DOES NOT SHOW UP IN CROSS SECTIONS
3 - FILL	DOES NOT INCLUDE UNUSABLE PAVEMENT EXC VOLUME
8 - MASS ORDINATE	CUT - SALVAGED PAVT - (FILL * FILL FACTOR)














PROJECT NO: 3846-00-74

HWY: HILLSIDE RD

COUNTY: WALWORTH

CROSS SECTIONS: HILLSIDE RD

SHEET

E

FILE NAME : G:\00-PROJECT FILES\2023\23137 ID 3846-00-04 T LINN - HILLSIDE RD BRIDGE OVER CMSTPP RAILROAD P-64-0101\0-CAD\Sheets\090201\_XS.DWG  
LAYOUT NAME - 090206\_xs

PLOT DATE : 10/10/2025 8:47 AM


PLOT BY : ERIK MEYER

PLOT NAME :

PLOT SCALE : 1 IN:10 FT HORZ. / 1 IN:10 FT VERT.

WISDOT/CADDSS

WISDOT/CADD5 STREET 45



PROJECT NO: 3846-00-74

HWY: HILLSIDE RD

COUNTY: WALWORTH

## CROSS SECTIONS: RAILROAD GRADING

SHEET

E

FILE NAME : G:\00-PROJECT FILES\2023\23137 ID 3846-00-04 T LINN - HILLSIDE RD BRIDGE OVER CMSTPP RAILROAD P-64-0101\0-CAD\Sheets\090207\_XS.DWG  
LAYOUT NAME - 090207\_xs

PLOT DATE : 10/10/2025 8:48 AM


PLOT BY : ERIK MEYER

PLOT NAME

PLOT SCALE : 1 IN:10 FT HORZ. / 1 IN:10 FT VERT.

1/ISDOT/CADD\$ SHEET 49

WISDOT/CADD5 STREET 45



PROJECT NO: 3846-00-74

HWY: HILLSIDE RD

COUNTY: WALWORTH

## CROSS SECTIONS: RAILROAD GRADING

SHEET

E |

FILE NAME : G:\00-PROJECT FILES\2023\23137 ID 3846-00-04 T LINN - HILLSIDE RD BRIDGE OVER CMSTPP RAILROAD P-64-0101\0-CAD\Sheets\090207\_XS.DWG  
LAYOUT NAME - 090208\_xs


PLOT DATE : 10/10/2025 8:48 AM


PLOT BY : ERIK MEYE


PLOT NAME

PLOT SCALE : 1 IN:10 FT HORZ. / 1 IN:10 FT VERT.

1/ISDOT/CADD\$ SHEET 49







PROJECT NO: 3846-00-74

HWY: HILLSIDE RD

COUNTY: WALWORTH

## CROSS SECTIONS: RAILROAD GRADING

SHEET

E

FILE NAME : G:\00-PROJECT FILES\2023\23137 ID 3846-00-04 T LINN - HILLSIDE RD BRIDGE OVER CMSTPP RAILROAD P-64-0101\0-CAD\Sheets\090207\_XS.DWG  
LAYOUT NAME - 090211\_xs


PLOT DATE : 10/10/2025 8:48 AM

PLOT BY : ERIK MEYE

PLOT NAME

PLOT SCALE : 1 IN:10 FT HORZ. / 1 IN:10 FT VERT.

WISDOT/CADDS SHEET 40



## ***Wisconsin Department of Transportation***

Dedicated people creating transportation solutions  
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>