


FEBRUARY 2026

ORDER OF SHEETS

Section No. 1 Title
 Section No. 2 Typical Sections and Details
 Section No. 3 Estimate of Quantities
 Section No. 3 Miscellaneous Quantities
 Section No. 4 Right of Way Plat
 Section No. 5 Plan and Profile
 Section No. 6 Standard Detail Drawings
 Section No. 7 Sign Plates
 Section No. 8 Structure Plans
 Section No. 9 Computer Earthwork Data
 Section No. 9 Cross Sections

TOTAL SHEETS = 64



DESIGN DESIGNATION 4008-02-00

A.A.D.T. (2026) = 800
 A.A.D.T. (2046) = 830
 D.H.V. = 100
 D.D. = 60/40
 T. = 3.9%
 DESIGN SPEED = 30 MPH
 ESALS = 52,000

CONVENTIONAL SYMBOLS

PLAN	PROFILE
CORPORATE LIMITS	GRADE LINE
PROPERTY LINE	ORIGINAL GROUND
LOT LINE	MARSH OR ROCK PROFILE (To be noted as such)
LIMITED HIGHWAY EASEMENT	SPECIAL DITCH
EXISTING RIGHT OF WAY	GRADE ELEVATION
PROPOSED OR NEW R/W LINE	CULVERT (Profile View)
SLOPE INTERCEPT	UTILITIES
REFERENCE LINE	ELECTRIC
EXISTING CULVERT	FIBER OPTIC
PROPOSED CULVERT {Box or Pipe}	GAS
COMBUSTIBLE FLUIDS	SANITARY SEWER
MARSH AREA	STORM SEWER
WOODED OR SHRUB AREA	TELEPHONE
	WATER
	UTILITY PEDESTAL
	POWER POLE
	TELEPHONE POLE

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION

PLAN OF PROPOSED IMPROVEMENT

V CLEVELAND, CTH XX


BRANCH OF CENTERVILLE CREEK BRIDGE

CTH XX
 MANITOWOC COUNTY

STATE PROJECT NUMBER

4008-02-70

STATE PROJECT	FEDERAL PROJECT	
	PROJECT	CONTRACT
4008-02-70		



HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COORDINATE REFERENCE SYSTEM (WISCRS), MANITOWOC COUNTY NAD83 (2011), IN U.S. SURVEY FEET. POSITIONS SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES ARE THE SAME AS GROUND DISTANCES. ELEVATIONS ARE REFERENCED TO NAVD 88 (2012). GPS DERIVED ELEVATIONS ARE BASED ON GEOID 18.

ACCEPTED FOR
 MANITOWOC COUNTY

9/29/25 Murray R. Glen
 Highway Commissioner
 Signature and Title of Official

JT ENGINEERING



10/12/25 Murray R.
 (Professional Engineer Signature)

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION

PREPARED BY
 Surveyor JT ENGINEERING, INC.
 Designer JT ENGINEERING, INC.
 Project Manager MICHAEL COHEN
 Regional Examiner REGIONAL EXAMINER
 Regional Supervisor KIMBERLY SLEZAK

APPROVED FOR THE DEPARTMENT
 DATE: 10/12/25 Michael Cohen
 (Signature)

GENERAL NOTES

THE CONTRACTOR SHALL COORDINATE THEIR CONSTRUCTION ACTIVITIES WITH A CALL TO DIGGER'S HOTLINE AND/OR A DIRECT CALL TO THE UTILITIES THAT HAVE FACILITIES IN THE AREA.

ANY LOCAL OR MUNICIPAL UTILITY WHICH IS NOT A MEMBER OF THE DIGGERS HOTLINE MUST BE CONTACTED SEPARATELY.

NO TREES OR SHRUBS SHALL BE REMOVED WITHOUT APPROVAL OF THE ENGINEER

ALL DISTURBED AREAS NOT OTHERWISE SURFACED ARE TO BE TOPSOIL, FERTILIZER, SEEDED AND COVERED WITH EROSION MAT.

DO NOT PLACE FERTILIZER WITHIN 20 FEET OF A WETLAND OR WATER BODY.

THE LOCATIONS OF ALL EROSION CONTROL ITEMS AS SHOWN IN THE PLANS IS APPROXIMATE AND SHALL BE DETERMINED BY THE ENGINEER IN THE FIELD.

TRAFFIC CONTROL SHALL FOLLOW SDD "BARRICADES AND SIGNS FOR MAINLINE CLOSURES", DETAIL C.

HMA PAVEMENT WEIGHT CALCULATIONS ARE BASED ON 112 LBS/SY/IN.

TACK COAT HAS BEEN ESTIMATED AT AN APPLICATION OF 0.05 GAL/SY AND SHALL BE PLACED BETWEEN THE LAYERS OF ASPHALTIC PAVEMENT.

ANY REINFORCEMENT THAT IS IN THE CONCRETE PAVEMENT IS CONSIDERED INCIDENTAL TO REMOVING CONCRETE PAVEMENT

UTILITY CONTACTS

WE ENERGIES (ELECTRIC)
BRIAN DRESSLER
500 S 116TH STREET
WEST ALLIS, WI 53214
OFFICE: 608-219-2820
EMAIL: BRIAN.DRESSLER@WE-ENERGIES.COM

WISCONSIN PUBLIC SERVICE (GAS)
KASEY KAPPELMAN
800 COLUMBUS STREET
TWO RIVERS, WI 54241
OFFICE: 920-657-1862
EMAIL: KASEY.KAPPELMAN@WISCONSINPUBLICSERVICE.COM

TDS TELECOM (COMMUNICATIONS)
RYAN LATTE
10 COLLEGE AVENUE, SUITE 218A
APPLETON, WI 54911
OFFICE: 920-xxx-xxxx
EMAIL: RYAN.LATTA@TDSTELECOM.COM

VILLAGE OF CLEVELAND (WATER, SANITARY, STORM SEWER)
STACY GRUNWALD
1150 W WASHINGTON STREET
CLEVELAND, WI 53015
OFFICE: 920-693-3442
EMAIL: SGRUNWALD@CLEVELANDWI.GOV

ORDER OF SECTION 2 DETAIL SHEETS

GENERAL NOTES
TYPICAL SECTIONS
EROSION CONTROL

AGENCY/ PROJECTS CONTACTS

WDNR - NE REGION
MATT SCHAEVE
NORTHEAST REGION
2984 SHAWANO AVE
GREEN BAY, WI 54313
PHONE: 920-366-1544
E-MAIL: MATTHEW.SCHAEVE@WISCONSIN.GOV

DESIGN CONTACT

JT ENGINEERING, INC.
RICH GLEN
1077 CENTENNIAL CENTRE BLVD
HOBART, WI 54155
PHONE: 920-468-4771
EMAIL: RICHG@JT-ENGINEERING.COM

RUNOFF COEFFICIENT TABLE

	HYDROLOGIC SOIL GROUP											
	A			B			C			D		
	SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)		
LAND USE:	0-2	2-6	6 & OVER									
ROW CROPS	.08 .22	.16 .30	.22 .38	.12 .26	.20 .34	.27 .44	.15 .30	.24 .37	.33 .50	.19 .34	.28 .41	.38 .56
MEDIAN STRIP-TURF	.19 .24	.20 .26	.24 .30	.19 .25	.22 .28	.26 .33	.20 .26	.23 .30	.30 .37	.20 .27	.25 .32	.30 .40
SIDE SLOPE: TURF			.25 .32			.27 .34			.28 .36			.30 .38
PAVEMENT:												
ASPHALT							.70 - .95					
CONCRETE							.80 - .95					
BRICK							.70 - .80					
DRIVES, WALKS							.75 - .85					
ROOFS							.75 - .95					
GRAVEL ROADS, SHOULDERS							.40 - .60					

TOTAL PROJECT AREA = 0.64 ACRES

TOTAL AREA EXPECTED TO BE DISTURBED BY CONSTRUCTION ACTIVITIES = 0.15 ACRES

STANDARD ABBREVIATIONS

ADT	AVERAGE DAILY TRAFFIC	NC	NORMAL CROWN
AC	ASPHALT CEMENT	PT	POINT OF TANGENT
AGG	AGGREGATE	PC	POINT OF CURVATURE
ASPH	ASPHALT	PI	POINT OF INTERSECTION
BM	BENCHMARK	PE	PRIVATE ENTRANCE
C/L	CENTERLINE	R	RADIUS
CONC	CONCRETE	REM	REMOVE
CMP	CORRUGATED METAL PIPE	R/L OR RL	REFERENCE LINE
CR	CREEK	RCCP	REINFORCED CONCRETE CULVERT PIPE
D	DEGREE OF CURVE	RPSS	REINFORCED CONCRETE STORM SEWER
DHV	DESIGN HOUR VOLUME	RO	RUNOUT
ESALS	EQUIVALENT SINGLE AXIS LOADS	R/W	RIGHT OF WAY
EXIST	EXISTING	STA	STATION
FE	FIELD ENTRANCE	SE	SUPER ELEVATION
HYD	HYDRANT	SS	STORM SEWER
IP	IRON PIPE	T	TANGENT
L	LENGTH OF CURVE	TEL	TELEPHONE
LC	LONG CHORD OF CURVE	TLE	TEMPORARY LIMITED EASEMENT
LR	LENGTH OF RUN OFF	T	TRUCKS
MH	MANHOLE	VC	VERTICAL CURVE
		W	WELL

PROJECT NO: 4008-02-70

HWY: CTH XX

COUNTY: MANITOWOC



GENERAL NOTES



SHEET


E


2

2









PROJECT NO: 4008-02-70

HWY: CTH XX

COUNTY: MANITOWOC

EROSION CONTROL

SHEET

E

FILE NAME : X:\PROJECTS\MANITOWOC\240016 4008-02-00 CTH XX V CLEVELAND BRIDGE\DESIGN\C3D\Sheets\PLAN\022001-EC.DWG
LAYOUT NAME - EC-01

PLOT DATE : 7/10/2025 6:05 AM

PLOT BY : JAKE NEERDAELS

PLOT NAME :

PLOT SCALE : 1 IN:40 FT

WISDOT/CADD'S SHEET 42

6

Estimate Of Quantities

4008-02-70

Line	Item	Item Description	Unit	Total	Qty
0002	203.0270	Removing Structure Over Waterway Debris Capture (structure) 01. B-36-913	EACH	1.000	1.000
0004	204.0100	Removing Concrete Pavement	SY	145.000	145.000
0006	204.0150	Removing Curb & Gutter	LF	17.000	17.000
0008	204.0165	Removing Guardrail	LF	462.000	462.000
0010	205.0100	Excavation Common	CY	320.000	320.000
0012	205.0400	Excavation Marsh	CY	75.000	75.000
0014	206.1001	Excavation for Structures Bridges (structure) 01. B-36-0256	EACH	1.000	1.000
0016	208.0100	Borrow	CY	72.000	72.000
0018	209.2500	Backfill Granular Grade 2	TON	150.000	150.000
0020	210.1500	Backfill Structure Type A	TON	480.000	480.000
0022	213.0100	Finishing Roadway (project) 01. 4008-02-70	EACH	1.000	1.000
0024	305.0110	Base Aggregate Dense 3/4-Inch	TON	70.000	70.000
0026	305.0120	Base Aggregate Dense 1 1/4-Inch	TON	605.000	605.000
0028	311.0110	Breaker Run	TON	40.000	40.000
0030	415.0410	Concrete Pavement Approach Slab	SY	192.000	192.000
0032	450.4000	HMA Cold Weather Paving	TON	90.000	90.000
0034	455.0605	Tack Coat	GAL	20.000	20.000
0036	465.0105	Asphaltic Surface	TON	90.000	90.000
0038	502.0100	Concrete Masonry Bridges	CY	239.000	239.000
0040	502.3200	Protective Surface Treatment	SY	307.000	307.000
0042	505.0400	Bar Steel Reinforcement HS Structures	LB	6,300.000	6,300.000
0044	505.0600	Bar Steel Reinforcement HS Coated Structures	LB	33,630.000	33,630.000
0046	513.4061	Railing Tubular Type M	LF	111.000	111.000
0048	516.0500	Rubberized Membrane Waterproofing	SY	18.000	18.000
0050	550.1100	Piling Steel HP 10-Inch X 42 Lb	LF	540.000	540.000
0052	606.0300	Riprap Heavy	CY	155.000	155.000
0054	612.0406	Pipe Underdrain Wrapped 6-Inch	LF	200.000	200.000
0056	614.0200	Steel Thrie Beam Structure Approach	LF	82.600	82.600
0058	614.0370	Steel Plate Beam Guard Energy Absorbing Terminal	EACH	4.000	4.000
0060	619.1000	Mobilization	EACH	1.000	1.000
0062	624.0100	Water	MGAL	11.000	11.000
0064	625.0100	Topsoil	SY	990.000	990.000
0066	628.1504	Silt Fence	LF	475.000	475.000
0068	628.1520	Silt Fence Maintenance	LF	475.000	475.000
0070	628.1905	Mobilizations Erosion Control	EACH	5.000	5.000
0072	628.1910	Mobilizations Emergency Erosion Control	EACH	3.000	3.000
0074	628.2008	Erosion Mat Urban Class I Type B	SY	990.000	990.000
0076	628.6005	Turbidity Barriers	SY	179.000	179.000
0078	628.7504	Temporary Ditch Checks	LF	90.000	90.000
0080	628.7560	Tracking Pads	EACH	2.000	2.000
0082	628.7570	Rock Bags	EACH	20.000	20.000
0084	629.0210	Fertilizer Type B	CWT	1.000	1.000
0086	630.0130	Seeding Mixture No. 30	LB	41.000	41.000
0088	630.0140	Seeding Mixture No. 40	LB	6.000	6.000
0090	630.0200	Seeding Temporary	LB	24.000	24.000
0092	630.0500	Seed Water	MGAL	23.000	23.000
0094	634.0614	Posts Wood 4x6-Inch X 14-FT	EACH	5.000	5.000
0096	637.2210	Signs Type II Reflective H	SF	3.000	3.000
0098	637.2230	Signs Type II Reflective F	SF	12.000	12.000

Estimate Of Quantities

4008-02-70

Line	Item	Item Description	Unit	Total	Qty
0100	638.2602	Removing Signs Type II	EACH	9.000	9.000
0102	638.3000	Removing Small Sign Supports	EACH	9.000	9.000
0104	642.5001	Field Office Type B	EACH	1.000	1.000
0106	643.0420	Traffic Control Barricades Type III	DAY	1,080.000	1,080.000
0108	643.0705	Traffic Control Warning Lights Type A	DAY	1,440.000	1,440.000
0110	643.0900	Traffic Control Signs	DAY	960.000	960.000
0112	643.5000	Traffic Control	EACH	1.000	1.000
0114	645.0111	Geotextile Type DF Schedule A	SY	130.000	130.000
0116	645.0120	Geotextile Type HR	SY	355.000	355.000
0118	646.2020	Marking Line Epoxy 6-Inch	LF	408.000	408.000
0120	650.4500	Construction Staking Subgrade	LF	370.000	370.000
0122	650.5000	Construction Staking Base	LF	370.000	370.000
0124	650.6501	Construction Staking Structure Layout (structure) 01. B-36-0256	EACH	1.000	1.000
0126	650.9911	Construction Staking Supplemental Control (project) 01. 4008-02-70	EACH	1.000	1.000
0128	650.9920	Construction Staking Slope Stakes	LF	370.000	370.000
0130	690.0150	Sawing Asphalt	LF	240.000	240.000
0132	690.0250	Sawing Concrete	LF	3.000	3.000
0134	715.0502	Incentive Strength Concrete Structures	DOL	1,434.000	1,434.000
0136	715.0720	Incentive Compressive Strength Concrete Pavement	DOL	500.000	500.000
0138	999.2000.S	Installing and Maintaining Bird Deterrent System (station) 01. 12+47.67	EACH	1.000	1.000
0140	SPV.0090	Special 01. Flashing Stainless Steel	LF	95.000	95.000

204 - PAVEMENT REMOVAL

CATEGORY	STATION	TO	STATION	LOCATION	204.0100		204.0150	
					REMOVING CONCRETE PAVEMENT	SY	REMOVING CURB & GUTTER	LF
0010	11+50	-	11+63	LT		-	17	
0010	12+60	-	13+25	LT & RT		145	-	
				TOTAL 0010		145		17

204 - REMOVING GUARDRAIL

CATEGORY	STATION	TO	STATION	LOCATION	204.0165 REMOVING GUARDRAIL	
					LF	
0010	11+92	-	13+92	LT	200	
0010	11+14	-	13+76	RT	262	
				TOTAL 0010		462

3

3

DIVISION	FROM/TO STATION	LOCATION	205.0100 COMMON EXCAVATION (CY) (1)		AVAILABLE MATERIAL (5)	205.0400 MARSH EXCAVATION (6)	REDUCED MARSH IN FILL (8)	REDUCED EBS IN FILL (9)	EXPANDED MARSH BACKFILL (10)	EXPANDED EBS BACKFILL (11)	UNEXPANDED FILL (13)	EXPANDED FILL (13)	MASS ORDINAT E +/- (14)	WASTE (15)	208.0100 BORROW (CY)	
			CUT (2)	EBS EXCAVATION (3)	SALVAGED/UNUSABLE PAVEMENT MATERIAL (4)		FACTOR	FACTOR	FACTOR	FACTOR		FACTOR				
DIVISION 1																
CTH XX	10+21/12+33	CTH XX	154	10	36	118	25	25	13	31	13	60	28	90	90	0
WEST B-36-0256			154	10	36	118	25	25	13	31	13	60	28	90	90	0
CTH XX	12+61/14+43	CTH XX	146	10	51	95	50	50	13	63	13	196	167	-72	0	72
EAST B-36-0256			146	10	51	95	50	50	13	63	13	196	167	-72	0	72
GRAND TOTAL			300	20	87	213	75	75	25	94	25	256	195	18	90	72
		TOTAL COMMON EXC		320												

NOTES:

- (1) COMMON EXCAVATION IS THE SUM OF THE CUT AND EBS EXCAVATION COLUMNS. ITEM NUMBER 205.0100
- (2) SALVAGED/UNUSABLE PAVEMENT MATERIAL IS INCLUDED IN CUT.
- (3) EBS EXCAVATION TO BE BACKFILLED WITH BREAKER RUN.
- (4) SALVAGED/UNUSABLE PAVEMENT MATERIAL
- (5) AVAILABLE MATERIAL = CUT - SALVAGED/UNUSABLE PAVEMENT MATERIAL
- (6) MARSH EXCAVATION - TO BE BACKFILLED WITH GRANULAR BACKFILL GRADE 2
- (8) REDUCED MARSH IN FILL - EXCAVATED MARSH MATERIAL IS USABLE IN FILLS OUTSIDE THE 1:1 SLOPE. MARSH IN FILL REDUCTION FACTOR = 1.00
- (9) REDUCED EBS IN FILL - EXCAVATED EBS MATERIAL IS USABLE IN FILLS OUTSIDE THE 1:1 SLOPE. EBS IN FILL REDUCTION FACTOR = 1.00
- (10) EXPANDED MARSH BACKFILL - THIS IS TO BE FILLED WITH GRANULAR BACKFILL GRADE 2. MARSH BACKFILL FACTOR = 1.00
- (11) EXPANDED EBS BACKFILL - THIS IS TO BE FILLED WITH BORROW OR CUT AS WELL.
- (13) EXPANDED FILL = (UNEXPANDED FILL - REDUCED MARSH - REDUCED EBS) * 1.25
- (14) THE MASS ORDINATE + OR - QTY CALCULATED FOR THE DIVISION. PLUS QUANTITY INDICATES AN EXCESS OF MATERIAL WITHIN THE DIVISION. MINUS INDICATES A SHORTAGE OF MATERIAL WITHIN THE DIVISION.
- (15) FACTORS USED TO COMPUTE ANTICIPATED WASTE AND THE COMPUTED WASTE VOLUME IDENTIFIED ARE FOR GENERAL INFORMATION ONLY.

305 - BASE AGGREGATE

CATEGORY	STATION	TO	STATION	LOCATION	209.2500	305.0110	305.0120	311.0110	624.0100
					BACKFILL GRANULAR GRADE 2	BASE AGGREGATE DENSE 3/4-INCH	BASE AGGREGATE DENSE 1 1/4-INCH	BREAKER RUN	WATER MGAL
0010	10+21	-	12+22	LT & RT	50	31	280	20	5
0010	12+74	-	14+43	LT & RT	100	39	325	20	6
				TOTAL 0010	150	70	605	40	11

415 - CONCRETE PAVEMENT

465 - ASPHALTIC SURFACE

415.0410 CONCRETE PAVEMENT APPROACH SLAB					
CATEGORY	STATION	TO	STATION	LOCATION	SY
0010	11+96	-	12+22	LT & RT	102
0010	12+74	-	12+96	LT & RT	90
TOTAL 0010				192	

450.4000 HMA COLD WEATHER PAVING TON					
455.0605 TACK COAT GAL					
465.0105 ASPHALTIC SURFACE TON					
CATEGORY	STATION	TO	STATION	LOCATION	TON
0010	10+95	-	11+96	LT & RT	53
0010	12+96	-	13+90	LT & RT	37
TOTAL 0010				90	20
					90

614 - GUARDRAIL

614.0200 STEEL THRIE BEAM STRUCTURE APPROACH					
614.0370 STEEL PLATE BEAM GUARD ENERGY ABSORBING TERMINAL					
CATEGORY	STATION	TO	STATION	LOCATION	LF
0010	11+41	-	12+10	RT	20.65
0010	11+63	-	12+31	LT	20.65
0010	12+86	-	13+33	RT	20.65
0010	11+63	-	13+54	LT	20.65
TOTAL 0010				82.60	4

628 - EROSION CONTROL

628.1504					
628.1520					
628.1905					
CATEGORY	STATION	TO	STATION	LOCATION	SILT FENCE LF
0010	10+56	-	12+08	RT	170
0010	11+50	-	12+46	LT	55
0010	12+45	-	14+20	RT	170
0010	12+90	-	14+42	LT	-
0010	12+18	-	12+57	BRANCH CENTERVILLE CREEK	-
0010	12+42	-	12+87	BRANCH CENTERVILLE CREEK	-
0010	UNDISTRIBUTED			CTH XX	80
TOTAL 0010				475	475
					5
					3
					179
					90
					2
					20

630 - LANDSCAPING

625.0100					
628.2008 EROSION MAT URBAN CLASS I TYPE					
629.0210					
CATEGORY	STATION	TO	STATION	LOCATION	TOPSOIL SY
0010	10+21	-	11+94	RT	250
0010	11+50	-	12+25	LT	100
0010	12+69	-	14+43	RT	235
0010	13+02	-	14+43	LT	240
0010	UNDISTRIBUTED			LT & RT	165
TOTAL 0010				990	990
					1.00
					41
					6
					24
					23

638 - SIGNING

CATEGORY	STATION	LOCATION	SIGN CODE	SIZE	634.0614	637.2210	637.2230	638.2602	638.3000	REMARKS
					POSTS WOOD 4X6-INCH X 14-FT EACH	SIGNS TYPE II REFLECTIVE H SF	SIGNS TYPE II REFLECTIVE F SF	REMOVING SIGNS TYPE II EACH	REMOVING SMALL SIGN SUPPORTS EACH	
0010	12+12	RT	W5-52R	12X36	1	-	3	1	1	
0010	12+33	LT	W5-52L	12X36	1	-	3	1	1	
0010	12+62	RT	W5-52R	12X36	1	-	3	1	1	
0010	12+84	LT	W5-52L	12X36	1	-	3	1	1	
0010	11+26	RT	-	24X36	-	-	-	1	1	REMOVE WEIGHT LIMIT 20 TONS
0010	11+78	LT	R2-1	24X36	1	3	-	1	1	SPEED LIMIT 25 MPH
0010	13+78	RT	-	24X36	-	-	-	1	1	REMOVE WEIGHT LIMIT 20 TONS
0010	CTH XX & CTH DAIRYLAND	RT	-	-	-	-	-	1	1	REMOVE 20 TON BRIDGE 0.6 MILES AHEAD
0010	CTH XX & LAKESHORE	LT	-	-	-	-	-	1	1	REMOVE 20 TON BRIDGE 0.6 MILES AHEAD
TOTAL 0010					5	3	12	9	9	

643 - TRAFFIC CONTROL

CATEGORY	STATION	TO	STATION	LOCATION	APPROX. SERVICE DAYS	NO. IN SERVICE	643.0420	643.0705	643.0900	643.5000	REMARKS	
							TRAFFIC CONTROL BARRICADES TYPE III DAY	TRAFFIC CONTROL WARNING LIGHTS TYPE A DAY	TRAFFIC CONTROL SIGNS DAY	TRAFFIC CONTROL EACH		
0010	10+21		11+75	CTH XX	60	4	240	6	360	7	420	-
0010	10+21	-	13+25	CTH XX	60	10	600	12	720	2	120	1
0010	13+25		14+69	CTH XX	60	4	240	6	360	7	420	-
TOTAL 0010						1,080		1,440		960	1	

646 - PAVEMENT MARKING


CATEGORY	STATION	TO	STATION	LOCATION	646.2020	REMARKS
					MARKING LINE EPOXY 6-INCH LF	
0010	11+46	-	13+25	CTH XX	50	YELLOW CENTERLINE
0010	11+46	-	13+25	CTH XX	358	WHITE EDGELINE
TOTAL 0010					408	

650 - CONSTRUCTION STAKING

CATEGORY	STATION	TO	STATION	LOCATION	650.4500	650.5000	650.6501.01	650.9911.01	650.9920
					CONSTRUCTION STAKING SUBGRADE LF	CONSTRUCTION STAKING BASE LF	CONSTRUCTION STAKING STRUCTURE LAYOUT (.01 B-36-256) EACH	CONSTRUCTION STAKING SUPPLEMENTAL CONTROL (4008-02-70) EACH	CONSTRUCTION STAKING SLOPE STAKES LF
0010	10+21	-	12+22	CTH XX	201	201	1	1	201
0010	12+74	-	14+43	CTH XX	169	169			169
TOTAL 0010					370	370	1	1	370


690 - SAWING

CATEGORY	STATION	TO	STATION	LOCATION	690.0150	690.0250
					SAWING ASPHALT LF	SAWING CONCRETE LF
0010	11+46	-	11+63	LT	-	3
0010	10+95	-	11+46	LT & RT	95	-
0010	13+25	-	13+90	LT & RT	145	-
TOTAL 0010					240	3




Standard Detail Drawing List


08E08-03	TYPICAL INSTALLATIONS OF EROSION BALES / TEMPORARY DITCH CHECKS
08E09-06	SILT FENCE
08E11-02	TURBIDITY BARRIER
08E14-01	TRACKING PAD
12A03-10	NAME PLATE (STRUCTURES)
13B02-09A	CONCRETE PAVEMENT APPROACH SLAB
13C19-03	HMA LONGITUDINAL JOINTS
14B15-11A	STEEL PLATE BEAM GUARD, CLASS "A" INSTALLATION & ELEMENTS
14B15-11B	STEEL PLATE BEAM GUARD, CLASS "A" INSTALLATION & ELEMENTS
14B15-11C	STEEL PLATE BEAM GUARD, CLASS "A", INSTALLATION & ELEMENTS
14B20-12A	STEEL THRIE BEAM STRUCTURE APPROACH
14B20-12F	STEEL THRIE BEAM STRUCTURE APPROACH, CONNECTION TO BRIDGE RAILING TYPE "M"
14B24-09A	STEEL PLATE BEAM GUARD ENERGY ABSORBING TERMINAL
14B24-09B	STEEL PLATE BEAM GUARD ENERGY ABSORBING TERMINAL
14B24-09C	STEEL PLATE BEAM GUARD ENERGY ABSORBING TERMINAL
15C02-09A	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C02-09B	BARRICADES AND SIGNS FOR VARIOUS CLOSURES
15C02-09C	DETOUR SIGNING FOR MAINLINE CLOSURES
15C03-05	BARRICADES AND SIGNS FOR SIDE ROAD CLOSURES
15C06-12	SIGNING & MARKING FOR TWO LANE BRIDGES
15C08-24A	PERMANENT LONGITUDINAL PAVEMENT MARKINGS



SECTION A-A



PLAN VIEW




FRONT ELEVATION

TEMPORARY DITCH CHECK USING EROSION BALES ①

GENERAL NOTES


DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

① TEMPORARY DITCH CHECKS EITHER EROSION BALES OR MANUFACTURED SHALL BE PAID FOR UNDER THE BID ITEM OF TEMPORARY DITCH CHECK. THE DEPARTMENT WILL NOT PAY FOR TEMPORARY DITCH CHECKS CONSTRUCTED OF A SINGLE ROW OF EROSION BALES.




PLAN VIEW

WHEN ALTERING THE DIRECTION OF FLOW



PLAN VIEW



FRONT ELEVATION


WHEN EXISTING GROUND SLOPES AWAY FROM FILL SLOPE

EROSION BALES FOR SHEET FLOW


TYPICAL INSTALLATIONS OF EROSION BALES / TEMPORARY DITCH CHECKS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
6/04/02 /S/ Beth Cann
DATE CHIEF ROADWAY DEVELOP 14
FHWA





PLAN VIEW
TYPICAL APPLICATION OF SILT FENCE



SILT FENCE AT MEDIAN SURFACE DRAINS



SILT FENCE




JOINING TWO LENGTHS OF SILT FENCE^⑤


GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND APPLICABLE SPECIAL PROVISIONS.

- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1/8" X 1/8" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.




TRENCH DETAIL




SILT FENCE TIE BACK
(WHEN REQUIRED BY THE ENGINEER)


SILT FENCE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 4-29-05 DATE	/S/ Beth Cannon CHIEF ROADWAY DEVELOP 15 FHWA




SECTION B - B

**TURBIDITY BARRIER - FLOAT ALTERNATIVE
CAUTION - SEE NOTE 6**


SECTION A - A

TURBIDITY BARRIER - STANDARD POST INSTALLATION
TURBIDITY BARRIER PLACEMENT DETAILS


PLAN VIEW




PLAN VIEW

GENERAL NOTES


DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

TURBIDITY BARRIER MAY BE REMOVED AT THE ENGINEERS DISCRETION, WHEN PERMANENT EROSION CONTROL MEASURES HAVE BEEN ESTABLISHED.

- ① DRIVEN STEEL POSTS, PIPES, OR CHANNELS. LENGTH SHALL BE SUFFICIENT TO SECURELY SUPPORT BARRIER AT HIGH WATER ELEVATIONS.
- ② SAND BAGS TO BE USED AS ADDITIONAL BALLAST WHEN ORDERED BY THE ENGINEER TO MEET ADVERSE FIELD CONDITIONS. SPACE AS APPROPRIATE FOR SITE CONDITIONS.
- ③ WHEN BARRIER HEIGHT "H" EXCEEDS 8 FEET, POST SPACING MAY NEED TO BE DECREASED.
- ④ IN WATERWAYS SUBJECT TO FLUCTUATING WATER ELEVATIONS, PROVISIONS SHOULD BE MADE TO ALLOW THE WATER TO EQUALIZE ON EACH SIDE OF THE BARRIER. THIS MAY BE ACCOMPLISHED BY LEAVING A PORTION OF THE BARRIER OPEN ON THE UPSTREAM END.
- ⑤ ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION PERIOD. MINIMUM BARRIER HEIGHT SHALL BE 2' GREATER THAN EITHER THE Q2 ELEVATION OR THE ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION, WHICHEVER IS GREATER.
- ⑥ FLOAT ALTERNATIVE WILL ONLY BE ALLOWED WITH WRITTEN APPROVAL OF THE ENGINEER, AND IS MEANT FOR LOCATIONS WHERE BEDROCK PREVENTS THE INSTALLATION OF POSTS.
- ⑦ ALLOW SUFFICIENT SLACK VERTICALLY AND HORIZONTALLY SO THAT SEDIMENT BUILD UP WILL NOT SEPARATE OR LOWER THE TURBIDITY BARRIER.
- ⑧ USE AS DIRECTED BY COAST GUARD OR DNR PERMIT WHEN WORKING IN NAVIGABLE WATERWAYS.



PLAN VIEW





SECTION C - C

**TURBIDITY BARRIER DETAIL SHOWING
TYPICAL PLACEMENT AT STRUCTURES**
TURBIDITY BARRIER

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
6/4/02 /S/ Beth Cannestra
DATE CHIEF ROADWAY DEVELOPMENT ENGINEER
FHWA 16

**SECTION B - B****GENERAL NOTES**

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

TRACKING PAD SHALL BE INSPECTED DAILY. DEFICIENT AREAS SHALL BE REPAIRED OR REPLACED IMMEDIATELY.


TRACKING PAD TO BE REMOVED AFTER CONSTRUCTION IS COMPLETED.

TRACKING PAD SHALL BE THE FULL WIDTH OF THE EGRESS POINT.

SURFACE WATER MUST BE PREVENTED FROM PASSING THROUGH THE TRACKING PAD. FLOWS SHALL BE DIVERTED AWAY, AROUND OR CONVEYED UNDER THE TRACKING PAD.

CULVERT PIPE OR OTHER BMP USED TO DIVERT WATER AWAY, AROUND OR UNDER THE TRACKING PAD SHALL BE DESIGNED TO CONVEY THE 2 YEAR - 24 HOUR EVENT.

THE COST OF ADDITIONAL BMP TO DIVERT WATER ARE INCIDENTAL TO THE TRACKING PAD BID ITEM.

**SECTION A - A****TRACKING PAD**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
3/24/2011 /S/ Jerry H. Zogg
DATE ROADWAY STANDARDS DEVE 17
FHWA ENGINEER

GENERAL NOTES


NAME PLATES TO BE INSTALLED ON BRIDGES, CULVERTS, AND RETAINING WALLS SHALL CONFORM TO THE REQUIREMENTS OF SECTION 502.3.11 OF THE STANDARD SPECIFICATIONS.

THE BRIDGE NUMBER AND YEAR BUILT SHOWN ON THIS DRAWING ARE EXAMPLES ONLY. SEE CONSTRUCTION PLANS FOR INDIVIDUAL NUMBERING AND YEAR BUILT.



- ① EPOXY RESIN SHALL BE FROM AN APPROVED MANUFACTURER AND USED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- ② REHABILITATION OF AN EXISTING STRUCTURE SHOULD USE THE DATE OF ORIGINAL STRUCTURE CONSTRUCTION.



TYPICAL NAME PLATE
(BRIDGES, CULVERTS, AND RETAINING WALLS)




**NUMBERING DESIGNATION
MULTI-UNIT STRUCTURES**




ALTERNATE LUG
(FOR ATTACHMENT TO PRECAST STRUCTURES)


NAME PLATE (STRUCTURES)
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION
APPROVED 3/26/10 /S/ Scot Beck DATE CHIEF STRUCTURAL DEVELOP 18 FHWA



**SKEWED APPROACH
(PAVEMENT MORE THAN TWO LANES)**




**SKEWS > 20°
(PAVEMENT WIDTH ≤ 30')**




**SKEWS ≤ 20°
(PAVEMENT WIDTH ≤ 30')**

APPROACH SLAB AND ADJACENT PAVEMENT


* (RS) = REINFORCED CONCRETE SLAB
* (PS) = PAVED CONCRETE SHOULDER OR CONCRETE DRAINAGE SLAB
* (NRS) = NON - REINFORCED CONCRETE SLAB
*** STANDARD DOWEL BAR DIAMETER (SEE SDD 13C11 AND SDD 13C13)



**SECTION A - A
REINFORCEMENT POSITIONING DETAIL**



**SECTION B - B
BEND DETAIL
BOTTOM REINFORCEMENT**




**SECTION C - C
TRANSITION DETAIL
APPROACH SLAB TO ADJACENT PAVEMENT**

GENERAL NOTES


THE CONTRACTOR MAY SPLIC NO. 6 BARS IN THE APPROACH SLAB FOR SKEWED STRUCTURES ONLY. STAGGER SPLICES WITH A MAXIMUM OF ONE SPLICE PER BAR. THE LENGTH OF LAP IS 20 INCHES.

TACK WELD DOWEL BARS TO THE BASKETS ON ALTERNATE ENDS.

- ① THE CONTRACTOR MAY USE NO. 4 BARS SPACED AT 2' - 0" C - C IN BOTH THE LONGITUDINAL AND TRANSVERSE DIRECTIONS FOR TOP REINFORCEMENT AS AN ALTERNATIVE TO THE WELDED WIRE FABRIC.
- ② THE CONTRACTOR MAY OMIT THE BARS BETWEEN REINFORCED SLABS WHERE SLAB REINFORCEMENT BARS EXTEND ACROSS THE CENTERLINE OR REFERENCE LINE.
- ③ DO NOT CONSTRUCT AN EXPANSION JOINT OR INSTALL DOWEL BARS WHEN ABUTTING AN HMA PAVEMENT.
- ④ USE A JOINT SEALANT CONFORMING TO STANDARD SPECIFICATION 415.2.6.
- ⑤ PLACE EXPANSION CAP ON THE END OF THE DOWEL THAT IS NOT TACK WELDED TO THE BASKET. DO NOT FORCE DOWEL BAR PAST THE DOWEL STOP.
- ⑥ EXTEND EXPANSION JOINT THROUGH ANY ADJACENT TIED CONCRETE.
- Ⓐ STANDARD CONTRACTION JOINT NORMAL TO C OR R.
- Ⓑ STANDARD LONGITUDINAL JOINT WITH TIE BARS.
- Ⓒ 1 1/2" EXPANSION JOINT WITH DOWEL BARS NORMAL TO C OR R.



**SECTION D - D
CONTRACTION JOINT**




EXPANSION JOINT DETAIL

**CONCRETE PAVEMENT
APPROACH SLAB**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
November 2018 /S/ Peter Kemp, P.E.
DATE
FHWA
PAVEMENT SUPERVISOR 19



**TYPICAL PAVEMENT CROSS SECTION
NOTCHED WEDGE JOINT**

GENERAL NOTES


IN ADDITION TO THE DETAILS PROVIDED IN THIS DRAWING, CONFORM TO STANDARD SPECIFICATION 450.3.2.8 FOR WHEN A NOTCHED WEDGE JOINT IS REQUIRED AND FOR GENERAL JOINT CONSTRUCTION REQUIREMENTS.

FOR ALL LONGITUDINAL JOINTS, ENSURE THE PAVER SCREED OVERLAPS THE PREVIOUSLY PLACED PAVEMENT BY $1'' \pm 0.5''$ AND THE HOT SIDE OF THE JOINT REMAINS HIGHER THAN THE COLD SIDE BY APPROXIMATELY $0.1''$ AFTER FINAL COMPACTION. (IT WILL BE FLUSH WHEN PAVING IN ECHELON.)


ONLY REMOVE THE LONGITUDINAL NOTCHED WEDGE JOINT FOR SMA PAVEMENT OR AS DIRECTED BY THE ENGINEER TO ADDRESS SPECIFIC LENGTHS OF JOINT DAMAGED BY TRAFFIC.

WHEN MILLING BACK OR REMOVING ANY LONGITUDINAL JOINT, LIMIT THE MATERIAL REMOVED TO $2''$ FROM THE TOP NOTCH OR FROM THE VERTICAL JOINT EDGE ON THE COLD SIDE OF THE JOINT.


USE LONGITUDINAL MILLED JOINT AS PLANS SHOW OR AS THE ENGINEER DIRECTS.



**TYPICAL PAVEMENT CROSS SECTION
VERTICAL JOINT**



OVERLAP DETAIL (TYPICAL)



**TYPICAL PAVEMENT CROSS SECTION
VERTICAL JOINT (MILLED)**

HMA LONGITUDINAL JOINTS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
November 2020 /S/ Steven Hefel
DATE HMA PAVEMENT ENGIN 20
FHWA

GENERAL NOTES


- ① WOOD OR STEEL POSTS (w6X9 OR w6X8.5) AND NOTCHED PLASTIC BLOCKOUTS ARE ACCEPTABLE ALTERNATIVES FOR 6"X8" WOOD POSTS WITH WOOD OR PLASTIC BLOCKOUTS. USE APPROVED NOTCHED PLASTIC BLOCKOUTS WITH STEEL POSTS. APPROVED PLASTIC BLOCKOUT DESIGNS MAY VARY FROM THIS TYPICAL DETAIL WHEN USED IN CONJUNCTION WITH STEEL POSTS. DO NOT MIX STEEL AND WOOD POSTS IN A SINGLE INSTALLATION.
- ② USE STRUCTURAL STEEL POSTS CONFORMING TO ASTM A 36. GALVANIZED POSTS ACCORDING TO AASHTO M 111. EITHER SET THE POSTS IN DRILLED HOLES OR DRIVE TO GRADE. REMOVE MUSHROOMING CAUSED BY DRIVING AND REPAIR DAMAGE SPALTER COATING ON GALVANIZED POSTS.
- ③ INSTALL STEEL POSTS WITH HOLES ON APPROACHING TRAFFIC SIDE.
- ④ USE EITHER WOOD OR APPROVED PLASTIC BLOCKOUTS ON WOOD POSTS.
- ⑤ IF THE DISTACE FROM BACK OF POST TO SHOULDER HIGHE POINT IS LESS THAN 2 FEET, INSTALL LONGER POST AT HALF POST SPACING, W BEAM (LHW).
- ⑥ IF ROCK IS ENCOUNTERED DURING EXCAVATION, THE ENGINEER MAY APPROVE USING A 12 INCHES IN DIAMETER POST HOLE EXTENDING 20 INCHES DEEP INTO THE ROCK. PLACE APPROXIMATELY 2 1/2" INCHES OF GRANULAR MATERIAL IN THE BOTTOM OF THE HOLE. CUT THE POSTS THE TO LENGTH AMD INSTALL. BACKFILL WITH EXCAVATED MATERIAL AND COMPACT ADEQUATELY.
- ⑦ WHEN USING STEEL POSTS AND WOOD BLOCKOUTS, INSTALL FOUR 16d GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.

INSTALL BEAM GUARD SECTIONS AND ALL NECESSARY HARDWARE ACCORDING TO THE APPLICABLE PLAN AND CURRENT STANDARD AND SUPPLEMENTAL SPECIFICATIONS.

ALL DIMENSIONS ARE SUBJECT TO MANUFACTURER'S TOLERANCES EXCEPT WHERE ALLOWABLE TOLERANCES ARE SHOWN.




END VIEW
SETTING STEEL OR WOOD POST IN ROCK ⑥




PLAN VIEW



WOOD POST, BLOCKOUT AND BEAM




STEEL POST AND NOTCHED PLASTIC BLOCKOUT ALTERNATIVE STANDARD INSTALLATION




WOOD POST, BLOCKOUT AND BEAM




**WOOD POST
(6" X 8") NOMINAL** ①




WOOD OR PLASTIC BLOCKOUT FOR WOOD POSTS



TYPICAL NOTCHED PLASTIC BLOCKOUT FOR STEEL POSTS




LOCATED ALONG A ROADWAY SHOULDER STANDARD INSTALLATION



**END VIEW
LOCATED ALONG A CURBED ROADWAY**




STEEL PLATE BEAM GUARD, CLASS "A" INSTALLATION AND ELEMENTS




FRONT VIEW

POST SPACING STANDARD INSTALLATION




FRONT VIEW


POST SPACING FOR LONGER POST AT HALF POST SPACING W BEAM (LHW)



SECTION THRU W BEAM



FRONT VIEW
BEAM SPLICING AT WOOD POST
AND POST MOUNTING DETAIL



FRONT VIEW
BEAM SPLICING AT STEEL POST

TYPICAL SPLICING DETAILS OF STEEL PLATE BEAM GUARD


GENERAL NOTES

FURNISH GUARDRAIL DEFLECTORS FROM APPROVED PRODUCTS LIST.

(9) DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL. START REFLECTORS AT POST #9 AND SPACE EVENLY EVERY 100 FEET (MAX.) TO THE END OF GUARDRAIL RUN, USING A MINIMUM OF 3 REFLECTORS.


(12) 8 - 5/8" ϕ x 2" BUTTON HEAD BOLTS WITH OVAL SHOULDERS & RECESS NUTS.

(13) 5/8" DIA. BUTTON HEAD BOLT AND RECESS NUT WITH 5/8" DIA. F844 FLAT WASHER UNDER NUT.




NESTED W BEAM (NW)

USE ALL OTHER STANDARD BEAM GUARD DETAILS FOR CONSTRUCTING NESTED W BEAM (NW)



4" X 12" GUARDRAIL REFLECTOR DETAIL
AND TYPICAL INSTALLATION *


* USE DOUBLE SIDED WHITE GUARDRAIL REFLECTORS ON ROADWAYS WITH BI-DIRECTIONAL TRAFFIC (NO MEDIAN). USE SINGLE SIDED WHITE (RIGHT SIDE) AND SINGLE SIDED YELLOW (LEFT SIDE) ON ROADWAYS WITH MEDIAN SEPARATION.



4" X 12" GUARDRAIL REFLECTOR


STEEL PLATE BEAM GUARD, CLASS "A", INSTALLATION & ELEMENTS

STATE OF WISCO²²
DEPARTMENT OF TRANSPORTATION



DETAIL FOR DOUBLE BLOCKS

THE NUMBER OF DOUBLE BLOCK POSTS
WITHIN A BARRIER RUN IS UNLIMITED




DETAIL FOR TRIPLE BLOCKS


TRIPLE BLOCK DETAIL IS LIMITED TO ONE
LOCATION WITHIN A BEAM GUARD RUN.

NOTES: USE DOUBLE OR TRIPLE BLOCKS WHEN UNDERGROUND OBSTACLES
PREVENT THE POST FROM BEING INSTALLED.

DO NOT USE EXTRA BLOCKOUTS IF IT CAUSES THE POST TO BE DRIVEN BEYOND
SHOULDER HINGE POINT OR CAUSES A FIXED OBJECT TO BE WITHIN THE DEFLECTION
DISTANCE OF THE BARRIER.



PLAN VIEW
BEAM LAPPING DETAIL




POST DRIVING FOR CONTINUOUS
UNDERGROUND OBSTRUCTION

STEEL PLATE BEAM GUARD,
CLASS "A",
INSTALLATION & ELEMENTS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June 2017 /S/ Rodney Taylor
DATE ROADWAY STANDARDS 23
FHWA UNIT SUPERVISOR



FRONT VIEW




PLATE WASHER DETAIL


GENERAL NOTES

BOLT THE THRIE BEAM TO ALL POSTS AND BLOCKOUTS. DRILL OR PUNCH BOLT HOLES IN THE BEAM IF THE POST SPACING IS LESS THAN 6'-3".

DO NOT USE STEEL POSTS AND NOTCHED PLASTIC BLOCKOUTS IN THE STEEL THRIE BEAM STRUCTURAL APPROACH AND THE TRANSITION SECTION OF STEEL PLATE BEAM GUARD, CLASS "A" INSTALLATIONS.

IF ROCK IS ENCOUNTERED, REMOVE ROCK TO FULL DEPTH OF POST PLUS 2 1/2", AND 12" DIAMETER AROUND POST. SEE 14B15 FOR MORE DETAILS.

- ① BRIDGE RAILING TYPE "W" DOES NOT REQUIRE A TERMINAL CONNECTOR.
- ② MINIMUM EMBEDMENT SHALL BE 4'- 0".
- ③ POST BOLTS ARE $\frac{5}{8}$ " DIAMETER ASTM A307 BUTTON HEAD BOLT. A POST BOLT REQUIRES A $\frac{5}{8}$ " DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX AND A $\frac{5}{8}$ " DIAMETER F844 FLAT WASHER. LENGTH OF POST BOLT MAY VARY.
- ④ ALL WOOD POSTS MUST BE 6" X 8" AND AT LEAST 7'-0" LONG.




TWO WAY TRAFFIC


ONE WAY TRAFFIC

- (T) THRIE BEAM CONNECTION
- (W) W-BEAM CONNECTION WHEN REQUIRED


TYPICAL LOCATIONS OF THRIE BEAM AND W-BEAM CONNECTIONS TO BRIDGE




THRIE BEAM TERMINAL CONNECTOR



THRIE BEAM SPLICE



SECTION THRU BEAM RAIL ELEMENT



SECTION A-A




STEEL THRIE BEAM STRUCTURE APPROACH

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION




APPROVED
November 2022 /S/ Rodney Taylor
DATE ROADWAY STANDARDS DEVE
WA ENGINEER 24

GENERAL NOTES

(1) VARY THIS DIMENSION DEPENDING ON ABUTMENT TYPE, WINGWALL DETAILS, AND ANGLE OF SKEW. PLACE THE FIRST WOOD POST OFF THE BRIDGE SHALL BE AS CLOSE AS FEASIBLE TO THE STEEL END POST.



SECTION I-I

**ANCHOR AND BACK-UP PLATE MOUNTING TO BRIDGE RAILING, TYPE "M"****STEEL THRIE BEAM STRUCTURE APPROACH, CONNECTION TO BRIDGE RAILING TYPE "M"**STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATIONAPPROVED
November 2022 /S/ Rodney Taylor
DATE ROADWAY STANDARDS DEVE
ENGINEER FHWA 25


BILL OF MATERIALS

NOTE NO.	DESCRIPTION
①	WOOD BREAKAWAY TERMINAL POST: 5 $\frac{1}{2}$ " x 7 $\frac{1}{2}$ " x 3'-9"
②	STEEL TUBE TS 8" x 6" x 0.188", 6'-0"
④	WOOD BREAKAWAY CRT POST: 6" x 8" x 6'-0"
⑤	WOOD OFFSET BLOCKS: 6' x 8" x 1'-2"
⑥	PIPE SLEEVE: 2" x 5 $\frac{1}{2}$ " STANDARD PIPE
⑦	BEARING PLATE
⑧	BCT CABLE ASSEMBLY
⑨	CABLE ANCHOR BOX
⑩	STRUT & YOKE
⑪	STEEL PLATE BEAM, END PANEL 12 GA.
⑫	STEEL PLATE BEAM: 12 GA. 13'-6 $\frac{1}{2}$ "
⑬	IMPACT HEAD
⑭	0.040" ALUMINUM SHEET WITH REFLECTIVE SHEETING TYPE F PER SECTION 637 OF THE STANDARD SPECIFICATIONS






GENERAL NOTES

FOLLOW MANUFACTURE'S BOLTING RECOMMENDATIONS.

- (A) THE SLOPE IN THE AREA BOUNDED BY THE GRADELINE, THE HINGE POINT LINE (HPL), AND THE CLEAR ZONE LIMITS (CZL) SHALL BE 4:1 OR FLATTER.
- (B) AFTER FINAL ASSEMBLY, RECHECK CABLE TO BE SURE IT IS TAUT AND HAS NOT RELAXED.
- (C) THE TOP OF THE STEEL TUBE ON POSTS 1 AND 2 SHALL NOT BE MORE THAN 3" ABOVE THE FINISH GROUND ELEVATION.
- (D) THE CENTER OF THE UPPER 3 $\frac{1}{2}$ " DIAMETER HOLE ON POST 3 THROUGH 8 SHALL BE $\frac{3}{4}$ " ABOVE THE FINISHED GROUND LINE.
- (E) ATTACH ALUMINUM SHEET TO E.A.T. HEAD USING 4 STAINLESS STEEL SELF-TAPPING SCREWS. ONE SCREW PER CORNER.
- STEEL POSTS SHALL NOT BE ALLOWED FOR USE WITH ENERGY ABSORBING TERMINALS.
- DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL.
- * DO NOT ATTACH BLOCKOUTS TO POSTS 1 AND 2.



ELEVATION



SECTION C-C
TYPICAL AT POST NOS. 6, 8

SECTION A-A
TYPICAL AT POST NO. 1*


SECTION B-B
TYPICAL AT POST NO. 2*

STEEL PLATE BEAM GUARD
ENERGY ABSORBING TERMINAL

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

6

S.D.D. 14 B 24-9b




STEEL PLATE BEAM GUARD
ENERGY ABSORBING TERMINAL


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

S.D.D. 14 B 24-9b


6



② 72" STEEL TUBE
(POSTS NO. 1-2)




① TERMINAL POST



④ CRT POST
(POSTS NO'S 5-8)


WOOD BREAKAWAY POSTS



⑤ WOOD OFFSET BLOCK
REQ'D. AT ALL POSTS EXCEPT POST NO'S 1 & 2


GENERAL NOTES

WHEN ROCK IS ENCOUNTERED DURING EXCAVATION, A 12 INCH DIA. POST HOLE EXTENDING 20 INCHES DEEP INTO THE ROCK MAY BE USED IF APPROVED BY THE ENGINEER. GRANULAR MATERIAL SHALL BE PLACED IN THE BOTTOM OF THE HOLE APPROXIMATELY 2 1/2" INCHES DEEP TO PROVIDE DRAINAGE. THE SOIL TUBES SHALL BE FIELD CUT TO LENGTH, PLACED IN THE HOLE AND BACKFILLED WITH ADEQUATELY COMPAKTED MATERIAL EXCAVATED FROM THE HOLE.




⑯ REFLECTIVE SHEETING DETAILS

TYPE H
YELLOW REFLECTIVE
SHEETING 3" X 9".
SEE STANDARD
SPECIFICATION 637.



FRONT VIEW




SIDE VIEW

E.A.T. MARKER POST

STEEL PLATE BEAM GUARD
ENERGY ABSORBING TERMINAL

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
June 2017 /S/ Rodney Taylor
DATE ROADWAY STANDARDS 28
FHWA UNIT SUPERVISOR ENT



DETAIL B
MAINLINE CLOSURE WITH POSTED DETOUR

WORK ZONE LESS THAN $\frac{1}{2}$ MILE FROM DETOUR ROUTE (1000 FEET IF URBAN)

LEGEND

- SIGN ON PERMANENT SUPPORT
- + TYPE III BARRICADE
- || TYPE III BARRICADE WITH ATTACHED SIGN
- TYPE "A" WARNING LIGHT (FLASHING)



WORK AREA



FLAGS, 16" X 16" MIN. (ORANGE)



AT BRIDGE OR CULVERT REPLACEMENTS, USE ADDITIONAL SET OF BARRICADES AND SIGN



OR



OR



OR




OR



OR



OR



OR



OR



OR



OR

OR

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE", SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION, OR FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL "D" FOR FULL ROAD CLOSURES.

TYPE "A" LOW - INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11 - 2, R11 - 3, M4 - 9, R11 - 4, AND R10 - 61 SIGNS PLACED ON THE BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE RAIL OR BOTTOM RAILS.

"WO" AND "MO" SIGNS ARE THE SAME AS "W" AND "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

R11 - 2 SHALL BE 48" X 30"

R11 - 3 SHALL, R11 - 4 AND R10 - 61 SHALL BE 60" X 30"

M4 - 9 SHALL BE 30" X 24"

M3 - X SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)


M4 - 8 SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)

M1 - 4, M1 - 5A AND M1 - 6 SHALL BE 24" X 24" (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS)

M05 - 1 AND M06 - 1 SHALL BE 21" X 21" (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS)

D1 - X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.


R1 - 1 SHALL BE 36" X 36"



DETAIL D
ROAD CLOSURE BARRICADE DETAIL
APPROACH VIEW

6

6



DETAIL E
LANE CLOSURE BARRICADE DETAIL
APPROACH VIEW

SEE SDD 15C2 - SHEET "a" FOR LEGEND


- ① TWO WARNING LIGHTS SHALL BE PROVIDED ON THE CENTER BARRICADE AND A MINIMUM OF ONE WARNING LIGHT SHALL BE PROVIDED ON EACH OF THE OTHER BARRICADES WITHIN THE ROADWAY LIMITS. SPACING OF THE WARNING LIGHTS SHALL BE UNIFORM TO THE EDGE OF ROADWAY AS SHOWN (APPROX. 8 FOOT LIGHT SPACING).
- ② THESE SIGNS AND BARRICADES ARE NOT REQUIRED IF ROAD CLOSURE BEGINS AT AN INTERSECTION.
- ③ FOR ROAD CLOSURE WITHOUT LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "D".
- ④ FOR ROAD CLOSURE WITH LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "E".
- ⑤ FOR BRIDGE OR CULVERT REPLACEMENTS, SUBSTITUTE "BRIDGE OUT" INSTEAD OF "ROAD CLOSED" ON R11 - 2 AND R11 - 3 SIGNS.
- ⑥ INSTALL DETOUR AND COMMUNITY GUIDE SIGNS AND ARROWS ONLY IF SPECIFIED IN THE CONTRACT. IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. MODIFY EXISTING SIGNS WHERE POSSIBLE. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. IF DETOUR SIGNS ARE BEING INSTALLED BY OTHERS, PLACE THE CONTRACTED TRAFFIC CONTROL SIGNS TO ALLOW FOR PLACEMENT OF ALL WARNING, DETOUR AND GUIDE SIGNS AS SHOWN.
- ⑦ "EAST" CARDINAL DIRECTION MARKERS AND RIGHT TURN ARROWS ARE SHOWN. USE OTHER CARDINAL DIRECTIONS AND ARROWS AS APPROPRIATE.

BARRICADES AND SIGNS FOR VARIOUS CLOSURES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
May 2023
DATE
FHWA


/S/ Andrew Heidke
WORK ZONE ENGINEER 30



SEE SPECIFIC PROJECT DETOUR
SIGNING DETAIL SHEETS AND
DETAIL A OR B ON SSD SHEET 15C02 - SHEET "a"

DETAIL F DETOUR SIGNING

LEGEND



GENERAL NOTES

THE EXACT NUMBER, LOCATION AND SPACING OF ALL SIGNS SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. MODIFY EXISTING SIGNS WHERE POSSIBLE.

THE SPACING BETWEEN TRAFFIC CONTROL AND DETOUR SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND TO PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.


"MO" SIGNS ARE THE SAME AS "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE

SIGN SIZES SHALL BE AS FOLLOWS

M3-X SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)
M4-8 SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)
M1-4, M1-5A AND M6-1 SHALL BE 24" X 24" (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS)
M05-1 AND M06-1 SHALL BE 21" X 21" (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS)
M4-9 AND M4-59 SHALL BE 30" X 24"
M4-8a SHALL BE 24" X 18"
G20-51 SHALL BE 60" X 24"
W20-2A SHALL BE 48" X 48"
D1-X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.

* OPTIONAL SIGNS. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS.


** FOR A TOWN ROAD OR LOCAL STREET DETOURED ONTO A STATE TRUNK HIGHWAY, PLACE A ROAD NAME PLAQUE ABOVE THE M4-9 SIGN AS SPECIFIED IN THE CONTRACT.




DETOUR SIGNING FOR MAINLINE CLOSURES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED _____ /S/ Andrew Heidtke
May 2023 _____ DATE WORK ZONE ENGINEER 31
/A




DETAIL 1
(NO ACCESS TO PROJECT)



DETAIL 3
(PUBLIC CROSS-TRAFFIC MAINTAINED.
CONTRACTOR, LOCAL BUSINESS AND
RESIDENT ACCESS TO PROJECT)



DETAIL 2
(PUBLIC CROSS-TRAFFIC MAINTAINED.
NO ACCESS TO PROJECT)



DETAIL 4
(CONTRACTOR, LOCAL BUSINESS AND
RESIDENT ACCESS TO PROJECT)

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE (500 FEET DESIRABLE) TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

IF A "STOP" SIGN MUST BE REMOVED FOR A WORK OPERATION, A TEMPORARY "STOP" SIGN SHALL BE PLACED PRIOR TO THE SIGN REMOVAL, OR A FLAGGER SHALL BE PROVIDED UNTIL THE SIGN IS REESTABLISHED.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY REESTABLISHED UPON COMPLETION OF THE OPERATION OR FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN SEVEN CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL "D" FOR FULL ROAD CLOSURES.

TYPE "A" LOW-INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11-2, R11-3, AND R11-4 SIGNS PLACED ON BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE OR BOTTOM RAILS.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

R11-2 SHALL BE 48" X 30".

R11-4 AND R11-3 SHALL BE 60" X 30".

* OMIT THE "ROAD CLOSED 500 FT." SIGN IF THE LAST INTERSECTION IS 500 FEET OR LESS FROM THE WORK ZONE.

** 500' MAX. OR AT LAST INTERSECTION, WHICHEVER IS CLOSEST.


LEGEND

- SIGN ON PERMANENT SUPPORT
- ± TYPE III BARRICADE
- || TYPE III BARRICADE WITH ATTACHED SIGN
- TYPE "A" WARNING LIGHT (FLASHING)
- ▨ WORK AREA

BARRICADES AND SIGNS FOR SIDEROAD CLOSURES


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
July 2018 /S/ Andrew Heidke
DATE
FHWA
WORK ZONE ENGINEER 32



SITUATION 1

WARRANTING CRITERIA:
BRIDGE WIDTH IS AT LEAST 16 FEET BUT LESS THAN 24 FEET.



SITUATION 2

WARRANTING CRITERIA:
1. BRIDGE WIDTH IS AT LEAST 24 FEET AND
2. BRIDGE SHOULDER WIDTH IS LESS THAN 6 FEET

GENERAL NOTES

DETAILS OF TRAFFIC CONTROL DEVICES AND INSTALLATION NOT SHOWN ON THE DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

LOCATE W5-52 SIGN POST(S) BEHIND GUARDRAIL WHEN PRESENT.

PLACE THE EDGE OF THE W-52 SIGN IN LINE WITH FACE OF CURB OR PARAPET.

ON BRIDGE ONLY PROJECTS, PLACE 300 FEET OF EDGELINE.

OMIT EDGELINES ON ROADWAYS WITHOUT EXISTING EDGELINES.

① OMIT ON ONE-WAY TRAVELED WAYS.

LEGEND

● SIGN ON PERMANENT SUPPORT

→ DIRECTION OF TRAFFIC


DISTANCE TABLE

POSTED OR 85TH PERCENTILE SPEED	DISTANCE "A"
25	150'
30	200'
35	250'
40	300'
45	400'
50	550'
55	700'

SIGNING AND MARKING FOR TWO LANE BRIDGES


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
May 2023 /S/ Jeannie Silver
DATE Statewide Pavement Marking Engineer
FHWA



TWO WAY TRAFFIC

PERMANENT PAVEMENT MARKING



ONE WAY TRAFFIC

GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.

* CONFIRM MARKING LINE WIDTH WITH THE MISCELLANEOUS QUANTITIES


- ① LOCATE THE NO PASSING ZONE W14-3 SIGN WITHIN 50 FEET OF THE "T" MARKING
- ② MEASURE FROM EDGE OF MARKING TO JOINT LINE. THIS DOES NOT INCLUDE SPACE NEEDED FOR GROOVING OPERATIONS.

LEGEND


- "T" MARKING
- SIGN ON PERMANENT SUPPORT
- DIRECTION OF TRAFFIC

PERMANENT LONGITUDINAL PAVEMENT MARKINGS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED	/S/ Jeannie Silver
December 2024	DATE
Statewide Pavement Marking Engineer FHWA	

URBAN AREA




RURAL AREA (See Note 2)




GENERAL NOTES

1. Signs wider than 4 feet or 20 sq.ft or larger, shall be mounted on multiple posts. Refer to plate A4-4.
2. If signs are mounted on or behind barrier wall, see A4-10 sign plate.
3. The Double Arrow sign (W12-1D) shall be mounted at a height of 2'-3" (\pm) 3". The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Enhanced Reference Markers, Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4'-3" (\pm) 3".
4. For expressways and freeways, mounting height is 7'-3" (\pm) 3" or 6'-3" (\pm) 3" depending upon existence of a sub-sign.
5. Minimum mounting height for signs mounted on traffic signal poles is 5'-3" (\pm) 3".
6. Offset distance shall be consistent with existing signs or consistent throughout length of project.
7. Folding signs shall be mounted at a height of 5'-3" (\pm) 3" or as directed by the Engineer.

2' Min - 4' Max (See Note 5)



White Edgeline Location



** The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

POST EMBEDMENT DEPTH

Area of Sign Installation (Sq. Ft.)	D (Min)
20 or Less	4'
Greater than 20	5'

* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

TYPICAL INSTALLATION
OF PERMANENT TYPE II
SIGNS ON SINGLE POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew P. Rauch*
for State Traffic Engineer

DATE 12/6/23 PLATE NO. A4-3.23


PROJECT NO:

HWY:

COUNTY:


SHEET NO: 35

E




ELEVATION VIEW

DETAIL OF WOOD 4 X 6 SIGN POST IN BOX-OUT



ELEVATION VIEW

DETAIL OF STEEL 2 X 2 SIGN POST IN BOX-OUT



PLAN VIEW

FOR NEW CONCRETE/ASPHALT INSTALLATIONS



SIGN POST
BOX-OUTS
A4-3B

WISCONSIN DEPT OF TRANSPORTATION



APPROVED
Matthew P Rauch
for State Traffic Engineer
DATE 1/27/14 PLATF NO A4-3B.1
36

GENERAL NOTES

- For 3 or 4 post installations, individual post spacing shall be greater than 3'-6".
- See tables below for required number of posts.
- For expressways and freeways, mounting height is 7'-3" (\pm 3") or 6'-3" (\pm 3") depending upon existence of sub-sign.
- The (\pm) tolerance for mounting height is 3 inches.
- J-Assemblies are considered to be one sign for mounting height.
- Offset distance shall be consistent with existing signs or consistent throughout length of project.
- Folding signs shall be mounted at a height of 5'-3" (\pm 3") or as directed by the engineer.
- The Double Arrow sign (W12-1) shall be mounted at a height of 2'-3" (\pm 3"). The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4"-3" (\pm 3").



RURAL AREA (See Note 3)



* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

** The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

*** See A4-3 sign plate for signs 4' or less in width and less than 20 S.F. in area.

SIGN SHAPE OTHER THAN DIAMOND (TWO POSTS REQUIRED)

L	E
Greater than 48"	12"
Less than 60"	
60" to 108"	L/5

SIGN SHAPE OTHER THAN DIAMOND (THREE POSTS REQUIRED)

L	E
Greater than 108" to 144"	12"

POST EMBEDMENT DEPTH

Area of Sign Installation (Sq. Ft.)	D (Min)
20 or Less	4'
Greater than 20	5'

TYPICAL INSTALLATION OF TYPE II SIGNS ON MULTIPLE POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

Matthew R. Rauch
for State Traffic Engineer

DATE 12/6/23 PLATE NO. A4-4.16


PROJECT NO:

HWY:


COUNTY:

SHEET NO: 37

E



SIGN SHALL BE MOUNTED TO PROJECT
ABOVE THE TOP OF THE POST



Nuts, bolts and lags used for mounting signs shall have hexagonal heads and shall be either :

- a. Hot dip galvanized in accordance with ASTM Designation: A 153, Class D, or SC 3
- b. Electro-galvanized in accordance with ASTM Designation :B 633, TYPE III, SC 3.

Threads on bolts and nuts shall be manufactured with sufficient allowance for the cadmium plate or galvanized coating to permit the nuts to run freely on the bolts.

STRINGER BOLTING TO ALUMINUM SIGNS (SEE SIGN PLATE A4-18)

MACHINE BOLTS - $\frac{5}{16}$ " X 1-3/4" Length w/ lock nuts

WOOD POSTS (4" x 6")

LAG SCREWS - $\frac{3}{8}$ " X 3" (NO STRINGERS ON BACK OF SIGN)
 $\frac{3}{8}$ " X 4" (STRINGERS ON BACK OF SIGN)

SQUARE STEEL POSTS (2" x 2")

MACHINE BOLTS - $\frac{3}{8}$ " X 3-1/4" Length w/ nuts (NO STRINGER ON BACK OF SIGN)
 $\frac{3}{8}$ " X 5" Length w/ nuts (STRINGERS ON BACK OF SIGN)

RIVETS - $\frac{9}{32}$ " (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM BODY/MANDREL

O.D. FLANGE .720-.765 INCH, GRIP RANGE .042-.375 INCH

WASHERS (ALL POSTS) -

1-1/4" O.D. X $\frac{3}{8}$ " I.D. X $\frac{1}{16}$ " STEEL

1-1/4" O.D. X $\frac{3}{8}$ " I.D. X .080 NYLON

* Two different fastening systems are shown for illustration purposes. On any individual sign, either one or the other system shall be used. Actual number of fasteners per sign varies with the sign area, but normally there are two. For a single post installation, all signs greater than 9 sq. ft. require the use of 3 fasteners.


ATTACHMENT OF SIGNS TO POSTS

WISCONSIN DEPT OF TRANSPORTATION


APPROVED *Matthew R Rauch*
for State Traffic Engineer

DATE 4/1/2020 PLATE NO. A4-8.9


TELESCOPIC TUBING ANCHORS TWO PIECE SYSTEM



DETAIL OF TUBULAR STEEL SIGN POST (IN Poured CONCRETE OR ASPHALT)



DETAIL OF TUBULAR STEEL SIGN POST (IN LOCATIONS OTHER THAN Poured CONCRETE OR ASPHALT)



Area of Sign Installation (Sq. Ft.)	Number of Required Posts
9 or less	1
Greater than 9 less than or equal to 18	2
Greater than 18 less than or equal to 27	3

Signs wider than 3 feet or larger than 9 sq. ft shall be mounted on multiple posts (see above table).

**TUBULAR STEEL
SIGN POST
A4-9**

WISCONSIN DEPT OF TRANSPORTATION

APPROVED
Matthew P. Rauch

for State Traffic Engineer

DATE 2/05/15 PLATI 39 14-9.9



PROJECT NO:

HWY:

COUNTY:

SHEET NO:

E



GENERAL NOTES

1. All 4 x 6 Wood Posts shall be modified by having two $1\frac{1}{2}$ " diameter holes drilled perpendicular to the roadway centerline.

4 X 6 WOOD POST MODIFICATIONS	
WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<i>Cheska J. Spangler</i> for State Traffic Engineer
DATE 3/27/97	
PLATE NO. A4-11.2	

PROJECT NO:

HWY:




COUNTY:

BANDING


GENERAL NOTES

1. Any sign over 3 feet in width shall use the V-Block banding method. See A5-10 standard plate.
2. Signs 3 feet or greater in height shall have three bracket bands installed. Signs less than 3 feet in height shall have two bracket bands installed.
3. Banding and assembly bracket shall be stainless steel. All bands shall be $\frac{3}{4}$ " in width and 0.025" thickness.
4. ALL SIGN MOUNTING BOLTS AND WASHERS SHALL BE EITHER:
 - a. Hot dip or mechanically galvanized in accordance with ASTM Designation: A 153, Class D
 - b. Electro-galvanized in accordance with ASTM designation: B 633, Type III, SC 3

SINGLE SIGN




WASHER PLACEMENT



WASHERS (ALL POSTS) -
 1-1/4" O.D. X $\frac{3}{8}$ " I.D. X $\frac{1}{16}$ " STEEL
 1-1/4" O.D. X $\frac{3}{8}$ " I.D. X .080 NYLON
 FOR ALL TYPE H SIGNS

"J" ASSEMBLY




STANDARD SIGN SIGN BANDING DETAILS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED


 for State Traffic Engineer
 DATE 6/10/19 PLATE NO. A5-9.4



GENERAL NOTES

1. WOOD 4"X6" POST MATERIAL SHALL CONFORM TO 507.2.2 OF THE WisDOT STANDARD SPECIFICATIONS
2. BLOCK BANDING AND CLIPS SHALL BE STAINLESS STEEL, $\frac{3}{4}$ " WIDTH AND 0.025" THICKNESS
3. SIGNS 3' OR GREATER IN HEIGHT SHALL UTILIZE 3 BLOCK BANDS. SIGNS UNDER 3' IN HEIGHT SHALL UTILIZE 2 BLOCK BANDS
4. ACTUAL NUMBER OF FASTENERS PER SIGN VARIES WITH THE SIGN AREA, BUT NORMALLY THERE ARE TWO. FOR SIGNS GREATER THAN 9 S.F. 3 FASTENERS SHALL BE USED.
5. ALL SIGN MOUNTING BOLTS AND WASHERS SHALL BE EITHER:
 - a. Hot dip or mechanically galvanized in accordance with ASTM Designation: A 153, Class D
 - b. Electro-galvanized in accordance with ASTM Designation : B 633, TYPE III, SC 3
6. ALL BOLTS SHALL HAVE HEXAGONAL HEADS.
7. STEEL WASHERS SHALL BE $1\frac{1}{4}$ " O.D. X $\frac{3}{8}$ " I.D. X $\frac{1}{16}$ "
8. NYLON WASHERS SHALL BE $1\frac{1}{4}$ " O.D. X $\frac{3}{8}$ " I.D. X .080 FOR TYPE H OR TYPE F FACE SIGN

＊ LAG BOLTS SHALL BE $\frac{3}{8}$ " X $2\frac{1}{2}$ "




BLOCK BANDING DETAIL
(V-BLOCK OPTION)

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R Rauch*
for State Traffic Engineer
DATE 4/19/2022 PLATE NO. A5-10.3

NOTES

1. Sign is Type II - Type H Reflective
2. Color:
Background - White
Message - Black
3. Message Series - E
4. Substitute appropriate numerals and optically adjust spacing to achieve proper balance.



R2-1

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	18	24	1 1/2	3/8	1/2	3	8	3	2	2	3	7 1/4	5 1/2												3.0		
2S	24	30	1 1/2	3/8	1/2	4	10	3	2 1/4	3 3/8	3 3/8	9 5/8	7 3/8												5.0		
2M	30	36	1 7/8	1/2	5/8	5	12	5	2 1/2	2 1/2	4	12	9 1/4												7.5		
3	36	48	1 7/8	1/2	5/8	6	14	6	5	5	6	14 3/8	11												12.0		
4	36	48	1 7/8	1/2	5/8	6	14	6	5	5	6	14 3/8	11												12.0		
5	48	60	3	3/4	1	8	20	6	4 1/2	6 3/4	6 3/4	19 1/4	14 5/8												20.0		

PROJECT NO:

HWY:


COUNTY:

STANDARD SIGN	
R2-1	
WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<i>Matthew P Rauch</i> State Traffic Engineer
DATE	2/1/23
PLATE NO.	R2-1.14


SHEET NO: 43

E

7



W5-52L



W5-52R

NOTES

1. Sign is Type II - Type F Reflective
2. Color:
Background - Yellow
Message - Black
3. Alternate colors of stripes as shown.

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4															3.0	
2M	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4															3.0	
3	18	54	1 1/2			6	5 1/2	8 1/2	45°	6	6 9/16															6.75	
4																											
5																											

PROJECT NO:

HWY:

COUNTY:

SHEET NO: 44 E


STANDARD SIGN
W5-52L & W5-52R

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R Rauch*


For State Traffic Engineer

DATE 3/4/2024 PLATE NO. W5-52.10



LEGEND

- COST OF EXCAVATION SHALL BE INCLUDED IN BID ITEM "EXCAVATION FOR STRUCTURES BRIDGES B-36-256".
- INDICATES WING WALL NUMBER
- FIXED BEARING
- PROVIDE FOR THREE BEAM GUARD RAIL ATTACHMENT.



ELEVATION

LOOKING NORTH
(NORMAL TO BR CENTERVILLE CREEK)

DESIGN DATA

LIVE LOAD:

DESIGN LOADING: HL-93
INVENTORY RATING: RF = 1.10
OPERATING RATING: RF = 1.42
WISCONSIN STANDARD PERMIT VEHICLE (WIS-SPV): 250 (KIPS)

STRUCTURE IS DESIGNED FOR A FUTURE WEARING SURFACE OF 20 POUNDS PER SQUARE FOOT.

MATERIAL PROPERTIES:

CONCRETE MASONRY:
SUPERSTRUCTURE — $f_c = 4,000$ PSI
ALL OTHER — $f_c = 3,500$ PSI

BAR STEEL REINFORCEMENT
GRADE 60 — $f_y = 60,000$ PSI

FOUNDATION DATA

ABUTMENTS TO BE SUPPORTED ON HP 10-INCH X 42 LB STEEL PILING
DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 170 TONS ** PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA.

ESTIMATED 25'-0" LONG AT WEST ABUTMENT.
ESTIMATED 35'-0" LONG AT EAST ABUTMENT.

**THE FACTORED AXIAL RESISTANCE OF PILES IN COMPRESSION USED FOR DESIGN IS THE REQUIRED DRIVING RESISTANCE MULTIPLIED BY A RESISTANCE FACTOR OF 0.5 USING MODIFIED GATES TO DETERMINE PILE CAPACITY.

HYDRAULIC DATA

100-YEAR FREQUENCY:

$Q_{100} = 620$ C.F.S.
 $V_{100} = 3.0$ F.P.S.
 $HW_{100} = EL. 631.51$
WATERWAY AREA = 210.0 SQ. FT.
DRAINAGE AREA = 3.0 SQ. MI.
ROADWAY OVERTOPPING = N/A
SCOUR CRITICAL CODE = 5

2-YEAR FREQUENCY:

$Q_2 = 160$ C.F.S.
 $V_2 = 1.2$ F.P.S.
 $HW_2 = EL. 628.96$

TRAFFIC DATA


FEATURE ON: CTH XX
ADT = 800 (2026)
ADT = 830 (2046)
R.D.S. = 30 MPH

LIST OF DRAWINGS:

- GENERAL PLAN AND ELEVATION
- CROSS SECTION, NOTES, AND QUANTITIES
- SUBSURFACE EXPLORATION
- WEST ABUTMENT
- WEST ABUTMENT DETAILS
- EAST ABUTMENT
- EAST ABUTMENT DETAILS
- ABUTMENT BAR STEEL
- SUPERSTRUCTURE
- SUPERSTRUCTURE DETAILS
- TUBULAR STEEL RAILING TYPE "M"

BENCH MARKS

NO.	STATION	DESCRIPTION	ELEV.	NORTHING	EASTING
BM 1	8+50.4, 37' RT.	TOP OF BUR TAG BOLT ON HYD	634.86	236021.62	210522.83
BM 2	12+51.94, 19.40' RT	BRIDGE CAP IN SE WING WALL	633.01	236042.40	210924.50
BM 3	14+43.67, 30.32' RT	TOP OF BUR TAG BOLT ON HYD	632.18	236033.27	211116.23



STRUCTURE DESIGN CONTACTS:
CHRISTOPHER MARCUM, PE 715-861-4823
AARON BONK 608-261-0261

NO.	DATE	REVISION	BY
jt ENGINEERING			
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
ACCEPTED	JLR DATE 12/17/25		
STRUCTURE B-36-256			
CTH XX OVER BR CENTERVILLE CREEK			
COUNTY	MANITOWOC	VILLAGE	CLEVELAND
DESIGN SPEC. AASHTO LRFD BRIDGE DESIGN SPECIFICATION			
DESIGNED BY	MPG	DESIGN CK'D	DRAWN BY ZRT/MPG
PLANS CK'D	CJM	DRAWN BY ZRT/MPG	CJM
GENERAL PLAN AND ELEVATION			
SHEET 1 OF 11			

GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

THE EXISTING STRUCTURE, B-36-913, IS A SINGLE SPAN REINFORCED CONCRETE CAST-IN-PLACE GIRDER BRIDGE ORIGINALLY CONSTRUCTED IN 1917, ON TIMBER PILING. THE EXISTING BRIDGE HAS AN OVERALL LENGTH OF 28'-9" AND AN OVERALL WIDTH OF 38'-9". EXISTING STRUCTURE B-36-913 IS TO BE REMOVED.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BEVEL EXPOSED EDGES OF CONCRETE $\frac{3}{4}$ " UNLESS OTHERWISE NOTED.

THE UPPER LIMITS OF "EXCAVATION FOR STRUCTURES B-36-256" SHALL BE THE EXISTING GROUNDLINE.

AT THE BACK FACE OF ABUTMENT ALL VOLUME WHICH CANNOT BE PLACED BEFORE ABUTMENT CONSTRUCTION AND IS NOT OCCUPIED BY THE NEW STRUCTURE SHALL BE BACKFILLED WITH STRUCTURE BACKFILL TYPE A.

EXCAVATE TO THE BOTTOM OF ABUTMENT ELEVATION PRIOR TO DRIVING PILES.

EXCAVATION BELOW THE ABUTMENT AND ABUTMENT BEDDING MATERIALS REQUIRES ENGINEER APPROVAL. GEOTEXTILE SHALL BE SET AT THE BOTTOM OF EXCAVATION AND EXTEND 2'-0" ABOVE BOTTOM OF ABUTMENT.

THE QUANTITY FOR BACKFILL STRUCTURE IS CALCULATED BASED ON THE DETAIL SHOWN IN THE PLANS.

PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO THE EXPOSED TOP OF SLAB, THE SLAB EDGES, THE EXTERIOR 1'-0" OF THE UNDERSIDE OF THE SLAB AND HAUNCH, THE EXPOSED TOP AND FRONT FACES OF THE ABUTMENT AND WINGS TO 1'-0" PAST THE EDGE OF SLAB.

THE SLOPE OF THE FILL IN FRONT OF THE ABUTMENTS SHALL BE COVERED WITH HEAVY RIPRAP AND GEOTEXTILE TYPE "HR" TO THE EXTENT SHOWN ON SHEET 1 AND THE ABUTMENT DETAILS.

SLAB FALSEWORK SHALL BE SUPPORTED ON PILES OR THE SUBSTRUCTURE, UNLESS AN ALTERNATE METHOD IS APPROVED BY THE ENGINEER.

THE UTILITY INFORMATION SHOWN ON THESE DRAWINGS CONCERNING TYPE AND LOCATION OF UNDERGROUND AND OVERHEAD UTILITIES IS NOT GUARANTEED TO BE ACCURATE OR ALL INCLUSIVE. THE CONTRACTOR IS RESPONSIBLE FOR MAKING THEIR OWN DETERMINATIONS AS TO THE TYPE AND LOCATION OF UNDERGROUND UTILITIES AS MAY BE NECESSARY TO AVOID DAMAGE.


HORIZONTAL POSITION SHOWN ON THIS PLAN ARE WISCONSIN COORDINATE REFERENCE SYSTEM (WISCRS), MANITOWOC COUNTY, NAD83 (2011), IN U.S. SURVEY FEET/POSITIONS SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES ARE THE SAME AS GROUND DISTANCES.

ELEVATIONS ARE REFERENCED TO NAVD 88 (2021). GPS DERIVED ELEVATIONS ARE BASED ON GEOID 18.

EXISTING SUBSTRUCTURE LOCATIONS ARE BASED ON SURVEY AND AS-BUILT PLANS. REMOVE EXISTING SUBSTRUCTURES AS NEEDED TO CONSTRUCT NEW SUBSTRUCTURES. COST OF REMOVAL IS INCIDENTAL TO THE BID ITEM "REMOVING STRUCTURE OVER WATERWAY DEBRIS CAPTURE."

PREFORMED FILLER SHALL CONFORM TO THE REQUIREMENTS OF A.A.S.H.T.O. DESIGNATION M153, TYPES I, II OR III OR M213.

AT ABUTMENTS, CONCRETE POURED UNDER WATER WILL BE ALLOWED AND SHALL BE DONE IN ACCORDANCE WITH SECTION 502.3.5.3 OF THE STANDARD SPECIFICATIONS.




LEGEND

(G01) $\frac{3}{4}$ " V-GROOVE REQUIRED, EXTEND TO 6" FROM FRONT FACE OF ABUTMENT DIAPHRAGM. TYP. AT EACH EDGE OF THE SLAB.

(G02) PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO THE ENTIRE EXPOSED TOP OF DECK, THE DECK EDGES, THE EXTERIOR 1'-0" OF THE UNDERSIDE OF THE DECK AND DIAPHRAGMS, THE EXPOSED TOP AND FRONT FACES OF THE ABUTMENT AND WINGS TO 1'-0" PAST THE EDGE OF DECK.

NOTE: PLACE HEAVY RIPRAP AS SHOWN IN WING ELEVATION DETAIL.




TYPICAL FILL SECTION AT WING

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	SUPER.	WEST ABUT.	EAST ABUT.	TOTALS
203.0270	REMOVING STRUCTURE OVER WATERWAY DEBRIS CAPTURE B-36-913	EACH	---	---	---	1
206.1001	EXCAVATION FOR STRUCTURES BRIDGES B-36-256	EACH	---	---	---	1
210.1500	BACKFILL STRUCTURE TYPE A	TON	---	240	240	480
502.0100	CONCRETE MASONRY BRIDGES	CY	168	36	35	239
502.3200	PROTECTIVE SURFACE TREATMENT	SY	270	18	19	307
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB	---	3,150	3,150	6,300
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	31,800	910	920	33,630
513.4061	RAILING TUBULAR TYPE M	LF	111	---	---	111
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	---	9	9	18
550.1100	PILENG STEEL HP 10-INCH X 42 LB	LF	---	225	315	540
606.0300	RIPRAP HEAVY	CY	---	75	80	155
612.0406	PIPE UNDERDRAIN WRAPPED 6-INCH	LF	---	100	100	200
645.0111	GEOTEXTILE DF SCHEDULE A	SY	---	65	65	130
645.0120	GEOTEXTILE TYPE HR	SY	---	175	180	355
SPV.0090	FLASHING STAINLESS STEEL	LF	95	---	---	95
NON-BID ITEMS						
PREFORMED JOINT FILLER		SIZE				$\frac{1}{2}$ " & $\frac{3}{4}$ "
NON-STAINING GRAY, NON-BITUMINOUS JOINT SEALER		SIZE				1"
NAME PLATE		EACH				1

ALL B-36-256 BID ITEMS ARE CATEGORY 0020




TYPICAL SECTION THRU ABUTMENT

▲ BACKFILL PAY LIMITS. BACKFILL BEYOND PAY LIMITS SHALL BE INCIDENTAL TO EXCAVATION FOR STRUCTURES. LIMITS OF EXCAVATION SHALL BE DETERMINED BY THE CONTRACTOR.

■ PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN.

ABUTMENT BACKFILL DIAGRAM

L = ABUTMENT BODY LENGTH AT BACKFACE (FT)
 H = AVERAGE ABUTMENT FILL HEIGHT (FT)
 $H1$ = WING 1 HEIGHT AT TIP (FT)
 $H2$ = WING 2 HEIGHT AT TIP (FT)
 W = WING LENGTH (FT)
 EF = EXPANSION FACTOR (1.20 FOR CY BID ITEMS AND 1.00 FOR TON BID ITEMS)
 V_{CF} = $(L)(3.0')(H) + (L)(0.5)(1.5H)(H) + (3')(0.5)(H1+H2+H+H)(W)$
 V_{CY} = $V_{CF}(EF)/27$
 V_{TON} = $V_{CY}(2.0)$




RODENT SHIELD DETAIL

* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SHIELD, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".

THE RODENT SHIELD SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALLY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SHIELD TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SHIELD SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH STAINLESS STEEL SHEET METAL SCREWS.



PROFILE GRADE LINE

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-256			
DRAWN BY ZRT/MPG PLANS CK'D CJM			
CROSS SECTION, NOTES, AND QUANTITIES	SHEET 2 OF 11	46	


BORING #	DATE COMPLETED	NORTHING (Y)	EASTING (X)
B-01	MARCH 19, 2024	236047.461	210883.225
B-02	MARCH 18, 2024	236074.561	210958.444

BORINGS COMPLETED BY: ECS MIDWEST, LLC.
REPORT COMPLETED BY: ECS MIDWEST, LLC.
ALL COORDINATES REFERENCED TO WCCS NAD 83(2011) MANITOWOC COUNTY


NOTES

BORING STATIONS AND OFFSETS ARE BASED ON C/L CTH XX.

THE SUBSURFACE INFORMATION PRESENTED HEREIN IS AN ABBREVIATED VERSION OF THE INFORMATION PRESENTED IN THE GEOTECHNICAL ENGINEERING REPORT. REVIEW THE APPROPRIATE GEOTECHNICAL REPORT AND SOIL BORING LOGS FOR ADDITIONAL SUBSURFACE INFORMATION.



PLAN




STATE PROJECT NUMBER

4008-02-70

MATERIAL SYMBOLS

ASPHALT	TOPSOIL	PEAT
CONCRETE	FILL	GRAVEL
SAND	CLAY	SILT
BOULDERS OR COBBLES	LIMESTONE	BEDROCK (UNKNOWN)
SHALE	SANDSTONE	IGNEOUS/META

LEGEND OF BORING



⁽¹⁾ UNCONFINED STRENGTH, AS DETERMINED BY A POCKET PENETROMETER (TSF)

⁽²⁾ UNLESS OTHERWISE, SPECIFIED THE SPT 'N' VALUE IS BASED ON AASHTO T-206, STANDARD PENETRATION TEST. THE SPT 'N' VALUE PRESENTED HAS NOT BEEN CORRECTED FOR OVERBURDEN PRESSURE OR HAMMER EFFICIENCY.

GROUND WATER ELEVATION

- ▽ AT TIME OF DRILLING
- ▼ END OF DRILLING
- ▽ AFTER DRILLING

ABBREVIATIONS

F-FINE M-MEDIUM C-COARSE ST-SHELBY TUBE

SUBSURFACE EXPLORATION FOR FOUNDATION DESIGN AND BIDDERS INFORMATION

BORINGS WERE COMPLETED AT POINTS APPROXIMATELY AS INDICATED ON THIS DRAWING TO OBTAIN INFORMATION CONCERNING THE CHARACTER OF SUBSURFACE MATERIALS FOUND AT THE SITE. BECAUSE THE INVESTIGATED DEPTHS ARE LIMITED AND THE AREA OF THE BORINGS IS VERY SMALL IN RELATION TO THE ENTIRE SITE, THE WISCONSIN DEPARTMENT OF TRANSPORTATION DOES NOT WARRANT SIMILAR SUBSURFACE CONDITIONS BELOW, BETWEEN, OR BEYOND THESE BORINGS. VARIATIONS IN SOIL CONDITIONS SHOULD BE EXPECTED AND FLUCTUATIONS IN GROUNDWATER LEVELS MAY OCCUR.


NO. DATE REVISION BY

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

STRUCTURE B-36-256


DRAWN BY ZRT/MPG PLANS CK'D CJM

SUBSURFACE EXPLORATION SHEET 3 OF 11
47




EL E V A T I O N

LOOKING WEST AT FRONT FACE



PLAN



PILE PLAN

HOWING HORIZ. REINF.

NOTES

**DO NOT PLACE BACKFILL ABOVE 3'-0" FROM BOTTOM OF ABUTMENT
UNTIL SUPERSTRUCTURE IS IN PLACE**

SOME BARS HAVE BEEN OMITTED FOR CLARITY, SEE BILL OF BARS ON SHEET 8


FOR PILE SPLICING DETAIL SEE SHEET 8

SPACE REINFORCEMENT TO MISS PILING STEEL

CONCRETE POURED UNDERWATER WILL BE ALLOWED AND SHALL BE DONE IN ACCORDANCE WITH SECTION 502.3.5.3 OF THE STANDARD SPECIFICATIONS

STATE PROJECT NUMBER

4008-02-70



SECTION THRU BODY

LEGEND

- (A01) CONST. JOINT KEYWAY FORMED BY A BEVELED 2" X 6".
- (A02) OPT. KEYED CONST. JOINT FORMED BY A BEVELED 2" X 6".
- (A03) $\frac{1}{2}$ " FILLER. EXTEND FROM BEARING ELEVATION TO TOP OF WING AS SHOWN. SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER (1" DEEP AND HOLD $\frac{1}{8}$ " BELOW SURFACE OF CONCRETE).
- (A04) SUPPORT ABUTMENT ON HP 10 X 42 STEEL PILING ESTIMATED 25'-0" LONG WITH A REQUIRED DRIVING RESISTANCE OF 170 TONS PER PILE.
- (A05) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN. SEE SHEET 2 FOR DETAILS.
- (A06) 18" RUBBERIZED MEMBRANE WATERPROOFING (RMW). SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.
- (A07) B508 BARS @ 1'-0" CTRS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. EMBED BARS 1'-0".
- (A08) ALTERNATE THE POSITION OF THE 90° AND 180° HOOKS AT EACH VERTICAL LAYER OF TIES.
- (X) INDICATES WINGWALL NUMBER

F.F. = FRONT FACE B.F. = BACK FACE

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			


STRUCTURE B-36-256


DRAWN
BY CJM PLANS
CK'D NAR

SHEET 4 OF 11

WEST ABUTMENT


HEET 4 OF 11






WING 3 ELEVATION

SHOWING F.F. WING




WING 4 ELEVATION

SHOWING F.F. WING




WING 3 PLAN

SHOWING UPPER WING REINFORCEMENT




WING 4 PLAN

SHOWING UPPER WING REINFORCEMENT




WING 3 PLAN

SHOWING LOWER WING REINFORCEMENT



WING 4 PLAN

SHOWING LOWER WING REINFORCEMENT



SECTION A-A

SECTION THRU WING

TYPICAL BOTH WINGS

LFGEND


- (B09) SUPPORT ABUTMENT ON HP 10 x 42 STEEL PILING, ESTIMATED 35'-0" LONG WITH A REQUIRED DRIVING RESISTANCE OF 170 TONS PER PILE.
- (B10) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN. SEE SHEET 2 FOR DETAILS.
- (B11) 18" (RMW) RUBBERIZED MEMBRANE WATERPROOFING SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.
- (B12) OPTIONAL KEYED CONST. JOINT FORMED BY BEVELED 2" X 6". PROVIDE $\frac{3}{4}$ " "V" GROOVE ON F.F. OF WINGWALL IF OPTIONAL JOINT IS USED.
- (B13) $\frac{3}{2}$ " FILLER, EXTEND FROM BEARING ELEVATION TO TOP OF WING AS SHOWN. SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER (1" DEEP AND HOLD $\frac{1}{4}$ " BELOW SURFACE OF CONCRETE).

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-256			
		DRAWN BY	PLANS CK'D
		MPG	CJM
EAST ABUTMENT DETAILS		SHEET 7 OF 11	
		51	


BILL OF BARS - WEST ABUTMENT

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.


BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
A501		100	6'-0"	X		BODY VERT. BOT.
A502		46	9'-0"	X		BODY VERT. TOP
A503		9	48'-10"			BODY HORIZ. F.F.
A804		18	30'-11"	X		BODY HORIZ. B.F.
A405		39	2'-11"	X		BODY HORIZ. TIES
A406		3	8'-4"			BODY HORIZ. TOP
A507		9	4'-9"	X		BODY VERT. TOP
A508	X	44	2'-0"			BODY DOWELS
A409	X	30	10'-7"	X		WING 1 VERT.
A510	X	9	12'-7"	X		WING 1 HORIZ. F.F.
A811	X	9	14'-7"	X		WING 1 HORIZ. B.F.
A512	X	3	12'-6"	X		WING 1 VERT. TOP
A513	X	1	5'-4"			WING 1 VERT. F.F.
A414	X	4	9'-11"	X		WING 1 HORIZ. TOP
A415	X	6	11'-3"			WING 1 HORIZ. E.F.
A416	X	2	11'-3"	X		WING 1 DIAG. E.F.
A417	X	28	10'-7"	X		WING 2 VERT.
A518	X	9	11'-8"	X		WING 2 HORIZ. F.F.
A819	X	9	13'-7"	X		WING 2 HORIZ. B.F.
A520	X	2	12'-6"	X		WING 2 VERT. TOP
A521	X	1	5'-4"			WING 2 VERT. B.F.
A422	X	4	7'-4"	X		WING 2 HORIZ. TOP
A423	X	2	10'-2"			WING 2 HORIZ. E.F.
A424	X	2	8'-9"			WING 2 HORIZ. E.F.
A425	X	2	5'-8"			WING 2 HORIZ. E.F.
A426	X	2	10'-4"	X		WING 2 DIAG. E.F.



A501



A502, A507



A409, A512




A417, A520


BILL OF BARS - EAST ABUTMENT

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.


BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
B501		100	6'-1"	X		BODY VERT. BOT.
B502		46	9'-0"	X		BODY VERT. TOP
B503		9	48'-10"			BODY HORIZ. F.F.
B804		18	30'-11"	X		BODY HORIZ. B.F.
B405		39	2'-11"	X		BODY HORIZ. TIES
B406		3	7'-4"			BODY HORIZ. TOP
B507		8	4'-6"	X		BODY VERT. TOP
B508	X	44	2'-0"			BODY DOWELS
B409	X	30	10'-7"	X		WING 3 VERT.
B510	X	3	12'-6"	X		WING 3 VERT. TOP
B511	X	9	12'-0"	X		WING 3 HORIZ. F.F.
B812	X	9	14'-7"	X		WING HORIZ. B.F.
B513	X	1	5'-4"			WING 3 VERT. F.F.
B414	X	4	9'-11"	X		WING 3 HORIZ. TOP
B415	X	6	11'-3"			WING 3 HORIZ. E.F.
B416	X	2	11'-3"	X		WING 3 DIAG. E.F.
B417	X	28	10'-7"	X		WING 4 VERT.
B518	X	9	11'-8"	X		WING 4 HORIZ. F.F.
B819	X	9	13'-4"	X		WING 4 HORIZ. B.F.
B520	X	2	12'-6"	X		WING 4 VERT. TOP
B521	X	1	5'-4"			WING 4 VERT. B.F.
B422	X	4	7'-4"	X		WING 4 HORIZ. TOP
B423	X	2	9'-4"			WING 4 HORIZ. E.F.
B424	X	2	8'-1"			WING 4 HORIZ. E.F.
B425	X	2	5'-9"			WING 4 HORIZ. E.F.
B426	X	2	10'-6"	X		WING 4 DIAG. E.F.




B501




B502, B507, B409




B510, B417, B520




B405




B414




B422




B416




B426




A804, A510, A811, A518, A819




A416




A426




A405



A414



A422




'HP' PILE DETAILS

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE	B-36-256		
DRAWN BY MPG/CJM	PLANS CK'DJM/NAR		


ABUTMENT BAR STEEL

SHEET 8 OF 11

52



CROSS SECTION THRU BRIDGE



PLAN

BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
S501	X	79	7'-8"	X		SLAB AT ABUT.
S502	X	79	4'-0"	X		SLAB AT ABUT.
S1103	X	84	46'-2"			SLAB LONG. BOT.
S604	X	69	44'-0"			SLAB TRANS. BOT.
S505	X	53	44'-0"			SLAB TRANS. TOP.
S506	X	39	49'-6"			SLAB LONG. TOP
S607	X	36	11'-2"	X		SLAB AT RAIL POSTS
S608	X	56	6'-0"			SLAB AT INT. RAIL POSTS
S609	X	16	4'-8"	X		SLAB AT END RAIL POSTS

NOTES

FILL IN THE TABLE OF "SURVEY TOP OF SLAB ELEVATIONS" FOR EACH SPAN ON SHEET 10.

TOP TRANSVERSE BARS IN SLAB SHALL BE SUPPORTED BY INDIVIDUAL BAR CHAIRS AT APPROXIMATELY 3'-0" CENTERS EACH WAY. BOTTOM LONGITUDINAL BARS SHALL BE SUPPORTED BY CONTINUOUS BAR CHAIRS AT APPROXIMATELY 4'-0" CENTERS.


ALL SLAB THICKNESS DIMENSIONS ARE MINIMUM. ANY TOLERANCES NECESSARY TO CORRECT CONSTRUCTION DISCREPANCIES ARE TO BE PLUS (+).

NO.	DATE	REVISION	BY
			STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION

STRUCTURE B-36-256

DRAWN BY	MPG	PLANS CK'D	CJM

SUPERSTRUCTURE			
SHEET 9 OF 11			53



LEGEND

- (S01) $\frac{3}{4}$ " V-GROOVE REQ'D. EXTEND TO 6" FROM FRONT FACE OF ABUTMENT HAUNCH.
- (S02) PROTECTIVE SURFACE TREATMENT SHALL BE APPLIED TO THE ENTIRE TOP OF SLAB, EDGE OF SLAB, EXTERIOR 1'-0" OF THE BOTTOM OF SLAB, AND TO THE PAVING NOTCHES.
- (S03) CONSTRUCTION JOINT. KEYWAY FORMED BY A BEVELED 2" X 6".
- (S04) 4" X $\frac{3}{4}$ " PREFORMED FILLER (TO EXTEND BETWEEN EDGES OF SLAB).
- (S05) 18" (RMW) RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZONTAL AND VERTICAL JOINTS AT BACK FACE OF ABUTMENT.

* DIMENSION IS NORMAL TO C/L BRG. ABUT.

PARTIAL LONGITUDINAL SECTION

DIMENSIONS ARE GIVEN PARALLEL TO C/L CTH XX.
UNLESS OTHERWISE NOTED.


TOP OF SLAB ELEVATIONS

LOCATION	C/L BRG. W. ABUT.	1/10 PT.	2/10 PT.	3/10 PT.	4/10 PT.	5/10 PT.	6/10 PT.	7/10 PT.	8/10 PT.	9/10 PT.	C/L BRG. E. ABUT.
N. EDGE OF DECK	632.95	632.97	632.99	633.01	633.02	633.04	633.06	633.07	633.09	633.11	633.12
C/L CTH XX	633.30	633.32	633.34	633.35	633.37	633.39	633.40	633.42	633.44	633.46	633.47
S. EDGE OF DECK	632.88	632.90	632.91	632.93	632.95	632.96	632.98	633.00	633.02	633.03	633.05


SURVEY TOP OF SLAB ELEVATIONS

LOCATION	W. ABUT	5/10 PT.	E. ABUT
N. EDGE OF DECK			
C/L CTH XX			
S. EDGE OF DECK			

PRIOR TO RELEASING SLAB FALSEWORK, TAKE TOP OF SLAB ELEVATIONS AT THE C/L OF ABUTMENTS AND AT 5/10 PTS. TO VERIFY CAMBER. TAKE ELEVATIONS ALONG EDGE OF DECK AND CROWN OR R/L. RECORD THE ELEVATIONS IN THE ABOVE TABLE FOR THE "AS BUILT" PLANS.



CAMBER DIAGRAM




THICKNESS DIAGRAM

TO DETERMINE FALSEWORK ELEVATION AT EDGE OF SLAB AND CROWN FOLLOW THIS PROCEDURE:

TOP OF SLAB ELEVATION AT FINAL GRADE
MINUS..... SLAB THICKNESS
PLUS..... CAMBER
PLUS..... FORM SETTLEMENT/DEFLECTION DUE TO PLACEMENT OF
SLAB CONCRETE (TO BE COMPUTED BY THE CONTRACTOR)

EQUALS = TOP OF SLAB FALSEWORK ELEVATION

CAMBER SHOWN IS BASED ON 3 TIMES DEAD LOAD DEFLECTIONS. CAMBER SPANS AS SHOWN TO
PROVIDE FOR DEAD LOAD DEFLECTION AND FUTURE CREEP. CAMBER DOES NOT INCLUDE
ALLOWANCE FOR FORM SETTLEMENT.




TYPICAL EDGE OF SLAB DETAIL

BAR STEEL OMITTED FOR CLARITY



NOTE

THE BID ITEM "FLASHING STAINLESS STEEL" SHALL INCLUDE PROVIDING AND INSTALLING THE STAINLESS STEEL FLASHING, CAULK, $\frac{3}{16}$ " CONCRETE SCREWS, AND CLEANING OF THE EDGE OF THE DECK PRIOR TO ATTACHMENT OF THE FLASHING.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-0256			
DRAWN BY MPG PLANS CK'D CJM			
SUPERSTRUCTURE DETAILS			
SHEET 10 OF 11			
54			




FIELD ERECTION JOINT DETAIL




SECTION B-B



SECTION THRU POST WEB



ANCHOR BOLTS



SECTION THRU RAIL


NOTE: CONNECTIONS AT LOWER RAILS SHOWN. CONNECTIONS AT TOP RAIL SIMILAR.

TYPICAL RAIL TO POST CONNECTIONS

LEGEND

- ① W6 X 25 WITH 1 1/8" X 1 1/2" HORIZ. SLOTS ON EACH SIDE OF POST TO MATCH CROSS SLOPE OF ROADWAY. CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY. PLACE POST VERTICAL. PLACE POSTS NORMAL TO GRADE LINE.
- ② PLATE 1 1/4" X 11 3/4" X 1'-8" WITH 1 1/16" DIA. OVERSIZED HOLES FOR ANCHOR BOLTS NO. 3. WELD TO NO. 1 AS SHOWN.
- ③ ASTM A449 - 1 1/4" DIA. ANCHOR BOLTS WITH NUT AND HARDENED WASHER (ALL GALVANIZED). 5 REQ'D. PER POST. THREAD 3" AND PLACE NORMAL TO PLATE NO. 2. CHAMFER TOP OF BOLTS BEFORE THREADING. USE 1 1/9" LONG IN ABUTMENT WINGS. AT POSTS ON CONCRETE SLAB SUPERSTRUCTURES WHERE THE SLAB THICKNESS IS > 16" USE 1 1/3" LONG. USE 10 1/4" LONG AT ALL OTHER LOCATIONS. (AN EQUIVALENT THREADED ROD WITH NUTS AND HARDENED WASHERS MAY BE SUBSTITUTED FOR ANCHOR BOLTS IN WINGS IF REQ'D. FOR CONSTRUCTABILITY.)
- ④ 5/8" X 11" X 1'-8" ANCHOR PLATE (GALVANIZED) WITH 1 1/16" DIA. HOLES FOR ANCHOR BOLTS NO. 3.
- ⑤ TS 5 X 4 X 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- ⑥ TS 5 X 5 X 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- ⑦ 1/2" THK. BACK-UP PLATE WITH 2 7/8" X 1 1/2" THREADED SHOP WELDED STUDS (NO. 12). BOLT TO RAIL AS SHOWN IN DETAIL. REQUIRED AT THRIE BEAM GUARD RAIL ATTACHMENTS ONLY. PLACE SYMMETRICALLY ABOUT TUBES NO. 5A.
- ⑧ 1" DIA. HOLES IN PLATE NO. 7 & TUBES NO. 5A FOR 7/8" DIA. A325 BOLTS WITH HEX NUTS AND WASHERS. 6 HOLES IN TUBES AND PLATE NO. 7.
- ⑨ SPLICE SLEEVE FABRICATED FROM 1/4" PLATE. PROVIDE "SLIDING FIT".
- ⑩ 3/8" X 3 3/8" X 2'-4" PLATE. 2 PER RAIL. USED IN NO. 5 & 5A.
- ⑪ 3/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER, AND LOCK WASHER. USE 1 1/16" X 1 1/4" LONGIT. SLOTTED HOLES IN PLATE NO. 10A. AT FIELD JOINTS AND 1 1/8" X 2 1/4" MIN. LONGIT. SLOTTED HOLES AT EXP. JOINTS IN PLATE NO. 10A. PROVIDE 1 1/16" DIA. ROUND HOLES IN TUBES NO. 5 AND NO. 5A.
- ⑫ 7/8" DIA. X 1 1/2" LONG THREADED SHOP WELDED STUDS (2 REQ'D.).
- ⑬ 3/8" X 8" X 1'-6" PLATE. BOLT TO RAIL AS SHOWN IN DETAIL. REQ'D. AT THRIE BEAM GUARD RAIL ATTACHMENTS ONLY. PLACE SYMM. ABOUT TUBES NO. 5A.
- ⑭ 7/8" DIA. X 2" LONG A325 HEX BOLT WITH NUT AND WASHER (5 REQ'D.).
- ⑮ 1" DIA. HOLES IN TUBES NO. 5A FOR 7/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER AND LOCK WASHER (4 REQ'D.). 4 HOLES IN TUBES.


SECTION THRU RAILING ON DECK




SECTION A-A



TOP VIEW AT END POST







SECTION C-C SECTION D-D



ANCHOR PLATE

GENERAL NOTES

1. BID ITEM SHALL BE "RAILING TUBULAR TYPE M" WHICH INCLUDES ALL ITEMS SHOWN.
2. RAIL POST AND BASE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 50. HOLLOW RAILING STRUCTURAL TUBING SHALL CONFORM TO THE REQUIREMENTS OF ASTM A500 GRADE B OR C WITH A CERTIFIED FY = 50 KSI. ANCHOR PLATES, AND SPLICE TUBE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 36.
3. THE NUT SECURING THE POST BASE PLATE TO THE CONCRETE SHALL BE TIGHTENED TO A SNUG FIT AND GIVEN AN ADDITIONAL 1/2 TURN.
4. RAILS SHALL BE CONTINUOUS OVER A MINIMUM OF THREE (3) POSTS WITHOUT SPLICES WHERE POSSIBLE. RAILS SHALL BE SPLINED IN A PANEL OVER EXPANSION JOINTS.
5. ENDS OF TUBE SECTIONS SHALL BE SAWED. GRIND SMOOTH EXPOSED EDGES. ALL CUT ENDS SHALL BE TRUE AND SMOOTH.
6. WELD IS THE SAME ON BOTH FLANGES. FLANGE WELD DOES NOT REQUIRE MAGNETIC PARTICLE TESTING.
7. FILL BOLT SLOT OPENINGS IN POST SHIMS AND PLATE NO. 2 AND CAULK AROUND PERIMETER OF PLATE NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. STEEL POST SHIMS MAY BE USED UNDER POSTS WHERE REQ'D. FOR ALIGNMENT.
8. POST BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.
9. ALL MATERIAL SHALL BE GALVANIZED AFTER FABRICATION. PRIOR TO GALVANIZING, ALL STEEL RAILING POSTS & STEEL TUBING SHALL BE GIVEN A NO. 6 BLAST CLEANING BY SSPC SPECIFICATIONS.

ANCHOR PLATE
AT RAIL TO DECK CONNECTIONPOST SHIM
DETAILBACK-UP PLATE DETAIL
AT BEAM GUARD ATTACHMENT

PART ELEVATION OF RAILING


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-36-256			
DRAWN BY	MPG	PLANS CK'D	CJM
TUBULAR STEEL RAILING TYPE "M"	SHEET 11 OF 11	55	SCALE = 2:00


STATION	REAL STATION	DISTANCE	AREA (SF)		INCREMENTAL VOL (CY) (UNADJUSTED)		CUMULATIVE VOL (CY)		
			CUT	FILL	CUT	FILL	CUT	EXPANDED FILL	MASS ORDINATE
					NOTE 1	NOTE 3	NOTE 1	NOTE 8	
10+21	1021.55	0.00	6.05	0.00	0	0	0	0	0
10+30	1030.00	8.45	6.02	0.09	2	0	2	0	2
10+40	1040.00	10.00	5.98	0.39	2	0	4	0	4
10+50	1050.00	10.00	5.95	1.02	2	0	6	0	6
10+60	1060.00	10.00	5.58	2.72	2	1	8	1	7
10+70	1070.00	10.00	5.49	4.62	2	1	10	3	8
10+80	1080.00	10.00	5.57	6.19	2	2	12	5	7
10+90	1090.00	10.00	5.99	6.90	2	2	14	8	7
11+00	1100.00	10.00	7.76	7.21	3	3	17	11	6
11+10	1110.00	10.00	8.11	8.23	3	3	20	15	5
11+20	1120.00	10.00	7.56	9.48	3	3	23	19	4
11+30	1130.00	10.00	7.20	11.82	3	4	26	24	2
11+40	1140.00	10.00	7.01	14.41	3	5	29	30	-1
11+50	1150.00	10.00	17.8	15.70	5	6	34	38	-4
11+60	1160.00	10.00	13.96	14.75	6	6	40	45	-5
11+70	1170.00	10.00	25.86	14.23	7	5	47	51	-4
11+80	1180.00	10.00	60.73	14.11	16	5	63	58	6
11+90	1190.00	10.00	58.34	13.65	22	5	85	64	21
12+00	1200.00	10.00	58.24	3.95	22	3	107	68	40
12+10	1210.00	10.00	56.36	1.67	21	1	128	69	59
12+20	1220.00	10.00	34.60	3.10	17	1	145	70	75
12+29	1229.03	9.03	11.41	13.23	8	3	153	74	79
12+33	1233.00	3.97	0.00	0.00	1	1	154	75	79


STATION	REAL STATION	DISTANCE	AREA (SF)		INCREMENTAL VOL (CY) (UNADJUSTED)		CUMULATIVE VOL (CY)		
			CUT	FILL	CUT	FILL	CUT	EXPANDED FILL	MASS ORDINATE
					NOTE 1	NOTE 3	NOTE 1	NOTE 8	
12+61	1261.00	0.00	0.00	0.00	0	0	0	0	0
12+64	1263.87	2.87	4.44	4.47	0	0	0	0	0
12+70	1270.00	6.13	16.90	24.89	2	3	2	4	-2
12+80	1280.00	10.00	37.96	24.08	10	9	12	15	-3
12+90	1290.00	10.00	48.85	24.46	16	9	28	26	2
13+00	1300.00	10.00	47.63	46.43	18	13	46	43	4
13+10	1310.00	10.00	47.90	47.18	18	17	64	64	0
13+20	1320.00	10.00	48.73	48.45	18	18	82	86	-4
13+30	1330.00	10.00	12.69	43.64	11	17	93	108	-15
13+40	1340.00	10.00	12.50	40.41	5	16	98	128	-30
13+50	1350.00	10.00	12.87	37.75	5	14	103	145	-42
13+60	1360.00	10.00	13.13	34.97	5	13	108	161	-53
13+70	1370.00	10.00	13.36	31.48	5	12	113	176	-63
13+80	1380.00	10.00	12.69	29.16	5	11	118	190	-72
13+90	1390.00	10.00	12.38	25.95	5	10	123	203	-80
14+00	1400.00	10.00	10.61	19.60	4	8	127	213	-86
14+10	1410.00	10.00	10.37	14.62	4	6	131	220	-89
14+20	1420.00	10.00	10.53	19.17	4	6	135	228	-93
14+30	1430.00	10.00	10.83	17.87	4	7	139	236	-97
14+43	1442.42	12.42	17.61	11.03	7	7	146	245	-99

9

9







PROJECT NO: 4008-02-70

HWY: CTH X

COUNTY: MANITOWOC

CROSS SECTIONS: CROSS SECTIONS

SHEET

FILE NAME : X:\PROJECTS\MANITOWOC\240016 4008-02-00 CTH XX V CLEVELAND BRIDGE\DESIGN\C3D\SheetsPlan\090201-XS.DWG
LAYOUT NAME - 090201-xs03


PLOT DATE : 3/10/2025 3:24 PM


PLOT BY : JAKE NEERDAELS


PLOT NAME :

PLOT SCALE : 1 IN:10 FT HORZ. / 1 IN:10 FT VERT.




100/ISDOT/CA







END CONSTRUCTION
STA 14+43



PROJECT NO: 4008-02-70


HWY: CTH XX

COUNTY: MANITOWOC

CROSS SECTIONS: CROSS SECTIONS

SHEET

E



Wisconsin Department of Transportation

Dedicated people creating transportation solutions
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>