

**CONVERGENT CONNECTIVITY TECHNOLOGY** 


# C142IMSA19T502

14/2 Stranded tin copper conductors, shielded, **Description:** 

with an overall jacket

IMSA 50/2 **Standards:** 

**Applications:** traffic signal installations and suitable for conduit installation in wet or dry locations



### CONSTRUCTION

Conductor: 14 AWG Tinned Copper

Stranding: 19 Strand

**Insulation Material:** Low Density Polyethylene

**Insulation Thickness:** 0.030 in. (0.762 mm.) Nominal

Number of Conductors: 2 Conductors

Insulation Color (Per IMSA 50/2): Black, Natural (Clear)

Shield: Aluminum/Polyester Tape (100% Coverage)

Drain: 16AWG 7 Strand Tinned Copper

Jacket Material: Low Density Polyethylene

Jacket Thickness: 0.030 in. (0.762 mm.) Nominal

Overall Cable Diameter: 0.338 in. (8.585 mm.) Nominal

Jacket Color: Black

Approx Cable Weight /1,000 ft.: 62 lbs.

Ident Tape: CONVERGENT CONNECTIVITY TECHNOLOGY 14AWG 2

CONDUCTOR IMSA 50-2 600V

(Month & Year of Manufacture) (Lot #)

Footage Marking: None

## **ELECTRICAL PROPERTIES**

Operative Voltage: 600 V, RMS

> Issue Date: June '15 Revision: 1

THE STRONGEST LINK IN YOUR SUPPLY CHAIN


PHONE: 866-905-6744 **PO BOX 454** FAX: 845-651-3564 FLORIDA, NY 10921

techsupport@cctcable.com



**CONVERGENT CONNECTIVITY TECHNOLOGY** 

C142IMSA19T502



**Note:** While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification	n sheet and upon confirmation of your order; e non-cancelable and non-returnable.
Signature:	
Company:	
Date:	

Vour signature constitutes that you have read and agreed to

Issue Date: June '15 Revision: 1

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564