



DOOR SUPPLIED BLANK OR LOGO IN ALUMINUM
 STD 1/4" -20 S.S. HEX SCREW OR VANDAL SCREW TO FIT YOUR SPECIFICATIONS
 ALL WASHERS TO BE ZINC MECHANICAL COATED PER ASTM B695-85 CLASS 50
 356T-6 ALUMINUM ALLOY / CHEMICAL AND PHY. CERTS TO BE SUPPLIED WITH EACH SHIPMENT

ADHESIVE BREAKAWAY AND CAUTION LABELS TO APPEAR
 ON INSIDE WALL OPPOSITE DOOR OPENING
 NOTE: PROVIDE W/ EACH POLE - 4 EA. 1" DIA. x 3 3/4" LONG ASTM A325
 HEX HEAD STEEL BOLTS, HD GALV. PER ASTM A153 W/ ALL
 FLATWASHERS, LOCKWASHERS, NUTS AND SHIMS REQD.
 (FOR POLE-TO-BASE CONNECTION)

QTY = 115

NO.	DATE	BY	REVISIONS
1			
2			

95 GNARLED HOLLOW RD.
 EAST SETAUKET, N.Y. 11733
Flagpoles, Inc.
 ALUMINUM LIGHT STANDARDS
 TUBULAR METAL PRODUCTS

P&K
 TUBULAR PRODUCTS, INC.

1985 AASHTO T-BASE

DRAWN BY	DATE	MATERIAL
SAF	12/1/14	AS NOTED
CHK'D	JS	
SCALE	NTS	
WORK ORDER #	47385	
DRAWING NO.	12962	

MATERIAL MELTED AND MANUFACTURED IN THE USA. CASTINGS PRODUCED IN THE USA.
ORDER "H" AFTER PART NUMBER WHEN A HINGE DOOR APPLICATION IS REQUIRED