

Highway Maintenance ManualChapter 08Roadside FacilitiesSection 15Site AmenitiesSubject 05Toilet Buildings

1.0 General Maintenance Checklist

- 1. Check building roof for damage and loose or missing shingles. Check roof plates and gable ends. Repair if necessary.
- 2. Check skylight for damage and leaks. Caulk and repair if necessary.
- 3. Check doors, doorframes, hinges, closures and handles. Repair, repaint or restain as necessary.
- 4. Check windows, screens and floor vents for damage. If window screens are in poor condition, replace frame and screen. Replace floor vents if they are in poor condition.
- 5. Check ceiling, windowsills, trim and storage cabinet for damage. Repair, repaint or restain as necessary.
- 6. Check toilets, toilet seats, seat brackets and urinals for damage. Caulk seams along floors and walls, and repair or replace all parts in poor condition.
- 7. Check toilet partitions, doors, hasps, hinges, grab bars and paper holders. Repair or replace as needed.
- 8. Check the vault cover, bolts and locking devices for damage or missing pieces. Repair and repaint if necessary.
- 9. Check the MEN and WOMEN signs on the buildings and doors. Repaint, refasten or replace as necessary.
- 10. Check the entry stoops for settling. Raise or wedge to accommodate wheelchairs.
- 11. Check concrete-block walls inside and outside for cracks and damage. Patch and tuck point if necessary.
- 12. Check anti-graffiti finish on walls. Touch up or repaint if needed.
- 13. Check light fixtures for damage. Clean, repair and replace fixtures or bulbs if necessary.
- 14. Check outside privacy screen for damage and leaning. Straighten, repair and restain if necessary.
- 15. Remove cobwebs, dirt and old bird and bee nests from window screen and sills, roof plates, gable ends, ceilings and skylights. Sweep down the walls and floors.
- 16. Hose down and wash skylight, walls, partitions, fixtures and floors. Remove or paint over graffiti.
- 17. Place odor-control material in the vault.